


SAR EVALUATION REPORT

For

Feitian Technologies Co., Ltd.

Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road, Haidian District, Beijing, China

FCC ID: ZD3FTF360

Report Type: Original Report	Product Name: Android POS Terminal
Report Number:	<u>RKSA240319001-20B</u>
Report Date:	<u>2024-10-23</u>
Reviewed By:	<u>Bard Liu</u> 
Approved By:	<u>Oscar Ye</u> 
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government. This report contains data not covered by NVLAP certification

TABLE OF CONTENTS

REPORT REVISION HISTORY	3
REFERENCE, STANDARDS, AND GUIDELINES.....	6
SAR LIMITS	6
FACILITIES.....	7
DESCRIPTION OF TEST SYSTEM	8
EQUIPMENT LIST AND CALIBRATION	17
EQUIPMENTS LIST & CALIBRATION INFORMATION	17
SAR MEASUREMENT SYSTEM VERIFICATION	18
LIQUID VERIFICATION	18
SYSTEM ACCURACY VERIFICATION.....	22
SAR SYSTEM VALIDATION DATA.....	24
EUT TEST STRATEGY AND METHODOLOGY	32
TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS.....	32
TEST DISTANCE FOR SAR EVALUATION.....	32
SAR EVALUATION PROCEDURE.....	33
CONDUCTED OUTPUT POWER MEASUREMENT	34
TEST PROCEDURE	34
RADIO CONFIGURATION	34
MAXIMUM TARGET OUTPUT POWER	40
TEST RESULTS:	42
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	62
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	63
STANDALONE SAR ESTIMATION:	63
SAR MEASUREMENT RESULTS.....	65
SAR TEST DATA.....	65
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	71
APPENDIX A SAR PLOTS OF SAR MEASUREMENT	72
APPENDIX B MEASUREMENT UNCERTAINTY	87
APPENDIX C EUT TEST POSITION PHOTOS	89
APPENDIX D CALIBRATION CERTIFICATES	91

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA240319001-20B	R1V1	2024-10-23	Initial Release

EUT Information	
Applicant:	Feitian Technologies Co., Ltd.
Product Type	Portable
Exposure Category:	Population / Uncontrolled
Body-Worn Accessories:	None
Operation Mode :	GPRS/EGPRS WCDMA FDD-LTE/ TDD-LTE WLAN2.4G WLAN5G Bluetooth BLE NFC
Power Supply:	DC 3.7V from battery
Normal Operation:	Body Supported
Frequency Band:	GPRS/EGPRS 850: 824-849 MHz(TX), 869-894 MHz(RX) GPRS/EGPRS 1900: 1850-1910 MHz(TX), 1930-1990 MHz(RX) WCDMA Band II: 1850-1910 MHz(TX), 1930-1990 MHz(RX) WCDMA Band IV: 1710-1755 MHz(TX), 1930-1990 MHz(RX) WCDMA Band V: 824-849 MHz(TX), 869-894 MHz(RX) LTE Band 2: 1850-1910 MHz(TX), 1930-1990 MHz(RX) LTE Band 4: 1710-1755 MHz(TX), 2110-2155 MHz(RX) LTE Band 5: 824-849 MHz(TX), 869-894 MHz(RX) LTE Band 7: 2500-2570 MHz(TX), 2620-2690 MHz(RX) LTE Band 38: 2570-2620 MHz(TX), 2570-2620 MHz(RX) WLAN (2.4G): 2412 -2462 MHz (TX&RX) WLAN (5.2G): 5150-5250MHz(TX&RX) WLAN (5.3G):5250-5350MHz(TX&RX) WLAN (5.6G):5470-5725MHz(TX&RX) WLAN (5.8G) : 5725~5850 MHz(TX&RX) Bluetooth: 2402 MHz-2480 MHz(TX&RX) BLE(1 Mbps): 2402 MHz-2480 MHz(TX&RX) NFC:13.56MHz
Tested Model:	F360
Product name:	Android POS Terminal
Serial Number:	RKSA240319001-1
Test Date:	2024-09-16~2024-09-21

MODE	Max. SAR Level(s) Reported(W/kg)	Limit
GSM850	0.521 W/kg 1g Body SAR	1.6(W/kg)
DCS1900	0.308 W/kg 1g Body SAR	
WCDMA Band II	0.407 W/kg 1g Body SAR	
WCDMA Band IV	0.515 W/kg 1g Body SAR	
WCDMA Band V	0.423 W/kg 1g Body SAR	
LTE Band 2	0.258 W/kg 1g Body SAR	
LTE Band 4	0.348 W/kg 1g Body SAR	
LTE Band 5	0.212 W/kg 1g Body SAR	
LTE Band 7	0.408 W/kg 1g Body SAR	
LTE Band 38	0.470 W/kg 1g Body SAR	
2.4GHz WLAN	0.124 W/kg 1g Body SAR	
5.2GHz WLAN	0.255 W/kg 1g Body SAR	
5.3GHz WLAN	0.203 W/kg 1g Body SAR	
5.6GHz WLAN	0.193 W/kg 1g Body SAR	
5.8GHz WLAN	0.184 W/kg 1g Body SAR	
Simultaneous	0.776 W/kg 1g Body SAR	
Applicable Standards		
▲ FCC 47 CFR part 2.1093 Radiofrequency radiation exposure evaluation: portable devices		
▲ RF Exposure Procedures: TCB Workshop April 2019		
IEEE 1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques		
▲ KDB procedures KDB 447498 D01 General RF Exposure Guidance v06 KDB 648474 D04 Handset SAR v01r03 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D01 3G SAR Procedures v03r01 KDB 941225 D05 SAR for LTE Devices v02r05 KDB 248227 D01 802.11 Wi-Fi SAR v02r02		
Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in FCC 47 CFR part 2.1093 and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures. The results and statements contained in this report pertain only to the device(s) evaluated.		

REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

SAR Limits

FCC Limit

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).


General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg for 1g Body SAR applied to the EUT.

FACILITIES

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.


Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN5055.

These measurements were performed with the automated near-field scanning system DASY6 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



DASY6 System Description

The DASY6 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY6 Measurement Server

The DASY6 measurement server is based on a PC/104 CPU board with a 400 MHz Intel ULV Celeron, 128 MB chip-disk and 128 MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16-bit AD converter system for optical detection and digital I/O interface are contained on the DASY6 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluations of field measurements and surface detection, controls robot movements, and handles safety operations. The PC operating system cannot interfere with these time-critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program- controlled robot movements. Furthermore, the measurement server is equipped with an expansion port, which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Connection of devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.


The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 E-Field Probes

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

SAM Twin Phantom



The SAM Twin Phantom (shown in front of DASY6) is a fiberglass shell phantom with shell thickness 2 mm, except in the ear region where the thickness is increased to 6 mm. The phantom has three measurement areas: 1) Left Head, 2) Right Head, and 3) Flat Section. For larger devices, the use of the ELI-Phantom (shown behind DASY6) is required. For devices such as glasses with a wireless link, the Face Down Phantom is the most suitable (between the SAM Twin and ELI phantoms). When the phantom is mounted inside allocated slot of the DASY6 platform, phantom reference points can be taught directly in the DASY5 V5.2 software. When the DASY6 platform is used to mount the Phantom, some of the phantom teaching points cannot be reached by the robot in DASY5 V5.2. A special tool called P1a-P2aX-Former is provided to transform two of the three points, P1 and P2, to reachable locations. To use these new teaching points, a revised phantom configuration file is required.


In addition to our standard broadband liquids, the phantom can be used with the following tissue simulating liquids:

Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.

DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).

Do not use other organic solvents without previously testing the solvent resistivity of the phantom.

Approximately 25 liters of liquid is required to fill the SAM Twin phantom.

ELI Phantom

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30MHz to 6 GHz. ELI is fully compatible with the latest draft of the standard IEEE 1528:2013 and the use of all known tissue simulating liquids. ELI has been optimized for performance and can be integrated into a SPEAG standard phantom table. A cover is provided to prevent evaporation of water and changes in liquid parameters. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.

The phantom can be used with the following tissue simulating liquids:

- Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.
- DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).
- Do not use other organic solvents without previously testing the solvent resistivity of the phantom.

Approximately 25 liters of liquid is required to fill the ELI phantom.

Robots

The DASY6 system uses the high-precision industrial robots TX60L, TX90XL, and RX160L from Staubli SA (France). The TX robot family - the successor of the well-known RX robot family - continues to offer the features important for DASY6 applications:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is provided

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE 1528:2013

Recommended Tissue Dielectric Parameters for Head liquid

Table 2 – Dielectric properties of the tissue-equivalent medium

Frequency MHz	Real part of the complex relative permittivity, ϵ'_r	Conductivity, σ S/m	Penetration depth (E-field), δ mm
4	55,0	0,75	293,0
13	55,0	0,75	165,5
30	55,0	0,75	112,8
150	52,3	0,76	62,0
300	45,3	0,87	46,1
450	43,5	0,87	43,0
750	41,9	0,89	39,8
835	41,5	0,90	39,0
900	41,5	0,97	36,2
1 450	40,5	1,20	28,6
1 800	40,0	1,40	24,3
1 900	40,0	1,40	24,3
1 950	40,0	1,40	24,3
2 000	40,0	1,40	24,3
2 100	39,8	1,49	22,8
2 450	39,2	1,80	18,7
2 600	39,0	1,96	17,2
3 000	38,5	2,40	14,0
3 500	37,9	2,91	11,4
4 000	37,4	3,43	10,0
4 500	36,8	3,94	9,7

Frequency MHz	Real part of the complex relative permittivity, ϵ'_r	Conductivity, σ S/m	Penetration depth (E-field), δ mm
5 000	36,2	4,45	1,5
5 200	36,0	4,66	8,4
5 400	35,8	4,86	8,1
5 600	35,5	5,07	7,5
5 800	35,3	5,27	7,3
6 000	35,1	5,48	7,0
6 500	34,5	6,07	6,7
7 000	33,9	6,65	6,4
7 500	33,3	7,24	6,1
8 000	32,7	7,84	5,9
8 500	32,1	8,46	5,3
9 000	31,6	9,08	4,8
9 500	31,0	9,71	4,4
10 000	30,4	10,40	4,0

NOTE For convenience, permittivity and conductivity values are linearly interpolated for frequencies that are not a part of the original data from Drossos et al. [2]. They are shown in italics in Table 2. The italicized values are linearly interpolated (below 5800 MHz) or extrapolated (above 5800 MHz) from the non-italicized values that are immediately above and below these values.

Note:


- 1, Effective February 19, 2019, FCC has permitted the use of single head-tissue simulating liquid specified in IEEE 1528:2013 for all SAR tests.
- 2, Mix and Match of traditional FCC SAR TSLs and IEEE 1528:2013 TSL in a single application is not permitted TSL can be changed in a Permissive Change.
- 3, If SAR increases and original SAR > 1.2 W/kg, additional SAR measurements will be required IEEE 1528:2013 TSL is an alternative, not mandatory at this time.
- 4, If FCC parameters are used, $\pm 5\%$ tolerance. If IEC parameters, $\pm 10\%$.
- 5, In this case, IEC parameters applied.

EQUIPMENT LIST AND CALIBRATION**Equipments List & Calibration Information**

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52 52.10.2	N/A	N/A	N/A
DASY6 Measurement Server	DASY6 6.0.31	N/A	N/A	N/A
Data Acquisition Electronics	DAE4	527	2024/03/26	2025/03/25
E-Field Probe	EX3DV4	7557	2024/03/26	2025/03/25
Mounting Device	MD4HHTV5	SD 000 H01 KA	N/A	N/A
Twin-SAM Phantom	QD 000 P41 Ax	1963	N/A	N/A
Dipole, 835MHz	D835V2	445	2023/02/10	2026/02/09
Dipole,1750MHz	D1750V2	1140	2024/06/17	2027/06/16
Dipole,1900MHz	D1900V2	5d206	2024/06/15	2027/06/14
Dipole,2450MHz	D2450V2	970	2024/06/15	2027/06/14
Dipole,2600MHz	D2600V2	1162	2022/08/22	2025/08/21
Dipole,5GHz	D5GHzV2	1296	2022/08/17	2025/08/16
Simulated Tissue LiquidHead	HBBL600-6000V6	180611-3	Each Time	
Network Analyzer	E5071B	SG42400155	2024/04/23	2025/04/22
Dielectric Assessment Kit	DAK-3.5	SM DAK 300AB	N/A	N/A
Signal Generator	SMBV100A	261558	2024/04/25	2025/04/24
Power Amplifier	ZHL-5W-202-S+	416402204	N/A	N/A
Power Amplifier	ZVE-8G+	558401902	N/A	N/A
Directional Coupler	4242-10	3307	N/A	N/A
Attenuator	3dB	5402	N/A	N/A
Attenuator	10dB	AU 3842	N/A	N/A
Radio Communication Analyzer	MT8820C	6200930956	2024/04/24	2025/04/23
Hygrothermograph	HTC-1	N/A	2024/04/20	2025/04/19
Thermometer	UL-IL01	N/A	2024/04/20	2025/04/19
Power Meter	E4419B	MY41291878	2024/04/23	2025/04/22

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
835	Head	0.902	41.842	0.900	41.500	0.22	0.82	± 5
836.6	Head	0.904	41.819	0.901	41.500	0.33	0.77	± 5
824.2	Head	0.892	41.983	0.898	41.512	-0.67	1.13	± 5
848.8	Head	0.915	41.664	0.909	41.500	0.66	0.40	± 5
826.4	Head	0.894	41.955	0.898	41.508	-0.45	1.08	± 5
846.6	Head	0.913	41.689	0.907	41.500	0.66	0.46	± 5
836.5	Head	0.903	41.826	0.901	41.500	0.22	0.79	± 5
829	Head	0.896	41.926	0.899	41.504	-0.33	1.02	± 5
844	Head	0.91	41.725	0.904	41.500	0.66	0.54	± 5

Liquid Verification above was performed on 2024/09/16.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
1750	Head	1.373	41.104	1.370	40.100	0.22	2.50	± 5
1732.6	Head	1.356	41.174	1.377	40.065	-1.53	2.77	± 5
1712.4	Head	1.336	41.275	1.364	40.104	-2.05	2.92	± 5
1752.6	Head	1.375	41.098	1.388	40.034	-0.94	2.66	± 5
1732.5	Head	1.356	41.174	1.377	40.065	-1.53	2.77	± 5
1720	Head	1.343	41.237	1.369	40.089	-1.90	2.86	± 5
1745	Head	1.368	41.122	1.384	40.046	-1.16	2.69	± 5

Liquid Verification above was performed on 2024/09/17.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
1900	Head	1.442	39.543	1.400	40.000	3.00	-1.14	± 5
1880	Head	1.421	39.641	1.400	40.000	1.50	-0.90	± 5
1850.2	Head	1.388	39.781	1.400	40.000	-0.86	-0.55	± 5
1909.8	Head	1.453	39.5	1.400	40.000	3.79	-1.25	± 5
1852.4	Head	1.391	39.772	1.400	40.000	-0.64	-0.57	± 5
1907.6	Head	1.451	39.504	1.400	40.000	3.64	-1.24	± 5
1860	Head	1.399	39.737	1.400	40.000	-0.07	-0.66	± 5

Liquid Verification above was performed on 2024/09/18.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
2450	Head	1.865	38.699	1.800	39.200	3.61	-1.28	± 5
2437	Head	1.850	38.757	1.788	39.219	3.47	-1.18	± 5
2412	Head	1.821	38.847	1.765	39.256	3.17	-1.04	± 5
2462	Head	1.879	38.649	1.812	39.183	3.70	-1.36	± 5
2535	Head	1.970	38.366	1.888	39.084	4.34	-1.84	± 5
2510	Head	1.939	38.465	1.861	39.117	4.19	-1.67	± 5

Liquid Verification above was performed on 2024/09/19

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
2600	Head	2.046	37.665	1.960	39.000	4.39	-3.42	± 5
2560	Head	1.999	38.250	1.916	39.051	4.33	-2.05	± 5
2595	Head	2.040	37.688	1.955	39.006	4.35	-3.38	± 5
2580	Head	2.022	37.745	1.938	39.025	4.33	-3.28	± 5
2610	Head	2.057	37.628	1.971	38.987	4.36	-3.49	± 5

Liquid Verification above was performed on 2024/09/19.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
5250	Head	4.758	36.537	4.710	35.900	1.02	1.77	± 5
5200	Head	4.693	36.658	4.660	36.000	0.71	1.83	± 5
5180	Head	4.668	36.699	4.639	36.020	0.63	1.89	± 5
5240	Head	4.744	36.545	4.701	35.960	0.91	1.63	± 5
5280	Head	4.788	36.458	4.740	35.920	1.01	1.50	± 5
5260	Head	4.764	36.524	4.721	35.940	0.91	1.62	± 5
5320	Head	4.836	36.364	4.780	35.880	1.17	1.35	± 5

Liquid Verification above was performed on 2024/09/20.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
5600	Head	5.169	35.709	5.070	35.500	1.95	0.59	± 5
5580	Head	5.143	35.778	5.070	35.500	1.44	0.78	± 5
5500	Head	5.047	35.945	4.965	35.650	1.65	0.83	± 5
5700	Head	5.291	35.489	5.170	35.400	2.34	0.25	± 5
5720	Head	5.317	35.439	5.190	35.380	2.45	0.17	± 5

Liquid Verification above was performed on 2024/09/21.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
5750	Head	5.353	35.371	5.220	35.400	2.55	-0.08	± 5
5785	Head	5.399	35.31	5.255	35.315	2.74	-0.01	± 5
5745	Head	5.347	35.384	5.215	35.355	2.53	0.08	± 5
5825	Head	5.445	35.208	5.296	35.275	2.81	-0.19	± 5

Liquid Verification above was performed on 2024/09/21.


System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- $s = 15 \text{ mm} \pm 0,2 \text{ mm}$ for $300 \text{ MHz} \leq f \leq 1\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $1\,000 \text{ MHz} < f \leq 3\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $3\,000 \text{ MHz} < f \leq 6\,000 \text{ MHz}$.

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band	Liquid Type	Input Power (mW)	Measured SAR (W/kg)		Normalized to 1W (W/kg)	Target Value (W/kg)	Delta (%)	Tolerance (%)
2024/09/16	835MHz	Head	250	1g	2.54	10.16	9.53	6.61	±10
2024/09/17	1750MHz	Head	250	1g	9.64	38.56	36.00	7.11	±10
2024/09/18	1900MHz	Head	250	1g	9.28	37.12	39.20	-5.31	±10
2024/09/19	2450MHz	Head	250	1g	14.20	56.8	53.10	6.97	±10
2024/09/19	2600MHz	Head	250	1g	13.30	53.2	54.90	-3.10	±10
2024/09/20	5250MHz	Head	100	1g	8.49	84.9	79.40	6.93	±10
2024/09/21	5600MHz	Head	100	1g	8.14	81.4	81.50	-0.12	±10
2024/09/21	5750MHz	Head	100	1g	8.04	80.4	79.00	1.77	±10

The SAR values above are normalized to 1 Watt forward power.

SAR SYSTEM VALIDATION DATA

System Check_Head_835MHz

DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:445

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.902$ S/m; $\epsilon_r = 41.842$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(9.88, 9.88, 9.88); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=250mW/Area Scan (6x6x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.63 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 57.85 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.71 W/kg

SAR(1 g) = 2.54 W/kg; SAR(10 g) = 1.68 W/kg

Maximum value of SAR (measured) = 2.95 W/kg



$$0 \text{ dB} = 2.95 \text{ W/kg} = 4.70 \text{ dBW/kg}$$

System Check_Head_1750MHz

DUT: Dipole 1750 MHz D1750V2; Type: D1750V2; Serial: D1750V2 - SN:1140

Communication System: UID 0, CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.373$ S/m; $\epsilon_r = 41.104$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(8.28, 8.28, 8.28); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=250mW/Area Scan (6x6x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 9.42 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 93.30 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 16.9 W/kg

SAR(1 g) = 9.64 W/kg; SAR(10 g) = 5.2 W/kg

Maximum value of SAR (measured) = 12.0 W/kg



$$0 \text{ dB} = 12.0 \text{ W/kg} = 10.79 \text{ dBW/kg}$$

System Check_Head_1900MHz

DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2 - SN:5d206

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.442$ S/m; $\epsilon_r = 39.543$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.92, 7.92, 7.92); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=250mW/Area Scan (7x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 11.2 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 88.48 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 16.4 W/kg

SAR(1 g) = 9.28 W/kg; SAR(10 g) = 4.93 W/kg

Maximum value of SAR (measured) = 11.6 W/kg



$$0 \text{ dB} = 11.6 \text{ W/kg} = 10.64 \text{ dBW/kg}$$

System Check_Head_2450MHz

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:970

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.865$ S/m; $\epsilon_r = 38.699$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.27, 7.27, 7.27); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=250mW/Area Scan (7x7x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 17.5 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.81 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 27.6 W/kg

SAR(1 g) = 14.2 W/kg; SAR(10 g) = 6.83 W/kg

Maximum value of SAR (measured) = 18.5 W/kg



$$0 \text{ dB} = 18.5 \text{ W/kg} = 12.67 \text{ dBW/kg}$$

System Check_Head_2600MHz

DUT: D2600V2-1162; Type: D2600V2; Serial: D2600V2 - SN:1162

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.046$ S/m; $\epsilon_r = 37.665$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.02, 7.02, 7.02); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=250mW/Area Scan (7x7x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 20.2 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.2 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 26.8 W/kg

SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.2 W/kg

Maximum value of SAR (measured) = 21.9 W/kg



0 dB = 21.9 W/kg = 13.40 dBW/kg

System Check_Head_5250MHz

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1296

Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.758$ S/m; $\epsilon_r = 36.537$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(5.25, 5.25, 5.25); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=100mW/Area Scan (9x9x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 16.4 W/kg


Pin=100mW/Zoom Scan (7x7x17)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.94 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 30.4 W/kg

SAR(1 g) = 8.49 W/kg; SAR(10 g) = 2.53 W/kg

Maximum value of SAR (measured) = 20.4 W/kg



$$0 \text{ dB} = 20.4 \text{ W/kg} = 13.10 \text{ dBW/kg}$$

System Check_Head_5600MHz

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1296

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.169$ S/m; $\epsilon_r = 35.709$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(4.63, 4.63, 4.63); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=100mW/Area Scan (9x9x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 9.47 W/kg


Pin=100mW/Zoom Scan (10x10x17)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 60.77 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 32.8 W/kg

SAR(1 g) = 8.14 W/kg; SAR(10 g) = 2.3 W/kg

Maximum value of SAR (measured) = 12.8 W/kg



$$0 \text{ dB} = 12.8 \text{ W/kg} = 11.07 \text{ dBW/kg}$$

System Check_Head_5750MHz

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1296

Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5750$ MHz; $\sigma = 5.353$ S/m; $\epsilon_r = 35.371$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(4.78, 4.78, 4.78); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=100mW/Area Scan (8x8x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 16.3 W/kg


Pin=100mW/Zoom Scan (7x7x17)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 62.40 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 33.7 W/kg

SAR(1 g) = 8.04 W/kg; SAR(10 g) = 2.39 W/kg

Maximum value of SAR (measured) = 19.5 W/kg



$$0 \text{ dB} = 19.5 \text{ W/kg} = 12.90 \text{ dBW/kg}$$

EUT TEST STRATEGY AND METHODOLOGY

Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

Test Distance for SAR Evaluation

In this case the EUT (Equipment under Test) is set against from the phantom, the test distance is 0mm (Body supported).

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.


All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.


CONDUCTED OUTPUT POWER MEASUREMENT

Test Procedure

The RF output of the transmitter was connected to the input of the Communication Test Set and Power Meter through Connector.



EGPRS&GPRS&WCDMA<E



WLAN&Bluetooth

Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

- > Slot configuration > Uplink/Gamma

- > 33 dBm for GPRS 850

- > 30 dBm for GPRS 1900

- > 27 dBm for EGPRS 850

- > 26 dBm for EGPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel
Hopping > Off

Main Timeslot > 3
Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)
Bit Stream > 2E9-1 PSR Bit Stream
AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
Connection Press Signal on to turn on the signal and change settings

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	$\beta_d(\text{SF})$	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c / β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs} = \beta_{hs} / \beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

HSPA+

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105
Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0). Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default. Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value. Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.											

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
NS_05	6.6.3.3.1	1	10, 15, 20	Table 6.2.4-4	
NS_06	6.6.2.2.3	12, 13, 14, 17	10, 15, 20	≥ 50	≤ 1
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 5.6-1	N/A
NS_08	6.6.3.3.3	19	10, 15	Table 6.2.4-2	
NS_09	6.6.3.3.4	21	10, 15	> 44	≤ 3
				> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

TDD-LTE

P TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

We used configuration 0 for LTE Band 38 SAR test, that is 63.33%(1:1.58)for duty cycle.

Maximum Target Output Power**Full Power Target power**

Mode/Band	Max Target Power(dBm)		
	Channel		
	Low	Middle	High
GSM850 GPRS 1 TX	33.0	33.0	33.0
GSM850 GPRS 2 TX	31.8	31.8	31.8
GSM850 GPRS 3 TX	29.5	29.5	29.5
GSM850 GPRS 4 TX	28.5	28.5	28.5
GSM850 EDGE 1 TX	26.5	26.5	26.5
GSM850 EDGE 2 TX	25.5	25.5	25.5
GSM850 EDGE 3 TX	24.5	24.5	24.5
GSM850 EDGE 4 TX	23.2	23.2	23.2
DCS1900GPRS 1 TX	28.6	28.6	28.6
DCS1900GPRS 2 TX	28	28	28
DCS1900GPRS 3 TX	25.3	25.3	25.3
DCS1900GPRS 4 TX	24.2	24.2	24.2
DCS1900EDGE 1 TX	25	25	25
DCS1900EDGE 2 TX	24.5	24.5	24.5
DCS1900EDGE 3 TX	22.5	22.5	22.5
DCS1900EDGE 4 TX	21.3	21.3	21.3
WCDMA Band 2	22.3	22.3	22.3
WCDMA Band 4	23.0	23.0	23.0
WCDMA Band 5	23	23	23
LTE Band 2	22.4	22.4	22.4
LTE Band 4	22.5	22.5	22.5
LTE Band 5	22.5	22.5	22.5
LTE Band 7	23.6	23.6	23.6
LTE Band 38	22.7	22.7	22.7
2.4G WLAN(802.11b)	16	16.5	16
2.4G WLAN(802.11g)	16	16	14
2.4G WLAN(802.11n20)	16	16	15
2.4G WLAN(802.11n40)	13	14	12
5.2G WLAN(802.11a)	14.3	14	14
5.2G WLAN(802.11n20)	14	14	13
5.2G WLAN(802.11n40)	14.2	/	14
5.2G WLAN(802.11ac20)	14	14	13
5.2G WLAN(802.11ac40)	14.2	/	14

5.2G WLAN(802.11ac80)	/	10	/
5.3G WLAN(802.11a)	14.3	13	13
5.3G WLAN(802.11n20)	14	14	14
5.3G WLAN(802.11n40)	14.2	/	10
5.3G WLAN(802.11ac20)	14	14	14
5.3G WLAN(802.11ac40)	14.2	/	10
5.3G WLAN(802.11ac80)	/	11	/
5.8G WLAN(802.11a)	16.5	15.5	15.5
5.8G WLAN(802.11n20)	16	15	15
5.8G WLAN(802.11n40)	16.3	/	15
5.8G WLAN(802.11ac20)	16	15	15
5.8G WLAN(802.11ac40)	16.3	/	15
5.8G WLAN(802.11ac80)	/	16.3	/
Bluetooth (BDR GFSK)	-2	-2	-3
Bluetooth (EDR $\pi/4$ -DQPSK)	-0.5	-0.5	-0.5
Bluetooth (EDR 8-DPSK)	-0.5	-0.5	-0.5
BLE (1M)	-2.5	-2.5	-2.5

Full Power Target power

Mode/Band	Max Target Power(dBm)			
	Channel			
	Low	Middle	Low High	High
5.6G WLAN(802.11a)	16	16.5	13.3	16.5
5.6G WLAN(802.11n20)	14.2	14.2	13	14.2
5.6G WLAN(802.11n40)	13	15.5	15.5	15
5.6G WLAN(802.11ac20)	14.2	14.2	13	14.2
5.6G WLAN(802.11ac40)	13	15.5	15.5	15
5.6G WLAN(802.11ac80)	11	15.5	16.3	/

Note:

Channels without Max Target Power are represented by /.

Test Results:**Maximum Output Power:****GPRS:**

Mode	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM850	128	824.2	32.70	31.63	29.25	28.22
	190	836.6	32.54	31.48	29.15	28.14
	251	848.8	32.66	31.66	29.28	28.44
DCS1900	512	1850.2	28.49	27.36	25.12	24.07
	661	1880	28.18	27.01	24.88	23.82
	810	1907.6	28.28	27.11	25.01	23.91

EGPRS:

Mode	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM850	128	824.2	26.32	25.35	24.06	23.09
	190	836.6	26.18	25.19	23.90	22.94
	251	848.8	26.15	25.23	23.83	22.82
DCS1900	512	1850.2	24.88	24.19	22.43	21.08
	661	1880	24.67	24.06	22.23	20.95
	810	1907.6	24.88	24.17	22.32	21.15

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power for GPRS

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM850	128	824.2	23.7	25.63	25	25.22
	190	836.6	23.54	25.48	24.9	25.14
	251	848.8	23.66	25.66	25.03	25.44
DCS1900	512	1850.2	19.49	21.36	20.87	21.07
	661	1880	19.18	21.01	20.63	20.82
	810	1907.6	19.28	21.11	20.76	20.91

The time based average power for EGPRS

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM850	128	824.2	17.32	19.35	19.81	20.09
	190	836.6	17.18	19.19	19.65	19.94
	251	848.8	17.15	19.23	19.58	19.82
DCS1900	512	1850.2	15.88	18.19	18.18	18.08
	661	1880	15.67	18.06	17.98	17.95
	810	1907.6	15.88	18.17	18.07	18.15

WCDMA Band 2

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power(dBm)		
			Low Channel	Mid Channel	High Channel
Normal	Rel 99 RMC	1	22.25	22.06	22.16
	HSDPA	1	21.90	22.04	21.81
		2	21.31	21.86	21.35
		3	22.15	21.32	21.99
		4	22.21	21.41	21.71
	HSUPA	1	21.27	21.12	21.49
		2	21.44	21.28	22.01
		3	22.06	21.39	21.88
		4	21.26	21.84	21.52
		5	22.09	21.95	21.44
	HSPA+	1	22.14	21.42	21.79

WCDMA Band 4

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power(dBm)		
			Low Channel	Mid Channel	High Channel
Normal	Rel 99 RMC	1	22.61	22.64	22.6
	HSDPA	1	22.15	22.04	21.98
		2	21.44	21.6	21.33
		3	21.38	21.24	21.66
		4	22.18	21.33	21.71
	HSUPA	1	21.77	21.58	21.25
		2	21.97	21.16	21.63
		3	21.36	21.41	21.71
		4	21.42	21.82	21.24
		5	22.21	21.37	21.91
	HSPA+	1	21.73	21.53	21.39

WCDMA Band 5

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power(dBm)		
			Low Channel	Mid Channel	High Channel
Normal	Rel 99 RMC	1	21.95	21.88	22.09
	HSDPA	1	21.60	21.41	22.02
		2	21.54	21.54	21.91
		3	21.53	21.40	21.68
		4	21.51	21.31	21.46
	HSUPA	1	22.00	21.78	21.13
		2	22.23	22.02	21.70
		3	21.81	21.63	21.34
		4	21.66	21.84	21.22
		5	21.54	21.17	21.84
	HSPA+	1	21.32	21.93	21.85

Note:

The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model 1.

LTE Band 2

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1#0	21.99	21.58	21.78
		1#3	21.57	21.21	21.24
		1#5	21.82	21.20	21.38
		3#0	22.17	21.93	22.01
		3#3	21.89	21.66	21.62
		6#0	21.32	21.26	21.55
	16-QAM	1#0	21.67	21.24	21.72
		1#3	21.55	21.75	21.79
		1#5	21.68	21.21	21.82
		3#0	21.33	21.65	21.92
		3#3	21.67	21.57	21.41
		6#0	22.17	21.27	21.44
3M	QPSK	1#0	21.43	21.31	21.53
		1#8	21.97	21.75	21.30
		1#14	21.55	21.88	21.89
		6#0	22.23	22.09	21.41
		6#9	22.12	21.36	21.02
		15#0	21.36	21.32	22.00
	16-QAM	1#0	21.28	21.96	21.32
		1#8	22.05	21.47	21.61
		1#14	21.40	21.41	21.35
		6#0	21.67	21.52	21.64
		6#9	22.18	21.38	21.95
		15#0	22.09	21.25	21.43

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	21.97	21.46	21.48
		1#13	21.56	21.69	21.24
		1#24	21.49	21.64	21.29
		15#0	22.15	21.39	21.51
		15#10	21.84	21.97	21.97
		25#0	21.39	21.13	21.96
	16-QAM	1#0	21.61	21.59	21.95
		1#13	21.47	21.42	21.27
		1#24	21.46	21.40	21.21
		15#0	21.31	21.13	21.91
		15#10	21.71	21.98	21.82
		25#0	21.68	22.02	21.67
10M	QPSK	1#0	21.74	21.68	21.08
		1#25	21.40	21.30	21.38
		1#49	21.93	21.47	21.98
		25#0	21.62	21.70	21.30
		25#25	21.78	21.16	21.87
		50#0	21.28	21.27	21.56
	16-QAM	1#0	21.81	21.14	21.10
		1#25	22.08	21.90	21.18
		1#49	21.63	21.59	21.67
		25#0	21.33	21.71	21.44
		25#25	21.52	22.10	21.89
		50#0	21.69	22.09	21.77

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	21.27	21.83	21.49
		1#38	21.58	21.87	21.30
		1#74	22.13	21.69	21.49
		36#0	22.13	21.32	21.13
		36#39	21.51	21.99	21.96
		75#0	21.93	21.28	21.56
	16-QAM	1#0	21.88	21.42	21.83
		1#38	21.71	21.57	21.89
		1#74	22.14	21.91	21.90
		36#0	22.20	21.20	21.99
		36#39	21.88	21.16	21.50
		75#0	21.89	21.66	21.81
20M	QPSK	1#0	22.13	22.01	22.29
		1#50	22.10	21.18	21.46
		1#99	22.07	21.52	21.11
		50#0	21.97	21.66	21.45
		50#50	22.06	21.72	21.24
		100#0	21.80	21.11	21.63
	16-QAM	1#0	21.46	21.12	21.21
		1#50	21.93	21.78	21.87
		1#99	21.72	21.76	21.59
		50#0	21.71	21.50	21.49
		50#50	21.79	21.15	21.44
		100#0	21.71	21.47	21.02

LTE Band 4

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1#0	22.04	21.95	22.26
		1#3	22.00	21.94	21.95
		1#5	21.92	22.02	21.93
		3#0	22.24	21.89	22.02
		3#3	22.03	22.21	22.06
		6#0	21.96	22.02	22.23
	16-QAM	1#0	21.93	22.18	22.07
		1#3	22.20	22.02	22.22
		1#5	22.14	22.06	22.22
		3#0	21.87	21.94	22.02
		3#3	21.87	22.03	22.19
		6#0	22.06	21.93	21.91
3M	QPSK	1#0	22.20	22.11	21.95
		1#8	22.20	22.17	22.13
		1#14	22.10	21.93	21.96
		6#0	21.93	22.16	22.26
		6#9	22.17	22.01	21.88
		15#0	22.18	22.06	22.26
	16-QAM	1#0	21.86	22.15	22.05
		1#8	21.95	22.16	22.08
		1#14	21.89	22.09	21.99
		6#0	22.06	21.95	22.06
		6#9	21.90	21.94	22.15
		15#0	22.17	21.97	22.20

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	22.06	22.25	22.25
		1#13	22.20	21.92	21.96
		1#24	22.10	22.26	21.90
		15#0	21.92	21.95	22.26
		15#10	21.93	22.22	21.92
		25#0	22.10	22.15	21.98
	16-QAM	1#0	21.98	22.04	22.17
		1#13	21.88	22.04	22.12
		1#24	21.95	21.88	22.22
		15#0	22.18	22.11	21.97
		15#10	22.21	21.88	22.25
		25#0	21.96	22.07	21.88
10M	QPSK	1#0	21.96	22.05	21.93
		1#25	22.20	22.22	22.25
		1#49	22.02	21.86	22.20
		25#0	21.97	21.88	22.19
		25#25	21.97	21.94	22.21
		50#0	21.89	22.01	22.24
	16-QAM	1#0	21.95	22.15	22.04
		1#25	22.06	22.15	22.10
		1#49	21.99	21.86	22.08
		25#0	21.97	21.90	21.88
		25#25	22.20	21.89	21.94
		50#0	22.12	22.09	22.11

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	22.20	21.91	22.18
		1#38	21.96	22.21	22.06
		1#74	21.88	22.18	22.15
		36#0	21.89	21.87	22.02
		36#39	21.96	22.22	22.14
		75#0	21.96	22.00	22.20
	16-QAM	1#0	22.01	22.18	22.10
		1#38	22.16	21.98	22.00
		1#74	21.93	21.91	22.06
		36#0	21.97	22.07	22.20
		36#39	22.21	22.06	22.23
		75#0	21.86	21.99	22.03
20M	QPSK	1#0	22.19	22.27	22.22
		1#50	21.99	21.98	22.22
		1#99	21.90	21.97	21.96
		50#0	22.13	21.97	22.05
		50#50	22.13	22.24	22.03
		100#0	21.87	21.86	21.88
	16-QAM	1#0	22.12	21.90	21.98
		1#50	22.03	21.92	22.24
		1#99	21.96	22.04	21.93
		50#0	22.12	22.24	22.22
		50#50	22.13	22.06	21.94
		100#0	22.02	22.13	22.23

LTE Band 5

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1#0	22.00	22.22	22.33
		1#3	22.36	22.17	21.84
		1#5	22.28	21.95	22.10
		3#0	22.00	22.02	22.14
		3#3	21.83	22.10	22.14
		6#0	22.32	22.31	22.38
	16-QAM	1#0	22.00	22.22	22.11
		1#3	22.24	22.28	22.04
		1#5	22.24	22.17	22.09
		3#0	22.05	22.13	22.12
		3#3	21.91	22.02	21.91
		6#0	22.16	21.95	22.33
3M	QPSK	1#0	22.14	22.03	21.83
		1#8	22.31	22.28	21.96
		1#14	22.25	22.31	22.28
		6#0	22.17	22.15	22.14
		6#9	21.99	21.90	22.08
		15#0	21.88	22.00	21.84
	16-QAM	1#0	22.33	22.28	22.11
		1#8	22.29	21.92	22.03
		1#14	22.19	21.84	21.96
		6#0	21.86	22.00	22.26
		6#9	22.19	21.93	22.12
		15#0	22.01	22.25	22.17

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	22.10	22.17	22.16
		1#13	21.85	22.29	22.19
		1#24	22.25	21.97	21.95
		15#0	21.84	21.87	21.83
		15#10	22.13	22.14	22.03
		25#0	21.90	22.13	21.98
	16-QAM	1#0	22.35	22.05	22.16
		1#13	22.23	22.09	22.21
		1#24	21.83	22.21	22.13
		15#0	22.23	22.21	21.83
		15#10	22.25	21.86	21.84
		25#0	22.14	21.96	21.92
10M	QPSK	1#0	22.03	22.39	22.23
		1#25	22.27	22.29	22.14
		1#49	22.33	22.01	22.38
		25#0	22.31	22.17	22.23
		25#25	22.11	22.12	21.98
		50#0	22.11	22.02	22.31
	16-QAM	1#0	22.33	21.91	22.18
		1#25	21.84	22.00	21.98
		1#49	22.12	22.19	22.28
		25#0	22.21	22.18	22.08
		25#25	21.97	22.28	21.94
		50#0	22.05	22.09	21.90

LTE Band 7

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	23.45	23.12	23.07
		1#13	22.99	23.22	23.19
		1#24	23.46	22.91	22.92
		15#0	23.18	23.18	23.42
		15#10	22.94	23.26	23.15
		25#0	23.24	23.21	23.08
	16-QAM	1#0	23.16	23.33	23.30
		1#13	23.27	23.38	23.11
		1#24	23.24	23.35	23.09
		15#0	23.13	23.19	23.09
		15#10	22.94	23.34	23.36
		25#0	23.40	23.14	23.11
10M	QPSK	1#0	23.22	23.14	23.23
		1#25	23.16	23.44	22.96
		1#49	23.43	23.16	23.29
		25#0	23.44	23.32	22.96
		25#25	23.27	23.25	22.92
		50#0	23.28	23.06	23.08
	16-QAM	1#0	23.12	23.12	23.15
		1#25	23.32	23.23	23.14
		1#49	23.32	23.12	23.25
		25#0	23.28	23.21	23.04
		25#25	23.45	23.32	23.28
		50#0	23.07	23.28	23.46

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	23.45	23.00	23.11
		1#38	23.38	23.18	23.08
		1#74	23.13	23.35	23.08
		36#0	23.15	23.02	23.09
		36#39	23.08	23.30	23.17
		75#0	23.17	23.36	23.25
	16-QAM	1#0	23.36	23.32	23.17
		1#38	23.38	23.27	23.32
		1#74	23.19	23.25	23.29
		36#0	23.35	23.24	23.32
		36#39	22.94	23.08	23.05
		75#0	23.18	23.16	23.11
20M	QPSK	1#0	23.48	23.33	23.06
		1#50	23.38	22.96	22.97
		1#99	23.34	23.06	23.27
		50#0	23.43	23.40	23.30
		50#50	23.31	23.25	23.41
		100#0	23.33	23.34	23.14
	16-QAM	1#0	22.97	23.02	23.44
		1#50	23.14	22.98	23.36
		1#99	23.34	23.41	22.96
		50#0	23.00	23.37	23.14
		50#50	22.92	23.32	23.29
		100#0	23.01	23.14	22.91

LTE Band 38

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	22.35	22.24	22.25
		1#13	22.55	22.26	22.39
		1#24	22.52	22.52	22.35
		15#0	22.54	22.24	22.55
		15#10	22.44	22.37	22.33
		25#0	22.36	22.34	22.49
	16-QAM	1#0	22.35	22.55	22.43
		1#13	22.28	22.54	22.50
		1#24	22.33	22.49	22.25
		15#0	22.40	22.55	22.46
		15#10	22.20	22.47	22.38
		25#0	22.33	22.24	22.20
10M	QPSK	1#0	22.35	22.30	22.26
		1#25	22.36	22.40	22.54
		1#49	22.31	22.49	22.26
		25#0	22.49	22.23	22.43
		25#25	22.45	22.25	22.21
		50#0	22.39	22.37	22.51
	16-QAM	1#0	22.38	22.54	22.30
		1#25	22.49	22.30	22.53
		1#49	22.29	22.29	22.52
		25#0	22.50	22.20	22.52
		25#25	22.27	22.38	22.44
		50#0	22.48	22.56	22.21

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	22.22	22.42	22.44
		1#38	22.28	22.25	22.39
		1#74	22.45	22.36	22.21
		36#0	22.47	22.49	22.53
		36#39	22.35	22.52	22.40
		75#0	22.55	22.53	22.41
	16-QAM	1#0	22.41	22.39	22.26
		1#38	22.23	22.29	22.42
		1#74	22.25	22.51	22.30
		36#0	22.31	22.28	22.37
		36#39	22.39	22.46	22.25
		75#0	22.39	22.27	22.40
20M	QPSK	1#0	22.58	22.43	22.31
		1#50	22.43	22.39	22.51
		1#99	22.19	22.21	22.40
		50#0	22.42	22.35	22.32
		50#50	22.34	22.33	22.28
		100#0	22.28	22.43	22.20
	16-QAM	1#0	22.56	22.20	22.50
		1#50	22.21	22.27	22.51
		1#99	22.43	22.32	22.47
		50#0	22.39	22.33	22.45
		50#50	22.50	22.32	22.34
		100#0	22.39	22.37	22.22

WLAN 2.4G:

Mode	Channel frequency (MHz)	Data Rate	Conducted Average Output Power(dBm)
802.11b	2412	1Mbps	15.592
	2437		16.201
	2462		15.941
802.11g	2412	6Mbps	15.282
	2437		15.915
	2462		13.385
802.11n HT20	2412	MCS0	15.131
	2437		15.795
	2462		14.422
802.11n HT40	2422	MCS0	12.356
	2437		13.256
	2452		11.427

Note:

2.4G wifi duty cycle is 98.14%. Refer to the report for details RKSA240319001-00B

WLAN 5.2G:

Test mode	Band	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	5150-5250 MHz	5180	13.707
		5200	13.557
		5240	13.054
802.11ac20	5150-5250 MHz	5180	13.521
		5200	13.371
		5240	12.872
802.11n-HT20	5150-5250 MHz	5180	13.434
		5200	13.361
		5240	12.789
802.11ac40	5150-5250 MHz	5190	13.646
		5230	13.576
802.11n-HT40	5150-5250 MHz	5190	13.758
		5230	13.586
802.11ac80	5150-5250 MHz	5210	9.295

Note:

5.2G wifi duty cycle is 97.38%. Refer to the report for details RKSA240319001-00D

WLAN 5.3G:

Test mode	Band	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	5250-5350 MHz	5260	13.525
		5280	12.494
		5320	12.704
802.11ac20	5250-5350 MHz	5260	13.372
		5280	13.317
		5320	13.498
802.11n-HT20	5250-5350 MHz	5260	13.326
		5280	13.314
		5320	13.485
802.11ac40	5250-5350 MHz	5270	13.435
		5310	9.945
802.11n-HT40	5250-5350 MHz	5270	13.288
		5310	9.763
802.11ac80	5250-5350 MHz	5290	10.403

Note:

5.3G wifi duty cycle is 97.38%. Refer to the report for details RKSA240319001-00D

WLAN 5.6G:

Test mode	Band	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	5470-5725 MHz	5500	15.515
		5580	15.733
		5700	12.539
		5720	15.811
802.11ac20	5470-5725 MHz	5500	13.442
		5580	13.665
		5700	12.549
		5720	14.144
802.11n-HT20	5470-5725 MHz	5500	13.428
		5580	13.663
		5700	12.541
		5720	14.137
802.11ac40	5470-5725 MHz	5510	12.764
		5550	14.363
		5670	15.176
		5710	14.536
802.11n-HT40	5470-5725 MHz	5510	12.772
		5550	14.166
		5670	15.099
		5710	14.469
802.11ac80	5470-5725 MHz	5530	10.675
		5610	15.225
		5690	15.615

Note:

5.6G wifi duty cycle is 98.14%. Refer to the report for details RKSA240319001-00D

WLAN 5.8G:

Test mode	Band	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	5725-5850 MHz	5745	15.706
		5785	14.926
		5825	15.003
802.11ac20	5725-5850 MHz	5745	15.555
		5785	14.776
		5825	14.559
802.11n-HT20	5725-5850 MHz	5745	15.145
		5785	14.606
		5825	14.457
802.11ac40	5725-5850 MHz	5755	15.629
		5795	14.741
802.11n-HT40	5725-5850 MHz	5755	15.483
		5795	14.639
802.11ac80	5725-5850 MHz	5775	15.562

Note:

5.8G wifi duty cycle is 97.38%. Refer to the report for details RKSA240319001-00D

Bluetooth:


Mode	Average Power (dBm)		
	Low	Middle	High
BDR(GFSK)	-3.34	-2.91	-3.76
EDR($\pi/4$ -DQPSK)	-1.41	-0.96	-1.80
EDR(8-DPSK)	-1.00	-0.71	-1.40

Mode	Average Power (dBm)		
	Low	Middle	High
BLE (1M)	-3.22	-2.72	-3.25

Standalone SAR test exclusion considerations

Antennas Location:

F360



Standalone SAR Test Exclusion Considerations

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
WLAN 2.4G	2437	16.5	44.67	0	13.95	3	No
WLAN 5.2G	5180	14.3	26.92	0	12.25	3	No
WLAN 5.3G	5260	14.3	26.92	0	12.35	3	No
WLAN 5.6G	5580	16.5	44.67	0	21.10	3	No
WLAN 5.8G	5745	16.5	44.67	0	21.41	3	No
Bluetooth	2480	-0.5	0.89	0	0.28	3	YES
BLE	2480	-2.5	0.56	0	0.18	3	YES

NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Standalone SAR estimation:

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Distance (mm)	Estimated 1-g (W/kg)
BT Body	2480	-0.5	0.89	10	0.04
BLE Body	2480	-2.5	0.56	10	0.02

Note: The bluetooth based Peak power for calculation.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$
 $[\sqrt{f(\text{GHz})/x}]$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR. and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion

According to KDB447498 D01 General RF Exposure Guidance v06: 4.3. General SAR test exclusion guidance

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz

Measurement Result:

For NFC, the power of EUT: E-Field@3m is 79.58 dBuV/m = -15.62dBm (0.03mW)

Note: $E[\text{dB } \mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$ for $d = 3$ m.

SAR test exclusion threshold for NFC(13.56MHz) separation distance < 50 mm

$$= [474 * (1 + \log(100/f(\text{MHz}))) / 2]$$

$$= 443\text{mW}$$

$$> 0.03 \text{ mW}$$

Conclusion:

The NFC SAR evaluation can be exempted.

Note:

For NFC, please refer to report RKSA240319001-00E

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

SAR Test Data

Environmental Conditions

Temperature:	22.2-23.1 °C	22.4-23.3 °C	22.5-23.3 °C
Relative Humidity:	54 %	53 %	52 %
Test Date:	2024/09/16	2024/09/17	2024/09/18
Temperature:	22.7-23.5 °C	22.5-23.1 °C	22.6-23.5 °C
Relative Humidity:	50 %	49 %	51 %
Test Date:	2024/09/19	2024/09/20	2024/09/21

Testing was performed by Allen

GSM850:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
GSM850	Front(0mm)	836.6	GPRS 2 Tx slots	31.48	31.8	1.076	0.046	0.049	1.6	
GSM850	Back (0mm)	836.6	GPRS 2 Tx slots	31.48	31.8	1.076	0.369	0.397	1.6	
GSM850	Back (0mm)	824.2	GPRS 2 Tx slots	31.63	31.8	1.040	0.501	0.521	1.6	1#
GSM850	Back(0mm)	848.8	GPRS 2 Tx slots	31.66	31.8	1.033	0.492	0.508	1.6	

PCS1900:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
DCS1900	Front(0mm)	1880	GPRS 2 Tx slots	27.01	28	1.256	0.056	0.070	1.6	
DCS1900	Back(0mm)	1880	GPRS 2 Tx slots	27.01	28	1.256	0.209	0.263	1.6	
DCS1900	Back(0mm)	1850.2	GPRS 2 Tx slots	27.36	28	1.159	0.266	0.308	1.6	2#
DCS1900	Back(0mm)	1909.8	GPRS 2 Tx slots	27.11	28	1.227	0.248	0.304	1.6	

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel must be used.

WCDMA Band 2:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WCDMA Band 2	Front(0mm)	1880	RMC	22.06	22.3	1.057	0.087	0.092	1.6	
WCDMA Band 2	Back(0mm)	1880	RMC	22.06	22.3	1.057	0.385	0.407	1.6	3#
WCDMA Band 2	Back(0mm)	1852.4	RMC	22.25	22.3	1.012	0.347	0.351	1.6	
WCDMA Band 2	Back(0mm)	1907.6	RMC	22.16	22.3	1.033	0.36	0.372	1.6	

WCDMA Band 4

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WCDMA Band 4	Front(0mm)	1732.6	RMC	22.64	23	1.086	0.072	0.078	1.6	
WCDMA Band 4	Back(0mm)	1732.6	RMC	22.64	23	1.086	0.474	0.515	1.6	4#
WCDMA Band 4	Back(0mm)	1712.4	RMC	22.61	23	1.094	0.434	0.475	1.6	
WCDMA Band 4	Back(0mm)	1752.6	RMC	22.6	23	1.096	0.392	0.430	1.6	

WCDMA Band 5

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WCDMA Band 5	Front(0mm)	836.6	RMC	21.88	23	1.294	0.033	0.043	1.6	
WCDMA Band 5	Back(0mm)	836.6	RMC	21.88	23	1.294	0.288	0.373	1.6	
WCDMA Band 5	Back(0mm)	826.4	RMC	21.95	23	1.274	0.332	0.423	1.6	5#
WCDMA Band 5	Back(0mm)	846.6	RMC	22.09	23	1.233	0.310	0.382	1.6	

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. The EUT transmit and receive through the same antenna while testing SAR.
3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model.
4. KDB 941225 D01-Body SAR is not required for HSUPA/HSDPA /HSPA+ when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.
5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

LTE FDD Band 2:

EUT Position	Freq. (MHz)	Modulation Type	Bandwidth (MHz)	RB	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
Front(0mm)	1880	QPSK	20	1RB	22.01	22.4	1.094	0.055	0.060	1.6	
Front(0mm)	1880	QPSK	20	50%RB	21.66	22.4	1.186	0.044	0.052	1.6	
Back(0mm)	1880	QPSK	20	1RB	22.01	22.4	1.094	0.236	0.258	1.6	6#
Back(0mm)	1860	QPSK	20	1RB	22.13	22.4	1.064	0.226	0.240	1.6	
Back(0mm)	1900	QPSK	20	1RB	22.29	22.4	1.026	0.219	0.225	1.6	
Back(0mm)	1880	QPSK	20	50%RB	21.66	22.4	1.186	0.197	0.234	1.6	

LTE FDD Band 4:

EUT Position	Freq. (MHz)	Modulation Type	Bandwidth (MHz)	RB	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
Front(0mm)	1732.5	QPSK	20	1RB	22.27	22.5	1.054	0.038	0.040	1.6	
Front(0mm)	1732.5	QPSK	20	50%RB	21.97	22.5	1.130	0.033	0.038	1.6	
Back(0mm)	1732.5	QPSK	20	1RB	22.27	22.5	1.054	0.330	0.348	1.6	7#
Back(0mm)	1720	QPSK	20	1RB	22.19	22.5	1.074	0.305	0.328	1.6	
Back(0mm)	1745	QPSK	20	1RB	22.22	22.5	1.067	0.292	0.311	1.6	
Back(0mm)	1732.5	QPSK	20	50%RB	21.97	22.5	1.130	0.254	0.287	1.6	

LTE FDD Band 5:

EUT Position	Freq. (MHz)	Modulation Type	Bandwidth (MHz)	RB	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
Front(0mm)	836.5	QPSK	10	1RB	22.39	22.5	1.026	0.016	0.016	1.6	
Front(0mm)	836.5	QPSK	10	50%RB	22.17	22.5	1.079	0.011	0.012	1.6	
Back(0mm)	836.5	QPSK	10	1RB	22.39	22.5	1.026	0.135	0.138	1.6	
Back(0mm)	829	QPSK	10	1RB	22.03	22.5	1.114	0.189	0.211	1.6	
Back(0mm)	844	QPSK	10	1RB	22.23	22.5	1.064	0.199	0.212	1.6	8#
Back(0mm)	836.5	QPSK	10	50%RB	22.17	22.5	1.079	0.155	0.167	1.6	

LTE FDD Band 7:

EUT Position	Freq. (MHz)	Modulation Type	Bandwidth (MHz)	RB	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
Front(0mm)	2535	QPSK	20	1RB	23.33	23.6	1.064	0.009	0.010	1.6	
Front(0mm)	2535	QPSK	20	50%RB	23.4	23.6	1.047	0.006	0.007	1.6	
Back(0mm)	2535	QPSK	20	1RB	23.33	23.6	1.064	0.324	0.345	1.6	
Back(0mm)	2510	QPSK	20	1RB	23.48	23.6	1.028	0.272	0.280	1.6	
Back(0mm)	2560	QPSK	20	1RB	23.06	23.6	1.132	0.360	0.408	1.6	9#
Back(0mm)	2535	QPSK	20	50%RB	23.4	23.6	1.047	0.293	0.307	1.6	

LTE TDD Band 38:

EUT Position	Freq. (MHz)	Modulation Type	Bandwidth (MHz)	RB	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
Front(0mm)	2595	QPSK	20	1RB	22.43	22.7	1.064	0.006	0.006	1.6	
Front(0mm)	2595	QPSK	20	50%RB	22.35	22.7	1.084	0.003	0.003	1.6	
Back(0mm)	2595	QPSK	20	1RB	22.43	22.7	1.064	0.303	0.322	1.6	
Back(0mm)	2580	QPSK	20	1RB	22.58	22.7	1.028	0.346	0.356	1.6	
Back(0mm)	2610	QPSK	20	1RB	22.31	22.7	1.094	0.430	0.470	1.6	10#
Back(0mm)	2595	QPSK	20	50%RB	22.35	22.7	1.084	0.255	0.276	1.6	

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. Worst case SAR for 50% RB allocation is selected to be tested.
3. KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg.
4. KDB941225D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

WLAN 2.4G:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Duct cycle Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WLAN2.4G	Front(0mm)	2437	802.11b 1Mbps	16.201	16.5	1.071	1.019	0.032	0.035	1.6	
WLAN2.4G	Back(0mm)	2437	802.11b 1Mbps	16.201	16.5	1.071	1.019	0.114	0.124	1.6	11#
WLAN2.4G	Back(0mm)	2412	802.11b 1Mbps	15.592	16	1.098	1.019	0.089	0.099	1.6	
WLAN2.4G	Back(0mm)	2462	802.11b 1Mbps	15.941	16	1.014	1.019	0.089	0.092	1.6	

WLAN 5.2G:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Duct cycle Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WLAN5.2G	Front(0mm)	5200	802.11a 6Mbps	13.557	14	1.107	1.027	0.022	0.025	1.6	
WLAN5.2G	Back(0mm)	5200	802.11a 6Mbps	13.557	14	1.107	1.027	0.224	0.255	1.6	12#
WLAN5.2G	Back(0mm)	5180	802.11a 6Mbps	13.707	14.3	1.146	1.027	0.198	0.233	1.6	
WLAN5.2G	Back(0mm)	5240	802.11a 6Mbps	13.054	14	1.243	1.027	0.151	0.193	1.6	

WLAN 5.3G:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Duct cycle Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WLAN5.3G	Front(0mm)	5280	802.11a 6Mbps	12.494	13	1.124	1.027	0.021	0.025	1.6	
WLAN5.3G	Back(0mm)	5280	802.11a 6Mbps	12.494	13	1.124	1.027	0.176	0.203	1.6	13#
WLAN5.3G	Back(0mm)	5260	802.11a 6Mbps	13.525	14.3	1.195	1.027	0.156	0.192	1.6	
WLAN5.3G	Back(0mm)	5320	802.11a 6Mbps	12.704	13	1.071	1.027	0.128	0.141	1.6	

WLAN 5.6G:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Duct cycle Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WLAN5.6G	Front(0mm)	5580	802.11a 6Mbps	15.733	16.5	1.193	1.019	0.027	0.033	1.6	
WLAN5.6G	Back(0mm)	5580	802.11a 6Mbps	15.733	16.5	1.193	1.019	0.159	0.193	1.6	14#
WLAN5.6G	Back(0mm)	5500	802.11a 6Mbps	15.515	16	1.118	1.019	0.118	0.134	1.6	
WLAN5.6G	Back(0mm)	5700	802.11a 6Mbps	12.539	13.3	1.192	1.019	0.115	0.140	1.6	
WLAN5.6G	Back(0mm)	5720	802.11a 6Mbps	15.811	16.5	1.172	1.019	0.137	0.164	1.6	

WLAN 5.8G:

Band	EUT Position	Freq. (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	Scaled Factor	Duct cycle Factor	Meas. (W/Kg)	Scaled SAR (W/Kg)	Limit (W/Kg)	Plot
WLAN5.8G	Front(0mm)	5785	802.11a 6Mbps	14.926	15.5	1.141	1.027	0.017	0.020	1.6	
WLAN5.8G	Back(0mm)	5785	802.11a 6Mbps	14.926	15.5	1.141	1.027	0.157	0.184	1.6	15#
WLAN5.8G	Back(0mm)	5745	802.11a 6Mbps	15.706	16.5	1.201	1.027	0.135	0.166	1.6	
WLAN5.8G	Back(0mm)	5825	802.11a 6Mbps	15.003	15.5	1.121	1.027	0.119	0.137	1.6	

Note:

1. When the SAR Value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel must be used.
4. According to IEC62209-1, If the correction Δ SAR is within $\pm 5\%$, the measured SAR results should not be corrected.

SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA/LTE) + 2.4GWLAN+NFC	√	×
WWAN(GSM/WCDMA/LTE) + 5GWLAN+NFC	√	×
WWAN(GSM/WCDMA/LTE) + Bluetooth+NFC	√	×

Simultaneous Transmission Consideration Detail

Transmitter Combination	Position	Max SAR(W/kg)		Σ SAR< 1.6W/kg
		SAR1(WWAN)	SAR2(WLAN)	
WWAN+ 2.4GWLAN	Body Front	0.092	0.035	0.127
	Body Back	0.521	0.124	0.645

Transmitter Combination	Position	Max SAR(W/kg)		Σ SAR< 1.6W/kg
		SAR1(WWAN)	SAR2(WLAN)	
WWAN+5GWLAN	Body Front	0.092	0.033	0.125
	Body Back	0.521	0.255	0.776

Transmitter Combination	Position	Max SAR(W/kg)		Σ SAR< 1.6W/kg
		SAR1(WWAN)	SAR2(WLAN)	
WWAN+Bluetooth	Body	0.521	0.04	0.561

Conclusion:

Sum of SAR: **1.6 W/kg** therefore simultaneous transmission SAR result is **Compliance**.

APPENDIX A SAR PLOTS OF SAR MEASUREMENT

1#_GSM850_GPRS 2 Tx slots_Back_0mm_Ch128

Communication System: UID 0, GSM850 (0); Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 824.2$ MHz; $\sigma = 0.892$ S/m; $\epsilon_r = 41.983$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(9.88, 9.88, 9.88); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.838 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.63 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.69 W/kg

SAR(1 g) = 0.501 W/kg; SAR(10 g) = 0.228 W/kg

Maximum value of SAR (measured) = 1.07 W/kg



0 dB = 1.07 W/kg = 0.29 dBW/kg

2#_GSM1900_GPRS 2 Tx slots_Back_0mm_Ch512

Communication System: UID 0, GSM 1900 (0); Frequency: 1850.2 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.388$ S/m; $\epsilon_r = 39.781$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.92, 7.92, 7.92); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.404 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.978 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.549 W/kg

SAR(1 g) = 0.266 W/kg; SAR(10 g) = 0.135 W/kg

Maximum value of SAR (measured) = 0.444 W/kg



$$0 \text{ dB} = 0.444 \text{ W/kg} = -3.53 \text{ dBW/kg}$$

3#_WCDMA II_RMC 12.2Kbps_Back_0mm_Ch9400

Communication System: UID 0, WCDMA 3G (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.421$ S/m; $\epsilon_r = 39.641$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.92, 7.92, 7.92); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.430 W/kg


Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.997 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.901 W/kg

SAR(1 g) = 0.385 W/kg; SAR(10 g) = 0.193 W/kg

Maximum value of SAR (measured) = 0.737 W/kg



0 dB = 0.737 W/kg = -1.33 dBW/kg

4#_WCDMA IV_RMC 12.2Kbps_Back_0mm_Ch1413

Communication System: UID 0, WCDMA 3G (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1732.6$ MHz; $\sigma = 1.356$ S/m; $\epsilon_r = 41.174$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(8.28, 8.28, 8.28); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.515 W/kg


Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.685 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.474 W/kg; SAR(10 g) = 0.215 W/kg

Maximum value of SAR (measured) = 1.07 W/kg



$$0 \text{ dB} = 1.07 \text{ W/kg} = 0.29 \text{ dBW/kg}$$

5#_ WCDMA V_RMC 12.2Kbps_Back_0mm_Ch4132

Communication System: UID 0, WCDMA 3G (0); Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.894$ S/m; $\epsilon_r = 41.955$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(9.88, 9.88, 9.88); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.547 W/kg


Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.329 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.332 W/kg; SAR(10 g) = 0.148 W/kg

Maximum value of SAR (measured) = 0.685 W/kg



0 dB = 0.685 W/kg = -1.64 dBW/kg

6#_LTE Band 2_20M_QPSK_1RB_0offset_Back_0mm_Ch18900

Communication System: UID 0, FDD LTE 4G (0); Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.421$ S/m; $\epsilon_r = 39.641$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.92, 7.92, 7.92); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.289 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.239 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.559 W/kg

SAR(1 g) = 0.236 W/kg; SAR(10 g) = 0.114 W/kg

Maximum value of SAR (measured) = 0.445 W/kg



0 dB = 0.445 W/kg = -3.52 dBW/kg

7#_LTE Band 4_20M_QPSK_1RB_0offset_Back_0mm_Ch20175

Communication System: UID 0, FDD LTE 4G (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.356$ S/m; $\epsilon_r = 41.174$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(8.28, 8.28, 8.28); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.320 W/kg


Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.982 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.945 W/kg

SAR(1 g) = 0.330 W/kg; SAR(10 g) = 0.151 W/kg

Maximum value of SAR (measured) = 0.770 W/kg



0 dB = 0.770 W/kg = -1.14 dBW/kg

8#_LTE Band 5_10M_QPSK_1RB_0offset_Back_0mm_Ch20600

Communication System: UID 0, FDD LTE 4G (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 41.725$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(9.88, 9.88, 9.88); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.392 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.777 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.656 W/kg

SAR(1 g) = 0.199 W/kg; SAR(10 g) = 0.097 W/kg

Maximum value of SAR (measured) = 0.414 W/kg



$$0 \text{ dB} = 0.414 \text{ W/kg} = -3.83 \text{ dBW/kg}$$

9#_LTE Band 7_20M_QPSK_1RB_0offset_Back_0mm_Ch21350

Communication System: UID 0, FDD LTE 4G (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.999$ S/m; $\epsilon_r = 38.25$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.02, 7.02, 7.02); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (12x12x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.457 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.6850 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.814 W/kg

SAR(1 g) = 0.360 W/kg; SAR(10 g) = 0.165 W/kg

Maximum value of SAR (measured) = 0.605 W/kg



0 dB = 0.605 W/kg = -2.18 dBW/kg

10#_LTE Band 38_20M_QPSK_1RB_0offset_Back_0mm_Ch38150

Communication System: UID 0, TDD LTE 4G (0); Frequency: 2610 MHz; Duty Cycle: 1:1.58

Medium parameters used : $f = 2610$ MHz; $\sigma = 2.057$ S/m; $\epsilon_r = 37.628$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.02, 7.02, 7.02); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (12x12x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.643 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.5410 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.15 W/kg

SAR(1 g) = 0.430 W/kg; SAR(10 g) = 0.178 W/kg

Maximum value of SAR (measured) = 0.831 W/kg



0 dB = 0.831 W/kg = -0.80 dBW/kg

11#_WLAN 2.4GHz_802.11b 1Mbps_Back_0mm_Ch6

Communication System: UID 0, WIFI2.4G (0); Frequency: 2437 MHz; Duty Cycle: 1: 1.019

Medium parameters used : $f = 2437$ MHz; $\sigma = 1.85$ S/m; $\epsilon_r = 38.757$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.27, 7.27, 7.27); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (12x12x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.218 W/kg


Zoom Scan (10x9x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.351 W/kg

SAR(1 g) = 0.114 W/kg; SAR(10 g) = 0.060 W/kg

Maximum value of SAR (measured) = 0.221 W/kg



$$0 \text{ dB} = 0.221 \text{ W/kg} = -6.56 \text{ dBW/kg}$$

12#_WLAN 5.2GHz_802.11a 6Mbps_Back_0mm_Ch40

Communication System: UID 0, WIFI 5G (0); Frequency: 5200 MHz; Duty Cycle: 1: 1.027

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.693$ S/m; $\epsilon_r = 36.658$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(5.25, 5.25, 5.25); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x15x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.322 W/kg


Zoom Scan (9x9x17)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.722 W/kg

SAR(1 g) = 0.224 W/kg; SAR(10 g) = 0.071 W/kg

Maximum value of SAR (measured) = 0.537 W/kg



$$0 \text{ dB} = 0.537 \text{ W/kg} = -2.70 \text{ dBW/kg}$$

13#_WLAN 5.3GHz_802.11a 6Mbps_Back_0mm_Ch56

Communication System: UID 0, WIFI 5G (0); Frequency: 5280 MHz; Duty Cycle: 1: 1.027

Medium parameters used: $f = 5280$ MHz; $\sigma = 4.788$ S/m; $\epsilon_r = 36.458$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(5.25, 5.25, 5.25); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x14x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.269 W/kg


Zoom Scan (9x9x17)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.946 W/kg

SAR(1 g) = 0.176 W/kg; SAR(10 g) = 0.051 W/kg

Maximum value of SAR (measured) = 0.407 W/kg



14#_WLAN 5.6GHz_802.11a 6Mbps_Back_0mm_Ch116

Communication System: UID 0, WIFI 5G (0); Frequency: 5580 MHz; Duty Cycle: 1: 1.019

Medium parameters used: $f = 5580$ MHz; $\sigma = 5.143$ S/m; $\epsilon_r = 35.778$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(4.63, 4.63, 4.63); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x14x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.297 W/kg


Zoom Scan (9x9x17)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.432 W/kg

SAR(1 g) = 0.159 W/kg; SAR(10 g) = 0.045 W/kg

Maximum value of SAR (measured) = 0.318 W/kg



0 dB = 0.318 W/kg = -4.98 dBW/kg

15#_WLAN 5.8GHz_802.11a 6Mbps_Back_0mm_Ch157

Communication System: UID 0, WIFI 5G (0); Frequency: 5785 MHz; Duty Cycle: 1: 1.027

Medium parameters used : $f = 5785$ MHz; $\sigma = 5.399$ S/m; $\epsilon_r = 35.31$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(4.78, 4.78, 4.78); Calibrated: 3/26/2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 3/26/2024
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (10x14x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.329 W/kg


Zoom Scan (9x9x17)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.441 W/kg

SAR(1 g) = 0.157 W/kg; SAR(10 g) = 0.044 W/kg

Maximum value of SAR (measured) = 0.312 W/kg



$$0 \text{ dB} = 0.329 \text{ W/kg} = -4.83 \text{ dBW/kg}$$

APPENDIX B MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE 1528:2013 SAR test


Source of uncertainty	Tolerance/ uncertainty $\pm$ %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty $\pm$ %, (1 g)	Standard uncertainty $\pm$ %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Test sample related							
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Device holder uncertainty	6.3	N	1	1	1	6.3	6.3
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Liquid conductivity target)	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity target)	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Combined standard uncertainty		RSS				12.2	12.0
Expanded uncertainty 95 % confidence interval)						24.3	23.9

Measurement uncertainty evaluation for IEC 62209-2:2010 SAR test


Source of uncertainty	Tolerance/ uncertainty $\pm$ %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty $\pm$ %, (1 g)	Standard uncertainty $\pm$ %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Modulation Response	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Test sample related							
Device holder Uncertainty	6.3	N	1	1	1	6.3	6.3
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Power scaling	4.5	R	$\sqrt{3}$	1	1	2.6	2.6
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Algorithm for correcting SAR for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.1	0.9
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity (meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Temp. unc. - Conductivity	1.7	R	$\sqrt{3}$	0.78	0.71	0.8	0.7
Temp. unc. - Permittivity	0.3	R	$\sqrt{3}$	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.2	12.1
Expanded uncertainty 95 % confidence interval)						24.5	24.2

APPENDIX C EUT TEST POSITION PHOTOS


Liquid depth $\geq 15\text{cm}$



WWAN/WLAN Front (0mm)



WWAN/WLAN Back (0mm)



APPENDIX D CALIBRATION CERTIFICATES

Please Refer to the Attachment.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.
6. This report may contain standards and test items that are not covered by the accreditation scope and shall be marked with an asterisk “▲”.

***** END OF REPORT *****