



14. Radio Frequency Exposure

14.1 Applicable Standards

<input type="checkbox"/>	§1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.				
<input type="checkbox"/>	§1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and the antenna / radiating structure, where $R > \lambda / 2\pi$.				
TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION						
RF Source Frequency		Minimum Distance			Threshold ERP	
f_L MHz	f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W		
0.3	—	1.34	159 m	—	35.6 m	1,920 R^2
1.34	—	30	35.6 m	—	1.6 m	3,450 R^2/f^2
30	—	300	1.6 m	—	159 mm	3.83 R^2
300	—	1,500	159 mm	—	31.8 mm	0.0128 R^2/f
1,500	—	100,000	31.8 mm	—	0.5 mm	19.2 R^2
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						
Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$						
P_{th} (mW) = $\begin{cases} ERP_{20\ cm}(d/20\ cm)^x & d \leq 20\ cm \\ ERP_{20\ cm} & 20\ cm < d \leq 40\ cm \end{cases}$						
Where						
$x = -\log_{10} \left(\frac{60}{ERP_{20\ cm} \sqrt{f}} \right)$ and f is in GHz;						
and						
$ERP_{20\ cm}$ (mW) = $\begin{cases} 2040f & 0.3\ GHz \leq f < 1.5\ GHz \\ 3060 & 1.5\ GHz \leq f \leq 6\ GHz \end{cases}$						
d = the separation distance (cm);						



14.2 EUT Specification

Frequency band (Operating)	<input type="checkbox"/> WLAN: 2412MHz ~ 2462MHz <input type="checkbox"/> WLAN: 5150MHz ~ 5250MHz <input type="checkbox"/> WLAN: 5250MHz ~ 5350MHz <input type="checkbox"/> WLAN: 5470MHz ~ 5725MHz <input type="checkbox"/> WLAN: 5725MHz ~ 5850MHz <input type="checkbox"/> Bluetooth: 2402MHz ~ 2480MHz <input checked="" type="checkbox"/> 902MHz~928MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption (20 公分以上) <input type="checkbox"/> SAR-based Exemption (20 公分以下)
Remark: The maximum conducted output power is <u>29.18dBm (827.942 mW)</u> at <u>927.25MHz</u> (with <u>5.5dBi antenna gain</u> .)	

14.3 Result

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Antenna Cable Loss(dB)	Max.Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p power (mW)
927.25	29.18	29.68	5.5	0.5	32.53	1790.61

No non-compliance noted.

-----THE END OF REPORT-----