

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: ShenZhen Foscam Intelligent Technology Co., Limited
Address of applicant: 9/F, Block F5, TCL International E City, No.1001 ZhongShanyuan Rd.,
NanShan District, Shenzhen, China,

Manufacturer: ShenZhen Foscam Intelligent Technology Co., Limited
Address of manufacturer: 9/F, Block F5, TCL International E City, No.1001 ZhongShanyuan Rd.,
NanShan District, Shenzhen, China,

General Description of EUT:

Product Name: Optical Zoom PTZ IP Camera
Trade Name: FOSCAM
Model No.: FI9926P
R2 Plus、 R2 Plus VX、 Z2、 Z2 VX、 FI9926P、 FI9926P VX、 R2P、
Adding Model(s): R2P VX、 R4 Plus、 R4 Plus VX、 R4P、 R4P VX (Note “VX” represent
the software version ,which “X” can be from 0 to 9)
FCC ID: ZDEFI9926P
Rated Voltage: DC5V

Technical Characteristics of EUT:

Support Standards: 802.11a, 802.11n(HT20) , 802.11n-HT40, 802.11ac-VH80
Frequency Range: 5150-5250MHz, 5725-5850MHz
RF Output Power: 9.80dBm (Conducted)
Type of Modulation: QPSK, 16QAM, 64QAM
Data Rate: 6-54Mbps, up to 200Mbps
Quantity of Channels: 15
Type of Antenna: External Antenna
Antenna Gain: 2.0dBi
Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n-HT20
RF Output Power: 9.84dBm (Conducted)
Type of Modulation: CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate: 1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels: 11 for 802.11b/g/n-HT20
Channel Separation: 5MHz
Type of Antenna: External Antenna
Antenna Gain: 2.0dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalent power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For WIFI2.4GHz:

Maximum Tune-Up output power: 9.84 (dBm)

Maximum peak output power at antenna input terminal: 9.64 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2462 (MHz)

Antenna gain: 2.0 (dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.003(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

For WIFI5.1GHz:

Maximum Tune-Up output power: 9.80 (dBm)

Maximum peak output power at antenna input terminal: 9.55 (mW)

Prediction distance: >20(cm)

Prediction frequency: 5200 (MHz)

Antenna gain: 2.0 (dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.003(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

For WIFI5.8GHz:

Maximum Tune-Up output power: 9.40 (dBm)

Maximum peak output power at antenna input terminal: 8.71 (mW)

Prediction distance: >20(cm)

Prediction frequency: 5785 (MHz)

Antenna gain: 2.0 (dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.003(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass