

# 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

---

## 1.1 General Information

### Client Information

Applicant: ShenZhen Foscam Intelligent Technology Co., Limited  
Address of applicant: Room A, 9/F, Block F5, TCL International E City, No. 1001  
Zhongshanyuan Road, Xili Street, Nanshan District, shenzhen

Manufacturer: ShenZhen Foscam Intelligent Technology Co., Limited  
Address of manufacturer: Room A, 9/F, Block F5, TCL International E City, No. 1001  
Zhongshanyuan Road, Xili Street, Nanshan District, shenzhen

### General Description of EUT:

Product Name: Battery Camera  
Trade Name: FOSCAM  
Model No.: S1  
Adding Model(s): S1 VX, FR5008W VX, S2 VX, FR5016W VX, S3 VX, FR5032W VX,  
FN5108W VX, FR5108W VX, FN5008WR VX, FR5008WR VX,  
FN500WE VX, FR5008WE VX

FCC ID: ZDES1  
Rated Voltage: DC 12V  
Battery Capacity:

### Technical Characteristics of EUT:

Support Standards: 802.11b, 802.11g, 802.11n  
Frequency Range: 2412-2462MHz  
Max RF Output Power: Antenna 0: 13.06dBm (Conducted)  
Antenna 1: 13.98dBm (Conducted)  
Type of Modulation: CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM  
Type of Antenna: External Antenna  
Antenna Gain: 5.0dBi  
Device Category: fixed Device

## 1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E)	Magnetic Field Strength (H)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or
--------------------------	--------------------------------	--------------------------------	--	---

	(V/m)	(A/m)		S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: \* = Plane-wave equivalent power density

### 1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 1.4 MPE Calculation Result

### WIFI Ant 0:

Maximum Tune-Up output power: 13.06 (dBm)

Maximum peak output power at antenna input terminal: 20.23 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2412(MHz)

Antenna gain: 5.0(dBi)

Directional gain (numeric gain): 3.16

The worst case is power density at prediction frequency at 20cm: 0.013(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

### WIFI Ant 1:

Maximum Tune-Up output power: 13.98 (dBm)

Maximum peak output power at antenna input terminal: 25.00 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2462(MHz)

Antenna gain: 5.0(dBi)

Directional gain (numeric gain): 3.16

The worst case is power density at prediction frequency at 20cm: 0.016(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

### Transmit simultaneously with WIFI Ant 0 and WIFI Ant 1 11n-HT20/40:

Maximum Tune-Up output power: 16.04 (dBm)

Maximum peak output power at antenna input terminal: 40.18 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2437(MHz)

Antenna gain: 5.0(dBi)

Directional gain (numeric gain): 3.16

The worst case is power density at prediction frequency at 20cm: 0.025(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

Result: Pass

## 1.5 Test Setup Photos

