

TEST REPORT

Product Name : Wireless IP Camera
Model Number : SD8P, SD8, SD8T, SD8V
FCC ID : ZDESD8P

Prepared for : ShenZhen Foscam Intelligent Technology Co., Ltd
Address : Room 902, Building 1B, Shenzhen International
innovationValley, Xingke 1st Street, Nanshan District,
Shenzhen, Guangdong, China, 518055.

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2406070166E00803R
Date(s) of Tests : June 07, 2024 to August 22, 2024
Date of issue : August 22, 2024

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
RF EXPOSURE EVALUATION	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : ShenZhen Foscam Intelligent Technology Co., Ltd

Address : Room 902,Building 1B, Shenzhen International innovationValley, Xingke 1st Street, Nanshan District, Shenzhen,Guangdong, China, 518055.

Manufacturer : ShenZhen Foscam Intelligent Technology Co., Ltd

Address : Room 902,Building 1B, Shenzhen International innovationValley, Xingke 1st Street, Nanshan District, Shenzhen,Guangdong, China, 518055.

Factory : ShenZhen Foscam Intelligent Technology Co., Ltd

Address : 701, 7th Floor, Building D, Guangming Port Intelligent Manufacturing Innovation Park, No. 8 Jinjun Road, Huangjiang Town, Dongguan, Guangdong, China, 523769

EUT : Wireless IP Camera

Model Name : SD8P, SD8, SD8T, SD8V

Trademark : FOSCAM

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : June 07, 2024 to August 22, 2024

Prepared by : *Warren Deng*

Warren Deng /Editor

Reviewer : *Tim Dong*

Tim Dong /Supervisor

Approve & Authorized Signer : 

Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2406070166E00803R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Wireless IP Camera
Model Number:	SD8P, SD8, SD8T, SD8V (The Model: SD8P is the same as the Model: SD8, SD8T, SD8V in hardware aspect. The difference in model number serves as marketing strategy.)
Sample:	1#
Data Rate:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Modulation:	DSSS, OFDM
Operating Frequency Range(s) :	2412-2462MHz for 802.11b/g/n(HT20); 2422-2452MHz for 802.11n(HT40); 5745-5825MHz for 802.11a/n(HT20); 5755-5795MHz for 802.11n(HT40);
Transmit Power Max:	2.4G WIFI: 16.12 dBm(0.040926 W) UNII-3 Band: 12.69 dBm(0.018578 W)
Antenna Gain:	5.12dBi for 2.4G WIFI 4.36dBi for UNII-3 Band
Power supply:	DC 12V 2A from Adapter
Hardware version:	1.0
Evaluation applied:	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

gain:	5.12 dBi	WIFI 2.4G FCC EMF							
Mode	Frequency (MHz)	Output Power (dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power(dBm) tolerance	Max tuneup power(mW) tolerance	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
802.11b	2412	16.10	21.22	8±1	22	158.49	0.102501	1	PASS
	2437	15.62	20.74	9±1	21	125.89	0.081420	1	PASS
	2462	14.87	19.99	6±1	20	100.00	0.064674	1	PASS
802.11g	2412	15.77	20.89	7±1	21	125.89	0.081420	1	PASS
	2437	14.8	19.92	5±1	20	100.00	0.064674	1	PASS
	2462	15.18	20.3	6±1	21	125.89	0.081420	1	PASS
802.11n(HT 20)	2412	15.78	20.9	-1±1	21	125.89	0.081420	1	PASS
	2437	14.66	19.78	-1±1	20	100.00	0.064674	1	PASS
	2462	14.44	19.56	-2±1	20	100.00	0.064674	1	PASS
802.11n(HT 40)	2422	15.48	20.6	2±1	21	125.89	0.081420	1	PASS
	2437	14.63	19.75	-4±1	20	100.00	0.064674	1	PASS
	2452	14.32	19.44	-3±1	20	100.00	0.064674	1	PASS

gain:	UNII-3 Band: 4.36 dBi									
Mode	Frequency (MHz)	Output Power (dBm)	E.I.R.P(dBm)	Target Power W/tolera nce (dBm)	Max tune up power(dB m) tolerance	Max tuneup power(mW) toleranc e	Power Density at R=20cm (mW/cm 2)	Limit (mW/ cm2)	Verd ict	
802.11a	5745	12.69	17.05	8±1	18	63.10	0.034255	1	Pass	
	5785	11.36	15.72	9±1	16	39.81	0.021614	1	Pass	
	5825	12.45	16.81	6±1	17	50.12	0.027210	1	Pass	
802.11n(HT 20)	5745	12.51	16.87	7±1	17	50.12	0.027210	1	Pass	
	5785	11.21	15.57	5±1	16	39.81	0.021614	1	Pass	
	5825	12.33	16.69	6±1	17	50.12	0.027210	1	Pass	
802.11n(HT 40)	5795	11.89	16.25	-1±1	17	50.12	0.027210	1	Pass	
	5775	11.02	15.38	-1±1	16	39.81	0.021614	1	Pass	

Simultaneous launch
MAX Power Density at R=20cm (mW/cm²)

Wireless specification	2.4G WIFI	5GWIFI		
MAX Power Density at R=20cm (mW/cm ²)	0.102501	0.034255		
business accounting	0.136756	Limit (mW/cm ²)	1	
Verdict	Pass			

According to KDB 447498, no stand-alone required for WIFI antenna, and no simultaneous SAR measurement is required.

*** End of Report ***