

## SAR test exclusion considerations

**FCC Regulation(s): Part 1.1307**

**Guidance Applied: KDB 447498 D04v01**

Part 1.1307(b)(3) Determination of exemption.

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

The output power of the UWB is as below.

Mode	Frequency (MHz)	Measured average power(dBm)	Max tune-up power(dBm)	Max tune-up power(mW)	Part 1.1307(b)(3)(i)(A) Requirement(mW)
UWB	6489.6	-25.2	-21.5	0.007	1.000

Note 1: The conducted average power was measured using a wideband gated RF power meter and gate parameters was adjusted such that the power is measured only when the EUT is transmitting at its maximum power.

Note 2: Please refer to the operation description for Max target power.

EUT integrate a certified BLE module(FCC ID: 2AX9WMD02) and BLE output power is as below.

Mode	Frequency (MHz)	Separation distance(Cm)	Max tune-up power(dBm)	Ant. Gain (dBi)	Max. power (dBm) <sup>Note1</sup>	Max. power (mW) <sup>Note1</sup>	Part 1.1307(b)(3)(i)(B) P <sub>th</sub> (mW)
1 Mbps	2480	0.5	4.0	2.29	4.14	2.59	2.72

Note 1: The available maximum time-averaged power or effective radiated power (ERP), whichever is greater.

Note 2: Please refer to the operation description for Max target power.

Note 3: ERP(dBm) = EIRP(dBm) – 2.15 dB

WLAN and BT cannot transmit at the same time.

**Conclusion:** SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required