



Shenzhen BCTC Technology Co., Ltd.

FCC §15.247 (i), §2.1091 – RF Exposure

**FCC ID: ZGM-MV2400**

**IC: 23051-MV2400**

**Applied procedures / limit**

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

**Limits for Occupational / Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

**Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

\* = Plane-wave equivalent power density



## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

## TEST RESULTS

	tune up power tolerance (dBm)		max. output power(mW)		Antenna Gain (numeric)	Power Density (S) (mW/ cm2)		Total Power Density (S) (mW/ cm2)	Power Density (S) (W/m <sup>2</sup> )	Limit of Power Density (S) (mW/ cm2)	RSS-102 Limit of Power Density (S) (W/m <sup>2</sup> )	Result
	ANT1	ANT2	ANT1	ANT2		ANT1	ANT2					
2.4g 802.11b	15±1	15±1	39.81	39.81	2.0 (3.0dBi)	0.01580	0.01580	/	0.15803	1	5.37	Pass
2.4g 802.11g	14±1	14±1	31.62	31.62	2.0 (3.0dBi)	0.01255	0.01255	/	0.00263	1	5.37	Pass
2.4g 802.11n (HT20)	13±1	13±1	25.12	25.12	3.98 (6.0dBi)	0.01989	0.01989	0.03978	0.00539	1	5.37	Pass
2.4g 802.11n (HT40)	12±1	12±1	19.95	19.95	3.98 (6.0dBi)	0.01580	0.01580	0.03160	0.00505	1	5.37	Pass

Note: the Directional Gain=3dBi+10log(2)=6dBi