

TEST REPORT

Part 15 Subpart C 15.247

Equipment under test Wireless Receiver

Model name GPWM-900R

FCC ID ZGPGPWM-900R

Derivative model GPWM-900A1DA, GPWM-900A1GN

Applicant GPI KOREA, Inc

Manufacturer GPI KOREA, Inc

Date of test(s) 2014.11.26 ~ 2014.12.01

Date of issue 2014.12.04

Issued to


GPI KOREA, Inc

Daebang Triplaoon B-dong 201, 158 Haneulmaeul-ro, Ilsandong-gu,
Goyang-si, Gyeonggi-do, KOREA

Issued by

KES Co., Ltd.

C-3701, Simin-daero 365-40, Dongan-gu, Anyang-si,
Gyeonggi-do, 431-716, Korea
473-29, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea

Test and report completed by :	Report approval by :
	
Hyeon-Su Jang Test engineer	Jeff Do Technical manager



Revision history

Revision	Date of issue	Test report No.	Description
-	2014.12.04	KES-RF-14T0055	Initial

TABLE OF CONTENTS

1.	General information.....	4
1.1.	EUT description	4
1.2.	Frequency/channel operations.....	5
1.3.	Information about derivative model	5
2.	Summary of tests	6
3.	Test results	7
3.1.	Radiated restricted band and emissions.....	7
3.2.	Conducted band edge and out of band emissions.....	15
3.3.	20 dB bandwidth	21
3.4.	Output power.....	24
3.5.	Carrier frequency separation	27
3.6.	Number of hopping frequency.....	29
3.7.	Time of occupancy	30
Appendix A.	Measurement equipment	32
Appendix B.	Test setup photo.....	33

1. General information

Applicant: GPI KOREA, Inc
Applicant address: Daebang Triplalon B-dong 201, 158 Haneulmaeul-ro, Ilsandong-gu, Goyang-si, Gyeonggi-do, KOREA
Test site: KES Co., Ltd.
Test site address: C-3701, Simin-daero 365-40, Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
473-29, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
FCC rule part(s): 15.247
Model: GPWM-900R
Derivative model: GPWM-900A1DA, GPWM-900A1GN
FCC ID: ZGPGPWM-900R
Test device serial No.: Production Pre-production Engineering

1.1. EUT description

Equipment under test Wireless Receiver
Frequency range 902.5 MHz ~ 927.0 MHz
Modulation technique FHSS
Number of channels 50
Antenna specification Antenna type : 1/2 Wavelength Dipole Antenna // Peak gain: 1.8 dBi
Power source DC 12.0 V

15.247(a)(1) that the rx input bandwidths shift frequencies in synchronization with the transmitted

15.247(g): The system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): The system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

Pseudorandom frequency hopping sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 50 RF channels.

Equal hopping frequency use

All channels are used equally on average.

Example of a 50 hopping sequence in data mode:

48, 22, 17, 34, 11, 09, 40, 05, 32, 06, 03, 49, 33, 38, 26, 01, 07, 42, 36, 21, 25, 45, 29, 23, 18, 43, 37, 14, 41, 15, 10, 35, 02, 46, 27, 39, 13, 08, 04, 28, 47, 12, 16, 31, 50, 20, 24, 19, 44, 30

System receiver input bandwidth

Each channel bandwidth is 0.5 MHz

1.2. Frequency/channel operations

Ch.	Frequency (MHz)
01	902.50
..	..
26	915.00
..	..
50	927.00

1.3. Information about derivative model

Derivative model is same as basic model for the purchaser treatment.

2. Summary of tests

Reference	Test description	Test results
15.247(a)(1)(i)	20 dB bandwidth	Pass
15.247(b)(2)	Output power	Pass
15.247(a)(1)	Channel separation	Pass
15.247(b)(2)	Number of channels	Pass
15.247(a)(1)(i)	Time of occupancy	Pass
15.205, 15.209	Radiated restricted band and emission	Pass
15.207(d)	Conducted band edge and out of band emissions	Pass

Note:


1. The EUT was tested per the guidance of DA 00-705, ANSI C63.10-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing.

3. Test results


3.1. Radiated restricted band and emissions

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 24 GHz emissions.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

Test procedure

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. Average measurements > 1 GHz using RBW = 1 MHz and VBW = 3 kHz. Peak measurements > 1 GHz using RBW = 1 MHz and VBW = 3 MHz. Both average and peak measurements were made using a peak detector.

Note:

1. The spectrum is measured from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1 GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20 dB of the respective limits were not reported.
2. When Average result is different from peak result over 20 dB (over-averaging), according to 15.35 (c), as a "duty cycle correction factor", pulse averaging with $20 \log(\text{duty cycle})$ has to be used.
3. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
4. Average test would be performed if the peak result were greater than the average limit.
5. "*" means restricted band edge.
5. Field strength(dB μ V/m) = Level(dB μ V) + Correction factors(dB/m) + Cable loss(dB) + F_d (dB)
6. Correction factors(dB/m) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB)
7. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
8. $F_d = 40\log(D_m / D_s)$

Where:

F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters



Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (μ V/m)
0.009 ~ 0.490	300	2 400 / F(kHz)
0.490 ~ 1.705	30	24 000 / F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.



Test results (Below 30 MHz)

Channel: 01
Operating frequency: 902.5 MHz (Worst case)
Distance of measurement: 3 meter

Frequency (MHz)	Level (dB μ V)	Ant. Pol.	Correction factors (dB/m)	F _d (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
No emission has been detected							

Test results (Below 1 000 MHz)

Channel: 01
Operating frequency: 902.5 MHz (Worst case)
Distance of measurement: 3 meter

Frequency (MHz)	Level (dB μ V)	Ant. Pol.	Correction factors (dB/m)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Emission levels are not reported much lower than the limits by over 20 dB						



Test results (Above 1 000 MHz)

Channel: 01
Operating frequency: 902.5 MHz
Distance of measurement: 3 meter

Frequency (MHz)	Level (dB μ V)	Detector	Ant. Pol.	Correction factors (dB/m)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1805.00	64.97	PK	H	-2.53	62.44	74.00	11.56
1805.00	52.20	AV	H	-2.53	49.67	54.00	4.33
1805.00	54.26	PK	V	-2.53	51.73	74.00	22.27
2707.50	58.15	PK	H	0.86	59.01	74.00	14.99
2707.50	42.36	AV	H	0.86	43.22	54.00	10.78
2707.50	53.67	PK	V	0.86	54.53	74.00	19.47
2707.50	37.32	AV	V	0.86	38.18	54.00	15.82
3610.00	40.82	PK	H	3.08	43.90	74.00	30.10
3610.00	42.22	PK	V	3.08	45.30	74.00	28.70
4512.50	52.49	PK	H	8.34	60.83	74.00	13.17
4512.50	34.13	AV	H	8.34	42.47	54.00	11.53
4512.50	54.33	PK	V	8.34	62.67	74.00	11.33
4512.50	37.05	AV	V	8.34	45.39	54.00	8.61
5415.00	46.46	PK	H	12.61	59.07	74.00	14.93
5415.00	32.10	AV	H	12.61	44.71	54.00	9.29
5415.00	46.05	PK	V	12.61	58.66	74.00	15.34
5415.00	32.64	AV	V	12.61	45.25	54.00	8.75

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.



Channel: 26
Operating frequency: 915.00 MHz
Distance of measurement: 3 meter

Frequency (MHz)	Level (dB μ N)	Detector	Ant. Pol.	Correction factors (dB/m)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
1830.00	62.74	PK	H	-2.38	60.36	74.00	13.64
1830.00	49.36	AV	H	-2.38	46.98	54.00	7.02
1830.00	52.20	PK	V	-2.38	49.82	74.00	24.18
2745.00	51.05	PK	H	0.95	52.00	74.00	22.00
2745.00	55.84	PK	V	0.95	56.79	74.00	17.21
2745.00	35.84	AV	V	0.95	36.79	54.00	17.21
3660.00	43.01	PK	H	3.32	46.33	74.00	27.67
3660.00	43.98	PK	V	3.32	47.30	74.00	26.70
4575.00	51.74	PK	H	8.67	60.41	74.00	13.59
4575.00	33.70	AV	H	8.67	42.37	54.00	11.63
4575.00	51.98	PK	V	8.67	60.65	74.00	13.35
4575.00	40.02	AV	V	8.67	48.69	54.00	5.31
5490.00	44.08	PK	H	12.91	56.99	74.00	17.01
5490.00	31.61	AV	H	12.91	44.52	54.00	9.48
5490.00	50.44	PK	V	12.91	63.35	74.00	10.65
5490.00	32.87	AV	V	12.91	45.78	54.00	8.22

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.




Channel: 50
Operating frequency: 927.0 MHz
Distance of measurement: 3 meter

Frequency (MHz)	Level (dB μ V)	Detector	Ant. Pol.	Correction factors (dB/m)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1854.00	58.12	PK	H	-2.23	55.89	74.00	18.11
1854.00	41.71	AV	H	-2.23	39.48	54.00	14.52
1854.00	51.25	PK	V	-2.23	49.02	74.00	24.98
2781.00	53.08	PK	H	1.03	54.11	74.00	19.89
2781.00	36.87	AV	H	1.03	37.90	54.00	16.10
2781.00	50.45	PK	V	1.03	51.48	74.00	22.52
3708.00	36.63	PK	H	3.56	40.19	74.00	33.81
3708.00	38.00	PK	V	3.56	41.56	74.00	32.44
4635.00	50.94	PK	H	8.99	59.93	74.00	14.07
4635.00	34.26	AV	H	8.99	43.25	54.00	10.75
4635.00	54.10	PK	V	8.99	63.09	74.00	10.91
4635.00	40.44	AV	V	8.99	49.43	54.00	4.57
5562.00	42.72	PK	H	13.11	55.83	74.00	18.17
5562.00	30.74	AV	H	13.11	43.85	54.00	10.15
5562.00	43.80	PK	V	13.11	56.91	74.00	17.09
5562.00	33.18	AV	V	13.11	46.29	54.00	7.71

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3.2. Conducted band edge and out of band emissions

Test setup



Test procedure

DA 00-705



Test setting

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions(e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.
2. RBW = 100 kHz
3. VBW \geq 300 kHz
4. Detector = Peak
5. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize



Limit

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

Ch. 01





Ch. 26





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

Ch. 50




Hopping mode




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

Band edge – Hopping Enabled Ch. 01




Band edge – Hopping Enabled Ch. 50



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

3.3. 20 dB bandwidth

Test setup



Test procedure

DA 00-075

Test setting


1. Span = 1 MHz (Approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel)
2. RBW \geq 10 kHz (\geq 1% of the span)
3. VBW \geq 10 kHz (\geq RBW)
4. Sweep = auto
5. Detector function = peak
6. Sweep = auto couple
7. Trace mode = max hold
8. The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down on side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level.

Limit

Not applicable

Frequency(MHz)	Channel no.	20 dB bandwidth(kHz)
902.5	01	379.2
915.0	26	377.7
927.0	50	379.2

Ch. 01




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

Ch. 26




Ch. 50



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

3.4. Output power

Test setup



Test procedure

DA 00-075

Test setting


1. Span = 5 MHz (Approximately 5 times the 20 dB bandwidth, centered on a hopping channel)
2. RBW = 1 MHz (the 20 dB bandwidth of the emission being measured)
3. VBW = 1 MHz (\geq RBW)
4. Sweep = Auto
5. Detector function = Peak
6. Trace = Max hold

Limit

For frequency hopping systems operating in the 902 ~ 928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.


Frequency(MHz)	Channel no.	Measured power(dBm)
902.5	01	13.69
915.0	26	13.58
927.0	50	12.80

Ch. 01




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

Ch. 26




Ch. 50



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

3.5. Carrier frequency separation

Test setup



Test procedure

DA 00-075

Test Setting


1. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
2. Span = 1 MHz (wide enough to capture the peaks of two adjacent channels)
3. RBW = 10 kHz ($\geq 1\%$ of the span)
4. VBW = 10 kHz (\geq RBW)
5. Sweep = auto
6. Detector function = peak
7. Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Operation mode	Channel separation(kHz)	Minimum bandwidth (kHz)
Hopping mode	487.7	379.2



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.

3.6. Number of hopping frequency

Test setup



Test procedure

DA 00-075


Test setting

1. The EUT must have its hopping function enabled.
2. Frequency range: 902.5 MHz ~ 927 MHz
3. Span = the frequency band of operation
4. RBW = 10 kHz (\geq 1% of the span)
5. VBW = 10 kHz (\geq RBW)
6. Sweep = auto
7. Detector function = peak
8. Trace = max hold

All the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.


Limit

For frequency hopping systems operating in the 902 ~ 928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.



3.7. Time of occupancy

Test setup



Test procedure

DA 00-075

Test setting



1. The EUT must have its hopping function enabled.
2. Span = zero span, centered on a hopping channel
4. RBW = 300 kHz
5. VBW = 300 kHz (\geq RBW)
6. Sweep = as necessary to capture the entire dwell time per hopping channel
7. Detector function = peak
8. Trace = max hold

Limit

For frequency hopping systems operating in the 902 ~ 928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Frequency (MHz)	Dwell time (ms)	Transmission occurred	Result (ms)	Limit (ms)
915	110.14	2	220.28	400

Dwell time



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The test results in the report only apply to the tested sample.



Appendix A. Measurement equipment



Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum analyzer	R&S	FSV30	101389	1 year	2015.05.06
8360B Series Swept Signal Generator	HP	83630B	3844A00786	1 year	2015.04.30
Brodband coaxial preamplifier	Schwarzbeck Mess-Elektronik	BBV 9718	9718-245	1 year	2015.08.13
Trilog-broadband antenna	Schwarzbeck	VULB 9168	9168-385	2 years	2015.05.09
Horn antenna	A.H.	SAS-571	414	2 years	2015.02.28
Attenuator	HP	8494B	2630A12857	1 year	2015.04.30
DC Power Supply	HP	6632B	US36351824	1 year	2015.07.23
Preamplifier	HP	8447F	2805A02570	1 year	2015.04.30
High pass filter	Weinschel	WHKX1.2/15G-6TT	1	1 year	2015.07.23

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook	Samsung	NT-R519	ZLT393BSBOOZO4H

Appendix B. Test setup photo

Radiated spurious



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.