



12. Radio Frequency Exposure

12.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1093)

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

12.2 EUT Specification

Frequency band (Operating)	<input checked="" type="checkbox"/> 2.4GHz: 2402MHz ~ 2480MHz <input type="checkbox"/> Bluetooth: 2402MHz ~ 2480MHz
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input type="checkbox"/> MPE-based Exemption <input checked="" type="checkbox"/> SAR-based Exemption
Remark:	
The maximum conducted output power is <u>0.4dBm (1.096mW)</u> at <u>2402MHz</u> (with <u>4.82dBi antenna gain.</u>)	



12.3 Result

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Max. Tune up power (mW)	Antenna Gain(dBi)	Max.Tune up e.i.r.p. Power (dBm)	Max.Tune up e.r.p. Power (dBm)	Max.Tune up e.r.p. Power (mW)	Distance (mm)	SAR test exclusion thresholds (mW)
2402-2480	0.40	0.90	1.23	4.82	5.72	3.57	2.28	5	2.72

No non-compliance noted.

-----THE END OF REPORT-----