





FCC RADIO TEST REPORT

Applicant : SteelSeries ApS.
Address : 656 W Randolph St., Suite 3E Chicago, IL 60661, USA
Equipment : Mouse
Model No. : M-00022
Trade Name : 
FCC ID. : ZHK-M00022

I HEREBY CERTIFY THAT :

The sample was received on Jan.16, 2020 and the testing was completed on Feb. 23, 2020 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:



Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

- 1. **Summary of Test Procedure and Test Results**..... 5
 - 1.1 Applicable Standards 5
- 2. **Test Configuration of Equipment under Test**..... 6
 - 2.1 Feature of Equipment..... 6
 - 2.2 Carrier Frequency of Channels 6
 - 2.3 Test Mode and Test Software 7
 - 2.4 Description of Test System..... 7
 - 2.5 General Information of Test..... 8
 - 2.6 Measurement Uncertainty 8
- 3. **Test Equipment and Ancillaries Used for Tests** 9
- 4. **Antenna Requirements**..... 10
 - 4.1 Antenna Construction and Directional Gain 10
- 5. **Test of AC Power Line Conducted Emission** 11
 - 5.1 Test Limit 11
 - 5.2 Test Procedures 11
 - 5.3 Typical Test Setup 12
 - 5.4 Test Result and Data 13
- 6. **Test of Radiated Spurious Emission**..... 14
 - 6.1 Test Limit 14
 - 6.2 Test Procedures 14
 - 6.3 Typical Test Setup 15
 - 6.4 Test Result and Data (9KHz ~ 30MHz) 16
 - 6.5 Test Result and Data (30MHz ~ 1GHz)..... 16
 - 6.6 Test Result and Data (1GHz ~ 25GHz)..... 18
 - 6.7 Restricted Bands of Operation 24
 - 6.8 Test Photographs (30MHz ~ 1GHz) 25
 - 6.9 Test Photographs (1GHz ~ 25GHz) 26
- 7. **Test of Conducted Spurious Emission** 28
 - 7.1 Test Limit 28
 - 7.2 Test Procedure 28
 - 7.3 Test Setup Layout 28
 - 7.4 Test Result and Data 28
- 8. **On Time, Duty Cycle and Measurement methods** 31
 - 8.1 Test Limit 31
 - 8.2 Test Procedure 31
 - 8.3 Test Setup Layout 31
 - 8.4 Test Result and Data 31
- 9. **6dB Bandwidth Measurement Data** 33
 - 9.1 Test Limit 33
 - 9.2 Test Procedures 33
 - 9.3 Test Setup Layout 33
 - 9.4 Test Result and Data 33



- 10. Maximum Peak and Average Output Power 35**
 - 10.1 Test Limit 35
 - 10.2 Test Procedures 35
 - 10.3 Test Setup Layout 35
 - 10.4 Test Result and Data 35
- 11. Power Spectral Density 36**
 - 11.1 Test Limit 36
 - 11.2 Test Procedures 36
 - 11.3 Test Setup Layout 36
 - 11.4 Test Result and Data 36
- 12. Radio Frequency Exposure 38**
 - 12.1 Applicable Standards 38
 - 12.2 EUT Specification 38



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak and Average Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
2.1091	. Radio Frequency Exposure	PASS

*The lab has lowered the uncertainty risk of test equipment, environment, and staff technicians according to ISO-IEC17025. Therefore we define test result as compliant when it complies with the standard without further evaluation of test result uncertainty.

*This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report(TEFD2001124).



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment

Frequency Range	BLE: 2402-2480MHz 2.4GHz: 2402-2480MHz
Modulation Type	BLE: GFSK 2.4GHz: $\pi/4$ DQPSK
Data Rate	BLE: GFSK: 1Mbps 2.4GHz: $\pi/4$ DQPSK: 2Mbps
Antenna Type	PCB Antenna
Antenna Gain	2400-2483.5MHz: 3.27dBi For BLE 2400-2483.5MHz: 3.27dBi For 2.4G

Note: For more details, please refer to the User's manual of the EUT.

2.2 Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
*00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	*19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	*39	2480
12	2426	26	2454	--	--
13	2428	27	2456	--	--

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- b. The complete test system included Remote workstation and EUT for RF test. The Remote workstation included Notebook.
- c. An executive program, " Terminal ver. v1.93b" under Windows OS system was executed to transmit and receive data via WLAN.
- d. The following test modes were performed for the test:

Radiation Emissions (30MHz ~ 1GHz)	
Test Mode	Operating Description
1	$\pi/4$ -DQPSK (2Mbps), Transmitter
caused "Test Mode 1" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	$\pi/4$ -DQPSK (2Mbps), Transmitter
caused "Test Mode 1" generated the worst case, it was reported as the final data.	

2.4 Description of Test System

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Vostro 3560	N/A	Adapter / 1.8m / NS
RS232	NETmate	KW-825	1.8m / NS	N/A
Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Vostro 3560	N/A	Adapter / 1.8m / NS
RS232	NETmate	KW-825	1.8m / NS	N/A



2.5 General Information of Test

Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881	
	FCC	TW1079, TW1439
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication test C-4663 for Conducted emission test R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

Test Item	Test Site	Finish Date	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2020/02/23	24°C / 55%	Nick Guan
Radiated Emissions	3M02-NK	2020/02/17	23°C / 46%	Leon Huang

2.6 Measurement Uncertainty

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±1.60dB
Radiated Spurious Emission(9KHz~30MHz)	±3.405dB
Radiated Spurious Emission(30MHz~1GHz)	±5.326dB
Radiated Spurious Emission(1GHz~25GHz)	±5.918dB
Conducted Spurious Emission	±2.156dB
6dB Bandwidth	±4.401%
20dB Bandwidth	±4.40%
Occupied Bandwidth	±4.41%
Peak Output Power(Conducted Power Meter)	±1.31dB
Dwell Time	±0.11%
Power Spectral Density	±2.146dB
Duty Cycle	±0.17%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	275	2019/09/24	2020/09/23
Bilog Antenna	Schwarzbeck	VULB9168	369	2019/03/29	2020/03/28
Active Loop Antenna	EMCO	6507	40855	2019/05/24	2020/05/23
Horn Antenna	EMCO	3115	31589	2019/04/01	2020/03/31
Horn Antenna	EMCO	3116	31974	2019/09/17	2020/09/16
EMI Receiver	ROHDE & SCHWARZ	ESCI	101423	2019/05/14	2020/05/13
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2019/03/28	2020/03/27
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2019/08/02	2020/08/01
Preamplifier	EM Electronics corp.	EM330	60660	2019/03/11	2020/03/10
Preamplifier	EMC INSTRUMENTS	EMC051845SE	980333	2019/09/20	2020/09/19
Preamplifier	Agilent	8449B	3008A01954	2019/03/11	2020/03/10
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2019/11/07	2020/11/06
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2019/04/07	2020/04/06
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2019/04/09	2020/04/08
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1316	2019/09/20	2020/09/19
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 100	805443/4	2019/05/20	2020/05/19
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 100	805796/4	2019/05/20	2020/05/19
Cable-8m(1G-40G)	HUBER SUHNER	SUCOFLEX 100	805795/4	2019/05/20	2020/05/19
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2019/03/28	2020/03/27
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2019/08/02	2020/08/01
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2019/04/07	2020/04/06
Attenuator	KEYSIGHT	8491B	MY39250703	2019/09/12	2020/09/11
TEMP & HUMI CHAMBER	T-MACHINE	TMJ-9712	T-12-040111	2019/08/28	2020/08/27
Power Meter	Anritsu	ML2495A	1224005	2019/04/11	2020/04/10
Power Sensor	Anritsu	MA2411B	1207295	2019/04/09	2020/04/08



4. Antenna Requirements

4.1 Antenna Construction and Directional Gain

Antenna Type	PCB Antenna
Antenna Gain	2402-2480MHz: 3.27dBi

2402-2480MHz

For Power directional gain= $G_{ant}= 3.27$ dBi

For PSD directional gain = $G_{ant}= 3.27$ dBi



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.4-2014. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



5.3 Typical Test Setup





5.4 Test Result and Data

The power supply is DC source, so this item doesn't require testing.



6. Test of Radiated Spurious Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3


6.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9KHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	: DC 1.5V from battery	Pol/Phase	: VERTICAL
Test Mode	: Mode 1		




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	70.63	-12.11	44.85	32.74	40.00	-7.26	Peak	100	0	P
2	322.64	-7.72	44.28	36.56	46.00	-9.44	Peak	100	0	P
3	454.59	-4.40	40.11	35.71	46.00	-10.29	Peak	100	0	P
4	712.71	0.24	35.25	35.49	46.00	-10.51	Peak	100	0	P
5	831.62	2.19	33.45	35.64	46.00	-10.36	Peak	100	0	P
6	910.52	3.47	33.52	36.99	46.00	-9.01	Peak	100	0	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: DC 1.5V from battery	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	78.36	-13.94	49.45	35.51	40.00	-4.49	Peak	100	0	P
2	258.74	-10.02	48.17	38.15	46.00	-7.85	Peak	100	0	P
3	303.26	-8.33	45.61	37.28	46.00	-8.72	Peak	100	0	P
4	454.58	-4.40	38.80	34.40	46.00	-11.60	Peak	100	0	P
5	776.40	1.59	34.26	35.85	46.00	-10.15	Peak	100	0	P
6	910.58	3.47	30.05	33.52	46.00	-12.48	Peak	100	0	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

Power	: DC 1.5V from battery	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH00		




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	45.84	42.20	54.00	-11.80	Average	100	184	P
2	2390.00	-3.64	54.82	51.18	74.00	-22.82	Peak	100	184	P
3	4804.00	3.65	37.08	40.73	54.00	-13.27	Average	400	80	P
4	4804.00	3.65	42.83	46.48	74.00	-27.52	Peak	400	80	P
5	12010.00	13.50	33.67	47.17	54.00	-6.83	Average	100	167	P
6	12010.00	13.50	42.26	55.76	74.00	-18.24	Peak	100	167	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: DC 1.5V from battery	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH00		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	45.91	42.27	54.00	-11.73	Average	100	191	P
2	2390.00	-3.64	55.21	51.57	74.00	-22.43	Peak	100	191	P
3	4804.00	3.65	37.56	41.21	54.00	-12.79	Average	100	256	P
4	4804.00	3.65	42.88	46.53	74.00	-27.47	Peak	100	256	P
5	12010.00	13.50	27.18	40.68	54.00	-13.32	Average	100	218	P
6	12010.00	13.50	42.05	55.55	74.00	-18.45	Peak	100	218	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: DC 1.5V from battery	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH19		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	45.28	41.64	54.00	-12.36	Average	100	145	P
2	2390.00	-3.64	55.65	52.01	74.00	-21.99	Peak	100	145	P
3	2483.50	-3.30	45.22	41.92	54.00	-12.08	Average	100	145	P
4	2483.50	-3.30	55.80	52.50	74.00	-21.50	Peak	100	145	P
5	4880.00	3.97	36.96	40.93	54.00	-13.07	Average	100	75	P
6	4880.00	3.97	42.57	46.54	74.00	-27.46	Peak	100	75	P
7	7320.00	8.83	32.74	41.57	54.00	-12.43	Average	100	173	P
8	7320.00	8.83	40.86	49.69	74.00	-24.31	Peak	100	173	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: DC 1.5V from battery	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH19		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	45.22	41.58	54.00	-12.42	Average	100	302	P
2	2390.00	-3.64	56.14	52.50	74.00	-21.50	Peak	100	302	P
3	2483.50	-3.30	45.87	42.57	54.00	-11.43	Average	100	302	P
4	2483.50	-3.30	55.20	51.90	74.00	-22.10	Peak	100	302	P
5	4880.00	3.97	39.30	43.27	54.00	-10.73	Average	100	340	P
6	4880.00	3.97	43.75	47.72	74.00	-26.28	Peak	100	340	P
7	7320.00	8.83	32.22	41.05	54.00	-12.95	Average	100	142	P
8	7320.00	8.83	42.43	51.26	74.00	-22.74	Peak	100	142	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: DC 1.5V from battery	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH39		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	45.76	42.46	54.00	-11.54	Average	100	177	P
2	2483.50	-3.30	54.14	50.84	74.00	-23.16	Peak	100	177	P
3	4960.00	4.21	35.55	39.76	54.00	-14.24	Average	100	271	P
4	4960.00	4.21	42.82	47.03	74.00	-26.97	Peak	100	271	P
5	7440.00	8.98	33.66	42.64	54.00	-11.36	Average	100	105	P
6	7440.00	8.98	42.51	51.49	74.00	-22.51	Peak	100	105	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: DC 1.5V from battery	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH39		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	46.25	42.95	54.00	-11.05	Average	100	226	P
2	2483.50	-3.30	59.41	56.11	74.00	-17.89	Peak	100	226	P
3	4960.00	4.21	33.55	37.76	54.00	-16.24	Average	100	83	P
4	4960.00	4.21	40.83	45.04	74.00	-28.96	Peak	100	83	P
5	7440.00	8.98	32.82	41.80	54.00	-12.20	Average	100	181	P
6	7440.00	8.98	41.70	50.68	74.00	-23.32	Peak	100	181	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



7. Test of Conducted Spurious Emission


7.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

- a. The transmitter output was connected to the spectrum analyzer via a low loss cable.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- c. Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- d. The band edges was measured and recorded.

7.3 Test Setup Layout




7.4 Test Result and Data






Note: Test plots refers to the following pages.



Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH00






Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH19





Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH39





8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout




8.4 Test Result and Data

Modulation Type	On Time (ms)	Period Time (ms)	Duty Cycle (%)
$\pi/4$ DQPSK	0.07	1.18	5.88%



Modulation Type: $\pi/4$ DQPSK (2Mbps)





9. 6dB Bandwidth Measurement Data


9.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW to 300 KHz.
- c. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- d. The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout




9.4 Test Result and Data


Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
$\pi/4$ DQPSK	0	2402	816.00	500
	19	2440	804.00	500
	39	2480	810.00	500




Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH00



Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH19



Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH39





10. Maximum Peak and Average Output Power

10.1 Test Limit


The Maximum Peak Output Power Measurement is 30dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

10.2 Test Procedures

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Test Result and Data

Power Set	Modulation Type	Channel	Frequency (MHz)	Power Output (dBm)		Power Output (mW)	
				Peak	Average	Peak	Average
0x00	π/4 DQPSK	0	2402	0.34	0.26	1.081	1.062
0x00		19	2440	0.57	0.49	1.140	1.119
0x00		39	2480	0.71	0.63	1.178	1.156

Note: Average power is for reference only.



11. Power Spectral Density

11.1 Test Limit


The Maximum of Power Spectral Density Measurement is 8dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

11.2 Test Procedures

- a. The transmitter output was connected to spectrum analyzer.
- b. The spectrum analyzer's resolution bandwidth were set at 3kHz RBW and 10KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- c. The power spectral density was measured and recorded.

11.3 Test Setup Layout




11.4 Test Result and Data


Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 3KHz Bandwidth(dBm)	Limit
$\pi/4$ DQPSK	0	2402	-18.86	8.00
	19	2440	-18.69	8.00
	39	2480	-18.57	8.00



Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH00



Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH19



Modulation Type: $\pi/4$ DQPSK (2Mbps)
CH39

