

TEST REPORT

Applicant Name : Dragino Technology Co., Limited.
Address : Room 202, BaoChengTai industrial park, No.8 CaiYun,
LongCheng Street, LongGang District, Shenzhen, China
Report Number : SZNS220819-37799E-RF-00B
FCC ID: ZHZLA66

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: LoRaWAN IoT Module
Model No.: LA66 LoRaWAN Module
Multiple Model(s) No.: N/A
Trade Mark: DRAGINO
Date Received: 2022/08/19
Report Date: 2022/10/31

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Roger Ling

Roger Ling
EMC Engineer

Approved By:

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*" .

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "**". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY.....	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION.....	6
EUT EXERCISE SOFTWARE.....	6
EQUIPMENT MODIFICATIONS.....	6
DUTY CYCLE.....	6
BLOCK DIAGRAM OF TEST SETUP.....	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §15.247 (I) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	11
FCC §15.203 - ANTENNA REQUIREMENT	12
APPLICABLE STANDARD.....	12
ANTENNA CONNECTOR CONSTRUCTION.....	12
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD.....	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE.....	13
TRANSD FACTOR & MARGIN CALCULATION.....	14
TEST DATA.....	14
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	17
APPLICABLE STANDARD.....	17
EUT SETUP.....	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	18
TEST PROCEDURE.....	18
CORRECTED FACTOR & MARGIN CALCULATION.....	18
TEST DATA.....	18
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH	24
APPLICABLE STANDARD.....	24
TEST PROCEDURE.....	24
TEST DATA.....	24
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	27
APPLICABLE STANDARD.....	27
TEST PROCEDURE.....	27
TEST DATA.....	27
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	28
APPLICABLE STANDARD.....	28
TEST PROCEDURE.....	28
TEST DATA.....	28

FCC §15.247(E) - POWER SPECTRAL DENSITY.....30
APPLICABLE STANDARD30
TEST PROCEDURE30
TEST DATA30

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	903-914.2MHz
Maximum Conducted Peak Output Power	16.62dBm
Technique	DTS
Antenna Specification*	2dBi (provide by applicant)
Voltage Range	DC3.3V
Sample serial number	SZNS220819-37799E-RF-S1 for Radiated Emissions SZNS220819-37799E-RF-S2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Line Conducted emission		2.72dB
Emissions, Radiated	30MHz – 1GHz	4.28dB
	1GHz – 18GHz	4.98dB
	18GHz – 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. To collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

Channel list:

Channel	Freq.(MHz)	Channel	Freq.(MHz)	Channel	Freq.(MHz)	Channel	Freq.(MHz)
64	903	65	904.6	66	906.2	67	907.8
68	909.4	69	911	70	912.6	71	914.2

EUT was test with channel 64/67/71

EUT Exercise Software

“serial_port_utility.exe” software was used to the EUT tested and power level is 7, The software and power level was provided by the applicant.

Equipment Modifications


No modification was made to the EUT tested.

Special Accessories

No special accessory.

Duty cycle

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
DTS	23.043	108.261	21.28



Date: 26.SEP.2022 13:06:38

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	PC	Latitude	11429208685
DELL	Adapter	DA130PE1-00	CN-0JU012-68219-18B-JEYY-A04
Dragino	Testing Jig	LA66 LoRaWAN Shield	Unkonwn

External I/O Cable


Cable Description	Length (m)	From/Port	To
Un-shielding Detachable AC Cable	1.5	Adapter	LISN
Un-shielding Un-Detachable DC Cable	1.5	Adapter	PC
Shielding Detachable USB Cable	1.0	PC	Testing Jig

Block Diagram of Test Setup

For conducted emission:



For radiated emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure(MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emission Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
CD	High Pass Filter	HPM-1.2/18G-60	110	2021/12/14	2022/12/13
Radiated Emission Test Software: e3 19821b (V9)					
RF Conducted Test					
Rohde & Schwarz	Open Switch and ControlUnit	OSP120 + OSP-B157	101244 + 100866	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101948	2021/12/13	2022/12/12
WEINSCHHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBm)	(dBi)	(dBd)	(dBm)	(W)		
DTS	903-914.2	17.0	2.0	-0.15	16.85	0.048	0.2	0.462

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.

2. 0dBd=2.15dBi

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one external antenna with unique antenna connector, the antenna gain is 2.0dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the device was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data


Environmental Conditions

Temperature:	23 °C
Relative Humidity:	41%
ATM Pressure:	101.0 kPa

The testing was performed by Jason on 2022-10-25.

EUT operation mode: Transmitting (worst case is Middle channel)


AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Job No. : SZNS220819-37799E-RF
 Mode : DTS
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.162	9.80	6.44	16.24	55.37	-39.13	Average
2	0.162	9.80	24.85	34.65	65.37	-30.72	QP
3	0.205	9.80	28.40	38.20	53.43	-15.23	Average
4	0.205	9.80	34.38	44.18	63.43	-19.25	QP
5	0.342	9.80	20.89	30.69	49.15	-18.46	Average
6	0.342	9.80	23.46	33.26	59.15	-25.89	QP
7	0.615	9.81	21.27	31.08	46.00	-14.92	Average
8	0.615	9.81	21.53	31.34	56.00	-24.66	QP
9	4.981	9.85	18.93	28.78	46.00	-17.22	Average
10	4.981	9.85	24.53	34.38	56.00	-21.62	QP
11	5.051	9.85	16.73	26.58	50.00	-23.42	Average
12	5.051	9.85	22.10	31.95	60.00	-28.05	QP

AC 120V/60 Hz, Neutral



Site : Shielding Room
 Condition: Neutral
 Job No. : SZNS220819-37799E-RF
 Mode : DTS
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.176	9.80	6.16	15.96	54.69	-38.73	Average
2	0.176	9.80	23.57	33.37	64.69	-31.32	QP
3	0.206	9.80	27.84	37.64	53.38	-15.74	Average
4	0.206	9.80	34.20	44.00	63.38	-19.38	QP
5	0.341	9.80	20.56	30.36	49.18	-18.82	Average
6	0.341	9.80	22.76	32.56	59.18	-26.62	QP
7	1.911	9.82	21.70	31.52	46.00	-14.48	Average
8	1.911	9.82	22.38	32.20	56.00	-23.80	QP
9	4.845	9.88	17.79	27.67	46.00	-18.33	Average
10	4.845	9.88	23.79	33.67	56.00	-22.33	QP
11	5.055	9.89	11.52	21.41	50.00	-28.59	Average
12	5.055	9.89	18.10	27.99	60.00	-32.01	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 10GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Factor & Margin Calculation

The Corrected Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level/Corrected Amplitude} &= \text{Read Level} + \text{Corrected Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	25~26.8°C
Relative Humidity:	52~60 %
ATM Pressure:	101.0 kPa


The testing was performed by Level Li on 2022-09-22 for below 1G and on 2022-08-29 for above 1G.

EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case of orientation was recorded)

30MHz - 1GHz: (worst case is Middle channel)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.


Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : SZNS220819-37799E-RF
 Test Mode: DTS

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	45.815	-9.98	27.68	17.70	40.00	-22.30	Peak
2	107.982	-11.99	29.06	17.07	43.50	-26.43	Peak
3	197.373	-11.55	35.94	24.39	43.50	-19.11	Peak
4	284.478	-9.45	28.34	18.89	46.00	-27.11	Peak
5	434.255	-5.72	32.00	26.28	46.00	-19.72	Peak
6	814.539	-0.23	35.00	34.77	46.00	-11.23	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220819-37799E-RF
 Test Mode: DTS

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	45.795	-9.98	29.98	20.00	40.00	-20.00	Peak
2	64.773	-12.43	31.62	19.19	40.00	-20.81	Peak
3	79.975	-16.79	33.99	17.20	40.00	-22.80	Peak
4	101.912	-11.58	28.28	16.70	43.50	-26.80	Peak
5	434.255	-5.72	28.39	22.67	46.00	-23.33	Peak
6	834.048	0.17	34.62	34.79	46.00	-11.21	Peak

Above 1 GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(903MHz)									
1806	61.91	PK	355	1.7	H	-8.72	53.19	74	-20.81
1806	54.64	AV	355	1.7	H	-8.72	45.92	54	-8.08
1806	60.09	PK	197	2.2	V	-8.72	51.37	74	-22.63
1806	51.80	AV	197	2.2	V	-8.72	43.08	54	-10.92
2709	55.52	PK	142	1.2	H	-6.61	48.91	74	-25.09
2709	45.24	AV	142	1.2	H	-6.61	38.63	54	-15.37
2709	55.89	PK	77	1.7	V	-6.61	49.28	74	-24.72
2709	45.48	AV	77	1.7	V	-6.61	38.87	54	-15.13
3612	62.43	PK	120	2.3	H	-5.92	56.51	74	-17.49
3612	54.52	AV	120	2.3	H	-5.92	48.60	54	-5.40
3612	63.24	PK	42	1.5	V	-5.92	57.32	74	-16.68
3612	56.67	AV	42	1.5	V	-5.92	50.75	54	-3.25
Middle Channel(907.8MHz)									
1815.6	63.05	PK	197	1.7	H	-8.65	54.40	74	-19.60
1815.6	55.28	AV	197	1.7	H	-8.65	46.63	54	-7.37
1815.6	61.73	PK	116	1.5	V	-8.65	53.08	74	-20.92
1815.6	55.06	AV	116	1.5	V	-8.65	46.41	54	-7.59
2723.4	55.37	PK	63	1.2	H	-6.61	48.76	74	-25.24
2723.4	44.66	AV	63	1.2	H	-6.61	38.05	54	-15.95
2723.4	55.79	PK	26	1.7	V	-6.61	49.18	74	-24.82
2723.4	45.53	AV	26	1.7	V	-6.61	38.92	54	-15.08
3631.2	61.54	PK	302	2.3	H	-5.90	55.64	74	-18.36
3631.2	52.91	AV	302	2.3	H	-5.90	47.01	54	-6.99
3631.2	63.69	PK	145	1.1	V	-5.90	57.79	74	-16.21
3631.2	56.78	AV	145	1.1	V	-5.90	50.88	54	-3.12

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	PK/Ave		Height (m)	Polar (H/V)				
High Channel(914.2MHz)									
1828.4	63.85	PK	33	1.7	H	-8.54	55.31	74	-18.69
1828.4	56.91	AV	33	1.7	H	-8.54	48.37	54	-5.63
1828.4	64.14	PK	180	2.3	V	-8.54	55.60	74	-18.40
1828.4	57.02	AV	180	2.3	V	-8.54	48.48	54	-5.52
2742.6	56.28	PK	315	1.1	H	-6.60	49.68	74	-24.32
2742.6	45.74	AV	315	1.1	H	-6.61	39.13	54	-14.87
2742.6	56.61	PK	81	1.6	V	-6.60	50.01	74	-23.99
2742.6	46.14	AV	81	1.6	V	-6.60	39.54	54	-14.46
3656.8	60.93	PK	211	1.4	H	-5.84	55.09	74	-18.91
3656.8	52.65	AV	211	1.4	H	-5.84	46.81	54	-7.19
3656.8	63.74	PK	61	1.9	V	-5.84	57.90	74	-16.10
3656.8	56.47	AV	61	1.9	V	-5.84	50.63	54	-3.37

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit


The other spurious emission which is 20dB to the limit was not recorded.

Pre-scan with Middle channel

Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	29.1 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-09-08.


Test Result: Pass.

Please refer to the following table and plots.

EUT operation mode: Transmitting


Mode	Frequency (MHz)	DTS BW (kHz)	Limit (kHz)
DTS	903.0	631.0	≥500
	907.8	633.9	≥500
	914.2	633.9	≥500

Low Channel




Date: 8.SEP.2022 11:45:32

Middle Channel



Date: 8.SEP.2022 13:21:35

High Channel



Date: 8.SEP.2022 13:36:40


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

- c. Place the EUT on a bench and set it in transmitting mode.
- d. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- e. Add a correction factor to the display.



Note: the Open Switch and Control Unit has a built-in power sensor.

Test Data

Environmental Conditions

Temperature:	29.1 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-09-08.

EUT operation mode: Transmitting

Mode	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)
DTS	903.0	16.51	<=30
	907.8	16.48	<=30
	914.2	16.62	<=30


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- f. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- g. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- h. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- i. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- j. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	29.1 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Cat Kang on 2022-09-08.

EUT operation mode: Transmitting


Test Result: Compliance

Please refer to the following plots.

Left side



Right side




FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- k. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- l. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
- m. Set the VBW $\geq 3 \times \text{RBW}$.
- n. Set the span to 1.5 times the DTS bandwidth.
- o. Detector = peak.
- p. Sweep time = auto couple.
- q. Trace mode = max hold.
- r. Allow trace to fully stabilize.
- s. Use the peak marker function to determine the maximum amplitude level within the RBW.
- t. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	29.1 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Cat Kang on 2022-09-08.

EUT operation mode: Transmitting

Test Result: Pass


Mode	Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)
DTS	903.0	6.51	≤ 8
	907.8	6.37	≤ 8
	914.2	7.07	≤ 8

Low Channel




Date: 8.SEP.2022 13:09:47

Middle Channel



Date: 8.SEP.2022 13:26:40

High Channel



Date: 8.SEP.2022 13:42:03

******* END OF REPORT *******