

RF Exposure Evaluation declaration

Product Name : IPC

Model No. : AR-V5403FLxxxx (x=0~9,A~Z or Space)

FCC ID : ZJD-ARV5403FL

Applicant : Acrosser Technology Co., Ltd

Address : 10F., No.12, Lane 609, Sec. 5, Chongsin Rd., Sanchong
District, New Taipei City 241, Taiwan, R.O.C.

Date of Receipt : May. 11, 2011

Date of Declaration : May. 24, 2011

Report No. : 115211R-RF-US-RFEXP

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	30
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 23°C and 58% RH.

1.3. Test Result of RF Exposure Evaluation

Product : IPC
 Test Item : RF Exposure Evaluation
 Test Site : N/A

For 2G

GSM 850 GPRS-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
824.2	31.95	1/8	195.8	0.1232	0.55	Pass
836.4	31.94	1/8	195.4	0.1229	0.55	Pass
848.8	31.89	1/8	193.2	0.1215	0.55	Pass

GSM 850 EGPRS-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
824.2	27.09	1/8	64.0	0.0402	0.55	Pass
836.4	27.11	1/8	64.3	0.0404	0.55	Pass
848.8	27.03	1/8	63.1	0.0397	0.55	Pass

PCS 1900 GPRS-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
1850.2	29.35	1/8	107.6	0.0677	1	Pass
1880	29.15	1/8	102.8	0.0647	1	Pass
1909.8	29.08	1/8	101.1	0.0636	1	Pass

PCS 1900 EGPRS-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
1850.2	26.50	1/8	55.8	0.0351	1	Pass
1880	26.29	1/8	53.2	0.0335	1	Pass
1909.8	26.23	1/8	52.5	0.0330	1	Pass

For 3G
WCDMA V-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
826.4	23.11	1	204.6	0.1287	0.55	Pass
836.6	23.40	1	218.8	0.1376	0.55	Pass
846.6	23.15	1	206.5	0.1299	0.55	Pass

WCDMA V HSDPA-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
826.4	22.80	1	190.5	0.1199	0.55	Pass
836.6	23.16	1	207.0	0.1302	0.55	Pass
846.6	23.04	1	201.4	0.1267	0.55	Pass

WCDMA V HSUPA-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
826.4	22.08	1	161.4	0.1016	0.55	Pass
836.6	22.46	1	176.2	0.1108	0.55	Pass
846.6	22.84	1	192.3	0.1210	0.55	Pass

WCDMA II -Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
1852.4	23.59	1	228.6	0.1438	1	Pass
1880	23.33	1	215.3	0.1354	1	Pass
1907.6	23.25	1	211.3	0.1330	1	Pass

WCDMA II HSDPA-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
1852.4	23.66	1	232.3	0.1461	1	Pass
1880	23.37	1	217.3	0.1367	1	Pass
1907.6	23.30	1	213.8	0.1345	1	Pass

WCDMA II HSUPA-Peak Gain: 5dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
1852.4	22.82	1	191.4	0.1204	1	Pass
1880	23.12	1	205.1	0.1290	1	Pass
1907.6	22.33	1	171.0	0.1076	1	Pass

Note: The conducted output power is refer to report No.: 115211R-HPUSP07V01 from the QuieTek.

For WLAN / BT

802.11b- Peak Gain : 2.89 dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output power to Antenna (mW)	Power density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Pass / Fail
2412	15.1	1	32.4	0.1250	1	Pass
2437	17.9	1	61.7	0.0238	1	Pass
2462	18.2	1	66.1	0.0256	1	Pass

BT- Peak Gain : 2.89 dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output power to Antenna (mW)	Power density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Pass / Fail
2402	0.66	1	1.16	0.0005	1	Pass
2441	0.06	1	1.01	0.0004	1	Pass
2480	-1.88	1	0.65	0.0003	1	Pass

802.11n (20MHz)- Peak Gain : 2.89 dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output power to Antenna (mW)	Power density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Pass / Fail
2412	16.41	1	43.8	0.0169	1	Pass
2437	17.92	1	61.9	0.0240	1	Pass
2462	17.23	1	52.8	0.0205	1	Pass

802.11n (40MHz)- Peak Gain : 2.89 dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output power to Antenna (mW)	Power density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Pass / Fail
2422	14.78	1	30.1	0.0116	1	Pass
2437	14.82	1	30.3	0.0117	1	Pass
2452	15.11	1	32.4	0.0126	1	Pass