



APPENDIX I

RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

| EUT | IPC |
|-----------------------------------|--|
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others |
| Exposure classification | <input checked="" type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) <input type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | IEEE 802.11b mode: 17.91 dBm (61.8016mW) IEEE 802.11g mode: 17.60 dBm (57.5440mW) IEEE 802.11n HT 20 MHz mode: 17.57 dBm (57.1479mW) IEEE 802.11n HT 40 MHz mode: 16.88 dBm (48.7528mW) |
| Antenna gain (Max) | 5 dBi (Numeric gain: 3.16) |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A |

Remark:

The maximum output power is 17.91 dBm (61.8016mW) at 2442MHz (with 3.16 numeric antenna gain.)

TEST RESULTS

No non-compliance noted.

MPE EVALUATION

No non-compliance noted.



Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



IEEE 802.11b mode:

EUT output power = 61.8016mW

Numeric Antenna gain = 3.16

→ Power density = 0.03886 mW/cm²

IEEE 802.11g mode:

EUT output power = 57.5440 mW

Numeric Antenna gain = 3.16

→ Power density = 0.03619 mW/cm²

IEEE 802.11n HT 20 MHz mode:

EUT output power = 57.1479 mW

Numeric Antenna gain = 3.16

→ Power density = 0.03594 mW/cm²

IEEE 802.11n HT 40 MHz mode:

EUT output power = 48.7528mW

Numeric Antenna gain = 3.16

→ Power density = 0.03066 mW/cm²

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)