UM-TX2WM Transmitter User Manual

The Condolex UM-TX2WM transmitter is designed to be used with sensores which has a Form A or Form C relay output. It is to be used in conjunction with the Condoplex 2660 suite panel.

Connection

Connect the UM-TX-2WM flying 2 leads to the a sensor NO relay contacts.

Programming

The UM-TX2WM must be programmed into the Condoplex suit panel. Follow the instructions in the suite panel manual to programm the Wireless UM-TX2WM transmitter into the suite panel.

Battery

Ensure a battery is installed in the unit. When the battery is nearing the end of it's life the panel will indicate the battery needs replacement. Replace the battery with the same type of battery that was originally supplied.

Testing

The unit needs regular testing. Press the red button to test the unit. Follow the sensor manufacturers instructions to test the system.

FCC Notifications

Any changes or modifications not expressly approved by the party responsible for compliance will void the user's authority to operate the equipment.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, no change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

RADIO AND TELEVISION INTERFERENCE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

You may also find helpful the following booklet, prepared by the FCC: "How to Identify and Resolve Radio-TV Interference Problems." This booklet is available from the U.S. Government Printing Office, Washington D.C. 20402.

Changes and Modifications not expressly approved by Condoplex Monitoring Systems Inc. can void your authority to operate this equipment under Federal Communications Commissions rules.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.