

FCC Test Report

Applicant : Shenzhen SKY DRAGON Audio-video
Technology Co.,LTD

Address : B16, Laneway 3, Liuxian 2RD, District71,
Baoan, Shenzhen, China

Product Name : Microphone

Report Date : Jun. 01, 2023



Shenzhen Anbotek Compliance Laboratory Limited

Shenzhen Anbotek Compliance Laboratory Limited

Address:1/F.,Building D,Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 0755-26066440 Fax:(86) 0755-26014772 Email:service@anbotek.com

Code:AB-RF-05-b



Hotline

400-003-0500

www.anbotek.com.cn



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Configuration	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
2. Summary of Test Results	10
3. Conducted Emission Test	11
3.1. Test Standard and Limit	11
3.2. Test Setup	11
3.3. Test Procedure	11
4. RF Output Power Test	12
4.1. Test Standard and Limit	12
4.2. Test Setup	12
4.3. Test Procedure	12
4.4. Test Data	12
5. Frequency Stability Test	13
5.1. Test Standard and Limit	13
5.2. Test Setup	13
5.3. Test Procedure	13
5.4. Test Data	13
6. Operating Bandwidth & Emission Mask Test	15
6.1. Test Standard and Limit	15
6.2. Test Setup	15
6.3. Test Procedure	15
6.4. Test Data	15
7. Radiation Spurious Emission Test	17
7.1. Test Standard and Limit	17
7.2. Test Setup	17
7.3. Test Procedure	18
7.4. Test Data	18
APPENDIX I -- TEST SETUP PHOTOGRAPH	22
APPENDIX II -- EXTERNAL PHOTOGRAPH	22
APPENDIX III -- INTERNAL PHOTOGRAPH	22



TEST REPORT

Applicant : Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Manufacturer : Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Product Name : Microphone
Model No. : PKWMA210, K007, SingBar, SINGBAR-35, SINGBAR, SING-BAR, K008
Trade Mark : CKY,SAMESAY
Rating(s) : Input: DC 3V
Test Standard(s) : FCC Part15 Subpart C, Section 15.236
Test Method(s) : ANSI C63.10-2013

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt

May 17, 2023

Date of Test

May 17 ~ 23, 2023

Prepared By



(TuTu Hong)

Approved & Authorized Signer



(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jun. 01, 2023



1. General Information

1.1. Client Information

Applicant	:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address	:	B16, Laneway 3, Liuxian 2RD, District71, Baoan, Shenzhen, China
Manufacturer	:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address	:	B16, Laneway 3, Liuxian 2RD, District71, Baoan, Shenzhen, China
Factory	:	Huizhou Clinav Industrial Development Co.,LTD
Address	:	Shangnan Village Committee, Yuanzhou Town BoLuo County, Huizhou City, Guangdong, China

1.2. Description of Device (EUT)

Product Name	:	Microphone
Model No.	:	PKWMA210, K007, SingBar, SINGBAR-35, SINGBAR, SING-BAR, K008 (Note: All samples are the same except the model number, so we prepare "PKWMA210" for test only.)
Trade Mark	:	CKY,SAMESAY
Test Power Supply	:	DC 3V
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Operation Frequency	:	600.85MHz, 606MHz
Number of Channel	:	2 Channels
Modulation Type	:	FM
Antenna Type	:	Monopole Antenna
Antenna Gain(Peak)	:	2 dBi (Provided by customer)
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--

1.4. Description of Test Configuration


Channel	Frequency (MHz)
1	600.85
2	606.00
/	/

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2022	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 23, 2022	1 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 19, 2022	1 Year
19.	Power Meter	Agilent	N1914A	MY50001102	Oct. 26, 2022	1 Year



1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.207	Conducted Emission	N/A
15.236(d)	RF Output Power	PASS
15.236(f)(3)	Frequency Stability	PASS
15.236(f)(g)	Operating Bandwidth & Emission Mask	PASS
15.236(g)	Radiated Spurious Emissions	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Not applicable.

The EUT is powered by DC 3V, so there is no need to conduct this test.




4. RF Output Power Test

4.1. Test Standard and Limit

Test Standard	FCC Part15 Subpart C, §15.236(d)
Test Limit	In the bands allocated and assigned for broadcast television and in the 600 MHz service band: 50 mW (17dBm) EIRP. In the 600 MHz guard band and the 600 MHz duplex gap: 20 mW (13dBm) EIRP.

4.2. Test Setup



4.3. Test Procedure

1. The EUT was connected to a spectrum analyzer for the output power test.
2. The output power was set to 50 mW.
3. The modulated output power was measured using a QP detector per ANSI C63.10-2013 section 4.1.4.2.1.
4. The output power was measured at the low, middle, and high frequencies of the passband.
5. The cable loss from the EUT output to the spectrum analyzer input were input to the spectrum analyzer as correction factor before recording the output power.
6. RBW = 120 kHz, VBW = 3 x RBW, Detector = QP

4.4. Test Data

Test Item	:	Output Power	Test Mode	:	CH Low ~ CH High
Test Voltage	:	DC 3V	Temperature	:	23.6℃
Test Result	:	PASS	Humidity	:	53 %

Channel	Peak Power output (dBm)	EIRP (dBm)	EIRP Limit (dBm)	Results
Low	6.66	8.66	17	PASS
High	4.378	6.378	17	PASS

Note: EIRP=Peak Power+ Antenna gain (dBi)




5. Frequency Stability Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 Subpart C, 15.236(f)(3)
Test Limit	The frequency tolerance of the transmitter shall be ± 0.005 percent.

5.2. Test Setup



Note : Measurement setup for testing on Antenna connector

5.3. Test Procedure

1. The EUT was placed in an environmental test chamber and the RF output was connected to a spectrum analyzer.
2. The temperature was varied from -20°C to 50°C in 10°C increments. After a sufficient time for temperature stabilization the RF output frequency was measured.
3. At 20°C the power supply voltage to the EUT was varied from 85% to 115% of the nominal value and the RF output was measured.

5.4. Test Data

Test Item	: Frequency Stability	Test Mode	: CH High
Test Voltage	: DC 3V	Temperature	: 23.6°C
Test Result	: PASS	Humidity	: 53 %



Low channel: 600.85MHz				
Temperature (°C)	Power Supplied (VDC)	Measured frequency (MHz)	Error (ppm)	Limit (ppm)
-20	3.0	600.854809	8.00	± 50
-10		600.854450	7.41	± 50
0		600.854222	7.03	± 50
10		600.854825	8.03	± 50
20		600.854580	7.62	± 50
30		600.853831	6.38	± 50
40		600.853733	6.21	± 50
50		600.854042	6.73	± 50
20	2.7	600.853814	6.35	± 50
20	3.3	600.853016	5.02	± 50

High channel: 606MHz				
Temperature (°C)	Power Supplied (VDC)	Measured frequency (MHz)	Error (ppm)	Limit (ppm)
-20	3.0	606.005163	8.52	± 50
-10		606.004778	7.88	± 50
0		606.004533	7.48	± 50
10		606.005180	8.55	± 50
20		606.004918	8.11	± 50
30		606.004113	6.79	± 50
40		606.004008	6.61	± 50
50		606.004340	7.16	± 50
20	2.7	606.003238	5.34	± 50
20	3.3	606.004953	8.17	± 50




6. Operating Bandwidth & Emission Mask Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 Subpart C, §15.236 (f)(g)
Test Limit	The operating bandwidth shall not exceed 200 kHz. Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in § 8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08), Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range; Part 1: Technical characteristics and methods of measurement. Emissions outside of this band shall comply with the limits specified in section 8.4 of ETSI EN 300 422-1 V1.4.2 (2011-08).

6.2. Test Setup



6.3. Test Procedure

The OBW is according to ANSI C63.10-2013


The Emission Mask is according to section 8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08).

6.4. Test Data

Test Item	:	Bandwidth	Test Mode	:	CH Low ~ CH High
Test Voltage	:	DC 3V	Temperature	:	23.6°C
Test Result	:	PASS	Humidity	:	53 %

Test Channel	Bandwidth (kHz)	Limit (kHz)	Test Result
Low Channel	73.916	200	Pass
High Channel	76.791	200	Pass





7. Radiation Spurious Emission Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 Subpart C, §15.236(g)
Test Limit	The operating bandwidth shall not exceed 200 kHz. Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in § 8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08), Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range; Part 1: Technical characteristics and methods of measurement. Emissions outside of this band shall comply with the limits specified in section 8.4 of ETSI EN 300 422-1 V1.4.2 (2011-08).

7.2. Test Setup




Figure 1




Figure 2



7.3. Test Procedure

1. EUT was placed on a 0.8 meter for below 1GHz and 1.5 meter for above 1GHz high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAG) should be recorded after test.
6. The measurement results are obtained as described below:
Power(EIRP)=PMea- PAG - Pcl + Ga
We used SMF100A microwave signal generator which signal level can up to 33dBm,so we not used power Amplifier for substitution test; The measurement results are amend as described below:
Power(EIRP)=PMea- Pcl + Ga
7. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

7.4. Test Data

PASS


During the test, pre-scan all modes, only the worst case is recorded in the report.



Test Results:

Test Site: 2# Shielded Room
 Operating Condition: Low channel
 Test Specification: DC 3V
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 23.5°C/50%RH

Fundamental




No.	Freq. (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	61.9951	-64.47	-9.87	-74.34	-54.00	-20.34	QP			
2	95.7622	-66.83	-7.49	-74.32	-54.00	-20.32	QP			
3	143.3257	-56.30	-11.85	-68.15	-36.00	-32.15	QP			
4	191.7450	-59.72	-8.72	-68.44	-54.00	-14.44	QP			
5	383.9318	-62.04	-5.08	-67.12	-36.00	-31.12	QP			
6	556.7744	-64.42	-1.41	-65.83	-54.00	-11.83	QP			
7	600.8500	-24.66	0.60	-24.06	/	/	peak			

Note: Result = Reading + Factor Over Limit = Result - Limit



Test Site: 2# Shielded Room
 Operating Condition: Low channel
 Test Specification: DC 3V
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 23.5°C/50%RH

Fundamental



No.	Freq. (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	119.8555	-55.74	-14.13	-69.87	-36.00	-33.87	QP			
2	143.8291	-51.71	-12.67	-64.38	-36.00	-28.38	QP			
3	167.8240	-52.34	-12.86	-65.20	-36.00	-29.20	QP			
4	287.9904	-58.67	-8.20	-66.87	-36.00	-30.87	QP			
5	383.9318	-57.69	-6.55	-64.24	-36.00	-28.24	QP			
6	478.8455	-58.93	-5.42	-64.35	-54.00	-10.35	QP			
7	600.8500	-25.70	0.60	-25.10	/	/	peak			

Note: Result = Reading + Factor Over Limit = Result - Limit



Above 1GHz:

Test Channel: Low Channel				
Frequency MHz	Measurement (dBm)	Limit (dBm)	Margin (dB)	Antenna Polar (H/V)
1802.55	-30.69	-13.00	-17.69	H
1928.73	-43.46	-13.00	-30.46	H
2403.40	-53.83	-13.00	-40.83	H
1928.73	-34.91	-13.00	-21.91	V
1802.55	-50.09	-13.00	-37.09	V
2403.40	-47.40	-13.00	-34.40	V
Test Channel: High Channel				
Frequency MHz	Measurement (dBm)	Limit (dBm)	Margin (dB)	Antenna Polar (H/V)
1818.00	-32.05	-13.00	-19.05	H
1945.26	-45.69	-13.00	-32.69	H
2424.00	-53.65	-13.00	-40.65	H
1945.26	-33.84	-13.00	-20.84	V
1818.00	-47.17	-13.00	-34.17	V
2424.00	-48.62	-13.00	-35.62	V

Remark: Margin = Measurement - Limit



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

