

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

 Telephone:
 +86 (0) 755 2601 2053

 Fax:
 +86 (0) 755 2671 0594

 Email:
 ee.shenzhen@sgs.com

Report No.: SZEM141100601402 Page: 1 of 97

# FCC REPORT

Application No.:	SZEM1411006014CR
Applicant:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Manufacturer:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Factory:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Product Name:	Bluetooth Speaker
Model No.(EUT):	CK208t
Add Model No .:	CK208, CK208b, BC238
Trade Mark:	СКҮ
FCC ID:	ZJPCK208TBC238
Standards:	47 CFR Part 15, Subpart C (2013)
Date of Receipt:	2014-11-04
Date of Test:	2014-11-06 to 2014-11-11
Date of Issue:	2014-11-17
Test Result:	PASS *

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM141100601402 Page: 2 of 97

## 2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2014-11-17		Original	

Authorized for issue by:		
Tested By	Back Huang) /Project Engineer	2014-11-11  Date
Prepared By	(Linlin Lv) /Clerk	2014-11-17 Date
Checked By	Emen_L' (Emen Li) /Reviewer	2014-11-19  Date



Report No.: SZEM141100601402 Page: 3 of 97

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (b)	ANSI C63.10 (2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2009)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS

Remark:

Model No.: CK208t, CK208, CK208b, BC238

Only the model CK208t was tested, since the circuit design, PCB layout, electrical components used,

internal wiring and functions were identical for the above models, only different on color.

The CK208b and CK208t are identical except for model no, and TF card, CK208t have a TF card and CK208b haven't. One of two batteries was assembled in the product, one is DC3.7V 1600mAh, and the other is DC 3.7V 2800mAh.



Report No.: SZEM141100601402 Page: 4 of 97

### 4 Contents

Page
------

1	со	VER PAGE	1
2	VE	RSION	2
3	TE	ST SUMMABY	3
4	0	NTENTS	
5		NERAL INFORMATION	
J			
	5.1 5.2	CLIENT INFORMATION	
	5.2 5.3	Test Environment	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	
	5.7	DEVIATION FROM STANDARDS.	
	5.8 5.9	Abnormalities from Standard Conditions Other Information Requested by the Customer	
	5.9 5.10	EQUIPMENT LIST	
~			
6	IE:	ST RESULTS AND MEASUREMENT DATA	
	6.1	ANTENNA REQUIREMENT	
	6.2	CONDUCTED EMISSIONS	-
	6.3 6.4	CONDUCTED PEAK OUTPUT POWER	
	6.4 6.5	CARRIER FREQUENCIES SEPARATION	
	6.6	HOPPING CHANNEL NUMBER	
	6.7	Dwell Time	
	6.8	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.9	SPURIOUS RF CONDUCTED EMISSIONS	
	6.10	OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM RADIATED SPURIOUS EMISSION	
	6.11	1.1 Radiated Emission below 1GHz	
	••••	1.2 Transmitter Emission above 1GHz	-
	6.12	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PH	OTOGRAPHS - EUT TEST SETUP	96
	7.1	CONDUCTED EMISSIONS	
	7.1	RADIATED EMISSIONS	
8	ЪΠ	OTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	
0	гп	OTOMIALING - LOT CONSTRUCTIONAL DETAILS	



Report No.: SZEM141100601402 Page: 5 of 97

# 5 General Information

#### 5.1 Client Information

Applicant:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address of Applicant:	B16, Laneway 3, Liuxian 2RD, District71, Baoan, shenzhen
Manufacturer:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address of Manufacturer:	B16, Laneway 3, Liuxian 2RD, District71, Baoan, shenzhen
Factory:	Shenzhen SKY DRAGON Audio-video Technology Co.,LTD
Address of Factory:	B16, Laneway 3, Liuxian 2RD, District71, Baoan, shenzhen

#### 5.2 General Description of EUT

Product Name:	Bluetooth Speaker
Model No.:	CK208t, CK208, CK208b, BC238
Trade Mark:	СКҮ
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	4.0
	This test report is for classic mode.
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Portable production
Test Software of EUT:	CSR blue test3 (manufacturer declare )
Antenna Type:	Integral
Antenna Gain:	0dBi
Battery:	3.7V lithium battery 2800mAh
Dattery.	3.7V lithium battery 1600mAhx
Power Supply:	USB charge
Test Voltage:	DC 3.7V
USB Cable:	52cm



Report No.: SZEM141100601402 Page: 6 of 97

Operation F	Operation Frequency each of channel						
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 7 of 97

#### 5.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	995mbar

#### 5.4 Description of Support Units

The EUT has been tested independent unit.

#### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594 No tests were sub-contracted.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 8 of 97

#### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

#### • FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

#### 5.7 Deviation from Standards

None.

#### 5.8 Abnormalities from Standard Conditions

None.

#### 5.9 Other Information Requested by the Customer

None.



Report No.: SZEM141100601402 Page: 9 of 97

#### 5.10 Equipment List

	Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)	
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-06-10	
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-24	
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-16	
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T8-02	SEL0162	2015-08-30	
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T4-02	SEL0163	2015-08-30	
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T2-02	SEL0164	2015-08-30	
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-16	
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-29	
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24	
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16	

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 10 of 97

	RE in Chamber				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
13	Band filter	Amindeon	82346	SEL0094	2015-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04



Report No.: SZEM141100601402 Page: 11 of 97

	RF connected test				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

Note: The calibration interval is one year, all the instruments are valid.





Report No.: SZEM141100601402 Page: 12 of 97

### 6 Test results and Measurement Data

#### 6.1 Antenna Requirement

#### Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### EUT Antenna:





Report No.: SZEM141100601402 Page: 13 of 97


Test Requirement:	47 CFR Part 15C Section 15.207			
Test Method:	ANSI C63.10: 2009			
Test Frequency Range:	150kHz to 30MHz			
Limit:		Limit (dBuV)		
	Frequency range (MHz)	Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*	
	0.5-5	56	46	
	5-30	60	50	
	* Decreases with the logarithm of the frequency.			-
Test Procedure:	0.5-5         56         46           5-30         60         50		Line near were bund being ltiple a not e the was rear The bund f the SNs was ts of 2. ment	

#### 6.2 Conducted Emissions

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 14 of 97




#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.



Report No.: SZEM141100601402 Page: 15 of 97





Neutral Line:

#### SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM141100601402 Page: 16 of 97

#### Level (dBuV) 80 47 CFR PART15C QP 47 CFR PART15C AV 40 0 .15 .2 .5 2 5 1 10 20 30 Frequency (MHz) Site : Shielding Room : 47 CFR PART15C QP CE NEUTRAL Condition Job No. : 6014CR Mode : AC charge + TX mode Cable LISN Read Limit Over Freq Loss Factor Line Limit Remark Level Level MHz dB dB dBuV dBuV dBuV dB 0.02 9.70 16.65 26.37 53.84 -27.47 Average 1 0.19447 2 0.19447 0.02 9.70 30.40 40.12 63.84 -23.72 QP 3 0.36531 0.01 9.77 13.27 23.05 48.61 -25.56 Average 0.01 4 9.77 30.37 0.36531 40.15 58.61 -18.46 QP 50 0.54934 0.01 9.80 18.88 28.69 46.00 -17.31 Average 9.80 28.78 38.59 56.00 -17.41 QP 6 0.54934 0.01 7 0.79600 0.02 9.80 11.26 21.08 46.00 -24.92 Average 8 0.79600 0.02 9.80 25.77 35.59 56.00 -20.41 QP 2.931 0.02 9.84 28.25 38.11 56.00 -17.89 QP 9 9.84 14.61 24.47 46.00 -21.53 Average 9.99 18.85 28.85 50.00 -21.15 Average 10 2.931 0.02 46.00 -21.53 Average 11 6.878 0.01 6.878 0.01 9.99 8.66 18.67 60.00 -41.33 QP 12

#### Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:

2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM141100601402 Page: 17 of 97

#### 6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)		
Test Method: ANSI C63.10:2009			
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane		
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Limit:	30dBm		
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is worst case of 8DPSK modulation type.		
Instruments Used:	s Used: Refer to section 5.10 for details		
Test Results:	Pass		

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM141100601402 Page: 18 of 97

Measurement Data					
GFSK mode					
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result		
Lowest	-3.29	30.00	Pass		
Middle	1.29	30.00	Pass		
Highest	3.05	30.00	Pass		
	π/4DQPSK n	node			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result		
Lowest	-6.14	30.00	Pass		
Middle	-1.70	30.00	Pass		
Highest	-0.10	30.00	Pass		
	8DPSK mode				
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result		
Lowest	-5.66	30.00	Pass		
Middle	-0.84	30.00	Pass		
Highest	-0.96	30.00	Pass		




Report No.: SZEM141100601402 Page: 19 of 97






Report No.: SZEM141100601402 Page: 20 of 97






Report No.: SZEM141100601402 Page: 21 of 97






Report No.: SZEM141100601402 Page: 22 of 97





Report No.: SZEM141100601402 Page: 23 of 97



<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 24 of 97

#### 6.4 20dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane		
Limit:	NA		
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is worst case of $\pi$ /4DQPSK modulation type, 3-DH1 of data type is worst case of 8DPSK modulation type.		
Instruments Used:	Refer to section 5.10 for details		
Test Results:	Pass		

#### Measurement Data

Test channel	20dB Occupy Bandwidth (kHz)		
rest channel	GFSK	π/4DQPSK	8DPSK
Lowest	894.230769231	1211.538462	1211.538462
Middle	894.230769231	1216.346154	1216.346154
Highest	899.038461538	1221.153546	1216.346154




Report No.: SZEM141100601402 Page: 25 of 97






Report No.: SZEM141100601402 Page: 26 of 97






Report No.: SZEM141100601402 Page: 27 of 97






Report No.: SZEM141100601402 Page: 28 of 97





Report No.: SZEM141100601402 Page: 29 of 97



<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 30 of 97

#### 6.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)		
•			
Test Method:	ANSI C63.10:2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane		
Limit:	2/3 of the 20dB bandwidth		
	Remark: the transmission power is less than 0.125W.		
Exploratory Test Mode:	: Hopping transmitting with all kind of modulation and all kind of data type.		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is worst case of $\pi$ /4DQPSK modulation type, 3-DH1 of data type is worst case of 8DPSK modulation type.		
Instruments Used:	Refer to section 5.10 for details		
Test Results:	Pass		

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 31 of 97

#### **Measurement Data** GFSK mode **Carrier Frequencies** Test channel Limit (kHz) Result Separation (kHz) Lowest 1002 ≥599 Pass Middle 1002 ≥599 Pass Highest 1002 ≥599 Pass π/4DQPSK mode **Carrier Frequencies** Test channel Limit (kHz) Result Separation (kHz) Lowest 1002 ≥814 Pass Middle 1002 ≥814 Pass Highest 1002 ≥814 Pass 8DPSK mode **Carrier Frequencies** Test channel Limit (kHz) Result Separation (kHz) Lowest 1002 ≥811 Pass 1002 Middle ≥811 Pass 1002 Highest ≥811 Pass


#### Note: According to section 6.3,

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	899.038461538	599
π/4DQPSK	1221.153546	814
8DPSK	1216.346154	811






Report No.: SZEM141100601402 Page: 32 of 97






Report No.: SZEM141100601402 Page: 33 of 97






Report No.: SZEM141100601402 Page: 34 of 97






Report No.: SZEM141100601402 Page: 35 of 97





Report No.: SZEM141100601402 Page: 36 of 97





Report No.: SZEM141100601402 Page: 37 of 97

#### 6.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (b)	
Test Method:	ANSI C63.10:2009	
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane	
Limit:	At least 15 channels	
Test Mode:	Hopping transmitting with all kind of modulation.	
Instruments Used:	Refer to section 5.10 for details	
Test Results:	Pass	


#### **Measurement Data**

Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM141100601402 Page: 38 of 97





Report No.: SZEM141100601402 Page: 39 of 97





Report No.: SZEM141100601402 Page: 40 of 97

#### 6.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)	
Test Method:	ANSI C63.10:2009	
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table	
	Ground Reference Plane	
Instruments Used:	Refer to section 5.10 for details	
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.	
Limit:	0.4 Second	
Test Results:	Pass	



a auramant Data

# SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM141100601402 Page: 41 of 97

Measurement Data			
Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.12576	0.4
	DH3	0.26672	0.4
	DH5	0.32087	0.4
π/4DQPSK	2-DH1	0.12896	0.4
	2-DH3	0.26608	0.4
	2-DH5	0.32043	0.4
8DPSK	3-DH1	0.13344	0.4
	3-DH3	0.26672	0.4
	3-DH5	0.32219	0.4

#### Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

On (ms)\*total number=dwell time (ms)

The middle channel (2441MHz), as below:

DH1 time slot=0.393 (ms)\*total number=125.76 (ms)

DH3 time slot=1.667 (ms)\* total number =266.72 (ms)

DH5 time slot=2.917 (ms)\* total number =320.87 (ms)

2-DH1 time slot=0.403 (ms)\*total number=128.96 (ms)

2-DH3 time slot=1.663 (ms)\* total number =266.08 (ms)

2-DH5 time slot=2.913 (ms)\* total number =320.43 (ms)

3-DH1 time slot=0.417 (ms)\*total number=133.44 (ms)

3-DH3 time slot=1.667 (ms)\* total number = 266.72 (ms)


3-DH5 time slot=2.929 (ms)\* total number = 322.19 (ms)






Report No.: SZEM141100601402 Page: 42 of 97

#### Test plot as follows:






Report No.: SZEM141100601402 Page: 43 of 97






Report No.: SZEM141100601402 Page: 44 of 97






Report No.: SZEM141100601402 Page: 45 of 97






Report No.: SZEM141100601402 Page: 46 of 97






Report No.: SZEM141100601402 Page: 47 of 97






Report No.: SZEM141100601402 Page: 48 of 97






Report No.: SZEM141100601402 Page: 49 of 97





Report No.: SZEM141100601402 Page: 50 of 97





Report No.: SZEM141100601402 Page: 51 of 97


#### 6.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	ANSI C63.10:2009	
Test Setup:	Spectrum Analyzer E.U.T	
	Non-Conducted Table	
	Ground Reference Plane	
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.	
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is worst case of 8DPSK modulation type.	
Instruments Used:	Refer to section 5.10 for details	
Test Results:	Pass	






Report No.: SZEM141100601402 Page: 52 of 97






Report No.: SZEM141100601402 Page: 53 of 97






Report No.: SZEM141100601402 Page: 54 of 97






Report No.: SZEM141100601402 Page: 55 of 97






Report No.: SZEM141100601402 Page: 56 of 97





Report No.: SZEM141100601402 Page: 57 of 97





Report No.: SZEM141100601402 Page: 58 of 97


#### 6.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	ANSI C63.10:2009	
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane	
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.	
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is worst case of $\pi$ /4DQPSK modulation type, 3-DH1 of data type is worst case of 8DPSK modulation type.	
Instruments Used:	Refer to section 5.10 for details	
Test Results:	Pass	

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM141100601402 Page: 59 of 97






Report No.: SZEM141100601402 Page: 60 of 97






Report No.: SZEM141100601402 Page: 61 of 97






Report No.: SZEM141100601402 Page: 62 of 97






Report No.: SZEM141100601402 Page: 63 of 97






Report No.: SZEM141100601402 Page: 64 of 97






Report No.: SZEM141100601402 Page: 65 of 97






Report No.: SZEM141100601402 Page: 66 of 97






Report No.: SZEM141100601402 Page: 67 of 97






Report No.: SZEM141100601402 Page: 68 of 97






Report No.: SZEM141100601402 Page: 69 of 97






Report No.: SZEM141100601402 Page: 70 of 97






Report No.: SZEM141100601402 Page: 71 of 97






Report No.: SZEM141100601402 Page: 72 of 97






Report No.: SZEM141100601402 Page: 73 of 97






Report No.: SZEM141100601402 Page: 74 of 97






Report No.: SZEM141100601402 Page: 75 of 97





Report No.: SZEM141100601402 Page: 76 of 97



#### Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM141100601402 Page: 77 of 97

#### 6.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
The system shall hop to cha rate from a Pseudorandom of on the average by each tran	nnel frequencies that are selected at the system hopping ordered list of hopping frequencies. Each frequency must be used equally smitter. The system receivers shall have input bandwidths that match the s of their corresponding transmitters and shall shift frequencies in
channels during each transr receiver, must be designed transmitter be presented wit employing short transmissio	spectrum systems are not required to employ all available hopping nission. However, the system, consisting of both the transmitter and the to comply with all of the regulations in this section should the th a continuous data (or information) stream. In addition, a system on bursts must comply with the definition of a frequency hopping system missions over the minimum number of hopping channels specified in
the system to recognize oth independently chooses and The coordination of frequen	ence within a frequency hopping spread spectrum system that permits er users within the spectrum band so that it individually and adapts its hopsets to avoid hopping on occupied channels is permitted. cy hopping systems in any other manner for the express purpose of occupancy of individual hopping frequencies by multiple transmitters is
Compliance for section 15	5.247(a)(1)
stage shift register whose 5t outputs are added in a modu	ulo-two addition stage. And the result is fed back to the input of the first s with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized ages: 9 sequence: $2^9 - 1 = 511$ bits
Linear Feedback S	hift Register for Generation of the PRBS sequence
An example of Pseudorando	om Frequency Hopping Sequence as follow:
20 62 46 77	7 64 8 73 16 75 1
	y on the average by each transmitter.
bandwidths that match the	e Specification, Bluetooth receivers are designed to have input and IF hopping channel bandwidths of any Bluetooth transmitters and shift on with the transmitted signals.



Report No.: SZEM141100601402 Page: 78 of 97

#### Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

#### Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: SZEM141100601402 Page: 79 of 97


Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205						
Test Method:	ANSI C63.10: 2009						
Test Site:	Measurement Distance	: 3n	n (Semi-Anech	ioic Cham	ber)		
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark	
	0.009MHz-0.090MH	z	Peak	10kHz	z 30kHz	Peak	
	0.009MHz-0.090MH	z	Average	10kHz	z 30kHz	Average	
	0.090MHz-0.110MH	z	Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	0.110MHz-0.490MH	z	Peak	10kHz	z 30kHz	Peak	
	0.110MHz-0.490MH	z	Average	10kHz	z 30kHz	Average	
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	30MHz-1GHz		Quasi-peak	100 kH	lz 300kHz	Quasi-peak	
	Above 1GHz		Peak	1MHz	z 3MHz	Peak	
	Above IGH2		Peak	1MHz	z 10Hz	Average	
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measureme distance (m	
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300	
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30	
	1.705MHz-30MHz		30	-	-	30	
	30MHz-88MHz		100	40.0	Quasi-peak	3	
	88MHz-216MHz		150	43.5	Quasi-peak	3	
	216MHz-960MHz		200	46.0	Quasi-peak	3	
	960MHz-1GHz		500	54.0	Quasi-peak	3	
	Above 1GHz		500	54.0	Average	3	
	Note: 15.35(b), Unless emissions is 200 applicable to the peak emission le	dB a equ	bove the max	test. This	mitted average	ge emission li	mit

#### 6.11 Radiated Spurious Emission

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 80 of 97





Report No.: SZEM141100601402 Page: 81 of 97

	<ul> <li>margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz).</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</li> </ul>
	i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type. AC Charge + Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass






Report No.: SZEM141100601402 Page: 82 of 97

#### 6.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	AC Charge + Transmitting mode	Vertical




Condition: 47 CFR PART 15.209 3m 3142C VERTICAL Job.No : 6014CR


Mode : AC charge+TX mode

040			ntenna	Preamp Factor				Over Limit
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5 6	47.83 99.53 132.69 188.41 394.85 552.88	0.91 1.44 1.70 2.08 3.27 3.98	9.66 9.09 8.03 10.07 16.30 19.00	25.69 25.62 25.29 25.22 25.50 26.48	42.79 37.21	27.23 24.14 27.42	43.50 43.50 43.50 46.00	-16.13 -17.35 -16.27 -19.36 -18.58 -17.62



Report No.: SZEM141100601402 Page: 83 of 97





Condition: 47 CFR PART 15.209 3m 3142C HORIZONTAL

Job.No : 6014CR Mod

ode	· \$C ~	barge+1	[X mode					
oue	. ne c Freq	Cable	Antenna	Preamp Factor	Read Level		Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5 6	30.96 95.76 176.89 351.71 682.35 955.44	0.65 1.42 2.01 3.06 4.58 5.40	18.16 8.97 9.78 15.53 21.42 23.31	25.63 25.38 25.05 25.40 26.41 25.51	23.88 34.34 44.69 32.68 25.17 24.55	17.06 19.35 31.43 25.87 24.76 27.75	43.50 43.50 46.00 46.00	-22.94 -24.15 -12.07 -20.13 -21.24 -18.25



Report No.: SZEM141100601402 Page: 84 of 97

Worse case r	mode:	GFSK(DH1)	Test	channel:	Lowest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3663.017	6.87	33.05	38.81	47.41	48.52	74	-25.48	Vertical
4804.000	6.42	34.70	39.24	49.50	51.38	74	-22.62	Vertical
6140.076	8.05	36.15	39.17	47.52	52.55	74	-21.45	Vertical
7206.000	8.92	35.63	39.07	45.58	51.06	74	-22.94	Vertical
9608.000	9.99	37.33	37.93	44.39	53.78	74	-20.22	Vertical
11422.280	10.37	38.17	38.43	42.84	52.95	74	-21.05	Vertical
3447.042	7.07	32.83	38.72	48.22	49.40	74	-24.60	Horizontal
4804.000	6.42	34.70	39.24	48.91	50.79	74	-23.21	Horizontal
6122.333	8.05	36.16	39.17	46.77	51.81	74	-22.19	Horizontal
7206.000	8.92	35.63	39.07	46.07	51.55	74	-22.45	Horizontal
9608.000	9.99	37.33	37.93	43.14	52.53	74	-21.47	Horizontal
11128.630	10.31	38.11	38.29	43.50	53.63	74	-20.37	Horizontal

#### 6.11.2 Transmitter Emission above 1GHz

Worse case	mode:	GFSK(DH1	GFSK(DH1) Test c		Middle	Ren	nark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3589.562	6.92	32.99	38.78	48.60	49.73	74	-24.27	Vertical
4882.000	6.59	34.78	39.26	51.16	53.27	74	-20.73	Vertical
5947.702	8.00	36.20	39.19	48.06	53.07	74	-20.93	Vertical
7323.000	9.08	35.50	39.06	48.26	53.78	74	-20.22	Vertical
9764.000	9.90	37.81	37.84	43.01	52.88	74	-21.12	Vertical
11689.790	10.47	38.39	38.56	42.82	53.12	74	-20.88	Vertical
3243.802	7.47	32.37	38.62	49.91	51.13	74	-22.87	Horizontal
4882.000	6.59	34.78	39.26	50.25	52.36	74	-21.64	Horizontal
6034.386	8.07	36.26	39.18	47.82	52.97	74	-21.03	Horizontal
7323.000	9.08	35.50	39.06	48.27	53.79	74	-20.21	Horizontal
9764.000	9.90	37.81	37.84	42.77	52.64	74	-21.36	Horizontal
11672.890	10.47	38.37	38.55	43.55	53.84	74	-20.16	Horizontal



Report No.: SZEM141100601402 Page: 85 of 97

Worse case r	node:	GFSK(DH1	) Tes	st channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3631.354	6.89	33.02	38.80	48.94	50.05	74	-23.95	Vertical
4960.000	6.76	34.86	39.29	48.64	50.97	74	-23.03	Vertical
6122.333	8.05	36.16	39.17	50.77	55.81	74	-18.19	Vertical
7440.000	9.23	35.43	39.05	48.13	53.74	74	-20.26	Vertical
9920.000	9.81	38.27	37.75	44.54	54.87	74	-19.13	Vertical
11894.540	10.56	38.60	38.65	44.84	55.35	74	-18.65	Vertical
3599.965	6.91	33.00	38.79	47.52	48.64	74	-25.36	Horizontal
4960.000	6.76	34.86	39.29	51.25	53.58	74	-20.42	Horizontal
5999.562	8.08	36.30	39.18	47.00	52.20	74	-21.80	Horizontal
7440.000	9.23	35.43	39.05	47.51	53.12	74	-20.88	Horizontal
9920.000	9.81	38.27	37.75	41.72	52.05	74	-21.95	Horizontal
11323.540	10.35	38.14	38.38	43.47	53.58	74	-20.42	Horizontal

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100601402 Page: 86 of 97

#### 6.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 1	5.209 and 15.205	
Test Method:	ANSI C63.10: 2009		
Test Site:	Measurement Distance: 3m	n (Semi-Anechoic Chambe	r)
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
	Above IGHZ	74.0	Peak Value
Test Setup:			
AE EUT (Turntable) Ground Reference Pic Test Receiver		AE EUT (Turntable) Ground Reference Pla Test Receiver	Hom Antenna Tower
Figure 1. 30MHz	to 1GHz	Figure 2. Above	e 1 GHz



Report No.: SZEM141100601402 Page: 87 of 97

Test Procedure:       a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.         b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.         c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.         d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was turned to heights from 1 meters adol degrees to find the maximum reading.         e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.         f. Place a marker at the end of the restricted band. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.         g. Test the EUT in the lowest channel , the Highest channel.         h. The readiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.         i. Repeat above procedures until all frequencies measured was complete.         Final Test Mode:       Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type.         Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode, found the Charge + Transmitting mode.         Final Test Mode:       Through Pre-scan, find the DH5		
Exploratory Test Mode:Non-hopping transmitting mode with all kind of modulation and all kind of data type. Transmitting mode, Charge + Transmitting mode.Final Test Mode:Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case. Only the worst case is recorded in the report.Instruments Used:Refer to section 5.10 for details	Test Procedure:	<ul> <li>the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.</li> <li>g. Test the EUT in the lowest channel , the Highest channel.</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</li> <li>i. Repeat above procedures until all frequencies measured was</li> </ul>
modulation type.Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case. Only the worst case is recorded in the report.Instruments Used:Refer to section 5.10 for details	Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type.
	Final Test Mode:	modulation type. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case.
Test Results: Pass	Instruments Used:	Refer to section 5.10 for details
	Test Results:	Pass

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Test plot as follows:

Worse case mode:

GFSK (DH5)

#### SGS-CSTC Standards Technical Services Ltd.

Remark:

Lowest

Report No.: SZEM141100601402 Page: 88 of 97

Peak

Vertical

120	Level (dBuV/	m)								
110										
90										į
70									FCC	PART C 247
50	hinkingh	and the second second	Mr. marin	monet	ww	-	when	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Å	m
30										
10										
0		20			2350					
	2510 25	20				ncy (MHz)				
Site Condit Job No Mode:		PART ( 4CR 2 BT Ba	andedge	e		1				
		Cable Loss		Preamp	Read Level	Level	Limit Line	0∨er Limit		


3 pp 2402.29 4.92 32.41 38.46 96.08 94.95 74.00 20.95

Test channel:



Report No.: SZEM141100601402 Page: 89 of 97

Worse case mode: GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Horizontal
-----------------------------	---------------	--------	---------	------	------------




Site : chamber Condition: FCC PART C 247 PK 3m Horizontal Job No: : 6014CR Mode: : 2402 BT Bandedge									
		Cable	Ant	Preamp	Read		Limit	0ver	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.52	4.90	32.33	38.46	65.93	64.70	74.00	-9.30	
2	2390.00	4.90	32.35	38.46	55.26	54.05	74.00	-19.95	
Зрр	2402.29	4.92	32.41	38.46	101.29	100.16	74.00	26.16	



Report No.: SZEM141100601402 Page: 90 of 97

Worse case mode: GFSK (DH5)	Test channel:	Lowest	Remark:	Average	Vertical
-----------------------------	---------------	--------	---------	---------	----------




1	2390.00	4.90	32.35	38.46	34.39	33.18	54.00	-20.82
2 pp	2402.19	4.92	32.41	38.46	83.00	81.87	54.00	27.87



Report No.: SZEM141100601402 Page: 91 of 97

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	------------	---------------	--------	---------	---------	------------




Job No:	: : 6014	4CR						
Mode:	: 240	2 BT B	andedg	e				
		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
_								
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.93	4.90	32.34	38.46	34.61	33.39	54.00	-20.61
2 pp	2401.80	4.92	32.41	38.46	85.69	84.56	54.00	30.56





Report No.: SZEM141100601402 Page: 92 of 97

Worse case mode: GFSK (DH5	Test channel:	Highest	Remark:	Peak	Vertical	
----------------------------	---------------	---------	---------	------	----------	--




Mode:	: 248	0 ВТ В	andedg	e				
		Cable	Ant	Preamp	Read		Limit	0∨er
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
-								
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.86	5.02	32.44	38.47	97.76	96.75	74.00	22.75
2	2483.50	5.03	32.44	38.47	54.39	53.39	74.00	-20.61



Report No.: SZEM141100601402 Page: 93 of 97

Worse case mode: GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Horizontal
-----------------------------	---------------	---------	---------	------	------------




Site Conditi	Condition: FCC PART C 247 PK 3m Horizontal									
Job No:	: : 6014	4CR								
Mode:	: 2480	ЭВТВ	andedg	e						
		Cable	Ant	Preamp	Read		Limit	0ver		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit		
_	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1 pp	2479.86	5.02	32.44	38.47	102.05	101.04	74.00	27.04		
2	2483.50	5.03	32.44	38.47	58.67	57.67	74.00	-16.33		
3	2495.08	5.04	32.44	38.47	66.86	65.87	74.00	-8.13		



Report No.: SZEM141100601402 Page: 94 of 97

Worse case mode: GFSK	(DH5) Test channel:	Highest	Remark:	Average	Vertical
-----------------------	---------------------	---------	---------	---------	----------




		Cable	Ant	Preamp	Read		Limit	0∨er
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
_	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	7412	ab	GD/11	ab	abav	0007/11	abav/iii	ab
	2400.00	F 00	22.44	20.47	04 55	07.54	F 4 00	20 54
т рр	2480.06	5.02	32.44	38.4/	84.55	83.54	54.00	29.54
2	2483.50	5.03	32.44	38.47	46.61	45.61	54.00	-8.39



Report No.: SZEM141100601402 Page: 95 of 97

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	------------	---------------	---------	---------	---------	------------



Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor



Report No.: SZEM141100601402 Page: 96 of 97

# 7 Photographs - EUT Test Setup

Test model No.: CK208t

#### 7.1 Conducted Emissions



7.2 Radiated Emission





Report No.: SZEM141100601402 Page: 97 of 97



# 8 Photographs - EUT Constructional Details

Refer to Report No. SZEM141100601401 for EUT external and internal photos.