



## Maximum Permissible Exposure Report

## 1. Product Information

EUT	: Smart ARM PC BOX
Test Model	: APC390K
Additional Model No.	: APC390K2
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	: Input: 12.0V $\overline{=}$ 2.0A For AC Adapter Input: 100-240V~, 50/60Hz, 0.6A Max Adapter Output: 12.0V $\overline{=}$ 2.0A, 24.0W
Hardware Version	: CBD_APC390K_V1.2_20230421
Software Version	: rk3566_r_20240116
Bluetooth:	
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.2(DSS) 40 channels for Bluetooth V5.2 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.2 (DSS) 2MHz for Bluetooth V5.2 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.2(DSS) GFSK for Bluetooth V5.2 (DTS)
Bluetooth Version	: V5.2
Antenna Description	: External Antenna, 2.87dBi(Max.)
WIFI(2.4G Band):	
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: External Antenna, 2.87dBi(Max.) Ant2: External Antenna, 2.87dBi(Max.)
WIFI(5.2G Band):	
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Antenna Description	: Ant1: External Antenna, 3.61dBi(Max.) Ant2: External Antenna, 3.61dBi(Max.)
WIFI(5.3G Band):	
Frequency Range	: 5260MHz~5320MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5260MHz~5320MHz) 2 channels for 40MHz bandwidth(5270MHz~5310MHz) 1 channels for 80MHz bandwidth(5290MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: External Antenna, 3.61dBi(Max.) Ant2: External Antenna, 3.61dBi(Max.)
WIFI(5.5G Band):	
Frequency Range	: 5500MHz~5700MHz
Channel Number	: 11 Channels for 20MHz bandwidth(5500MHz~5700MHz) 5 Channels for 40MHz bandwidth(5510MHz~5670MHz) 2 Channels for 80MHz bandwidth(5530MHz, 5610MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: External Antenna, 3.61dBi(Max.) Ant2: External Antenna, 3.61dBi(Max.)
WIFI(5.8G Band)	
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: External Antenna, 3.61dBi(Max.) Ant2: External Antenna, 3.61dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device





## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

## 3. Limit

### 3. 1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

### 3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



#### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 5. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	1.32
	39	2441	1.43
	78	2480	0.8
$\pi/4$ DQPSK	0	2402	1.15
	39	2441	-0.4
	78	2480	0.9
8DPSK	0	2402	1.16
	19	2441	1.37
	39	2480	0.84

[BLE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE_1M	0	2402	-0.79
	19	2440	-0.86
	39	2480	-1.76
BLE_2M	0	2402	-0.2
	19	2440	-0.34
	39	2480	-1.98

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11B	1	2412	14.23	13.31
	6	2437	14.17	13.02
	11	2462	13.34	12.08
11G	1	2412	12.5	11.73
	6	2437	12.12	11.79
	11	2462	12.05	11.1
11N20 SISO	1	2412	11.38	10.25
	6	2437	11.62	10.67
	11	2462	11.64	10.65

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	1	2412	13.86
	6	2437	14.18
	11	2462	14.18





## [5.2G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	36	5180	12.90	12.38
	40	5200	12.95	11.67
	48	5240	12.69	12.39
11N20 SISO	36	5180	12.03	11.34
	40	5200	12.42	10.77
	48	5240	12.08	10.71
11N40 SISO	38	5190	11.78	10.31
	46	5230	12.13	10.35
11AC20 SISO	36	5180	11.71	11.16
	40	5200	12.5	11.09
	48	5240	12.24	11.27
11AC40 SISO	38	5190	11.89	10.63
	46	5230	11.68	10.29
11AC80 SISO	42	5210	11.31	10.51

## [5.2G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	36	5180	14.71
	40	5200	14.68
	48	5240	14.46
11N40 MIMO	38	5190	14.12
	46	5230	14.34
11AC20 MIMO	36	5180	14.45
	40	5200	14.86
	48	5240	14.79
11AC40 MIMO	38	5190	14.32
	46	5230	14.05
11AC80 MIMO	42	5210	13.94

## [5.3G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
IEEE 802.11a	52	5260	12.81	12.15
	60	5280	13.28	12.43
	64	5320	12.62	11.96
IEEE 802.11n HT20	52	5260	12.67	10.96
	60	5280	12.25	11.43
	64	5320	11.78	10.73
IEEE 802.11n HT40	54	5270	11.3	10.6
	62	5310	11.27	10.21
IEEE 802.11ac VHT20	52	5260	12.41	11.41
	60	5280	12.57	11.36
	64	5320	12.37	10.97
IEEE 802.11ac VHT40	54	5270	11.47	9.82
	62	5310	11.91	10.03
IEEE 802.11ac VHT80	58	5290	11.18	9.97



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity





## [5.3G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	52	5260	14.91
	60	5280	14.87
	64	5320	14.30
11N40 MIMO	54	5270	13.97
	62	5310	13.78
11AC20 MIMO	52	5260	14.95
	60	5280	15.02
	64	5320	14.74
11AC40 MIMO	54	5270	13.73
	62	5310	14.08
11AC80 MIMO	58	5290	13.63

## [5.5G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	100	5500	12.95	11.91
	116	5580	12.96	11.95
	140	5700	13.12	12.21
11N20 SISO	100	5500	12.32	10.53
	116	5580	12.23	10.68
	140	5700	12.53	11.38
11N40 SISO	102	5510	11.14	9.52
	110	5550	11.72	10.74
	134	5670	11.23	10.51
11AC20 SISO	100	5500	11.74	10.73
	116	5580	12.3	10.71
	140	5700	12.53	11.34
11AC40 SISO	102	5510	11.41	10.48
	110	5550	11.32	10.89
	134	5670	12.07	10.55
11AC80 SISO	106	5530	11.19	10.13
	122	5610	10.83	10.84

## [5.5G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	100	5500	14.53
	116	5580	14.53
	140	5700	15.00
11N40 MIMO	102	5510	13.42
	110	5550	14.27
	134	5670	13.90
11AC20 MIMO	100	5500	14.27
	116	5580	14.59
	140	5700	14.99
11AC40 MIMO	102	5510	13.98
	110	5550	14.12
	134	5670	14.39
11AC80 MIMO	106	5530	13.70
	122	5610	13.85




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## [5.8G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	149	5745	12.99	11.8
	157	5785	13.34	12.26
	165	5825	12.87	11.88
11N20 SISO	149	5745	12.16	11.42
	157	5785	12.25	11.43
	165	5825	11.87	10.89
11N40 SISO	151	5755	11.8	10.28
	159	5795	11.07	10.12
11AC20 SISO	149	5745	12.26	11.44
	157	5785	12.22	11.08
	165	5825	12.2	10.93
11AC40 SISO	151	5755	11.14	9.98
	159	5795	11.01	10.88
11AC80 SISO	155	5775	10.92	10.07

## [5.8G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11N20 MIMO	149	5745	14.82
	157	5785	14.87
	165	5825	14.42
11N40 MIMO	151	5755	14.12
	159	5795	13.63
11AC20 MIMO	149	5745	14.88
	157	5785	14.70
	165	5825	14.62
11AC40 MIMO	151	5755	13.61
	159	5795	13.96
11AC80 MIMO	155	5775	13.53







## 6. Manufacturing Tolerance

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	0	-1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	1.0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[BLE]

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	-1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
BT 2LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	-1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI ]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 MIMO(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0





## [5.2G WIFI]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 MIMO(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 MIMO(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	14.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 MIMO(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 MIMO(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	14.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 MIMO(Average)			
Channel	Channel 42		
Target (dBm)	13.0		
Tolerance $\pm$ (dB)	1.0		






## [5.3G WIFI]

11A (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	12.0	13.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT20 MIMO(Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT40 MIMO(Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	13.0	13.0	
Tolerance ± (dB)	1.0	1.0	
11AC VHT20 MIMO(Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	14.0	15.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT40 MIMO(Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	13.0	14.0	
Tolerance ± (dB)	1.0	1.0	
11AC VHT80 MIMO(Average)			
Channel	Channel 58		
Target (dBm)	13.0		
Tolerance ± (dB)	1.0		





## [5.5G WIFI]

11A (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	12.0	12.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT20 MIMO(Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	14.0	14.0	15.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT40 MIMO(Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	13.0	14.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT20 MIMO(Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC HT40 MIMO(Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	13.0	14.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT80 MIMO(Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	13.0	13.0	
Tolerance ± (dB)	1.0	1.0	





## [5.8G WIFI ]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	13.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20 MIMO(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40 MIMO(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	14.0	13.0	
Tolerance ±(dB)	1.0	1.0	
11AC20 MIMO(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	14.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40 MIMO(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	13.0	13.0	
Tolerance ±(dB)	1.0	1.0	
11AC80 MIMO(Average)			
Channel	Channel 155		
Target (dBm)	13.0		
Tolerance ±(dB)	1.0		





## 8. Measurement Results

## 8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

## [BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
GFSK	2.0	1.5849	2.87	1.9364	0.0006	1.0000
$\pi/4$ -DQPSK	2.0	1.5849	2.87	1.9364	0.0006	1.0000
8-DPSK	2.0	1.5849	2.87	1.9364	0.0006	1.0000

## [BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
BT LE	1.0	1.2589	2.87	1.9364	0.0005	1.0000
BT 2LE	1.0	1.2589	2.87	1.9364	0.0005	1.0000

## [2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11b	15.0	31.6228	2.87	1.9364	0.0122	1.0000
IEEE 802.11g	13.0	19.9526	2.87	1.9364	0.0077	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	2.87	1.9364	0.0122	1.0000

## [5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	13.0	19.9526	3.61	2.2961	0.0091	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11n HT40 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT20 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT40 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT80 MIMO	14.0	25.1189	3.61	2.2961	0.0115	1.0000







## [5.3G WIFI ]

Band/Mode	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	14.0	25.1189	3.61	2.2961	0.0115	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11n HT40 MIMO	14.0	25.1189	3.61	2.2961	0.0115	1.0000
IEEE 802.11ac VHT20 MIMO	16.0	39.8107	3.61	2.2961	0.0182	1.0000
IEEE 802.11ac VHT40 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT80 MIMO	14.0	25.1189	3.61	2.2961	0.0115	1.0000

## [5.5G WIFI ]

Band/Mode	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	14.0	25.1189	3.61	2.2961	0.0115	1.0000
IEEE 802.11n HT20 MIMO	16.0	39.8107	3.61	2.2961	0.0182	1.0000
IEEE 802.11n HT40 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT20 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT40 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT80 MIMO	14.0	25.1189	3.61	2.2961	0.0115	1.0000



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## [5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
IEEE 802.11a	14.0	25.1189	3.61	2.2961	0.0115	1.0000
IEEE 802.11n HT20 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11n HT40 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT20 MIMO	15.0	31.6228	3.61	2.2961	0.0144	1.0000
IEEE 802.11ac VHT40 MIMO	14.0	25.1189	3.61	2.2961	0.0115	1.0000
IEEE 802.11ac VHT80 MIMO	14.0	25.1189	3.61	2.2961	0.0115	1.0000

**Remark:**

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

**8.2 Simultaneous Transmission MPE Evaluation**

The EUT equipped with one BT/2.4GWIFI/5G WIFI antenna and one 2.4GWIFI/5G WIFI antenna. So, need consider simultaneous transmission;

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$  of MPE ratios  $\leq 1.0$

Simultaneous Transmission								
BT MPE ratios	2.4GWIFI MAX MPE ratios	5.2GWIFI MAX MPE ratios	5.3GWIFI MAX MPE ratios	5.5GWIFI MAX MPE ratios	5.8GWIFI MAX MPE ratios	$\sum$ MPE ratios	Limit	Results
0.0006	0.0122	/	/	/	/	0.0128	1.0	Pass
0.0006	/	0.0144	/	/	/	0.0150	1.0	Pass
0.0006	/	/	0.0182	/	/	0.0188	1.0	Pass
0.0006	/	/	/	0.0182	/	0.0188	1.0	Pass
0.0006	/	/	/	/	0.0182	0.0188	1.0	Pass

**Remark:**

1. Output power including turn-up tolerance;
2. BT/BLE/2.4G WIFI output power is burst peak power;
3. 5G WIFI output power is burst average power;
4. MPE evaluate distance is 20cm from user manual provide by manufacturer;
5. MPE values =  $PG/4\pi R^2$

**9. Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity