



## RADIO FREQUENCY EXPOSURE

### LIMIT

According to §15.247(i) and §15.407(f), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b) of this chapter.

### EUT Specification

|                                   |  |
|-----------------------------------|--|
| <b>EUT</b>                        | ATV582   |
| <b>Frequency band (Operating)</b> | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input type="checkbox"/> WLAN: 5.15GHz ~ 5.25GHz<br><input type="checkbox"/> WLAN: 5.25GHz ~ 5.35GHz<br><input type="checkbox"/> WLAN: 5.47GHz ~ 5.725GHz<br><input type="checkbox"/> WLAN: 5.725GHz ~ 5.85GHz<br><input type="checkbox"/> Others |
| <b>Device category</b>            | <input type="checkbox"/> Portable (<20cm separation)<br><input checked="" type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others   |
| <b>Exposure classification</b>    | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> )<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )  |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/> Single antenna<br><input type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input type="checkbox"/> Tx/Rx diversity   |
| <b>Max. output power</b>          | 2.412-2.462GHz<br>802.11b mode: 19.42dBm<br>802.11g mode: 15.78 dBm<br>802.11n HT20 MHz Channel mode: 14.48 dBm<br>802.11n HT40 MHz Channel mode: 14.59 dBm  |
| <b>Antenna gain (Max)</b>         | Dipole antennas for 2.4GHz Gain 2.0 dBi  |
| <b>Evaluation applied</b>         | <input checked="" type="checkbox"/> MPE Evaluation*<br><input type="checkbox"/> SAR Evaluation<br><input type="checkbox"/> N/A   |

### **Remark:**

1. The maximum output power is 19.42dBm (87.5mW) at 2412MHz (with 2.000 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.
4. All two antennas are completely uncorrelated with each other.



## **TEST RESULTS**

No non-compliance noted.

### **Calculation**

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where  $E$  = Field strength in Volts / meter

$P$  = Power in Watts

$G$  = Numeric antenna gain

$d$  = Distance in meters

$S$  = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where  $d$  = Distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

## **Maximum Permissible Exposure**

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where  $P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>



# Compliance Certification Services Inc.

Report No: C140801R01-RPB

FCC ID: ZJU00141730

Date of Issue :August 12, 2014

| Modulation Mode | Frequency band (MHz) | Max. Conducted output power(dBm) | Antenna gain (dBi) | Distance (cm) | Power density (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) |
|-----------------|----------------------|----------------------------------|--------------------|---------------|-------------------------------------|-----------------------------|
| 802.11b         | 2412-2462            | 19.42                            | 2.0                | 20            | 0.0276                              | 1                           |
| 802.11g         |                      | 15.78                            | 2.0                | 20            | 0.0120                              | 1                           |
| 802.11 n(20MHz) |                      | 14.48                            | 2.0                | 20            | 0.0088                              | 1                           |
| 802.11 n(40MHz) |                      | 14.59                            | 2.0                | 20            | 0.0091                              | 1                           |

Note:

WLAN 2.4G=0.0276

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)