

FCC CERTIFICATION TEST REPORT

For
FCC ID:ZKJ-BLEC002

Report Reference No..... : 18EFAS10049 A1

A2LA Cert. No..... : 4893.01

Date of issue : 2018-11-1

Testing Laboratory..... : DongGuan ShuoXin Electronic Technology Co., Ltd.

Address..... : Zone A, 1F, No. 6, XinGang Road YuanGang Street, XinAn District, ChangAn Town, DongGuan City, GuangDong, China

Applicant's name..... : Haier US Appliance Solutions, Inc.

Address..... : Appliance Park AP5-2N-67, Louisville, KY, United States (Zip Code : 40225)

Manufacturer..... : ITON Technology Corp.

Test specification:


Test item description..... : BT CAT BOARD ASM

Trade Mark..... : HAIER

Model/Type reference : 191D9618, GEMDBT4004

Ratings..... : DC5V

Responsible Engineer :


Smile Wang

Authorized Signatory:



King Wang

TABLE OF CONTENTS

1. Summary of test results.....	4
2. General test information	5
2.1. Description of EUT	5
2.2. Accessories of EUT	5
2.3. Assistant equipment used for test	5
2.4. Block diagram of EUT configuration for test	6
2.5. Test environment conditions.....	6
2.6. Measurement uncertainty	7
3. 20dB Bandwidth &99% Bandwidth	8
3.1. Test equipment.....	8
3.2. Block diagram of test setup	8
3.3. Limits	8
3.4. Test Procedure	8
3.5. Test Result	9
3.6. Original test data	9
4. CARRIER FREQUENCY SEPARATION TEST	14
4.1. Test equipment.....	14
4.2. The Requirement For Section 15.247(a)(1)	14
4.3. EUT Configuration on Measurement.....	14
4.4. Operating Condition of EUT	14
4.5. Test Procedure	14
4.6. Test Result	15
5. NUMBER OF HOPPING FREQUENCY TEST	19
5.1. Test equipment.....	19
5.2. The Requirement For Section 15.247(a)(1)(iii)	19
5.3. EUT Configuration on Measurement.....	19
5.4. Operating Condition of EUT	19
5.5. Test Procedure	19
5.6. Test Result	20
6. DWELL TIME TEST	22
6.1. Test equipment.....	22
6.2. The Requirement For Section 15.247(a)(1)(iii)	22
6.3. EUT Configuration on Measurement.....	22
6.4. Operating Condition of EUT	22
6.5. Test Procedure	22
6.6. Test Result	23

7. Maxmum Output Power.....	27
7.1.Test equipment.....	27
7.2.Block diagram of test setup	27
7.3.Limits	27
7.4.Test Procedure	28
7.5.Test Result	28
8. Spurious Emission.....	34
8.1.Test equipment.....	34
8.2.Block diagram of test setup	34
8.3.Limit.....	36
8.4.Test Procedure	37
8.5.Test Result	39
9. CONDUCTED EMISSION MEASUREMENT	47
9.1.POWER LINE CONDUCTED EMISSION LIMITS	47
9.2.MEASUREMENT INSTRUMENTS LIST	47
9.3.TEST PROCEDURE.....	48
9.4.DEVIATION FROM TEST STANDARD.....	48
9.5.TEST SETUP	48
9.6.EUT OPERATING CONDITIONS.....	48
9.7.TEST RESULTS.....	49
10. 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	51
10.1.Test Equipment	51
10.2.Limit.....	51
10.3.Test Procedure	51
10.4.Test result.....	52
11. Antenna Requirements.....	63
11.1.Limit.....	63
11.2.EUT ANTENNA	63

TEST REPORT DECLARE

Applicant	:	Haier US Appliance Solutions, Inc.
Address	:	Appliance Park AP5-2N-67, Louisville, KY, United States (Zip Code : 40225)
Equipment under Test	:	BT CAT BOARD ASM
Test Model No	:	191D9618
Manufacturer	:	ITON Technology Corp.
Address	:	7 Floor East, Building C, No. 1006 Shennan Road, Shenzhen International Innovation Center, Shenzhen, China.

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C (15.247)

Test procedure used: ANSI C63.10:2013

We Declare:

The equipment described above is tested by DongGuan ShuoXin Electronic Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and DongGuan ShuoXin Electronic Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	18EFAS10049 A1		
Date of Test:	2018-11-1	Date of Report:	2018-11-08

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of DongGuan ShuoXin Electronic Technology Co., Ltd.

1. SUMMARY OF TEST RESULTS

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
Bandwidth	FCC Part 15: 15.247(a)(1)	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1)	PASS
Number Of Hopping Frequency	FCC Part 15: 15.247(a)(1)(iii)	PASS
Dwell Time Test	FCC Part 15: 15.247(a)(1)(iii)	PASS
Maximum Output Power	FCC Part 15: 15.247(b)(1)	PASS
Band Edge Emission	FCC Part 15: 15.247(d)	PASS
Radiated Spurious Emissions	FCC Part 15.205 / 15.209	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Conducted Emission	FCC Part 15.207	PASS

2. GENERAL TEST INFORMATION

2.1. DESCRIPTION OF EUT

EUT* Name	:	BT CAT BOARD ASM
Model Number	:	191D9618, GEMDBT4004
Power supply	:	DC5V
Adaptor	:	N/A
Operation frequency	:	2402-2480MHz
Modulation	:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type	:	PCB Antenna
Antenna Gain	:	1.43 dBi
Date of Receipt	:	2018/10/19
Sample Type	:	N/A

2.2. ACCESSORIES OF EUT

Description of Accessories	Manufacturer	Model number or Type	Other
/	/	/	/

2.3. ASSISTANT EQUIPMENT USED FOR TEST

Description of Assistant equipment	Manufacturer	Model number or Type	EMC Compliance	SN
Adapter	Nokia	JF024WR	CE&FCC	/

2.4. BLOCK DIAGRAM OF EUT CONFIGURATION FOR TEST



The EUT has been tested as an independent unit. The following support were used to form a representative test configuration during the tests.

Remark: This product supports GFSK, $\pi/4$ -DQPSK, 8DPSK running at 1,2,3Mbps.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
GFSK	1	Low :CH0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
$\pi/4$ -DQPSK	2	Low :CH0	2402
	2	Middle: CH39	2441
	2	High: CH78	2480
8DPSK	3	Low :CH0	2402
	3	Middle: CH39	2441
	3	High: CH78	2480

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. TEST ENVIRONMENT CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.6. MEASUREMENT UNCERTAINTY

Test Item	Uncertainty
Uncertainty for Conduction emission test (9kHz-150kHz)	3.7 dB
Uncertainty for Conduction emission test (150kHz-30MHz)	3.3 dB
Uncertainty for Radiation Emission test (30MHz-200MHz)	4.60 dB (Polarize: V)
	4.60 dB (Polarize: H)
Uncertainty for Radiation Emission test (200MHz-1GHz)	6.10 dB (Polarize: V)
	5.08 dB (Polarize: H)
Uncertainty for Radiation Emission test (1GHz-6GHz)	5.01 dB (Polarize: V)
	5.01 dB (Polarize: H)
Uncertainty for Radiation Emission test (6GHz-18GHz)	5.26 dB (Polarize: V)
	5.26 dB (Polarize: H)
Uncertainty for Radiation Emission test (18GHz-40GHz)	5.06 dB (Polarize: V)
	5.06 dB (Polarize: H)
Uncertainty for radio frequency	$\pm 0.048\text{kHz}$
Uncertainty for conducted RF Power	$\pm 0.32\text{dB}$


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. 20DB BANDWIDTH & 99% BANDWIDTH

3.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	05/25/2019	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2018/12/17	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2018/12/17	1 Year
4	Spectrum analyzer	R&S	FSV40	101470	2019/06/28	1 Year

3.2. BLOCK DIAGRAM OF TEST SETUP



3.3. LIMITS

No limit requirement.

3.4. TEST PROCEDURE

- (1) Configure EUT and assistant system according clause 2.4 and 3.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) Set the spectrum analyzer as follows:

RBW:	30KHz
VBW:	100KHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode:	Max hold

- (5) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB and 99% bandwidth relative to the maximum level measured in the fundamental emission.

3.5. TEST RESULT


Mode	Freq	20dB	99%OBW	Conclusion
	(MHz)	(MHz)	(MHz)	
GFSK	2402	0.769	/	PASS
	2441	0.769	/	PASS
	2480	0.769	/	PASS

Mode	Freq	20dB	99%OBW	Conclusion
	(MHz)	(MHz)	(MHz)	
π/4-DQPSK	2402	1.153	/	PASS
	2441	1.151	/	PASS
	2480	1.148	/	PASS


Mode	Freq	20dB	99%OBW	Conclusion
	(MHz)	(MHz)	(MHz)	
8DPSK	2402	1.143	/	PASS
	2441	1.149	/	PASS
	2480	1.145	/	PASS

3.6. ORIGINAL TEST DATA


GFSK 2402MHZ




GFSK 2441MHZ




GFSK 2480MHZ




Π/4-DQPSK 2402MHZ




Π/4-DQPSK 2441MHZ




Π/4-DQPSK 2480MHZ




8DPSK 2402MHZ



8DPSK 2441MHZ



8DPSK 2480MHZ



4. CARRIER FREQUENCY SEPARATION TEST

4.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	05/25/2019	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2018/12/17	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2018/12/17	1 Year
4	Spectrum analyzer	R&S	FSV40	101470	2019/06/28	1 Year

4.2. THE REQUIREMENT FOR SECTION 15.247(A)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly

ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

4.3. EUT CONFIGURATION ON MEASUREMENT

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4. OPERATING CONDITION OF EUT

- (1) Setup the EUT and simulator as shown as Section 6.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz.
We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

4.5. TEST PROCEDURE

- (1) The transmitter output was connected to the spectrum analyzer through a low loss cable.
- (2) .Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 3 MHz.
- (3) Set the adjacent channel of the EUT maxhold another trace.
- (4) Measurement the channel separation

4.6. TEST RESULT

GFSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	0.999	>(25KHz or 2/3*20dB Bandwidth)	PASS
Middle	2441	0.999	>(25KHz or 2/3*20dB Bandwidth)	PASS
High	2479	0.999	>(25KHz or 2/3*20dB Bandwidth)	PASS


8DPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	0.999	>(25KHz or 2/3*20dB Bandwidth)	PASS
Middle	2441	0.999	>(25KHz or 2/3*20dB Bandwidth)	PASS
High	2479	0.999	>(25KHz or 2/3*20dB Bandwidth)	PASS


The spectrum analyzer plots are attached as below.

Note: GFSK and 8DPSK mode is worse case , and only worse case is reported


GFSK 2402MHZ




GFSK 2441MHZ




GFSK 2480MHZ




8DPSK 2402MHZ



8DPSK 2441MHZ



8DPSK 2480MHZ



5. NUMBER OF HOPPING FREQUENCY TEST

5.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	05/25/2019	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2018/12/17	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2018/12/17	1 Year
4	Spectrum analyzer	R&S	FSV40	101470	2019/06/28	1 Year

5.2. THE REQUIREMENT FOR SECTION 15.247(A)(1)(III)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

5.3. EUT CONFIGURATION ON MEASUREMENT

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. OPERATING CONDITION OF EUT

- (1) Setup the EUT and simulator as shown as Section 7.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in TX (Hopping on) modes measure it.

5.5. TEST PROCEDURE



- (1) The transmitter output was connected to the spectrum analyzer through a low loss cable.
- (2) Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.
- (3) Max hold, view and count how many channel in the band.

5.6. TEST RESULT

Total number of hopping channel	Measurement result(CH)	Limit(CH)
		79

The spectrum analyzer plots are attached as below

Number of hopping channels



Channle information									
CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency
0	2402	16	2418	32	2434	48	2450	64	2466
1	2403	17	2419	33	2435	49	2451	65	2467
2	2404	18	2420	34	2436	50	2452	66	2468
3	2405	19	2421	35	2437	51	2453	67	2469
4	2406	20	2422	36	2438	52	2454	68	2470
5	2407	21	2423	37	2439	53	2455	69	2471
6	2408	22	2424	38	2440	54	2456	70	2472
7	2409	23	2425	39	2441	55	2457	71	2473
8	2410	24	2426	40	2442	56	2458	72	2474
9	2411	25	2427	41	2443	57	2459	73	2475
10	2412	26	2428	42	2444	58	2460	74	2476
11	2413	27	2429	43	2445	59	2461	75	2477
12	2414	28	2430	44	2446	60	2462	76	2478
13	2415	29	2431	45	2447	61	2463	77	2479
14	2416	30	2432	46	2448	62	2464	78	2480
15	2417	31	2433	47	2449	63	2465	-	-

Note: GFSK and 8DPSK mode is worse case , and only worse case is reported

6. DWELL TIME TEST

6.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	05/25/2019	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2018/12/17	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2018/12/17	1 Year
4	Spectrum analyzer	R&S	FSV40	101470	2019/06/28	1 Year

6.2. THE REQUIREMENT FOR SECTION 15.247(A)(1)(III)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

6.3. EUT CONFIGURATION ON MEASUREMENT

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. OPERATING CONDITION OF EUT

- (1) Setup the EUT and simulator as shown as Section 8.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz.
We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. TEST PROCEDURE

- (1) The transmitter output was connected to the spectrum analyzer through a low loss cable.
- (2) Set center frequency of spectrum analyzer = operating frequency.
- (3) Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz

A Period Time = (channel number)*0.4

DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)

DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)

DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

6.6. TEST RESULT

GFSK

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.431	0.1379	400
DH3	2402	1.688	0.2701	400
DH5	2402	2.934	0.3130	400


8DPSK

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.435	0.1392	400
DH3	2402	1.691	0.2706	400
DH5	2402	2.938	0.3134	400


Note: GFSK and 8DPSK mode is worse case , and only worse case is reported

The spectrum analyzer plots are attached as below:


GFSK DH1




GFSK DH3




GFSK DH5




8DPSK DH1



8DPSK DH3



8DPSK DH5



7. MAXMUM OUTPUT POWER

7.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	05/25/2019	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2018/12/17	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2018/12/17	1 Year
4	Spectrum analyzer	R&S	FSV40	101470	2019/06/28	1 Year

7.2. BLOCK DIAGRAM OF TEST SETUP

FCC:Same with 3.2

7.3. LIMITS

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz bands: 0.125 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.4. TEST PROCEDURE

- (1) Configure EUT and assistant system according clause 2.4 and 3.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) Set the spectrum analyzer as follows:


GFSK,	RBW:	>20dB BW
$\pi/4$ -DQPSK, 8DPSK	VBW:	3XRBW
Span		>1.5x 20dB bandwidth
Detector Mode:		Peak
Sweep time:		auto
Trace mode		Max hold

- (5) Allow the trace to stabilize, Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges measure out the Average and PK output power.


7.5. TEST RESULT

EUT Set Mode	Data Rate (Mbps)	Frequency (MHz)	Result(dBm)
			Peak
GFSK	1	2402	2.24
		2441	2.43
		2480	2.60
$\pi/4$ -DQPSK	2	2402	0.84
		2441	1.18
		2480	0.82
8DPSK	3	2402	1.05
		2441	1.11
		2480	0.90
Limit: 21dBm		Conclusion: PASS	


GFSK 2402MHz




GFSK 2441MHz




GFSK 2480MHz




$\pi/4$ -DQPSK 2402MHz




$\pi/4$ -DQPSK 2441MHz




$\pi/4$ -DQPSK 2480MHz




8DPSK 2402MHz



8DPSK 2441MHz



8DPSK 2480MHz




8. SPURIOUS EMISSION

8.1. TEST EQUIPMENT


Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2018/12/17	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2018/12/17	1 Year
3	Loop antenna	TESEQ	HLA6120	20129	2018/12/17	1 Year
4	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2018/12/17	1 Year
5	Double Ridged Horn Antenna	Schwarzbeck	BBHA9120D	9120D 1065	2018/12/17	1 Year
6	Horn Antenna	Schwarzbeck	BBHA 9170	9170 1248	2018/12/17	1 Year
7	Pre-amplifier	A.H.	PAM-1840VH	562	2018/12/17	1 Year
8	Pre-amplifier	R&S	AFS33-18002 650-30-8P-44	SEL0080	2018/12/17	1 Year
9	Pre-Amplifier	HP	8449B	3274A06298	2018/12/17	1 Year
10	RF Cable	R&S	R01	10403	2018/12/17	1 Year
11	RF Cable	R&S	R02	10512	2018/12/17	1 Year

8.2. BLOCK DIAGRAM OF TEST SETUP


In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. LIMIT

8.3.1 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

8.3.2. Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

8.3.3. Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 30dB below the fundamental emissions, or comply with 15.209 limits.

8.4. TEST PROCEDURE

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and assistant system according clause 2.4 and 7.2
- (3) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used
9KHz-30MHz	Active Loop antenna
30MHz-1GHz	Trilog Broadband Antenna
1GHz-26.5GHz	Double Ridged Horn Antenna(1GHz-26.5GHz)

Remark: Because there is only a bottom noise above 18GHz, so the test report only put the data below 18GHz.

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (4) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:
 - (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)
 - (b) Change work frequency or channel of device if practicable.
 - (c) Change modulation type of device if practicable.
 - (d) new battery is used during testing
 - (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

- (5) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.
- (6) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (7) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

- (8) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure). Peak detector is used for Peak and AV measurement both.

8.5. TEST RESULT

Below 30M

EUT:	BLE CAT BOARD ASM	Model No.:	191D9618
Temperature:	24°C	Relative Humidity:	55%
Distance:	3m	Test Power:	DC 5V
Polarization:	--	Test Result:	Pass
Test Mode:	Keeping TX mode	Test By:	Lake

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	P
--	--	--	--	P

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor

Between 30M – 1000 MHz

EUT:	BLE CAT BOARD ASM	Model No.:	191D9618
Temperature:	24°C	Relative Humidity:	55%
Distance:	3m	Test Power:	DC 5V
Polarization:	Vertical	Test Result:	Pass
Test Time:	2018-11-07	Test By:	Lake
Standard:	(RE)FCC PART 15		
Test Mode:	Keeping TX mode		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		43.2017	23.13	-5.77	17.36	40.00	-22.64	QP
2		107.8876	23.44	-7.71	15.73	43.50	-27.77	QP
3		148.4410	23.53	-7.51	16.02	43.50	-27.48	QP
4		212.2694	23.44	-4.40	19.04	43.50	-24.46	QP
5		393.4723	24.48	-4.05	20.43	46.00	-25.57	QP
6	*	790.6187	23.81	7.69	31.50	46.00	-14.50	QP

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

EUT:	BLE CAT BOARD ASM	Model No.:	191D9618
Temperature:	24°C	Relative Humidity:	55%
Distance:	3m	Test Power:	DC 5V
Polarization:	Horizontal	Test Result:	Pass
Test Time:	2018-11-07	Test By:	Lake
Standard:	(RE)FCC PART 15		
Test Mode:	Keeping TX mode		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		42.4508	23.47	-1.94	21.53	40.00	-18.47	QP
2		106.7587	23.55	-7.16	16.39	43.50	-27.11	QP
3		186.4409	24.28	-6.50	17.78	43.50	-25.72	QP
4		244.2321	23.66	-6.49	17.17	46.00	-28.83	QP
5		545.1826	23.96	4.59	28.55	46.00	-17.45	QP
6	*	726.8052	24.80	7.22	32.02	46.00	-13.98	QP

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
- (3) Margin = Result - Limit

Between 1000M – 26500 MHz


EUT:	BLE CAT BOARD ASM	Model No.:	191D9618
Temperature:	24°C	Relative Humidity:	55%
Distance:	3m	Test Power:	DC 5V
Standard:	FCC PART 15.247	Test Result:	Pass
Test Time:	2018-11-07	Test By:	Lake
Test Mode:	TX		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)-Above 1G							
4804.211	59.47	-3.64	55.83	74.00	-18.17	Pk	Vertical
4804.211	41.71	-3.64	38.07	54.00	-15.93	AV	Vertical
7206.324	52.58	-0.95	51.63	74.00	-22.37	Pk	Vertical
7206.324	37.65	-0.95	36.70	54.00	-17.30	AV	Vertical
4804.142	59.81	-3.64	56.17	74.00	-17.83	Pk	Horizontal
4804.142	41.62	-3.64	37.98	54.00	-16.02	AV	Horizontal
7206.052	53.88	-0.95	52.93	74.00	-21.07	Pk	Horizontal
7206.052	37.57	-0.95	36.62	54.00	-17.38	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.085	59.35	-3.68	55.67	74.00	-18.33	Pk	Vertical
4882.085	39.82	-3.68	36.14	54.00	-17.86	AV	Vertical
7323.175	55.82	-0.82	55.00	74.00	-19.00	Pk	Vertical
7323.175	40.63	-0.82	39.81	54.00	-14.19	AV	Vertical
4882.307	58.35	-3.68	54.67	74.00	-19.33	Pk	Horizontal
4882.307	39.49	-3.68	35.81	54.00	-18.19	AV	Horizontal
7323.209	55.72	-0.82	54.90	74.00	-19.10	Pk	Horizontal
7323.209	39.93	-0.82	39.11	54.00	-14.89	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960.175	58.72	-3.59	55.13	74.00	-18.87	Pk	Vertical
4960.175	41.88	-3.59	38.29	54.00	-15.71	AV	Vertical
7440.263	53.19	-0.68	52.51	74.00	-21.49	Pk	Vertical
7440.263	37.43	-0.68	36.75	54.00	-17.25	AV	Vertical
4960.307	57.55	-3.59	53.96	74.00	-20.04	Pk	Horizontal
4960.307	39.72	-3.59	36.13	54.00	-17.87	AV	Horizontal
7440.089	53.09	-0.68	52.41	74.00	-21.59	Pk	Horizontal
7440.089	36.92	-0.68	36.24	54.00	-17.76	AV	Horizontal

Note: Mode 1Mbps is the worst mode.

Radiated band edge:

Test Site	: 3m Chamber	Vertical	
EUT	: BT CAT BOARD ASM	Tested By	: Smile
Power Supply	: DC 5V	Model Number	: 191D9618
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	Test Mode	: Tx mode: 1M 2402MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	21.99	30.85	52.84	74.00	-21.16	peak
2	2390.000	10.06	30.85	40.91	54.00	-13.09	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss
- (3) Margin = Result - Limit

Test Site	: 3m Chamber	Horizontal	
EUT	: BT CAT BOARD ASM	Tested By	: Smile
Power Supply	: DC 5V	Model Number	: 191D9618
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	Test Mode	: Tx mode: 1M 2402MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	22.41	30.85	53.26	74.00	-20.74	peak
2	2390.000	10.22	30.85	41.07	54.00	-12.93	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss
- (3) Margin = Result - Limit

Test Site	: 3m Chamber	Vertical	
EUT	: BT CAT BOARD ASM	Tested By	: Smile
Power Supply	: DC 5V	Model Number	: 191D9618
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	Test Mode	: Tx mode: 1M 2480MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.74	31.07	53.81	74.00	-20.19	peak
2	2483.500	10.52	31.07	41.59	54.00	-12.41	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss
- (3) Margin = Result - Limit

Test Site	: 3m Chamber	Horizontal	
EUT	: BT CAT BOARD ASM	Tested By	: Smile
Power Supply	: DC 5V	Model Number	: 191D9618
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	Test Mode	: Tx mode: 1M 2480MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.63	31.07	53.70	74.00	-20.30	peak
2	2483.500	10.29	31.07	41.36	54.00	-12.64	AVG

The test result is calculated as the following:

- (1) Result = Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss
- (3) Margin = Result - Limit

Note: Mode 1Mbps is the worst mode.

9. CONDUCTED EMISSION MEASUREMENT

9.1. POWER LINE CONDUCTED EMISSION LIMITS

(Frequency Range 150KHz-30MHz)

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

9.2. MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Pulse Limiter	MTS-systemtechnik	MTS-IMP-136	261115-010-0024	12/17/2018
2	EMI Test Receiver	R&S	ESCI	101308	12/17/2018
3	LISN	AFJ	LS16	16011103219	12/17/2018
4	LISN	SCHWARZBECK	NSLK 8127	8127-432	12/17/2018
5	Measurement Software	Farad	EZ-EMC (Ver.ATT-03A)	N/A	N/A

Rema: "N/A" denotes No Model No. , Serial No. or No Calibration specified.

9.3. TEST PROCEDURE

The EUT was placed on a non-conductive table, which is 0.8 meters above the horizontal reference ground plane and 0.4 meters from vertical reference ground plane. EUT has being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm / 50 uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables those are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.


LISN at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related paragraph – EUT Test Photo.

9.4. DEVIATION FROM TEST STANDARD

No deviation

9.5. TEST SETUP




9.6. EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting mode.

9.7. TEST RESULTS


EUT:	BLE CAT BOARD ASM	Model No.:	191D9618
Temperature:	24°C	Relative Humidity:	55%
Distance:	3m	Test Power:	DC 5V
Standard:	FCC PART 15.247	Test Result:	Pass
Test Time:	2018-11-07	Test By:	Lake
Test Mode:	TX		

Test Mode: TX	Phase : Line
---------------	--------------



Remark: Factor = LISN Factor + Cable Loss+ Pulse limiter Factor.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1		0.1500	25.31	11.94	37.25	55.99	-18.74	AVG
2	*	0.1700	45.27	11.55	56.82	64.96	-8.14	QP
3		0.4220	32.19	10.07	42.26	57.41	-15.15	QP
4		0.4220	22.10	10.07	32.17	47.41	-15.24	AVG
5		1.2940	20.34	9.92	30.26	46.00	-15.74	AVG
6		1.3260	30.97	9.92	40.89	56.00	-15.11	QP



Remark: Factor = LISN Factor + Cable Loss+ Pulse limiter Factor.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1		0.1500	27.13	11.94	39.07	55.99	-16.92	AVG
2	*	0.1580	49.65	11.75	61.40	65.56	-4.16	QP
3		0.2060	43.48	11.09	54.57	63.36	-8.79	QP
4		0.2180	24.95	11.00	35.95	52.89	-16.94	AVG
5		0.4540	34.33	10.03	44.36	56.80	-12.44	QP
6		0.4540	24.79	10.03	34.82	46.80	-11.98	AVG

10.100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

10.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2019/05/25	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2018/12/17	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2018/12/17	1 Year
4	Spectrum analyzer	R&S	FSV40	101470	2019/06/28	1 Year

10.2. LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

10.3. TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

10.4. TEST RESULT

PASS (See below detailed test result.)

Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
GFSK Non-hopping			
2400	56.43	20	Pass
2483.5	56.47	20	Pass



Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
GFSK hopping			
2400	56.20	20	Pass
2483.5	55.91	20	Pass

Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
8DPSK Non-hopping			
2400	54.72	20	Pass
2483.5	53.94	20	Pass



Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
8DPSK hopping			
2400	52.82	20	Pass
2483.5	53.19	20	Pass

Note: GFSK and 8DPSK mode is worse case , and only worse case is reported



GFSK Non-hopping





GFSK Hopping





8DPSK Non-hopping





8DPSK Hopping





GFSK 2402MHz





GFSK 2441MHz





GFSK 2480MHz





8DPSK 2402MHz



8DPSK 2441MHz



8DPSK 2480MHz



11. ANTENNA REQUIREMENTS

11.1. LIMIT

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. EUT ANTENNA

The EUT antenna is Internal Antenna. It comply with the standard requirement.

END OF REPORT