CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : Haier US Appliance Solutions, Inc.

Applicant Address : Appliance Park, AP2-226, Louisville, KY 40225,

United States

Kind of Product : Wi-Fi Module

Equipment : WCATA004

FCC ID : ZKJ-WCATA004

Certification : 10229A-WCATA004 Number IC

Antenna type : Chip Antenna

Antenna Gain : 1.47 dBi

CTK Co., Ltd.

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

** MPE Calculations **

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

 $G = Log^{-1}$ (dB antenna gain / 10)

Power density at the specific separation:

$S = PG/(4R^2\pi)$	Where,
	S = Maximum power density (mW/cm²) P = Power input to the antenna (mW)
	G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna
	(20cm = limit for MPE)

The Maximum permissible exposure (MPE) for the general population is 1 $\rm mW/cm^2$. The power density at 20cm does not exceed the 1 $\rm mW/cm^2$ limit.

Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where,
	P = Power input to the antenna (mW)
	G = Numeric power gain of the antenna
	R = Distance to the center of the radiation of the
	antenna
	(20cm = limit for MPE)



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Mode	P (dBm)	P (mW)	G (dBi)	S (mW/cm²)	R (cm)
802.11b	16.93	49.32	1.47	0.0138	
802.11g	12.58	18.11		0.0051	20
802.11n HT20	11.53	14.22		0.0040	