

EMISSIONS TEST REPORT

Report Number: 100398565BOX-002d

Project Number: G100398565

Report Issue Date: 11/04/2011

Product Designation: ZOLL E Series Data Comm Card (Bluetooth Mode)

Standards: CFR47 FCC Part 15:2011 Subpart C Section 15.247,
CFR47 FCC Part 15:2011 Subpart B Class B,
Industry Canada RSS-210 Issue 8 December 2010,
Industry Canada ICES-003 Issue 4 February 2004,
Industry Canada RSS-Gen Issue 3 December 2010

Tested by:

Intertek Testing Services NA, Inc.
70 Codman Hill Road
Boxborough, MA 01719

Client:

Zoll Medical Corporation
269 Mill Road
Chelmsford, MA 01824

Report prepared by Reviewer



Kouma Sinn / Senior Project Engineer

Report reviewed by



Michael F. Murphy / Staff Engineer, EMC

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 3.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

2 Test Summary

Section	Test full name	Result
3	Client Information	--
4	Description of Equipment Under Test	--
5	System Setup and Method	--
6	Maximum Peak Output Power FCC 15:2011 Subpart C, Section 15.247 (b) (1), (4) RSS-210 Issue 8 December 2010, A8.4 (2)	Pass
7	Transmitter Radiated Spurious Emissions FCC 15:2011 Subpart C Section 15.247 (d) RSS-210 Issue 8 December 2010, A8.5	Pass
8	Hopping Channel Separation FCC 15:2011 Subpart C Section 15.247 (a)(1) RSS-210 Issue 8 December 2010, A8.1 (b)	Pass
9	Number of Hopping Frequency FCC 15:2011 Subpart C Section 15.247 (a)(1) (iii) RSS-210 Issue 8 December 2010, A8.1 (d)	Pass
10	Hopping Channel Bandwidth FCC 15:2011 Subpart C Section 15.247 (a)(1) RSS-210 Issue 8 December 2010, A8.1 (b)	Pass
11	Hopping Dwell time FCC 15:2011 Subpart C Section 15.247 (a)(1) (iii) RSS-210 Issue 8 December 2010, A8.1 (d)	Pass
12	Band-edge Compliance FCC 15:2011 Subpart C Section 15.247 (d) RSS-210 Issue 8 December 2010, A8.5	Pass
13	Receiver Radiated Spurious FCC Part 15:2011 Subpart B Section 15.109 (a) RSS-Gen Issue 3 December 2010, Section 6.1 (Table 2)	Pass
14	AC Mains Conducted Emissions FCC Part 15:2011 Section 15.207 (a) RSS-Gen Issue 3 December 2010, Section 7.2.4 (Table 4)	Pass
15	Revision History	--

3 Client Information

This EUT was tested at the request of:

Company: Zoll Medical Corporation
269 Mill Road
Chelmsford, MA 01824

Contact: Mr. Don Paradis

Telephone: 978-421-9608

Fax: Not Available

Email: DParadis@zoll.com

4 Description of Equipment Under Test

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
ZOLL E Series Data Comm Card	Zoll Medical	ZOLL E Series Data Comm Card	IN0411-00032

Receive Date:	08/15/2011
Received Condition:	Good
Type:	Production

Description of Equipment Under Test (provided by client)	
Bluetooth transmitter inside E-Series Defibrillator. It utilizes an integral antenna on an E-series board which has 1.5 dBi of gain as stated by Zoll Medical. Bluetooth utilizes 79 channels starting at 2402 MHz and extending to 2480 MHz. Channels 1 (2402 MHz), 40 (2441 MHz) and 79 (2480 MHz) were selected for testing.	

Equipment Under Test Power Configuration			
Rated Voltage	Rated Current	Rated Frequency	Number of Phases
100-120V	220VA	50/60 Hz	1

Operating modes of the EUT:	
No.	Descriptions of EUT Exercising
1	Transmit mode – hopping enabled (DH1, DH3, and DH5) or hopping disabled, modulated on a single channel
2	Receive mode

5 System Setup and Method


Cables					
Qty	Description	Length (m)	Shielding	Ferrites	Termination
1	AC Mains Cable	3.0m	None	None	EUT/AC
1	ECG Cable	3.0m	Foil	None	EUT
1	ECGx1000 RS-232 Cable	1.2	Foil	None	EUT
1	SPO2 Cable	3.0m	Braid	None	EUT
1	Defibrillator Cable	2.2m	Braid	None	EUT
1	CO2 Cable	3.0m	Braid	None	EUT

Support Equipment			
Description	Manufacturer	Model Number	Serial Number
E-Series Defibrillator	Zoll Medical	E Series	AB11B016129

5.1 Method:

Configuration as required by ANSI C 63.4:2003, FCC Part 15:2011 Subpart C Section 15.247, RSS-210 Issue 8 December 2010, RSS-Gen Issue 3 December 2010, and FCC Public Notice DA 00-705 Released March 30, 2000.

5.2 EUT Block Diagram:



6 Maximum Peak Output Power

6.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, DA 00-705, ANSI C63.4, RSS-Gen, and RSS-210 Annex 8.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) $< U_{CISPR}$ (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 52.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB/m}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$FS = 32 \text{ dB}\mu\text{V/m}$$

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF/20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

$$NF = \text{Net Reading in dB}\mu\text{V}$$

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$

$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

6.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
SAF767'	Weatherstation	Davis Instruments	Perception II	PE91222A03	01/14/2011	01/14/2012
145-416'	Cables 145-400 145-408 145-402 145-404	Huber + Suhner	3m Track B cables	multiple	08/31/2010	08/31/2011
145108'	EMI Test Receiver (20Hz - 40GHz)	Rohde & Schwarz	ESIB40	100209	04/28/2011	04/28/2012
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/08/2010	10/08/2011

Software Utilized:

Name	Manufacturer	Version
Excel 2003	Microsoft	(11.8231.8221) SP3
EMI Boxborough.xls	Intertek	08/27/10

6.3 Results:

The sample tested was found to comply.

FCC 15 Subpart C, Section 15.247 (b) (1) & RSS-210, A8.4 (2)

The maximum peak conducted output power of the intentional radiator shall not exceed 0.125 watts for systems with channel separation of 2/3 of the channel bandwidth.

The antenna conducted tests cannot be performed on this device, radiated tests to show compliance was performed using the following formula per DA 00-705 Released March 30, 2000.

$$P = \frac{(E \cdot d)^2}{30G}$$

E is the measured maximum fundamental field strength in V/m.


G is the numeric gain of the transmitting antenna with reference to an isotropic radiator.

d is the distance in meters from which the field strength was measured.


P is the power in watts.

6.4 Setup Photographs:

Test Setup Photo # 1



Test Setup Photo # 2



6.5 Data:

Intertek

Radiated Emissions

Company: Zoll Medical
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Nicholas Abbondante
 Project #: G100398565 Date(s): 08/19/11
 Standard: FCC Part 15 Subpart C 15.247
 Receiver: R&S ESIB (145108) 04-06-2012 Limit Distance (m): 3
 PreAmp: NONE.
 PreAmp Used? (Y or N): N Voltage/Frequency: 115V/60Hz Frequency Range: Frequencies Shown
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth
Note: Fundamental Field Strength											
PK	V	2402.000	49.72	28.33	5.80	0.00	0.00	83.86	-	-	1/3 MHz
PK	H	2402.000	49.88	28.15	5.80	0.00	0.00	83.83	-	-	1/3 MHz
PK	V	2441.000	51.08	28.35	5.88	0.00	0.00	85.31	-	-	1/3 MHz
PK	H	2441.000	51.99	28.25	5.88	0.00	0.00	86.12	-	-	1/3 MHz
PK	V	2480.000	53.89	28.37	5.96	0.00	0.00	88.22	-	-	1/3 MHz
PK	H	2480.000	54.03	28.36	5.96	0.00	0.00	88.35	-	-	1/3 MHz
Note: 100 kHz reference for 20 dBc limit											
PK	V	2402.000	49.14	28.33	5.80	0.00	0.00	83.28	-	-	100/300 kHz
PK	H	2402.000	49.54	28.15	5.80	0.00	0.00	83.49	-	-	100/300 kHz
PK	V	2441.000	50.64	28.35	5.88	0.00	0.00	84.87	-	-	100/300 kHz
PK	H	2441.000	51.78	28.25	5.88	0.00	0.00	85.91	-	-	100/300 kHz
PK	V	2480.000	53.65	28.37	5.96	0.00	0.00	87.98	-	-	100/300 kHz
PK	H	2480.000	53.90	28.36	5.96	0.00	0.00	88.22	-	-	100/300 kHz

FCC IC

Maximum Peak Power Calculation Given a 1.5 dBi antenna gain:

Channels	dBuV/m	mW conducted	dBm conducted	mW EIRP	dBm EIRP
1	83.86	0.052	-12.86	0.073	-11.37
40	86.12	0.087	-10.60	0.123	-9.11
79	88.35	0.146	-8.37	0.205	-6.88

Test Personnel: Nicholas AbbondanteTest Date: 08/19/2011Supervising Engineer:
(Where Applicable)N/AEmissions below the limits
specified in section 6.3Product Standard: FCC Part 15.247, RSS-210 Annex 8

Test Levels:

Input Voltage: 120VAC/60Hz25 °CPretest Verification w/ Ambient
Signals or BB Source:Ambient Signals

Ambient Temperature:

54 %

Relative Humidity:

1003 mbar

Deviations, Additions, or Exclusions: None

7 Transmitter Radiated Spurious Emissions

7.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, DA 00-705, ANSI C63.4, RSS-Gen, and RSS-210 Annex 8.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) $< U_{CISPR}$ (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 52.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB/m}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$FS = 32 \text{ dB}\mu\text{V/m}$$

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF/20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

$$NF = \text{Net Reading in dB}\mu\text{V}$$

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$

$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

7.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
SAF767'	Weatherstation	Davis Instruments	Perception II	PE91222A03	01/14/2011	01/14/2012
145-414	Cables 145-400 145-409 145-4-5 145-403	Huber + Suhner	3m Track A cables	multiple	08/31/2010	08/31/2011
145034'	BiLog Antenna (30 MHz to 1GHz)	Schaffner Chase EMC	CBL6111C	none	01/07/2011	01/07/2012
145003'	Preamplifier (150 KHz to 1.3 GHz)	Hewlett Packard	8447D	2443A04077	09/24/2010	09/24/2011
145014'	Preamplifier (1 GHz to 26.5 GHz)	Hewlett Packard	8449B	3008A00232	12/28/2010	12/28/2011
HORN ANTENNA		EMCO	3115	9602-4675	10/08/2010	10/08/2011
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/10/2010	09/10/2011
REA002'	2.5GHz High Pass Filter	Reactel, Inc	7HS-2.5G/18G-S11	06-1	12/06/2010	12/06/2011
145-416'	Cables 145-400 145-408 145-402 145-404	Huber + Suhner	3m Track B cables	multiple	08/31/2010	08/31/2011
EMC02'	ANTENNA, RIDGED GUIDE, 1-18 GHZ	EMCO	3115	2784	10/08/2010	10/08/2011
CBL030'	High Frequency Cable 40GHz	Megaphase	TM40 K1K1 80	CBL030	01/06/2011	01/06/2012
MEG005'	High Frequency Cable	Megaphase	TM40-K1K1-197	8148601-001	01/06/2011	01/06/2012
PRE9'	100MHz-40GHz Preamp	MITEQ	NSP4000-NFG	1260417	05/12/2011	05/12/2012
ROS001'	Spectrum Analyzer 20Hz - 40 GHz	Rohde & Schwartz	FSEK-30	100225	01/13/2011	01/13/2012

Software Utilized:

Name	Manufacturer	Version
C5	Teseq	Build 5.26.00.3
Excel 2003	Microsoft	(11.8231.8221) SP3
EMI Boxborough.xls	Intertek	08/27/10

7.3 Results:

The sample tested was found to comply.

In any 100 kHz bandwidth outside the frequency band, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see 15.205(c)).

FCC Part 15.209(a) & RSS-210 A8.5 – Restricted Band Radiated Spurious/Harmonics Limits


Frequency (MHz)	Field Strength μV/m	Field Strength dBμV/m	Test Distance (meters)
30–88	100	40.00	3
88–216	150	43.52	3
216–960	200	46.02	3
Above 960	500	53.98	3

FCC Part 15.247(d) & RSS-210 A8.5 – Non Restricted Band Radiated Spurious/Harmonics Limits


Channels	Fundamental Field Strength (dB _{UV} /m)	Spurious/Harmonics Limits (dB _{UV} /m)	Test Distance (meters)
1	83.49	63.49	3
40	85.91	65.91	3
79	88.22	68.22	3

7.4 Setup Photographs:


Test Setup Photo # 1




Test Setup Photo # 2



Test Setup Photo # 3




Test Setup Photo # 4



7.5 Plots/Data:

FCC Part 15.209, FCC Part 15.247, RSS-210

Channel 1 (2.402GHz) Radiated Emissions @ 3m, Vertical Polarity, 30-1000MHz



"PORTRAIT"


- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable Level (dBuV/m) = AF + CL + PA + Raw
- AF = Antenna Factor
- CL = Cable Losses
- PA = Pre-Amplifier
- Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Vert (l)	Angle (deg)	Mast Height (m)	RBW (Hz)
30.850M	33.13	17.305	-26.553	40.00	-6.87	1	143	1.36	120k
48.932M	38.55	8.334	-26.310	40.00	-1.45	1	66	1.19	120k
50.029M	38.59	7.988	-26.289	40.00	-1.41	1	266	1.19	120k
53.001M	31.29	7.200	-26.229	40.00	-8.71	1	211	1.18	120k
61.847M	33.87	5.215	-26.080	40.00	-6.13	1	46	1.46	120k
84.098M	29.00	8.700	-26.000	40.00	-11.00	1	343	1.59	120k
207.555M	35.22	10.500	-24.888	43.52	-8.30	1	255	1.41	120k
211.212M	34.71	10.403	-24.882	43.52	-8.81	1	256	1.37	120k

FCC Part 15.209, FCC Part 15.247, RSS-210

Channel 1 (2.402GHz) Radiated Emissions @ 3m, Horizontal Polarity, 30-1000MHz



"PORTRAIT"

Measured Peak Value

Measured Quasi Peak Value

Measured Average Value

Maximum Value of Mast and Turntable Level (dBuV/m) = AF + CL + PA + Raw

AF = Antenna Factor

CL = Cable Losses

PA = Pre-Amplifier


Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Hor (--)	Angle (deg)	Mast Height (m)	RBW (Hz)
61.507M	28.67	5.551	-26.084	40.00	-11.33	--	163	3.07	120k
169.382M	34.64	9.700	-25.169	43.52	-8.88	--	349	1.83	120k
186.978M	37.00	9.000	-25.009	43.52	-6.52	--	315	1.53	120k
194.740M	37.89	9.000	-24.943	43.52	-5.63	--	319	1.19	120k
208.199M	36.72	9.236	-24.887	43.52	-6.80	--	333	1.18	120k
214.642M	36.78	9.014	-24.876	43.52	-6.74	--	190	1.52	120k

FCC Part 15.209, FCC Part 15.247, RSS-210

Channel 40 (2.441GHz) Radiated Emissions @ 3m, Vertical Polarity, 30-1000MHz



"PORTRAIT"


- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable
- Level (dBuV/m) = AF + CL + PA + Raw
- AF = Antenna Factor
- CL = Cable Losses
- PA = Pre-Amplifier
- Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Vert ()	Angle (deg)	Mast Height (m)	RBW (Hz)
31.135M	35.35	17.146	-26.551	40.00	-4.65		86	1.19	120k
47.389M	36.40	9.044	-26.340	40.00	-3.60		70	1.30	120k
49.385M	36.51	8.185	-26.302	40.00	-3.49		218	1.67	120k
59.665M	34.85	5.634	-26.106	40.00	-5.15		37	1.19	120k
62.080M	36.44	5.192	-26.078	40.00	-3.56		88	1.41	120k
204.588M	34.14	10.475	-24.892	43.52	-9.38		262	1.40	120k

FCC Part 15.209, FCC Part 15.247, RSS-210

Channel 40 (2.441GHz) Radiated Emissions @ 3m, Horizontal Polarity, 30-1000MHz



"PORTRAIT"

- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable


Level (dBuV/m) = AF + CL + PA + Raw
AF = Antenna Factor
CL = Cable Losses
PA = Pre-Amplifier
Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Hor (--)	Angle (deg)	Mast Height (m)	RBW (Hz)
31.022M	16.48	18.096	-26.552	40.00	-23.52	--	110	1.59	120k
61.139M	26.26	5.514	-26.088	40.00	-13.74	--	328	3.25	120k
187.747M	37.79	9.000	-25.002	43.52	-5.73	--	335	1.49	120k
203.757M	37.68	9.250	-24.894	43.52	-5.84	--	335	1.44	120k
212.025M	38.09	9.119	-24.880	43.52	-5.43	--	334	1.49	120k

FCC Part 15.209, FCC Part 15.247, RSS-210

Channel 79 (2.480GHz) Radiated Emissions @ 3m, Vertical Polarity, 30-1000MHz



"PORTRAIT"

Measured Peak Value

Measured Quasi Peak Value

Measured Average Value

Maximum Value of Mast and Turntable
Level (dBuV/m) = AF + CL + PA + Raw

AF = Antenna Factor

CL = Cable Losses

PA = Pre-Amplifier


Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Vert ()	Angle (deg)	Mast Height (m)	RBW (Hz)
31.370M	28.69	17.052	-26.549	40.00	-11.31		262	1.19	120k
46.441M	26.34	9.536	-26.359	40.00	-13.66		355	1.30	120k
61.648M	33.08	5.235	-26.082	40.00	-6.92		99	1.18	120k
76.385M	25.35	7.415	-26.000	40.00	-14.65		234	1.67	120k
82.944M	27.75	8.194	-26.000	40.00	-12.25		133	1.71	120k
206.472M	34.72	10.500	-24.889	43.52	-8.80		251	1.42	120k

FCC Part 15.209, FCC Part 15.247, RSS-210

Channel 79 (2.480GHz) Radiated Emissions @ 3m, Horizontal Polarity, 30-1000MHz



"PORTRAIT"

Measured Peak Value

Measured Quasi Peak Value

Measured Average Value

Maximum Value of Mast and Turntable
Level (dBuV/m) = AF + CL + PA + Raw

AF = Antenna Factor

CL = Cable Losses

PA = Pre-Amplifier

Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Hor (--)	Angle (deg)	Mast Height (m)	RBW (Hz)
121.236M	25.26	11.476	-25.646	43.52	-18.26	--	166	2.54	120k
190.493M	37.25	8.951	-24.979	43.52	-6.27	--	334	1.30	120k
199.018M	37.37	9.100	-24.908	43.52	-6.15	--	329	1.44	120k
203.053M	37.53	9.222	-24.895	43.52	-5.99	--	344	1.48	120k
207.227M	38.31	9.255	-24.888	43.52	-5.21	--	312	1.31	120k
213.097M	38.30	9.076	-24.879	43.52	-5.22	--	333	1.42	120k

FCC Part 15.209, FCC Part 15.247, RSS-210

Channel 1 (2.402GHz) Radiated Emissions @ 3m, 1-18GHz

Radiated Emissions

Company: Zoll Medical Corp
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Vathana Ven
 Project #: G100398565 Date(s): 07/26/11
 Standard: FCC Part 15.209, FCC Part 15.247, RSS-210
 Receiver: R&S ESI (145-128) 09-10-2011 Limit Distance (m): 3
 PreAmp: PRE_145014_12-28-2011.txt Test Distance (m): 3
 PreAmp Used? (Y or N): Y Voltage/Frequency: 120VAC/60Hz Frequency Range: 1-18GHz
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)

Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS: NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC	RB	Harmonic?
PK	V	4804.000	45.34	32.87	8.30	34.88	0.00	51.63	54.00	-2.37	1/3 MHz	RB	RB	RB	Noise Floor
AVG	V	4804.000	36.83	32.87	8.30	34.88	0.00	43.12	54.00	-10.88	1/3 MHz	RB	RB	RB	Noise Floor
PK	V	7206.000	30.48	35.94	10.52	35.53	0.00	41.41	63.49	-22.08	100/300 kHz	RB	RB	RB	Noise Floor
PK	V	9608.000	32.18	37.72	12.17	35.94	9.54	36.59	63.49	-26.90	100/300 kHz	RB	RB	RB	Noise Floor
PK	V	12010.000	42.14	39.35	13.24	35.17	9.54	50.02	54.00	-3.98	1/3 MHz	RB	RB	RB	Noise Floor
AVG	V	12010.000	29.28	39.35	13.24	35.17	9.54	37.16	54.00	-16.84	1/3 MHz	RB	RB	RB	Noise Floor
PK	V	14412.000	34.09	42.01	15.96	34.07	9.54	48.44	63.49	-15.05	100/300 kHz	RB	RB	RB	Noise Floor
PK	V	16814.000	30.42	39.76	16.88	34.87	9.54	42.65	63.49	-20.84	100/300 kHz	RB	RB	RB	Noise Floor

Channel 1 (2.402GHz) Radiated Emissions @ 3m, 18-25GHz

Radiated Emissions

Company: Zoll Medical Corp
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Kouma Sinn
 Project #: G100398565 Date(s): 08/16/11
 Standard: FCC Part 15.209, FCC Part 15.247, RSS-210
 Receiver: ROS001 Limit Distance (m): 3
 PreAmp: PRE9 05-12-2012.txt Test Distance (m): 1
 PreAmp Used? (Y or N): Y Voltage/Frequency: 120VAC/60Hz Frequency Range: 18-25GHz
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)

Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS: NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC	RB	Harmonic?
CH1 - 2.402GHz. No emissions were detected. Readings below are noise floor signals.															
PK	V	19216.000	21.70	45.33	17.13	29.02	9.54	45.60	74.00	-28.40	100/300kHz	RB	RB	RB	Noise Floor
AVG	V	19216.000	20.46	45.33	17.13	29.02	9.54	44.36	54.00	-9.64	100/300kHz	RB	RB	RB	Noise Floor
PK	V	19216.000	33.80	45.33	17.13	29.02	9.54	57.70	74.00	-16.30	1/3MHz	RB	RB	RB	Noise Floor
AVG	V	19216.000	25.00	45.33	17.13	29.02	9.54	48.90	54.00	-5.10	1/3MHz	RB	RB	RB	Noise Floor
PK	V	21618.000	23.50	45.47	18.15	26.74	9.54	50.84	74.00	-23.16	100/300kHz	RB	RB	RB	Noise Floor
AVG	V	21618.000	17.96	45.47	18.15	26.74	9.54	45.30	54.00	-8.70	100/300kHz	RB	RB	RB	Noise Floor
PK	V	24020.000	22.27	45.42	18.90	26.57	9.54	50.49	74.00	-23.51	100/300kHz	RB	RB	RB	Noise Floor
AVG	V	24020.000	17.96	45.42	18.90	26.57	9.54	46.18	54.00	-7.82	100/300kHz	RB	RB	RB	Noise Floor

Channel 40 (2.441GHz) Radiated Emissions @ 3m, 1-18GHz

Radiated Emissions

Company: Zoll Medical Corp
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Vathana Ven
 Project #: G100398565 Date(s): 07/26/11
 Standard: FCC Part 15.209, FCC Part 15.247, RSS-210
 Receiver: R&S ESI (145-128) 09-10-2011 Limit Distance (m): 3
 PreAmp: PRE_145014_12-28-2011.txt Test Distance (m): 3
 PreAmp Used? (Y or N): Y Voltage/Frequency: 120VAC/60Hz Frequency Range: 1-18GHz
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS: NF = Noise Floor, RB = Restricted Band: Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC	Harmonic?
PK	V	4882.000	46.17	32.97	8.38	34.88	0.00	52.64	54.00	-1.36	1/3 MHz	RB	RB	
AVG	V	4882.000	39.44	32.97	8.38	34.88	0.00	45.91	54.00	-8.09	1/3 MHz	RB	RB	
PK	V	7323.000	40.92	36.31	10.58	35.53	0.00	52.28	54.00	-1.72	1/3 MHz	RB	RB	
AVG	V	7323.000	29.70	36.31	10.58	35.53	0.00	41.06	54.00	-12.94	1/3 MHz	RB	RB	
PK	V	9764.000	33.55	37.81	12.34	35.94	0.00	47.76	63.49	-15.73	100/300 kHz			
PK	V	12205.000	42.56	39.17	13.67	35.17	9.54	50.69	54.00	-3.31	1/3 MHz	RB	1 Meter	Noise Floor
AVG	V	12205.000	29.36	39.17	13.67	35.17	9.54	37.49	54.00	-16.51	1/3 MHz	RB	1 Meter	Noise Floor
PK	V	14646.000	32.67	41.45	16.14	34.07	9.54	46.65	63.49	-16.84	100/300 kHz		1 Meter	Noise Floor
PK	V	17087.000	30.16	40.78	16.84	34.87	9.54	43.37	63.49	-20.12	100/300 kHz		1 Meter	Noise Floor

Channel 40 (2.441GHz) Radiated Emissions @ 3m, 18-25GHz

Radiated Emissions

Company: Zoll Medical Corp
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Kouma Sinn
 Project #: G100398565 Date(s): 08/16/11
 Standard: FCC Part 15.209, FCC Part 15.247, RSS-210
 Receiver: ROS001 Limit Distance (m): 3
 PreAmp: PRE9 05-12-2012.txt Test Distance (m): 1
 PreAmp Used? (Y or N): Y Voltage/Frequency: 120VAC/60Hz Frequency Range: 18-25GHz
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS: NF = Noise Floor, RB = Restricted Band: Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC	Harmonic?
CH40 - 2.441GHz. No emissions were detected. Readings below are noise floor signals.														
PK	V	19528.000	22.94	45.54	17.46	28.96	9.54	47.43	74.00	-26.57	100/300kHz	RB	RB	
AVG	V	19528.000	20.46	45.54	17.46	28.96	9.54	44.95	54.00	-9.05	100/300kHz	RB	RB	
PK	V	19528.000	33.79	45.54	17.46	28.96	9.54	58.28	74.00	-15.72	1/3MHz	RB	RB	
AVG	V	19528.000	24.26	45.54	17.46	28.96	9.54	48.75	54.00	-5.25	1/3MHz	RB	RB	
PK	V	21969.000	21.35	45.28	18.27	25.36	9.54	49.99	74.00	-24.01	100/300kHz			
AVG	V	21969.000	17.96	45.28	18.27	25.36	9.54	46.60	54.00	-7.40	100/300kHz			
PK	V	24410.000	23.14	45.93	19.66	27.96	9.54	51.24	74.00	-22.76	100/300kHz			
AVG	V	24410.000	18.52	45.93	19.66	27.96	9.54	46.62	54.00	-7.38	100/300kHz			

Channel 79 (2.480GHz) Radiated Emissions @ 3m, 1-18GHz

Radiated Emissions

Company: Zoll Medical Corp
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Vathana Ven
 Project #: G100398565 Date(s): 07/26/11
 Standard: FCC Part 15.209, FCC Part 15.247, RSS-210
 Receiver: R&S ESI (145-128) 09-10-2011 Limit Distance (m): 3
 PreAmp: PRE_145014_12-28-2011.txt Test Distance (m): 3
 PreAmp Used? (Y or N): Y Voltage/Frequency: 120VAC/60Hz Frequency Range: 1-18GHz
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS: NF = Noise Floor, RB = Restricted Band: Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC	Harmonic?
PK	V	4960.000	46.10	33.05	8.46	34.88	0.00	52.73	54.00	-1.27	1/3 MHz	RB	RB	
AVG	V	4960.000	41.74	33.05	8.46	34.88	0.00	48.37	54.00	-5.63	1/3 MHz	RB	RB	
PK	V	7440.000	37.91	36.35	10.65	35.63	0.00	49.28	54.00	-4.72	1/3 MHz	RB	RB	
AVG	V	7440.000	26.74	36.35	10.65	35.63	0.00	38.11	54.00	-15.89	1/3 MHz	RB	RB	Noise Floor
PK	V	9920.000	28.07	38.04	12.50	35.97	0.00	42.64	63.49	-20.85	100/300 kHz		1 Meter	Noise Floor
PK	V	12400.000	37.80	38.99	14.10	35.05	9.54	46.30	54.00	-7.70	1/3 MHz	RB	RB	Noise Floor
AVG	V	12400.000	25.40	38.99	14.10	35.05	9.54	33.90	54.00	-20.10	1/3 MHz	RB	RB	Noise Floor
PK	V	14880.000	26.09	40.25	15.94	34.47	9.54	38.27	54.00	-15.73	100/300 kHz		1 Meter	Noise Floor
PK	V	17360.000	22.60	42.08	17.38	34.64	9.54	37.89	54.00	-16.11	100/300 kHz		1 Meter	Noise Floor

Channel 79 (2.480GHz) Radiated Emissions @ 3m, 18-25GHz

Radiated Emissions

Company: Zoll Medical
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Kouma Sinn
 Project #: G100398565 Date(s): 08/16/11
 Standard: FCC Part 15.209, FCC Part 15.247, RSS-210
 Receiver: ROS001 Limit Distance (m): 3
 PreAmp: PRE9 05-12-2012.txt Test Distance (m): 1
 PreAmp Used? (Y or N): Y Voltage/Frequency: 120VAC/60Hz Frequency Range: 18-25GHz
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS: NF = Noise Floor, RB = Restricted Band: Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC	Harmonic?
CH79 -2.480GHz. No emissions were detected. Readings below are noise floor signals.														
PK	V	19840.000	21.42	45.42	17.44	28.98	9.54	45.76	74.00	-28.24	100/300kHz	RB	RB	
AVG	V	19840.000	18.52	45.42	17.44	28.98	9.54	42.86	54.00	-11.14	100/300kHz	RB	RB	
PK	V	19840.000	33.41	45.42	17.44	28.98	9.54	57.75	74.00	-16.25	1/3MHz	RB	RB	
AVG	V	19840.000	25.32	45.42	17.44	28.98	9.54	49.66	54.00	-4.34	1/3MHz	RB	RB	
PK	V	22320.000	22.06	45.36	18.13	25.52	9.54	50.49	74.00	-23.51	100/300kHz	RB	RB	
AVG	V	22320.000	16.71	45.36	18.13	25.52	9.54	45.14	54.00	-8.86	100/300kHz	RB	RB	
PK	V	22320.000	33.26	45.36	18.13	25.52	9.54	61.69	74.00	-12.31	1/3MHz	RB	RB	
AVG	V	22320.000	24.26	45.36	18.13	25.52	9.54	52.69	54.00	-1.31	1/3MHz	RB	RB	
PK	V	24800.000	22.13	46.34	19.59	29.64	9.54	48.88	74.00	-25.12	100/300kHz			
AVG	V	24800.000	20.00	46.34	19.59	29.64	9.54	46.75	54.00	-7.25	100/300kHz			

Test Personnel(s): Vathana Ven

Test Date(s): 07/26/2011

Kouma Sinn *KPS*

08/15/2011, 08/16/2011

Supervising Engineer:
(Where Applicable)

N/A

Emissions below the limits
specified in Section 7.3Product Standard:
FCC Part 15.247, RSS-210 Annex 8
Input Voltage:
115VAC/60Hz

Test Levels:

Ambient Temperature:

21, 21, 22 °C

Relative Humidity:

63, 65, 55 %

Atmospheric Pressure:

994, 999, 998 mbars

Pretest Verification w/ Ambient
Signals or BB Source: Ambient Signals

Deviations, Additions, or Exclusions: None

8 Hopping Channel Separation

8.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247 and RSS-210 Annex 8.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

8.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
SAF767'	Weatherstation	Davis Instruments	Perception II	PE91222A03	01/14/2011	01/14/2012
145-416'	Cables 145-400 145-408 145-402 145-404	Huber + Suhner	3m Track B cables	multiple	08/31/2010	08/31/2011
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/08/2010	10/08/2011
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/10/2010	09/10/2011

Software Utilized:

Name	Manufacturer	Version
None		

8.3 Results:


The sample tested was found to comply, since output power is below 125 mW and therefore the channel separation must be at least 2/3 of the 20 dB bandwidth.

FCC Part 15.247 (1) & RSS-210 A8.1 (b)


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

8.4 Setup Photographs:


Test Setup Photo # 1



Test Setup Photo # 2



8.5 Plots/Data:



Test Personnel: Kouma Sinn *KPS*

Test Date: 08/16/2011

Supervising Engineer:
(Where Applicable) N/A
Product Standard: FCC Part 15.247, RSS-210 Annex 8
Input Voltage: 115VAC/60Hz

Test Levels:	Emissions below the limits specified in Section 8.3
Ambient Temperature:	20 °C
Relative Humidity:	55 %
Atmospheric Pressure:	998 mbar

Pretest Verification w/ Ambient Signals or BB Source: **Ambient Signals**

Deviations, Additions, or Exclusions: None

9 Number of Hopping Frequency

9.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247 and RSS-210 Annex 8.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

9.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
SAF767'	Weatherstation	Davis Instruments	Perception II	PE91222A03	01/14/2011	01/14/2012
145-416'	Cables 145-400 145-408 145-402 145-404	Huber + Suhner	3m Track B cables	multiple	08/31/2010	08/31/2011
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/08/2010	10/08/2011
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/10/2010	09/10/2011

Software Utilized:

Name	Manufacturer	Version
None		

9.3 Results:


The sample tested was found to comply.

FCC Part 15.247 (1) (iii) & RSS-210 A8.1 (d)


Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

9.4 Setup Photographs:


Test Setup Photo # 1



Test Setup Photo # 2



9.5 Plots/Data:



Date: 16.AUG.2011 15:29:55

Test Personnel: Kouma Sinn *KPS*

Test Date: 08/16/2011

Supervising Engineer:
(Where Applicable)Emissions below the limits
specified in Section 9.3

Product Standard: FCC Part 15.247, RSS-210 Annex 8

Test Levels:

Input Voltage: 115VAC/60Hz

Ambient Temperature: 20 °C

Pretest Verification w/ Ambient
Signals or BB Source:

Relative Humidity: 55 %

Ambient Signals

Atmospheric Pressure: 998 mbar

Deviations, Additions, or Exclusions: None

10 Hopping Channel Bandwidth

10.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, DA 00-705, ANSI C63.4, RSS-Gen, and RSS-210 Annex 8.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

10.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
SAF767'	Weatherstation	Davis Instruments	Perception II	PE91222A03	01/14/2011	01/14/2012
145-416'	Cables 145-400 145-408 145-402 145-404	Huber + Suhner	3m Track B cables	multiple	08/31/2010	08/31/2011
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/08/2010	10/08/2011
145108'	EMI Test Receiver (20Hz - 40GHz)	Rohde & Schwarz	ESIB40	100209	04/28/2011	04/28/2012

Software Utilized:

Name	Manufacturer	Version
None		

10.3 Results:


The sample tested was found to comply.

FCC Part 15.247 (1) & RSS-210 A8.1 (b)


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

10.4 Setup Photographs:


Test Setup Photo # 1




Test Setup Photo # 2



10.5 Data:




Channel 40 20dB Bandwidth



Date: 19.AUG.2011 21:25:01

Channel 79 20dB Bandwidth



Date: 19.AUG.2011 20:55:02

Test Personnel: Nicholas Abbondante 

Test Date: 08/19/2011 (Night Shift)

Supervising Engineer:
(Where Applicable)

N/A

Test Levels: See section 10.3

Product Standard: FCC Part 15.247, RSS-210 Annex 8

Ambient Temperature: 25 °C

Input Voltage: 115VAC/60Hz

Relative Humidity: 54 %

Pretest Verification w/ Ambient
Signals or BB Source:

Ambient Signals

Atmospheric Pressure: 1003 mbar

11 Hopping Dwell time

11.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247 and RSS-210 Annex 8.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

11.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
SAF767'	Weatherstation	Davis Instruments	Perception II	PE91222A03	01/14/2011	01/14/2012
145-416'	Cables 145-400 145-408 145-402 145-404	Huber + Suhner	3m Track B cables	multiple	08/31/2010	08/31/2011
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/08/2010	10/08/2011
145108'	EMI Test Receiver (20Hz - 40GHz)	Rohde & Schwarz	ESIB40	100209	04/28/2011	04/28/2012

Software Utilized:

Name	Manufacturer	Version
None		

11.3 Results:

The sample tested was found to comply.


FCC Part 15.247 (1) (iii) & RSS-210 A8.1 (c)

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


Bluetooth utilizes 79 channels, therefore dwell time must not exceed 0.4 seconds in any 31.6 second period. The worst case dwell time was achieved using DH5 packets, with 312.4 ms of dwell time on a channel during a 31.6 second time frame.

11.4 Setup Photographs:


Test Setup Photo # 1




Test Setup Photo # 2




11.5 Plots/Data:






Date: 19.AUG.2011 23:20:05
DH1, Hops in 100ms, 98.75 ms interval





Date: 19.AUG.2011 23:20

DH1, 10 hops in 1 second




Date: 19.AUG.2011 23:21:39
DH1, 101 hops in 10 seconds







Date: 19.AUG.2011 23:47:08
DH3, one hop in 100 ms




Date: 19.AUG.2011 23:48:04
DH3, 6 hops in 1 second, 196.4ms hop interval







Date: 19.AUG.2011 23:54:10
DH5, Packet Length 2.92 ms



Date: 19.AUG.2011 23:54:51
DH5, one hop in 100 ms



Date: 19.AUG.2011 23:55:35
DH5, 4 hops in 1 second, 295.5 ms hop interval



Date: 19.AUG.2011 23:56:40
DH5, 34 hops in 10 seconds

For DH1, the packet length was measured to be 399.8 us. The hop interval is 98.75 ms, therefore the duty cycle is based on two hops in a 100ms period, or 0.8%. Dwell time in 31.6 seconds would include 320 hops based on the measured hop interval, resulting in a dwell time of 128 ms.

For DH3, the packet length was measured to be 1.67 ms. The hop interval is 196.4 ms, therefore the duty cycle is based on one hop in a 100ms period, or 1.67%. Dwell time in 31.6 seconds would include 161 hops based on the measured hop interval, resulting in a dwell time of 268.9 ms.

For DH5, the packet length was measured to be 2.92 ms. The hop interval is 295.5 ms, therefore the duty cycle is based on one hop in a 100ms period, or 2.92%. Dwell time in 31.6 seconds would include 107 hops based on the measured hop interval, resulting in a dwell time of 312.4 ms.

Test Personnel: Nicholas Abbondante Test Date: 08/19/2011Supervising Engineer:
(Where Applicable) N/ATest Levels: See section 11.3Product Standard:
FCC Part 15.247, RSS-210 Annex
8Ambient Temperature: 25 °C
Relative Humidity: 54 %Input Voltage: 115VAC/60HzAtmospheric Pressure: 1003 mbarPretest Verification w/ Ambient
Signals or BB Source: Ambient Signals

Deviations, Additions, or Exclusions: None

12 Band-edge Compliance

12.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, DA 00-705, ANSI C63.4, RSS-Gen, and RSS-210 Annex 8.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

12.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
SAF767'	Weatherstation	Davis Instruments	Perception II	PE91222A03	01/14/2011	01/14/2012
145-416'	Cables 145-400 145-408 145-402 145-404	Huber + Suhner	3m Track B cables	multiple	08/31/2010	08/31/2011
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/08/2010	10/08/2011
145108'	EMI Test Receiver (20Hz - 40GHz)	Rohde & Schwarz	ESIB40	100209	04/28/2011	04/28/2012

Software Utilized:

Name	Manufacturer	Version
None	Teseq	Build 5.26.00.3

12.3 Results:

The sample tested was found to comply. Note that the requirement is 20 dBc at the lower band edge, and the device must meet the general limits of 15.209 using the marker-delta method at the upper band edge due to the restricted band located there.


In any 100 kHz bandwidth outside the frequency band, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see 15.205(c)).

FCC Part 15.209(a) & RSS-210 A8.5 – Restricted Band Radiated Spurious/Harmonics Limits


Frequency (MHz)	Field Strength		Test Distance (meters)
30–88	100	40.00	3
88–216	150	43.52	3
216–960	200	46.02	3
Above 960	500	53.98	3

12.4 Setup Photographs:


Test Setup Photo # 1




Test Setup Photo # 2




12.5 Plots/Data:






Date: 19.AUG.2011 21:52:57
Lower Band Edge Compliance, Horizontal



Date: 19.AUG.2011 20:57:15
Upper Band Edge Compliance, Vertical Polarity, Marker Delta 32.11 dB



Date: 19.AUG.2011 21:02:36
 Upper Band Edge Compliance, Horizontal Polarity, Marker Delta 32.75 dB

Intertek

Radiated Emissions

Company: Zoll Medical
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineers: Nicholas Abbondante
 Project #: G100398565 Date(s): 08/19/11
 Standard: FCC Part 15 Subpart C 15.247
 Receiver: R&S ESIB (145108) 04-06-2012 Limit Distance (m): 3
 PreAmp: NONE. Test Distance (m): 3
 PreAmp Used? (Y or N): N Voltage/Frequency: 115V/60Hz Frequency Range: Frequencies Shown
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS: NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth
Note: Fundamental Field Strength											
PK	V	2402.000	49.72	28.33	5.80	0.00	0.00	83.86	-	-	1/3 MHz
PK	H	2402.000	49.88	28.15	5.80	0.00	0.00	83.83	-	-	1/3 MHz
PK	V	2441.000	51.08	28.35	5.88	0.00	0.00	85.31	-	-	1/3 MHz
PK	H	2441.000	51.99	28.25	5.88	0.00	0.00	86.12	-	-	1/3 MHz
PK	V	2480.000	53.89	28.37	5.96	0.00	0.00	88.22	-	-	1/3 MHz
PK	H	2480.000	54.03	28.36	5.96	0.00	0.00	88.35	-	-	1/3 MHz
Note: Upper Band Edge Compliance (using marker-delta method factor of 32.11 dB)											
Note: Average obtained by applying the worst case duty cycle (DH5 datarate, 2.92% duty cycle, -30.7 dB average factor)											
PK	V	2483.500	21.78	28.37	5.97	0.00	0.00	56.12	74.00	-17.88	1/3 MHz
AVG	V	2483.500	-8.92	28.37	5.97	0.00	0.00	25.42	54.00	-28.58	1/3 MHz
Note: Upper Band Edge Compliance (using marker-delta method factor of 32.75 dB)											
Note: Average obtained by applying the worst case duty cycle (DH5 datarate, 2.92% duty cycle, -30.7 dB average factor)											
PK	H	2483.500	21.28	28.37	5.97	0.00	0.00	55.61	74.00	-18.39	1/3 MHz
AVG	H	2483.500	-9.42	28.37	5.97	0.00	0.00	24.91	54.00	-29.09	1/3 MHz

See section 11 for plots of channel dwell time which were used to determine the duty cycle.

Test Personnel: Nicholas Abbondante 
 Supervising Engineer: _____
 (Where Applicable) N/A
 Product Standard: FCC Part 15.247, RSS-210 Annex
 Input Voltage: 8
 Pretest Verification w/ Ambient Signals or BB Source: Ambient Signals

Test Date: 08/19/2011
 Test Levels: See section 12.3
 Ambient Temperature: 25 °C
 Relative Humidity: 54 %
 Atmospheric Pressure: 1003 mbar

Deviations, Additions, or Exclusions: None

13 Receiver Spurious Emissions

13.1 Method

Tests are performed in accordance with ANSI C 63.4:2003 and RSS-Gen.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) $< U_{CISPR}$ (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 52.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB/m}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$FS = 32 \text{ dB}\mu\text{V/m}$$

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF/20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

$$NF = \text{Net Reading in dB}\mu\text{V}$$

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$

$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

13.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
DAV002'	Weather Station	Davis Instruments	7400	PE80519A93	08/12/2011	08/12/2012
145-410'	Cables 145-400 145-406 145-407 145-405 145-403	Huber + Suhner	10m Track A Cables	multiple	08/31/2010	08/31/2011
145034'	BiLog Antenna (30 MHz to 1GHz)	Schaffner Chase EMC	CBL6111C	none	01/07/2011	01/07/2012
145003'	Preamplifier (150 KHz to 1.3 GHz)	Hewlett Packard	8447D	2443A04077	09/24/2010	09/24/2011
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/10/2010	08/31/2011

Software Utilized:

Name	Manufacturer	Version
C5	Teseq	Build 5.26.00.3

13.3 Results:

The sample tested was found to comply.


The field strength of any emissions shall not exceed the limits as follows:

FCC Part 15:2011 Subpart B Section 15.109 (a) & RSS-Gen Issue 3 December 2010, Section 6.1 Table 2


Frequency (MHz)	Field Strength µV/m	Field Strength dBµV/m	Test Distance (meters)
30–88	100	40.00	3
88–216	150	43.52	3
216–960	200	46.02	3
Above 960	500	53.98	3

13.4 Setup Photographs:


Test Setup Photo # 1




Test Setup Photo # 2



Test Setup Photo # 3




Test Setup Photo # 4



13.5 Plots/Data:

FCC Part 15.209, RSS-Gen

Channel 40 (2.441GHz) Radiated Emissions @ 3m, Vertical Polarity, 30-1000MHz



"PORTRAIT"


- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable
- Level (dBuV/m) = AF + CL + PA + Raw
- AF = Antenna Factor
- CL = Cable Losses
- PA = Pre-Amplifier
- Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Vert (l)	Angle (deg)	Mast Height (m)	RBW (Hz)
54.345M	28.88	6.862	-26.203	40.00	-11.12		225	1.26	120k
58.454M	32.36	5.864	-26.127	40.00	-7.64		228	1.30	120k
71.746M	27.87	6.149	-26.000	40.00	-12.13		49	1.37	120k
83.988M	31.67	8.694	-26.000	40.00	-8.33		271	1.55	120k
194.905M	30.21	9.800	-24.942	43.52	-13.31		356	1.78	120k
207.474M	31.31	10.500	-24.888	43.52	-12.21		348	1.44	120k

FCC Part 15.209, RSS-Gen

Channel 40 (2.441GHz) Radiated Emissions @ 3m, Horizontal Polarity, 30-1000MHz



"PORTRAIT"

- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable

Level (dBuV/m) = AF + CL + PA + Raw


AF = Antenna Factor
 CL = Cable Losses
 PA = Pre-Amplifier
 Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Quasi-Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Hor (--)	Angle (deg)	Mast Height (m)	RBW (Hz)
131.946M	28.78	11.116	-25.535	43.52	-14.74	--	282	2.24	120k
176.092M	36.10	9.291	-25.106	43.52	-7.42	--	84	1.70	120k
182.213M	37.49	9.000	-25.051	43.52	-6.03	--	94	1.19	120k
194.232M	36.21	9.000	-24.947	43.52	-7.31	--	90	1.69	120k
207.440M	35.27	9.251	-24.888	43.52	-8.25	--	72	1.30	120k
843.901M	21.78	22.400	-23.328	46.02	-24.24	--	55	3.79	120k

FCC Part 15.209, RSS-Gen

Channel 40 (2.441GHz) Radiated Emissions @ 3m, Vertical Polarity, 1-13GHz



"PORTRAIT"

- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable

Level (dBuV/m) = AF + CL + PA + Raw

AF = Antenna Factor

CL = Cable Losses

PA = Pre-Amplifier

Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Peak


Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Vert (l)	Angle (deg)	Mast Height (m)	RBW (Hz)
6.177G	54.67	34.399	-24.967	74.00	-19.33	l	260	1.35	1M
6.744G	56.49	34.894	-25.525	74.00	-17.51	l	161	3.72	1M
9.988G	54.81	38.104	-23.392	74.00	-19.19	l	284	3.93	1M
11.187G	55.79	38.481	-21.738	74.00	-18.21	l	282	2.99	1M
11.724G	57.03	39.499	-21.769	74.00	-16.97	l	145	1.97	1M
12.840G	59.52	39.305	-19.881	74.00	-14.48	l	199	3.96	1M

Measured: Average

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Vert (l)	Angle (deg)	Mast Height (m)	RBW (Hz)
6.177G	43.95	34.399	-24.967	54.00	-10.05	l	260	1.35	1M
6.744G	46.02	34.894	-25.525	54.00	-7.98	l	161	3.72	1M
9.988G	44.42	38.104	-23.392	54.00	-9.58	l	284	3.93	1M
11.187G	45.33	38.481	-21.738	54.00	-8.67	l	282	2.99	1M
11.724G	46.48	39.499	-21.769	54.00	-7.52	l	145	1.97	1M
12.840G	49.85	39.305	-19.881	54.00	-4.15	l	199	3.96	1M

FCC Part 15.209, RSS-Gen

Channel 40 (2.441GHz) Radiated Emissions @ 3m, Horizontal Polarity, 1-13GHz



"PORTRAIT"

Measured Peak Value

Measured Quasi Peak Value

Measured Average Value

Maximum Value of Mast and Turntable
Level (dBuV/m) = AF + CL + PA + Raw

AF = Antenna Factor

CL = Cable Losses

PA = Pre-Amplifier

Raw = Raw Instrument Reading (Not listed on Spot Tables)

Measured: Peak

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Hor (--)	Angle (deg)	Mast Height (m)	RBW (Hz)
6.768G	55.83	34.905	-25.525	74.00	-18.17	--	224	2.56	1M
9.146G	53.89	37.697	-23.904	74.00	-20.11	--	13	3.63	1M
10.032G	53.82	38.123	-23.345	74.00	-20.18	--	303	1.49	1M
11.350G	56.29	38.776	-21.676	74.00	-17.71	--	331	1.54	1M
12.535G	57.89	38.797	-20.641	74.00	-16.11	--	165	3.09	1M
12.931G	59.94	39.408	-19.659	74.00	-14.06	--	101	3.32	1M

Measured: Average

Frequency (Hz)	Level (dBuV/m)	Ant. Fact. (dB)	Other Fact. (dB)	Limit (dBuV/m)	Margin (dB)	Hor (--)	Angle (deg)	Mast Height (m)	RBW (Hz)
6.768G	46.23	34.905	-25.525	54.00	-7.77	--	224	2.56	1M
9.146G	43.35	37.697	-23.904	54.00	-10.65	--	13	3.63	1M
10.032G	44.18	38.123	-23.345	54.00	-9.82	--	303	1.49	1M
11.350G	46.02	38.776	-21.676	54.00	-7.98	--	331	1.54	1M
12.535G	47.86	38.797	-20.641	54.00	-6.14	--	165	3.09	1M
12.931G	50.03	39.408	-19.659	54.00	-3.97	--	101	3.32	1M

Test Personnel: Kouma Sinn *KPS*Test Date: 08/16/2011Supervising Engineer:
(Where Applicable) N/AEmissions below the limits
specified in Section 14.3Product Standard: FCC Part 15.247, RSS-210 Annex 8
Input Voltage: 115VAC/60HzTest Levels: N/APerformance Criteria: N/APretest Verification w/ Ambient
Signals or BB Source: Ambient SignalsAmbient Temperature: 22 °CRelative Humidity: 55 %Atmospheric Pressure: 998mbars

Deviations, Additions, or Exclusions: None

14 AC Mains Conducted Emissions

14.1 Method

Tests are performed in accordance with ANSI C 63.4:2003 and RSS-Gen.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For conducted emissions, U_{lab} (3.2 dB in worst case) $< U_{CISPR}$ (3.6 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculations

The following is how net line-conducted readings were determined:

$$NF = RF + LF + CF + AF$$

Where NF = Net Reading in dB μ V

RF = Reading from receiver in dB μ V

LF = LISN Correction Factor in dB

CF = Cable Correction Factor in dB

AF = Attenuator Loss Factor in dB

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF/20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

NF = Net Reading in dB μ V

Example:

$$NF = RF + LF + CF + AF = 28.5 + 0.2 + 0.4 + 20.0 = 49.1 \text{ dB}\mu\text{V}$$

$$UF = 10^{(49.1 \text{ dB}\mu\text{V}/20)} = 285.1 \mu\text{V}/\text{m}$$

14.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
BAR3'	Digital 4 Line Barometer	Mannix	0ABA116	BAR3	08/11/2010	08/11/2012
ROS002'	9kHz to 3GHz EMI Test Receiver	Rohde & Schwartz	ESCI 1166.5950K03	100067	04/15/2011	04/15/2012
CBLBNC60'	Cable, BNC - BNC, 10m long	Alpha	RG-58C/U	CBL10MS1	09/15/2011	09/15/2012
145015'	LISN: 50 Ohm/50 microHenry	Solar Electronics	9252-50-R-24-BNC	971617	01/18/2011	01/18/2012
DS27'	Attenuator, 20dB	Mini Circuits	20dB, 50 ohm	DS27	04/19/2011	04/19/2012

Software Utilized:

Name	Manufacturer	Version
Excel 2003	Microsoft	(11.8231.8221) SP3
EMI Boxborough.xls	Intertek	08/27/10

14.3 Results:

The sample tested was found to comply.

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the table below

FCC Part 15.207 (a) & RSS-Gen Section 7.2.4 (Table 4)

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

14.4 Setup Photographs:

14.5 Data:

Conducted Emissions

Company: Zoll Medical Corp
 Model #: ZOLL E Series Data Comm Card
 Serial #: IN0411-00032
 Engineer(s): Vathana Ven
 Project #: G100398565 Date: 07/26/11
 Standard: FCC Part 15 Subpart C 15.247/RSS-210
 Barometer: BAR3 Temp/Humidity/Pressure: 20 deg C 60% 999 mB Attenuator: DS27_4-19-2012.txt
 Voltage/Frequency: 120VAC/60Hz Frequency Range: 0.150-30MHz

Net is the sum of worst-case lisn, cable, & attenuator losses, and initial reading, factors are not shown

Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor; Bandwidth denoted as RBW/VBW

Detector Type	Frequency MHz	Reading Line 1 dB(uV)	Reading Line 2 dB(uV)	Reading Line 3 dB(uV)	Reading Line 4 dB(uV)	Net dB(uV)	QP Limit dB(uV)	Margin dB	Bandwidth
QP	0.150	34.50	35.90			56.26	66.00	-9.74	9/30 kHz
QP	0.212	28.10	29.50			49.80	63.13	-13.32	9/30 kHz
QP	11.418	12.30	12.00			32.88	60.00	-27.12	9/30 kHz
QP	12.658	13.66	13.60			34.25	60.00	-25.75	9/30 kHz
QP	13.648	17.90	18.30			38.89	60.00	-21.11	9/30 kHz
QP	15.968	18.70	19.00			39.62	60.00	-20.38	9/30 kHz

Detector Type	Frequency MHz	Reading Line 1 dB(uV)	Reading Line 2 dB(uV)	Reading Line 3 dB(uV)	Reading Line 4 dB(uV)	Net dB(uV)	Average Limit dB(uV)	Margin dB	Bandwidth
AVG	0.150	10.60	12.50			32.86	56.00	-23.14	9/30 kHz
AVG	0.212	25.50	27.00			47.30	53.13	-5.82	9/30 kHz
AVG	11.418	0.40	0.00			20.98	50.00	-29.02	9/30 kHz
AVG	12.658	3.40	2.90			23.99	50.00	-26.01	9/30 kHz
AVG	13.648	15.30	15.50			36.09	50.00	-13.91	9/30 kHz
AVG	15.968	15.70	15.60			36.33	50.00	-13.67	9/30 kHz

Test Personnel: Vathana Ven
 Supervising Engineer: _____
 (Where Applicable) N/A
 Product Standard: FCC Part 15.247 & RSS-210 Annex 8
 Input Voltage: 120VAC/60Hz

Pretest Verification w/ Ambient Signals or BB Source: Ambient Signals

Test Date: 07/26/2011
 Test Levels: See test results
 Ambient Temperature: 20 °C
 Relative Humidity: 60 %
 Atmospheric Pressure: 999 mbars

Deviations, Additions, or Exclusions: None

15 Revision History

Revision Level	Date	Report Number	Notes
0	08/25/2011	100398565BOX-002a	Original Issue
1	10/31/2011	100398565BOX-002c	Changed model # from E-series with Zango Card to ZOLL E Series Data Comm Card
2	11/04/2011	100398565BOX-002d	E Series as host and serial number for card added