



TEST REPORT

REPORT NUMBER: I21W00049-Rev1

ON

Type of Equipment: BaseStation
Type of Designation: AIRE100A
Manufacturer: Micron Electronics LLC.
Brand Name: PRIME
FCC ID: ZKQ-BAS4GA

ACCORDING TO

FCC CFR 47 Part 2.1091 《Radiofrequency radiation exposure evaluation: mobile devices》

FCC CFR 47 Part1.1310 《Radiofrequency radiation exposure limits》

Chongqing Academy of Information and Communication Technology

Month date, year

Feb,14,2022

Signature

Xiang Luoyong

Director

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of Chongqing Academy of Information and Communications Technology.



Revision Version

Report Number	Revision	Date	Memo
I21W00049	01	2022-1-7	Initial creation of test report
I21W00049-Rev1	02	2022-2-14	First change of test report



CONTENTS

1. TEST LABORATORY.....	3
1.1. TESTING LOCATION.....	3
1.2. TESTING ENVIRONMENT.....	3
1.3. PROJECT DATA.....	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE).....	5
3.1. ABOUT EUT.....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST.....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
4. REFERENCE DOCUMENTS.....	6
4.1. APPLICABLE STANDARDS.....	6
4.2. TEST LIMITS.....	6
5. TEST RESULTS.....	7
5.1. RF POWER OUTPUT.....	7
5.2. CALCULATION INFORMATION.....	7
5.3. RESULTS.....	8
5.4. SIMULTANEOUS TRANSMISSION.....	8
5.5. RESULT OF LTE BAND 2.....	9
5.6. RESULT OF LTE BAND 4.....	9
5.7. RESULT OF LTE BAND 5.....	9
5.8. RESULT OF LTE BAND 12.....	10
5.9. RESULT OF LTE BAND 13.....	10

Chongqing Academy of Information and Communication Technology

Address: No. 8,Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China,401336
Tel: 0086-23-88069965 FAX:0086-23-88608777



Report NO.: I21W00049-Rev1

5.10. RESULT OF WIFI.....	10
5.11. RESULT OF BLUETOOTH.....	11
ANNEX A: EUT PHOTOGRAPH.....	12

Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336
Tel: 0086-23-88069965 FAX: 0086-23-88608777

1. Test Laboratory

1.1. Testing Location

Company Name:	Chongqing Academy of Information and Communications Technology
Address:	Building C, Technology Innovation Center, No.8, Yuma Road, Chayuan New Area, Nan'an District, Chongqing, People's Republic of China
Postal Code:	401336
Telephone:	0086-23-88069965
Fax:	0086-23-88608777

1.2. Testing Environment

Normal Temperature:	21.3°C
Relative Humidity:	65%

1.3. Project Data


Testing Start Date:	2022-1-7
Testing End Date:	2022-2-14

1.4. Signature




2022-2-14

Fu Bohao
(Prepared this test report)

Date

2022-2-14

Wang Lili
(Reviewed this test report)

Date

2022-2-14

Xiang Luoyong
Director of the laboratory
(Approved this test report)

Date

Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336
Tel: 0086-23-88069965 FAX: 0086-23-88608777



2. Client Information

2.1. Applicant Information

Company Name:	Micron Electronics LLC.
Address /Post:	1001 Yamato Road, Suite 400, Boca Raton, FL 33431, USA
Country:	CHINA
Telephone:	18885383489
Fax:	--
Email:	pcheng@micron-electronics.com
Contact Person:	Ping Cheng

2.2. Manufacturer Information

Company Name:	Micron Electronics LLC.
Address /Post:	1001 Yamato Road, Suite 400, Boca Raton, FL 33431, USA
Country:	CHINA
Telephone:	18885383489
Fax:	--
Email:	pcheng@micron-electronics.com
Contact Person:	Ping Cheng

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description:	BaseStation
Model name:	AIRE100A
LTE Frequency Band:	Band2/4/5/12/13
WLAN Frequency Band:	2.4GHz
Bluetooth Frequency Band:	BLE
Note: Photographs of EUT are shown in ANNEX A of this test report.	

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
S4	860371050880504	A106_V3	LS100AV05.01B04.I01	2021-12-8

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

EUT ID*	SN	Description
NA	NA	NA

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

FCC CFR 47 Part 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

MPE for the upper tier (people in controlled environments)

Frequency Range [MHz]	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

For the DUT, the limits for the general public when an RF safety program is unavailable.

5. Test Results

5.1. RF Power Output

Frequency Band	Highest Averaged Power Output(dBm)	Highest Frame-Averaged Output Power (dBm)	Antenna Gain(dBi)
LTE Band 2	25.7	25.7	3.37
LTE Band 4	25.7	25.7	3.87
LTE Band 5	25.7	25.7	0.68
LTE Band 12	25.7	25.7	0.10
LTE Band 13	25.7	25.7	1.63
WIFI	22.0	22.0	2.0
Bluetooth	3.73	3.73	2.0

Notes:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

2) According to the conducted power as above, the measurements are performed with 1Txslots for 850MHz and 1900MHz.

5.2. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$S = \frac{PG}{4\pi d^2}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336

Tel: 0086-23-88069965

FAX: 0086-23-88608777

5.3. Results

Frequency range	Limit(mW/cm ²)	Results(mW/cm ²)	Verdict
LTE Band 2	1.0	0.161	Pass
LTE Band 4	1.0	0.180	Pass
LTE Band 5	0.549	0.086	Pass
LTE Band 12	0.466	0.076	Pass
LTE Band 13	0.518	0.108	Pass
WIFI	1.0	0.050	Pass
Bluetooth	1.0	0.0007	Pass

5.4. Simultaneous transmission

From (5.3. Results) We can get the combination of the maximum value of simultaneous transmission as LTE Band13 and WIFI: $0.108/0.518+0.050/1.000=0.208+0.050=0.258$

Conclusion: max ratio 0.258 is less than 1,so compliance RF exposure requirement

5.5. Result of LTE Band 2

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1850.0 ~ 1909.9 MHz; The maximum conducted is 25.70 dBm. The maximum gain is 3.37 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (371.535 mW)

G = antenna gain (2.173numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(371.535*2.173)/(4 \pi *20^2)=0.161 \text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

5.6. Result of LTE Band 4

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0 ~ 1754.9MHz; The maximum conducted is 25.70 dBm. The maximum gain is 3.87 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (371.535 mW)

G = antenna gain (2.438numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(371.535*2.438)/(4 \pi *20^2)=0.180 \text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

5.7. Result of LTE Band 5

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 824.0 ~ 848.9 MHz; The maximum conducted is 25.70 dBm. The maximum gain is 0.68 dBi. Therefore, maximum limit for general public RF exposure: 824.0/1500=0.549 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (371.535 mW)

G = antenna gain (1.169numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(371.535*1.169)/(4 \pi *20^2)=0.086 \text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.549mW/cm² limit for uncontrolled exposure.

5.8. Result of LTE Band 12

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 699.0 ~ 715.9 MHz; The maximum conducted is 25.70 dBm. The maximum gain is 0.10 dBi. Therefore, maximum limit for general public RF exposure: $699.0/1500=0.466$ mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (371.535 mW)

G = antenna gain (1.023numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(371.535*1.023)/(4\pi*20^2)=0.076\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.466 mW/cm² limit for uncontrolled exposure.

5.9. Result of LTE Band 13

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 777.0 ~ 786.9 MHz; The maximum conducted is 25.70 dBm. The maximum gain is 1.63 dBi. Therefore, maximum limit for general public RF exposure: $777.0/1500=0.518$ mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (371.535 mW)

G = antenna gain (1.455numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(371.535*1.455)/(4\pi*20^2)=0.108\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.518 mW/cm² limit for uncontrolled exposure.

5.10. Result of WIFI

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 2412.0 ~ 2484.0 MHz; The maximum conducted is 22.0 dBm. The maximum gain is 2.0 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (158.489 mW)

G = antenna gain (1.585 numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(158.489*1.585)/(4\pi*20^2)=0.050\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.

Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336

Tel: 0086-23-88069965

FAX: 0086-23-88608777



5.11. Result of Bluetooth

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 2402.0 ~ 2480.0 MHz; The maximum conducted is 3.73 dBm. The maximum gain is 2.0 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm².

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (2.360 mW)

G = antenna gain (1.585numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(2.360*1.585)/(4 \pi *20^2)=0.0007mW/cm^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm² limit for uncontrolled exposure.



Report NO.: I21W00049-Rev1

ANNEX A: EUT photograph

See the document "AIRE100A -External Photos".

*****END OF REPORT*****

Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336
Tel: 0086-23-88069965 FAX: 0086-23-88608777