

Measurement Results

1-9100/19-01-12_log1_conducted

[Test logging](#)

This addendum is electronically signed and valid without handwritten signature.
For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorized:

Michael Dorongovski
Lab Manager
Radio Communication

Table of Content

EUT Summary	4
1. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 b-mode	5
2. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 b-mode	7
3. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 b-mode	9
4. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 g-mode	11
5. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 g-mode	13
6. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 g-mode	15
7. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode	17
8. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode	19
9. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode	21
10. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode	23
11. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode	25
12. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode	27
13. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode	29
14. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode	32
15. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode	35
16. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode	38
17. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode	41
18. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode	44
19. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode	47
20. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode	50
21. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode	53
22. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode	56
23. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode	59
24. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode	62
25. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode	65
26. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode	67
27. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode	69
28. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode	71
29. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode	73
30. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode	75
31. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode	77
32. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode	79
33. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode	81
34. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode	83
35. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode	85
36. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode	87
37. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode	89
38. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode	91
39. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode	93
40. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode	95
41. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode	97
42. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode	99
43. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode	101
44. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode	103
45. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode	105
46. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT40-mode	107
47. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT40-mode	109
48. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT40-mode	111

49. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode	113
50. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode	115
51. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode	117
52. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode	119
53. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode	121
54. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode	123
55. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode	125
56. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode	127
57. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT20-mode	129
58. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT40-mode	131
59. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT40-mode	133
60. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 nHT40-mode	135
61. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode	137
62. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode	139
63. Common2G4 Peak OP 3MHz/3MHz ~ WLAN2G4 b-mode	141

EUT Summary

IUT DEFINITION & Common settings	
Manufacturer	SAFEmine (part of Hexagon Mining)
Type	QC1000
Serial No. Setup No.	Sample 100 1.0
SW Version HW Version	NI A
Comment 1 2	
Tlow Tmid Thigh [°C]	-30 22 70
Vlow Vmid Vhigh [V] @Imax [A]	24 24 24 @1
Auto Control enabled Power Supply Climatic Box	No No
Antenna Gain [dBi] (only considered if explicitly mentioned in testresult)	0
Additional Path Loss [dB]	0
IUT Common Settings WLAN2G4	
Number of Antenna Ports	1
User Interaction	No

1. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:05:46
Ambit Temp [°C] Humidity [rel%]	22.5 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.45 15.57 15
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	9544	kHz	PASS



TEST FINISHED

General Verdict	29.09.2020 14:06:20 / RT: 34 s	PASS
-----------------	--------------------------------	------

2. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:40:17
Ambit Temp [°C] Humidity [rel%]	22.5 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.77 15.49 15
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	10048	kHz	PASS



TEST FINISHED

General Verdict	29.09.2020 14:40:50 / RT: 32 s	PASS
-----------------	--------------------------------	------

3. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:50:47
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.35 15.42 15
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	9548	kHz	PASS



TEST FINISHED

General Verdict	29.09.2020 14:51:19 / RT: 32 s	PASS
-----------------	--------------------------------	------

4. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:08:34
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.08 15.57 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	15068	kHz	PASS



TEST FINISHED

General Verdict 29.09.2020 15:09:07 / RT: 32 s

PASS

5. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:20:44
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.30 15.49 15
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	15108	kHz	PASS



TEST FINISHED

General Verdict	29.09.2020 15:21:15 / RT: 31 s	PASS
-----------------	--------------------------------	------

6. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:32:37
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.14 15.42 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	15076	kHz	PASS



TEST FINISHED

General Verdict	29.09.2020 15:33:09 / RT: 31 s	PASS
-----------------	--------------------------------	------

7. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 15:43:10
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.59 15.57 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	15080	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode_29092020_154342.png

TEST FINISHED

General Verdict	29.09.2020 15:43:43 / RT: 32 s	PASS
-----------------	--------------------------------	------

8. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:10:18
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.49 15.49 20
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	15104	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode_29092020_161049.png

TEST FINISHED

General Verdict	29.09.2020 16:10:49 / RT: 31 s	PASS
-----------------	--------------------------------	------

9. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:19:33
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.25 15.42 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	15068	kHz	PASS



TEST FINISHED

General Verdict	29.09.2020 16:20:06 / RT: 32 s	PASS
-----------------	--------------------------------	------

10. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:12:33
Ambit Temp [°C] Humidity [rel%]	20.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2422 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.90 15.54 15
Start [MHz] Stop [MHz]	2382.000 2462.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	33728	kHz	PASS



TEST FINISHED

General Verdict	30.09.2020 06:13:04 / RT: 30 s	PASS
-----------------	--------------------------------	------

11. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:49:11
Ambit Temp [°C] Humidity [rel%]	21.1 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.44 15.49 15
Start [MHz] Stop [MHz]	2397.000 2477.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	35080	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode_30092020_064941.png

TEST FINISHED

General Verdict	30.09.2020 06:49:42 / RT: 30 s	PASS
-----------------	--------------------------------	------

12. FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:59:18
Ambit Temp [°C] Humidity [rel%]	21.2 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2452 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.37 15.44 15
Start [MHz] Stop [MHz]	2412.000 2492.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	32552	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ WLAN2G4 nHT40-mode_30092020_065948.png

TEST FINISHED

General Verdict	30.09.2020 06:59:49 / RT: 30 s	PASS
-----------------	--------------------------------	------

13. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:07:10
Ambit Temp [°C] Humidity [rel%]	22.4 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.45 15.57 15
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE



RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	13195	kHz	INFO
T1 99%	2400.000000	---	2405.3567	MHz	PASS
T2 99%	---	2483.500000	2418.5513	MHz	PASS



RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	15396	kHz	INFO
T1 20dB	2400.000000	---	2404.2840	MHz	PASS
T2 20dB	---	2483.500000	2419.6800	MHz	PASS



TEST FINISHED

General Verdict

29.09.2020 14:07:55 / RT: 44 s

PASS

14. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:41:39
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.80 15.49 15
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	13379	kHz	INFO
T1 99%	2400.000000	---	2430.3287	MHz	PASS
T2 99%	---	2483.500000	2443.7073	MHz	PASS





Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode 99PCT_29092020_144210.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode_29092020_144213.png

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	15492	kHz	INFO
T1 20dB	2400.000000	---	2429.2680	MHz	PASS
T2 20dB	---	2483.500000	2444.7600	MHz	PASS



TEST FINISHED

General Verdict

29.09.2020 14:42:24 / RT: 44 s

PASS

15. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:52:08
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 b-mode
Add. Information	



Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60

Test at TX 2462 MHz



READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.31 15.42 15
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	13175	kHz	INFO
T1 99%	2400.000000	---	2455.4967	MHz	PASS
T2 99%	---	2483.500000	2468.6713	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	15380	kHz	INFO
T1 20dB	2400.000000	---	2454.3560	MHz	PASS
T2 20dB	---	2483.500000	2469.7360	MHz	PASS



TEST FINISHED

General Verdict

29.09.2020 14:52:52 / RT: 43 s

PASS

16. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:09:55
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.02 15.57 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE


RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	16234	kHz	INFO
T1 99%	2400.000000	---	2403.8408	MHz	PASS
T2 99%	---	2483.500000	2420.0752	MHz	PASS




RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	18020	kHz	INFO
T1 20dB	2400.000000	---	2402.9360	MHz	PASS
T2 20dB	---	2483.500000	2420.9560	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode 29092020_151034.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode 29092020_151038.png

TEST FINISHED

General Verdict

29.09.2020 15:10:39 / RT: 43 s

PASS

17. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:22:03
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.32 15.49 20
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE


RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	16450	kHz	INFO
T1 99%	2400.000000	---	2428.7528	MHz	PASS
T2 99%	---	2483.500000	2445.2032	MHz	PASS




RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	18308	kHz	INFO
T1 20dB	2400.000000	---	2427.8120	MHz	PASS
T2 20dB	---	2483.500000	2446.1200	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode 20dB_29092020_152241.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode_29092020_152245.png

TEST FINISHED

General Verdict

29.09.2020 15:22:46 / RT: 42 s

PASS

18. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:33:57
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.82 15.42 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE


RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	16226	kHz	INFO
T1 99%	2400.000000	---	2453.9208	MHz	PASS
T2 99%	---	2483.500000	2470.1472	MHz	PASS




RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	17944	kHz	INFO
T1 20dB	2400.000000	---	2453.0880	MHz	PASS
T2 20dB	---	2483.500000	2471.0320	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode_29092020_153435.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 g-mode_29092020_153439.png

TEST FINISHED

General Verdict

29.09.2020 15:34:40 / RT: 43 s

PASS

19. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 15:44:31
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 nHT20_mode
Add. Information	



Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60

Test at TX 2412 MHz


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.49 15.57 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE


RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17222	kHz	INFO
T1 99%	2400.000000	---	2403.3409	MHz	PASS
T2 99%	---	2483.500000	2420.5631	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	18908	kHz	INFO
T1 20dB	2400.000000	---	2402.5280	MHz	PASS
T2 20dB	---	2483.500000	2421.4360	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode 20dB_29092020_154510.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode_29092020_154513.png

TEST FINISHED

General Verdict

29.09.2020 15:45:14 / RT: 43 s

PASS

20. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:11:37
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.50 15.49 20
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17454	kHz	INFO
T1 99%	2400.000000	---	2428.2609	MHz	PASS
T2 99%	---	2483.500000	2445.7151	MHz	PASS




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode 99PCT_29092020_161207.png




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode_29092020_161210.png

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	19244	kHz	INFO
T1 20dB	2400.000000	---	2427.4000	MHz	PASS
T2 20dB	---	2483.500000	2446.6440	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode 20dB_29092020_161216.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode_29092020_161220.png

TEST FINISHED

General Verdict

29.09.2020 16:12:21 / RT: 43 s

PASS

21. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:20:54
Ambit Temp [°C] Humidity [rel%]	22.8 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.73 15.42 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE


RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17222	kHz	INFO
T1 99%	2400.000000	---	2453.4369	MHz	PASS
T2 99%	---	2483.500000	2470.6591	MHz	PASS




RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	18928	kHz	INFO
T1 20dB	2400.000000	---	2452.6040	MHz	PASS
T2 20dB	---	2483.500000	2471.5320	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode 20dB_29092020_162133.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT20-mode_29092020_162137.png

TEST FINISHED

General Verdict

29.09.2020 16:21:37 / RT: 43 s

PASS

22. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:13:55
Ambit Temp [°C] Humidity [rel%]	20.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2422 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.10 15.54 15
Start [MHz] Stop [MHz]	2382.000 2462.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	35860	kHz	INFO
T1 99%	2400.000000	---	2403.8658	MHz	PASS
T2 99%	---	2483.500000	2439.7262	MHz	PASS




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode 99PCT_30092020_061425.png




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode_30092020_061429.png

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	39664	kHz	INFO
T1 20dB	2400.000000	---	2402.0320	MHz	PASS
T2 20dB	---	2483.500000	2441.6960	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode 20dB_30092020_061434.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode_30092020_061438.png

TEST FINISHED

General Verdict

30.09.2020 06:14:39 / RT: 44 s

PASS

23. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:50:34
Ambit Temp [°C] Humidity [rel%]	21.1 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 nHT40_mode
Add. Information	


Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60

Test at TX 2437 MHz


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.20 15.49 15
Start [MHz] Stop [MHz]	2397.000 2477.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	36652	kHz	INFO
T1 99%	2400.000000	---	2418.6018	MHz	PASS
T2 99%	---	2483.500000	2455.2542	MHz	PASS




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode 99PCT_30092020_065104.png




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode_30092020_065108.png

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	41192	kHz	INFO
T1 20dB	2400.000000	---	2416.4880	MHz	PASS
T2 20dB	---	2483.500000	2457.6800	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode 20dB_30092020_065114.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode_30092020_065118.png

TEST FINISHED

General Verdict

30.09.2020 06:51:18 / RT: 44 s

PASS

24. FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 07:00:40
Ambit Temp [°C] Humidity [rel%]	21.2 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2452 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.09 15.44 15
Start [MHz] Stop [MHz]	2412.000 2492.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	35812	kHz	INFO
T1 99%	2400.000000	---	2434.2978	MHz	PASS
T2 99%	---	2483.500000	2470.1102	MHz	PASS




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode 99PCT_30092020_070110.png




Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode_30092020_070114.png

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	39752	kHz	INFO
T1 20dB	2400.000000	---	2432.5520	MHz	PASS
T2 20dB	---	2483.500000	2472.3040	MHz	PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode 20dB_30092020_070120.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ WLAN2G4 nHT40-mode_30092020_070124.png

TEST FINISHED

General Verdict

30.09.2020 07:01:25 / RT: 44 s

PASS

25. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:06:24
Ambit Temp [°C] Humidity [rel%]	22.5 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.46 15.57 15
Start [MHz] Stop [MHz]	2397.000 2427.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-8.38	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode_29092020_140705.png

TEST FINISHED

General Verdict	29.09.2020 14:07:06 / RT: 41 s	PASS
-----------------	--------------------------------	------

26. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:40:54
Ambit Temp [°C] Humidity [rel%]	22.5 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.79 15.49 15
Start [MHz] Stop [MHz]	2422.000 2452.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-11.48	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode_29092020_144134.png

TEST FINISHED

General Verdict	29.09.2020 14:41:35 / RT: 40 s	PASS
-----------------	--------------------------------	------

27. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:51:24
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.29 15.42 15
Start [MHz] Stop [MHz]	2447.000 2477.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-8.48	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 b-mode_29092020_145203.png

TEST FINISHED

General Verdict	29.09.2020 14:52:04 / RT: 40 s	PASS
-----------------	--------------------------------	------

28. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:09:11
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.02 15.57 20
Start [MHz] Stop [MHz]	2397.000 2427.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-9.52	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode_29092020_150950.png

TEST FINISHED

General Verdict	29.09.2020 15:09:51 / RT: 39 s	PASS
-----------------	--------------------------------	------

29. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:21:19
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.01 15.49 15
Start [MHz] Stop [MHz]	2422.000 2452.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-11.64	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode_29092020_152158.png

TEST FINISHED

General Verdict	29.09.2020 15:21:59 / RT: 39 s	PASS
-----------------	--------------------------------	------

30. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:33:13
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.40 15.42 20
Start [MHz] Stop [MHz]	2447.000 2477.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-8.57	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 g-mode_29092020_153352.png

TEST FINISHED

General Verdict	29.09.2020 15:33:53 / RT: 39 s	PASS
-----------------	--------------------------------	------

31. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 15:43:47
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.83 15.57 20
Start [MHz] Stop [MHz]	2397.000 2427.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-8.67	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode_29092020_154426.png

TEST FINISHED

General Verdict	29.09.2020 15:44:27 / RT: 39 s	PASS
-----------------	--------------------------------	------

32. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:10:54
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.66 15.49 15
Start [MHz] Stop [MHz]	2422.000 2452.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-12.66	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode_29092020_161132.png

TEST FINISHED

General Verdict	29.09.2020 16:11:33 / RT: 39 s	PASS
-----------------	--------------------------------	------

33. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:20:10
Ambit Temp [°C] Humidity [rel%]	22.8 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 nHT20_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.09 15.42 20
Start [MHz] Stop [MHz]	2447.000 2477.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-8.83	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT20-mode_29092020_162049.png

TEST FINISHED

General Verdict	29.09.2020 16:20:50 / RT: 39 s	PASS
-----------------	--------------------------------	------

34. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:13:08
Ambit Temp [°C] Humidity [rel%]	20.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2422 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.63 15.54 15
Start [MHz] Stop [MHz]	2392.000 2452.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-11.45	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode_30092020_061350.png

TEST FINISHED

General Verdict 30.09.2020 06:13:51 / RT: 42 s

PASS

35. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:49:47
Ambit Temp [°C] Humidity [rel%]	21.1 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.36 15.49 15
Start [MHz] Stop [MHz]	2407.000 2467.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-13.62	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode_30092020_065029.png

TEST FINISHED

General Verdict	30.09.2020 06:50:29 / RT: 42 s	PASS
-----------------	--------------------------------	------

36. FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:59:53
Ambit Temp [°C] Humidity [rel%]	21.2 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - WLAN 2G4 nHT40_mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2452 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.73 15.44 15
Start [MHz] Stop [MHz]	2422.000 2482.000
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-12.37	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ WLAN2G4 nHT40-mode_30092020_070035.png

TEST FINISHED

General Verdict 30.09.2020 07:00:36 / RT: 42 s

PASS

37. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:13:45
Ambit Temp [°C] Humidity [rel%]	22.5 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2412 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	17.24	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 14:13:53 / RT: 7 s	PASS

38. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:48:11
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2437 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	14.67	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 14:48:19 / RT: 7 s	PASS

39. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:58:39
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2462 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	18.06	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 14:58:47 / RT: 7 s	PASS

40. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:16:26
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2412 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	21.87	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 15:16:34 / RT: 7 s	PASS

41. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:28:32
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2437 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	19.8	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 15:28:40 / RT: 7 s	PASS

42. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:40:28
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2462 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	22.55	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 15:40:35 / RT: 7 s	PASS

43. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 15:51:01
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT20-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2412 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	21.86	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 15:51:09 / RT: 7 s	PASS

44. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:18:08
Ambit Temp [°C] Humidity [rel%]	22.7 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT20-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2437 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	19.63	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 16:18:16 / RT: 7 s	PASS

45. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT20-mode

Test References	
TC Start	29.09.2020 16:27:25
Ambit Temp [°C] Humidity [rel%]	22.8 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT20-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT20-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2462 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	22.29	dBm	PASS

TEST FINISHED		
General Verdict	29.09.2020 16:27:33 / RT: 7 s	PASS

46. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:20:28
Ambit Temp [°C] Humidity [rel%]	20.8 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT40-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2422 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	19.46	dBm	PASS

TEST FINISHED		
General Verdict	30.09.2020 06:20:36 / RT: 7 s	PASS

47. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 06:57:07
Ambit Temp [°C] Humidity [rel%]	21.1 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT40-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2437 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	18.14	dBm	PASS

TEST FINISHED		
General Verdict	30.09.2020 06:57:15 / RT: 7 s	PASS

48. FCC Part 15.247 Maximum Peak Conducted Output Power Powermeter DTS ~ WLAN2G4 nHT40-mode

Test References	
TC Start	30.09.2020 07:07:14
Ambit Temp [°C] Humidity [rel%]	21.2 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.3 PKPM1 Peak-reading Power Meter Method
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_Powermeter_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Powermeter Conducted DTS - WLAN 2G4 nHT40-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 nHT40-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2422
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2452
Switched Path	IUT - SignalingUnit - PowerMeter
Devices in use	PM: Keysight Technologies,U2021XA,MY59190010,A.04.06

Test at TX 2452 MHz

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Found Peak cond.	---	---	20.03	dBm	PASS

TEST FINISHED		
General Verdict	30.09.2020 07:07:22 / RT: 7 s	PASS

49. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:08:00
Ambit Temp [°C] Humidity [rel%]	22.5 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.65 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2410.50 MHz	---	---	5.36	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 24222.667 MHz	0	---	21.6	dB	INFO



TEST FINISHED

General Verdict 29.09.2020 14:12:53 / RT: 293 s

PASS

50. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:42:28
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2437 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.09 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2435.50 MHz	---	---	2.38	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 30 MHz	0	---	-146.36	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2437_29092020_144716.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2437_29092020_144719.png

TEST FINISHED

General Verdict 29.09.2020 14:47:21 / RT: 292 s

PASS

51. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode

Test References	
TC Start	29.09.2020 14:52:56
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 b-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 b-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60


Test at TX 2462 MHz

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	10.44 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2459.50 MHz	---	---	5.55	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 24161.333 MHz	0	---	14.99	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2462_29092020_145745.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 b-mode 2462_29092020_145747.png

TEST FINISHED

General Verdict 29.09.2020 14:57:49 / RT: 292 s

PASS

52. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:10:43
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60



Test at TX 2412 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.31 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2413.33 MHz	---	---	4.92	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 2399.5 MHz	0	---	14.06	dB	INFO



TEST FINISHED

General Verdict 29.09.2020 15:15:36 / RT: 292 s

PASS

53. FCC Part 15.247 TX Spurious Conducted ~ WLAN2G4 g-mode

Test References	
TC Start	29.09.2020 15:22:50
Ambit Temp [°C] Humidity [rel%]	22.6 0
System Version	1.0.0.51
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - WLAN 2G4 g-mode
Add. Information	

Test Parameter	
Technology to test	WLAN2G4 g-mode
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.60