

RF EXPOSURE EVALUATION

EUT Specification

EUT	U47 (Transmitter)
Model Name	Details refer model list.
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others(2446~2461MHz)
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	86.56 dBuV/m (-8.70dBm)(0.13mW)
Antenna gain	0dBi
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

Model list:

U29, U29W, U29S, U29S-E, U29Plus, U29D, U29Plus-G, UA22
U30, U31, U31W, U31R, U31D, U32, U33, U34, U34W, U35, U36, U36W, U36D, U37, U38, U39,
U40, U40W, U41, U41W, U42, U42W, U43, U43W, U44, U44W, U45, U45W, U46, U46W, U46C, U46C-W, U47, U47B, U47W, U48, U48W, U49, U49W, U49C,
U50, U51, U52, U52G, U52W, U53, U54, U54W, U54PLUS, U55, U56, U57, U58, U59,
U60, U61, U62, U63, U64, U65, U66, U67, U68, U69,
U70, U71, U72, U72, U73, U74, U75, U76, U77, U78, U79,
U80, U81, U82, U83, U84, U85, U86, U87, U88, U88PLUS, U88Plus-G, U89,
U818A PLUS, U818A PLUS-C, U818A, U818A-1, U818A HD, U818A WIFI, U818A PLUS-G
U90, U91, U92, U93, U94, U95, U96, U97, U98, U99,
U100, U101, U102, U103, U104, U105, U106, U107, U108, U109,
U110, U111, U112, U113, U114, U115, U116, U117, U118, U119,
U120, U121, U122, U123, U124, U125, U126, U127, U128, U129,
U130, U131, U132, U133, U134, U135, U136, U137, U138, U139,
U140, U141, U142, U143, U144, U145, U146, U147, U148, U149,

U150,
VR1, VR2, VR3, VR4, VR5, VR6, VR7, VR8, VR9, VR10,
UDI001, UDI002, UDI003, UDI004, UDI005, UDI006, UDI007, UDI008, UDI009, UDI010, UDI011, UDI012, UDI013, UDI014, UDI015, UDI016, UDI017, UDI018, UDI019, UDI020,
6182-7SN, 6182-7S DIL, 6182-7S, 6182-7RC DIL, 6182-7RC, 6182-7RC STE, 6182-7SN MCE, 6182-7S BI, ACDRVR, Archos Drone VR, U842-1, U842, U842-2, U842 WIFI, U845, U845 WIFI, U845 FPV, U841, U841-1, U839, U840, U27, U12, U12A, U13, U13A, U835, U829, U829A FPV, U28, U28-1, U28W, U42, U42W, U42HW, VR-2, U820, U843, D2, ZX-TTN, ZX-ATL, ZX-RHD, ZX-NVA, ZX-RAP, ZX-SPT, 6182-7RB TM1, ARCHOS DRONE WW, ARCHOS PICO DRONE, A15W, CW4, U48A, U48HW, TDFT0019, TDFT0014, RC60706, RC49581, RC46892, DRONE 200, DRONE 400, 25197, 25163, T5176, T5177, AA108, A18, A20, A25, A28, A30, T15, T18, T25, T28, T35, 25196, 25194, 25159, 25160, 23938, NT.SS9, NT.SF1M, RC18167, RC18168, RC15771, RC46892, RC49580, T5147, T5170, RGR3000, TDFT0005, TDFT0006, EC16238, EC16242, EC16241, EC16239, EC16243, 6182-7RC AEO, 6182-7SN AEO, 6182-7RB TM1, 6182-7SC BUR, ACPIDR, ACDRONE, A20W, CW 10, U88WIFI, AA 108, AA 818, 6182-7RCH, 8073472, 8073473, RC60706, TDFT0020, TDFT0021, Robin FPV, U60Pro-WCH, CW10

Standard Requirement

Portable Device

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v05, section 4.3.1.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

- $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR} \text{ and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$ where
- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation¹⁷
 - The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Measurement Result

Channel Frequency (MHz)	Max Output power (dBuV)	Max Output power (dBm)	Max Output power (mW)	Calculation Value ^(Note 1)	Threshold Value
2446	86.56	-8.70	0.13	0.0407	3.0
2451	84.73	-10.53	0.09	0.0282	3.0
2461	85.65	-9.61	0.11	0.0345	3.0

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

$$\text{EIRP}=E-104.8+20\log D=86.56-104.8+20\log 3=-8.70\text{dBm}$$

Note 1: Calculation Value =[(max. power of channel, mW)/(min. test separation distance, mm)] • [$\sqrt{f(\text{GHz})}$].

$$\text{For example: } 0.13/5 * \sqrt{2.446} = 0.0407 \leq 3.0$$

According to KDB447498 D01 V05, threshold at which no SAR required is ≤ 3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.

The SAR measurement is not necessary.