Radio Frequency Exposure

Graupner GmbH & Co. KG

FCC ID:	ZKZ-MX-12			
Product Description:	Computer System Graupner HoTT			
Model No.:	mx-12			
Prepared for:	Graupner GmbH & Co. KG			
	Henriettenstr. 94-96 D-73230 Kirchheim Teck, Germany			
Prepared by:	Shenzhen Laker Testing Technology Co.,Ltd			
	15C, Block 1, Sunshine Huayi Building, Nanhai West Road,			
	Nanshan, Shenzhen, China			
	Tel: 86-755-27617110			
	Fax: 86-755-27617110			
Report No.:	LK11ER-00100E			
Issue Date:	May 26,2011			
Test Date:	May 05~20,2011			
Test by:	Reviewed By:			
	Ower Li Jedminal Lor	V		
	Owen Li Edmund Zou	_		

Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See FCC part 15.247(i) and §1.1307(b)(1) of this chapter, According to KDB 447498 (2)(a)(i).

EUT Specification

201 Specification				
EUT	Computer System Graupner HoTT			
Type of Modulation:	FHSS			
Frequency Band:	2404 MHz ~ 2474 MHz			
Number of Channels:	70			
Channel Bandwidth:	1 MHz			
Device category	Portable (<20cm separation) Mobile (>20cm separation) Others			
Antenna diversity	☐ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity			
Antenna gain (Max)	1.8 dBi			

The test result of output power:

Channel Number:	Low(dBm)	Middle(dBm)	High(dBm)
Output Power:	10.95	10.97	11.27

Evaluation

maximum output power (mw)	Max Antenna Gain (dBi)	EIRP (mw)	60/f SAR Limitation (mw)
13.4	1.8	24.12	25

Maximum measured transmitter power: Remark: EIRP=P*G=13.4*1.8=24.12mW Threshold at which no SAR required is 25 mw.

Maximum Tx power is 24.12 mw EIRP.

Conclusion: No SAR is required.