



# FCC RADIO TEST REPORT

APPLICANT : Bullitt Group  
EQUIPMENT : Rugged Smart Phone  
BRAND NAME : CAT  
MODEL NAME : BM1S1B  
FCC ID : ZL5BM1S1BE  
STANDARD : FCC 47 CFR Part 2, and 25  
CLASSIFICATION : Licensed Non-Broadcast Station Transmitter (TNB)  
TEST DATE(S) : Dec. 30, 2022 ~ Jan. 13, 2023

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI/TIA-603-E and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (ShenZhen)**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055**

**People's Republic of China**



TABLE OF CONTENTS

1 GENERAL DESCRIPTION ..... 5
1.1 Applicant..... 5
1.2 Manufacturer ..... 5
1.3 Product Feature of Equipment Under Test ..... 5
1.4 Product Specification of Equipment Under Test ..... 5
1.5 Modification of EUT ..... 6
1.6 Maximum EIRP and Emission Designator ..... 6
1.7 Testing Location ..... 6
1.8 Test Software ..... 7
1.9 Applied Standards ..... 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8
2.1 Test Mode..... 8
2.2 Connection Diagram of Test System ..... 8
2.3 Support Unit used in test configuration and system ..... 8
2.4 Measurement Results Explanation Example ..... 9
2.5 Frequency List of Low/Middle/High Channels ..... 9
3 TEST RESULT ..... 10
3.1 RF Output Power and EIRP ..... 10
3.2 Frequency Stability ..... 11
3.3 Occupied Bandwidth ..... 12
3.4 Conducted Emissions Mask ..... 13
3.5 Conducted Spurious Emission ..... 15
3.6 Field Strength of Spurious Radiation ..... 17
3.7 Additional Limits on Emissions from Mobile Earth Station ..... 20
4 LIST OF MEASURING EQUIPMENT ..... 22
5 UNCERTAINTY OF EVALUATION ..... 23
APPENDIX A. TEST SETUP PHOTOGRAPHS
APPENDIX B. TEST RESULTS OF CONDUCTED TEST
APPENDIX C. TEST RESULTS OF RADIATED TEST



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG201410-01G	Rev. 01	Initial issue of report	Jan. 16, 2023



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046)	RF Output Power	-	Report Only	-
	§25.204(a)	Equivalent Isotropic Radiated Power	40dBW(max)	PASS	-
3.2	§2.1055, §25.202(d)	Frequency Stability	within 0.001 percent of the reference frequency.	PASS	-
3.3	§2.1049	Occupied Bandwidth	-	PASS	-
3.4	§2.1051, §25.202(f)(1)(2)	Conducted Emissions Mask	§25.202(f)(1)(2)	PASS	
3.5	§2.1051, §25.202(f)(3)	Conducted Spurious Emission	§25.202(f)(3)	PASS	-
3.6	§2.1053, §25.202(f)(3)	Field Strength of Spurious Radiation	§25.202(f)(3)	PASS	Under limit 30.33 dB at 6059.450 MHz
3.7	§25.216(c)(e)(h)(i)	Additional Limits on Emissions from Mobile Earth Station	§25.216(c)(e)(h)(i)	PASS	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

**Bullitt Group**

One Valpy, Valpy Street, Reading, Berkshire, RG1 1AR, United Kingdom

## 1.2 Manufacturer

**Bullitt Mobile Limited**

One Valpy, Valpy Street, Reading, Berkshire, RG1 1AR, United Kingdom

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Rugged Smart Phone
Brand Name	CAT
Model Name	BM1S1B
FCC ID	ZL5BM1S1BE
IMEI Code	Conducted: 352089780020354/352089780023838 Radiation: 352089780000417/352089780001910
EUT Stage	Identical Prototype

Note:

1. Dual SIM to Single SIM choose by writing different parameter values to the protection partition of the phone during production.
2. The device is Mobile earth station (MES) only and no Voice.
3. The device does not support 1 tone start 0 & 47 for SCS 3.75kHz and 1 tone start 0 & 11 for SCS 15kHz.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	NB-IOT Category NB1: NTN Band 23 : 2000 MHz ~ 2020 MHz NTN Band 255 : 1626.6 MHz ~ 1660 MHz
Rx Frequency	NB-IOT Category NB1: NTN Band 23 : 2180 MHz ~ 2200 MHz NTN Band 255 : 1525.1 MHz ~ 1558.5 MHz
Sub-carrier Spacing	3.75kHz, 15kHz
Bandwidth	200kHz
Maximum Output Power to Antenna	<Ant.5> NTN Band 23 : 23.53 dBm NTN Band 255 : 23.26 dBm
Antenna Type	IFA Antenna
Antenna Gain	<Ant.5> NTN Band 23 : -2.8 dBi NTN Band 255 : -2.7 dBi
Type of Modulation	BPSK / QPSK



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Maximum EIRP and Emission Designator

NTN Band 23		BPSK/QPSK	
SCS (kHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)
3.75	2000.1 ~ 2019.9	0.1183	59K3G7D
15	2000.1 ~ 2019.9	0.1172	191KG7D
NTN Band 255		BPSK/QPSK	
SCS (kHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)
3.75	1626.7 ~ 1659.9	0.1138	52K1G7D
15	1626.7 ~ 1659.9	0.1132	181KG7D

Note: All modulations have been tested, and only the worst test results are shown in the report.

### 1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Firm</b>	Sporton International Inc. (ShenZhen)		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-SZ	CN1256	421272

<b>Test Firm</b>	Sporton International Inc. (ShenZhen)		
<b>Test Site Location</b>	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH03-SZ	CN1256	421272



### 1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24

### 1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 25
- ♦ ANSI C63.26-2015
- ♦ ANSI/TIA-603-E
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.


## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.(X/Z-Plane)

### 2.2 Connection Diagram of Test System



### 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMW500	Fcc DoC	N/A	Shielded, 1.5m
2.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m





## 2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 5.0 + 10 = 15.0 \text{ (dB)}
 \end{aligned}$$

## 2.5 Frequency List of Low/Middle/High Channels

NTN Band 23 Channel and Frequency List				
SCS [kHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
3.75 / 15	Frequency	2000.1	2010	2019.9

NTN Band 255 Channel and Frequency List				
SCS [kHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
3.75 / 15	Frequency	1626.7	1643.3	1659.9



### 3 Test Result

#### 3.1 RF Output Power and EIRP

##### 3.1.1 Description of the Conducted Output Power and EIRP Measurement

###### FCC Part 25.204 (a)

In bands shared coequally with terrestrial radio communication services, the equivalent isotropically radiated power transmitted in any direction towards the horizon by an earth station, other than an ESV, operating in frequency bands between 1 and 15 GHz, shall not exceed the following limits except as provided for in paragraph (c) of this section:

- + 40 dBW in any 4 kHz band for  $\theta \leq 0^\circ$
- + 40 + 3 $\theta$  dBW in any 4 kHz band for  $0^\circ < \theta \leq 5^\circ$

Where  $\theta$  is the angle of elevation of the horizon viewed from the center of radiation of the antenna of the earth station and measured in degrees as positive above the horizontal plane and negative below it.

According to KDB 412172 D01 Power Approach,

$EIRP = PT + GT - LC$ ,  $ERP = EIRP - 2.15$ , where

PT = transmitter output power in dBm

GT = gain of the transmitting antenna in dBi

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

##### 3.1.2 Test Procedures

The output power is measured by using power meter and FTM (Factory Test Mode) when the transmitter is operating at the manufacturer's rated power and modulated with signals. The maximum antenna gain of EUT for the test range will then be added to the measured conducted power to calculate the EIRP. Since the power meter can only measure the overall power, the measured result will be worse than the one measured in 4 kHz RBW. The test result will be compared to the most restricted limit: +40 dBW.

##### 3.1.3 Test Results

Please refer to Appendix B.

## 3.2 Frequency Stability

### 3.2.1 Description of the Frequency Stability Measurement

**FCC Part 25.202 (d) Frequency tolerance, Earth stations.** The carrier frequency of each earth station transmitter authorized in these services shall be maintained within 0.001 percent of the reference frequency.


### 3.2.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.2.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. The power supply voltage to the EUT was varied from the lowermost voltage to the uppermost voltage. The range is specified by manufacturer.
5. The variation in frequency was measured for the worst case.

### 3.2.4 Test Setup



### 3.2.5 Test Results

Please refer to Appendix B.

### 3.3 Occupied Bandwidth

#### 3.3.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result

Please refer to Appendix B.



### 3.4 Conducted Emissions Mask

#### 3.4.1 Description of Conducted Spurious Emission Measurement

**FCC Part 25.202(f) Emissions Limitations** The mean power of the emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (1) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 50% up to and including 100% of the authorized bandwidth: 25 decibels;
- (2) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 100% up to and including 250% of the authorized bandwidth: 35 decibels;


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The highest RF power within the transmitting frequency was measured.
5. Make the measurement with the spectrum analyzer's RBW = 5kHz, VBW = 20kHz, taking the record of the worst unwanted emission.
6. If the test result in Step 5 exceed the limit, the following procedure will be used:
  - 6.1. Make the measurement with the spectrum analyzer's RBW = 1kHz, VBW = 3kHz.
  - 6.2. Record all measured worst frequencies.
  - 6.3. Use the Channel Power Function of the Spectrum Analyzer.
  - 6.4. Measure the powers of 4kHz bandwidth center the worst frequencies.
7. The limit line is derived from FCC 25.202 (f) below the transmitter power P(Watts)

### 3.4.4 Test Setup



### 3.4.5 Test Result

Please refer to Appendix B.



### 3.5 Conducted Spurious Emission

#### 3.5.1 Description of Conducted Spurious Emission Measurement

**FCC Part 25.202(f) Emissions Limitations** The mean power of the emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

(3) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 250% of the authorized bandwidth: an amount equal to 43 decibels plus 10 times Logarithm (to the base 10) of the transmitter power in watts.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The highest RF power within the transmitting frequency was measured.
5. Peak detector is used instead of RMS detector since the measured result of Peak detector is worse than the RMS one. If the test result of Peak detector exceed the limit, RMS detector will then be used.
6. Make the measurement with the spectrum analyzer's RBW = 100kHz, VBW = 300kHz, taking the record of the worst unwanted emission.
7. The conducted spurious emission for the whole frequency range was taken.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from FCC 25.202 (f) below the transmitter power P(Watts)

### 3.5.4 Test Setup



### 3.5.5 Test Result

Please refer to Appendix B.





### 3.6 Field Strength of Spurious Radiation

#### 3.6.1 Description of Radiated Spurious Emission

**FCC Part 25.202(f) Emissions Limitations** The mean power of the emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

(3) In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 250% of the authorized bandwidth: an amount equal to 43 decibels plus 10 times Logarithm (to the base 10) of the transmitter power in watts

#### 3.6.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures


1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable table with:
  - 0.8 meter above ground for emissions under 1 GHz
  - 1.5 meter above ground for emissions above 1 GHz
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Peak detector is used instead of RMS detector since the measured result of Peak detector is worse than the RMS one. If the test result of Peak detector exceed the limit, RMS detector will then be used.
7. Make the measurement with the spectrum analyzer's RBW = 100kHz, VBW = 300kHz, taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.6.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.6.5 Test Results

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix C.



### 3.7 Additional Limits on Emissions from Mobile Earth Station

Additional Limits on emissions from mobile earth stations for protection of aeronautical radionavigation-satellite service and Special requirements for ancillary terrestrial components operating in the 1626.5-1660.5 MHz and 2000-2020 MHz bands.

#### 3.7.1 Description of Additional Limits on Emissions from Mobile Earth Station

**FCC Part 25.216 Emissions Limitations:**

(c) The e.i.r.p. density of emissions from mobile earth stations placed in service after July 21, 2002 with assigned uplink frequencies between 1610 MHz and 1660.5 MHz shall not exceed  $-70$  dBW/MHz, averaged over any 2 millisecond active transmission interval, in the band 1559-1605 MHz. The e.i.r.p. of discrete emissions of less than 700 Hz bandwidth from such stations shall not exceed  $-80$  dBW, averaged over any 2 millisecond active transmission interval, in the 1559-1605 MHz band.

(e) The e.i.r.p density of emissions from mobile earth stations with assigned uplink frequencies between 1990 MHz and 2025 MHz shall not exceed  $-70$  dBW/MHz, averaged over any 2 millisecond active transmission interval, in frequencies between 1559 MHz and 1610 MHz. The e.i.r.p. of discrete emissions of less than 700 Hz bandwidth from such stations between 1559 MHz and 1605 MHz shall not exceed  $-80$  dBW, averaged over any 2 millisecond active transmission interval. The e.i.r.p. of discrete emissions of less than 700 Hz bandwidth from such stations between 1605 MHz and 1610 MHz manufactured more than six months after Federal Register publication of the rule changes adopted in FCC 03-283 shall not exceed  $-80$  dBW, averaged over any 2 millisecond active transmission interval.

(h) Mobile earth stations manufactured more than six months after Federal Register publication of the rule changes adopted in FCC 03-283 with assigned uplink frequencies in the 1626.5-1660.5 MHz band shall suppress the power density of emissions in the 1605-1610 MHz band-segment to an extent determined by linear interpolation from  $-70$  dBW/MHz at 1605 MHz to  $-46$  dBW/MHz at 1610 MHz, averaged over any 2 millisecond active transmission interval. The e.i.r.p of discrete emissions of less than 700 Hz bandwidth from such stations shall not exceed a level determined by linear interpolation from  $-80$  dBW at 1605 MHz to  $-56$  dBW at 1610 MHz, averaged over any 2 millisecond active transmission interval.

(i) The e.i.r.p density of carrier-off state emissions from mobile earth stations manufactured more than six months after Federal Register publication of the rule changes adopted in FCC 03-283 with assigned uplink frequencies between 1 and 3 GHz shall not exceed  $-80$  dBW/MHz in the 1559-1610 MHz band averaged over any two millisecond interval.

(j) A Root-Mean-Square detector shall be used for all power density measurements.


### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The highest RF power within the transmitting frequency was measured.
5. Make the measurement with the spectrum analyzer's RBW = 10kHz for discrete emissions, RBW = 1MHz for broadband emissions, and VBW = 3 x RBW Taking the record of maximum spurious emission.

### 3.7.4 Test Setup



### 3.7.5 Test Results

Please refer to Appendix B.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 07, 2022	Dec. 30, 2022~Jan. 13, 2023	Apr. 06, 2023	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04265	60.06.020.0077	0.4GHz~26.5GHz	Dec. 25, 2022	Dec. 30, 2022~Jan. 13, 2023	Dec. 24, 2023	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 07, 2022	Dec. 30, 2022~Jan. 13, 2023	Jul. 06, 2023	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 06, 2022	Jan. 10, 2023	Apr. 05, 2023	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	Jan. 10, 2023	Jun. 27, 2023	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Aug. 09, 2022	Jan. 10, 2023	Aug. 08, 2023	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 08, 2022	Jan. 10, 2023	Apr. 07, 2023	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 10, 2022	Jan. 10, 2023	Apr. 09, 2023	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz~3000MHz	Oct. 19, 2022	Jan. 10, 2023	Oct. 18, 2023	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 26, 2022	Jan. 10, 2023	Dec. 25, 2023	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 06, 2022	Jan. 10, 2023	Jul. 05, 2023	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002729	N/A	Nov. 10, 2022	Jan. 10, 2023	Nov. 09, 2023	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 10, 2023	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 10, 2023	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±1.34 dB
Conducted Emissions	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.6dB
---	-------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.8dB
---	-------



## Appendix B. Test Results of Conducted Test

Test Engineer :	Jung Kuo	Temperature :	24~26°C
		Relative Humidity :	50~53%

### NTN Band 23

#### Conducted Output Power (Average power) and EIRP

Band 23 SCS3.75kHz							Limit
Test Frequency (MHz)	SC Size	Conducted Power (dBm)		Antenna Gain (dBi)	EIRP Power (dBm)		Result
		BPSK	QPSK		BPSK	QPSK	
2000.1	1SC1	23.09	23.24	-2.8	20.29	20.44	PASS
	1SC46	23.15	23.23	-2.8	20.35	20.43	
2010	1SC1	23.43	23.53	-2.8	20.63	20.73	
	1SC46	23.45	23.48	-2.8	20.65	20.68	
2019.9	1SC1	23.38	23.51	-2.8	20.58	20.71	
	1SC46	23.45	23.41	-2.8	20.65	20.61	

Band 23 SCS15kHz							Limit
Test Frequency (MHz)	SC Size	Conducted Power (dBm)		Antenna Gain (dBi)	EIRP Power (dBm)		Result
		BPSK	QPSK		BPSK	QPSK	
2000.1	1SC1	23.12	23.36	-2.8	20.32	20.56	PASS
	1SC10	23.15	23.18	-2.8	20.35	20.38	
	3SC0	-	21.82	-2.8	-	19.02	
	3SC9	-	21.85	-2.8	-	19.05	
	6SC0	-	21.43	-2.8	-	18.63	
	6SC6	-	21.34	-2.8	-	18.54	
	12SC0	-	21.41	-2.8	-	18.61	
2010	1SC1	23.49	23.40	-2.8	20.69	20.6	
	1SC10	23.46	23.38	-2.8	20.66	20.58	
	3SC0	-	22.20	-2.8	-	19.4	
	3SC9	-	22.27	-2.8	-	19.47	
	6SC0	-	21.73	-2.8	-	18.93	
	6SC6	-	21.66	-2.8	-	18.86	
	12SC0	-	21.87	-2.8	-	19.07	
2019.9	1SC1	23.16	23.42	-2.8	20.36	20.62	
	1SC10	23.41	23.39	-2.8	20.61	20.59	
	3SC0	-	22.14	-2.8	-	19.34	
	3SC9	-	22.23	-2.8	-	19.43	
	6SC0	-	21.74	-2.8	-	18.94	
	6SC6	-	21.60	-2.8	-	18.8	
	12SC0	-	21.62	-2.8	-	18.82	






Occupied Bandwidth

Mode	Band 23 : 99%OBW(kHz)										
SCS	3.75kHz		15kHz								
Mod.	BPSK	QPSK	BPSK	QPSK	QPSK	QPSK	QPSK				
SC Size	1SC1	1SC1	1SC1	1SC1	3SC0	6SC0	12SC0				
Lowest CH	52.098	54.269	117.221	115.051	117.221	191.027	181.621				
Middle CH	52.822	55.716	120.116	113.603	117.221	183.068	181.621				
Highest CH	54.993	59.334	120.839	112.880	121.563	187.410	182.344				




Band 23 SCS3.75KHz

Lowest Channel / 1SC1 / BPSK




Date: 13.JAN.2023 10:35:55

Lowest Channel / 1SC1 / QPSK




Date: 13.JAN.2023 10:35:18

Middle Channel / 1SC1 / BPSK




Date: 13.JAN.2023 10:39:31

Middle Channel / 1SC1 / QPSK




Date: 13.JAN.2023 10:40:15

Highest Channel / 1SC1 / BPSK



Date: 13.JAN.2023 10:49:10

Highest Channel / 1SC1 / QPSK




Date: 13.JAN.2023 10:48:44




Band 23 SCS15KHz

Lowest Channel / 1SC1 / BPSK




Date: 13. JAN. 2023 10:28:50

Lowest Channel / 1SC1 / QPSK




Date: 13. JAN. 2023 10:30:18

Middle Channel / 1SC1 / BPSK




Date: 13. JAN. 2023 10:42:57

Middle Channel / 1SC1 / QPSK




Date: 13. JAN. 2023 10:41:38

Highest Channel / 1SC1 / BPSK



Date: 13. JAN. 2023 10:46:03

Highest Channel / 1SC1 / QPSK



Date: 13. JAN. 2023 10:46:30



Band 23 SCS15KHz																													
N/A	Lowest Channel / 3SC0 / QPSK																												
-	<p>CF 2.0001 GHz 691 pts Span 500.0 kHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.0000508 GHz</td> <td>21.70 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td>1.99999508 GHz</td> <td>-0.27 dBm</td> <td>Occ Bw</td> <td>117.221418234 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td>2.000112301 GHz</td> <td>0.03 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 12.JAN.2023 15:51:16</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.0000508 GHz	21.70 dBm			T1	1		1.99999508 GHz	-0.27 dBm	Occ Bw	117.221418234 kHz	T2	1		2.000112301 GHz	0.03 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																							
M1	1		2.0000508 GHz	21.70 dBm																									
T1	1		1.99999508 GHz	-0.27 dBm	Occ Bw	117.221418234 kHz																							
T2	1		2.000112301 GHz	0.03 dBm																									
N/A	Middle Channel / 3SC0 / QPSK																												
-	<p>CF 2.01 GHz 691 pts Span 500.0 kHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.0099508 GHz</td> <td>22.05 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td>2.009996527 GHz</td> <td>3.35 dBm</td> <td>Occ Bw</td> <td>117.221418234 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td>2.010013748 GHz</td> <td>-0.82 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 12.JAN.2023 15:58:44</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.0099508 GHz	22.05 dBm			T1	1		2.009996527 GHz	3.35 dBm	Occ Bw	117.221418234 kHz	T2	1		2.010013748 GHz	-0.82 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																							
M1	1		2.0099508 GHz	22.05 dBm																									
T1	1		2.009996527 GHz	3.35 dBm	Occ Bw	117.221418234 kHz																							
T2	1		2.010013748 GHz	-0.82 dBm																									
N/A	Highest Channel / 3SC0 / QPSK																												
-	<p>CF 2.0199 GHz 691 pts Span 500.0 kHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.01985007 GHz</td> <td>21.96 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td>2.019796527 GHz</td> <td>2.67 dBm</td> <td>Occ Bw</td> <td>121.562952243 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td>2.01991809 GHz</td> <td>-5.37 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 12.JAN.2023 16:09:50</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.01985007 GHz	21.96 dBm			T1	1		2.019796527 GHz	2.67 dBm	Occ Bw	121.562952243 kHz	T2	1		2.01991809 GHz	-5.37 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																							
M1	1		2.01985007 GHz	21.96 dBm																									
T1	1		2.019796527 GHz	2.67 dBm	Occ Bw	121.562952243 kHz																							
T2	1		2.01991809 GHz	-5.37 dBm																									



Band 23 SCS15KHz

N/A

Lowest Channel / 6SC0 / QPSK



Date: 12.JAN.2023 15:54:45

N/A

Middle Channel / 6SC0 / QPSK



Date: 12.JAN.2023 15:57:50

N/A

Highest Channel / 6SC0 / QPSK



Date: 12.JAN.2023 16:10:26



Band 23 SCS15KHz																													
N/A	Lowest Channel / 12SC0 / QPSK																												
-	<p>Spectrum            Ref Level 35.00 dBm Offset 15.00 dB RBW 3 kHz            Att 30 dB SWT 5.6 ms VBW 10 kHz Mode Sweep</p> <p>1PK Max 14.16 dBm            2.00014486 GHz            181.620839363 kHz</p> <p>CF 2.0001 GHz 691 pts Span 500.0 kHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.00014486 GHz</td> <td>14.16 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td>2.00010999 GHz</td> <td>2.75 dBm</td> <td>Occ Bw</td> <td>181.620839363 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td>2.000192619 GHz</td> <td>3.93 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 2.JAN.2023 10:52:21</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.00014486 GHz	14.16 dBm			T1	1		2.00010999 GHz	2.75 dBm	Occ Bw	181.620839363 kHz	T2	1		2.000192619 GHz	3.93 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																							
M1	1		2.00014486 GHz	14.16 dBm																									
T1	1		2.00010999 GHz	2.75 dBm	Occ Bw	181.620839363 kHz																							
T2	1		2.000192619 GHz	3.93 dBm																									
N/A	Middle Channel / 12SC0 / QPSK																												
-	<p>Spectrum            Ref Level 35.00 dBm Offset 15.00 dB RBW 3 kHz            Att 30 dB SWT 5.6 ms VBW 10 kHz Mode Sweep</p> <p>1PK Max 14.72 dBm            2.01000434 GHz            181.620839363 kHz</p> <p>CF 2.01 GHz 691 pts Span 500.0 kHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.01000434 GHz</td> <td>14.72 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td>2.009910999 GHz</td> <td>3.04 dBm</td> <td>Occ Bw</td> <td>181.620839363 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td>2.010092619 GHz</td> <td>4.45 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 2.JAN.2023 13:34:48</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.01000434 GHz	14.72 dBm			T1	1		2.009910999 GHz	3.04 dBm	Occ Bw	181.620839363 kHz	T2	1		2.010092619 GHz	4.45 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																							
M1	1		2.01000434 GHz	14.72 dBm																									
T1	1		2.009910999 GHz	3.04 dBm	Occ Bw	181.620839363 kHz																							
T2	1		2.010092619 GHz	4.45 dBm																									
N/A	Highest Channel / 12SC0 / QPSK																												
-	<p>Spectrum            Ref Level 35.00 dBm Offset 15.00 dB RBW 3 kHz            Att 30 dB SWT 5.6 ms VBW 10 kHz Mode Sweep</p> <p>1PK Max 14.90 dBm            2.01994486 GHz            182.344428365 kHz</p> <p>CF 2.0199 GHz 691 pts Span 500.0 kHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.01994486 GHz</td> <td>14.90 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td>2.019810999 GHz</td> <td>3.22 dBm</td> <td>Occ Bw</td> <td>182.344428365 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td>2.019993343 GHz</td> <td>2.91 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 2.JAN.2023 15:21:21</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.01994486 GHz	14.90 dBm			T1	1		2.019810999 GHz	3.22 dBm	Occ Bw	182.344428365 kHz	T2	1		2.019993343 GHz	2.91 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																							
M1	1		2.01994486 GHz	14.90 dBm																									
T1	1		2.019810999 GHz	3.22 dBm	Occ Bw	182.344428365 kHz																							
T2	1		2.019993343 GHz	2.91 dBm																									




**MASK**

**Band 23 SCS3.75kHz**

**Lowest Channel / 1SC1 / BPSK**


N/A



Date: 3, JAN, 2023 12:14:56

**Middle Channel / 1SC1 / BPSK**


N/A



Date: 3, JAN, 2023 11:47:39

**Highest Channel / 1SC1 / BPSK**

N/A




Date: 3, JAN, 2023 11:34:46




Band 23 SCS3.75kHz

Lowest Channel / 1SC46 / BPSK




Date: 4.JAN.2023 10:28:58

Lowest Channel / 1SC46 / BPSK-CP




Date: 4.JAN.2023 10:46:29

Middle Channel / 1SC46 / BPSK




Date: 4.JAN.2023 10:40:22

Middle Channel / 1SC46 / BPSK-CP




Date: 4.JAN.2023 10:46:51

Highest Channel / 1SC46 / BPSK



Date: 4.JAN.2023 10:50:24

Highest Channel / 1SC46 / BPSK-CP



Date: 4.JAN.2023 10:52:08

Remark: The above results of RBW 1kHz corrected by 10log(4kHz/1kHz) is passed.






Band 23 SCS3.75kHz

Lowest Channel / 1SC1 / QPSK


N/A



Date: 6-JAN-2023 11:35:19

Middle Channel / 1SC1 / QPSK


N/A



Date: 6-JAN-2023 16:55:48

Highest Channel / 1SC1 / QPSK

N/A




Date: 6-JAN-2023 14:25:06




Band 23 SCS3.75kHz

Lowest Channel / 1SC46 / QPSK




Date: 6.JAN.2023 13:43:56

Lowest Channel / 1SC46 / QPSK-CP




Date: 6.JAN.2023 13:45:17

Middle Channel / 1SC46 / QPSK




Date: 6.JAN.2023 13:17:54

Middle Channel / 1SC46 / QPSK-CP




Date: 6.JAN.2023 13:19:52

Highest Channel / 1SC46 / QPSK



Date: 6.JAN.2023 14:10:57

Highest Channel / 1SC46 / QPSK-CP



Date: 6.JAN.2023 14:22:02


Remark: The above results of RBW 1kHz corrected by 10log(4kHz/1kHz) is passed.



Band 23 SCS15kHz

Lowest Channel / 1SC1 / BPSK


N/A



Date: 2..JAN.2023 10:13:27

Middle Channel / 1SC1 / BPSK


N/A




Date: 3..JAN.2023 12:05:23

Highest Channel / 1SC1 / BPSK

Highest Channel / 1SC1 / BPSK-CP



Date: 3..JAN.2023 11:27:56




Date: 9..JAN.2023 11:44:25



Band 23 SCS15kHz

Lowest Channel / 1SC10 / BPSK


N/A



Date: 2-JAN-2023 10:39:17

Middle Channel / 1SC10 / BPSK


N/A



Date: 3-JAN-2023 11:54:47

Highest Channel / 1SC10 / BPSK

N/A




Date: 3-JAN-2023 11:23:30




Band 23 SCS15kHz

Lowest Channel / 1SC1 / QPSK




Date: 6-JAN-2023 11:42:46

Lowest Channel / 1SC10 / QPSK




Date: 6-JAN-2023 11:44:07

Middle Channel / 1SC1 / QPSK




Date: 6-JAN-2023 11:52:37

Middle Channel / 1SC10 / QPSK




Date: 6-JAN-2023 11:49:02

Highest Channel / 1SC1 / QPSK



Date: 6-JAN-2023 14:29:21

Highest Channel / 1SC10 / QPSK




Date: 6-JAN-2023 14:34:49




Band 23 SCS15kHz

Lowest Channel / 3SC0 / QPSK




Date: 2-JAN-2023 12:10:05

Lowest Channel / 3SC9 / QPSK




Date: 2-JAN-2023 11:58:27

Middle Channel / 3SC0 / QPSK




Date: 2-JAN-2023 14:29:42

Middle Channel / 3SC9 / QPSK




Date: 2-JAN-2023 14:28:14

Highest Channel / 3SC0 / QPSK



Date: 2-JAN-2023 14:43:35

Highest Channel / 3SC9 / QPSK




Date: 2-JAN-2023 14:42:06




Band 23 SCS15kHz

Lowest Channel / 6SC0 / QPSK




Date: 2-JAN-2023 13:01:53

Lowest Channel / 6SC6 / QPSK




Date: 2-JAN-2023 13:02:48

Middle Channel / 6SC0 / QPSK




Date: 2-JAN-2023 14:31:16

Middle Channel / 6SC6 / QPSK




Date: 2-JAN-2023 14:32:05

Highest Channel / 6SC0 / QPSK



Date: 2-JAN-2023 14:37:38

Highest Channel / 6SC6 / QPSK




Date: 2-JAN-2023 14:40:39



Band 23 SCS15kHz

Lowest Channel / 12SC0 / QPSK


N/A



Date: 2-JAN-2023 13:03:59

Middle Channel / 12SC0 / QPSK


N/A



Date: 2-JAN-2023 14:32:43

Highest Channel / 12SC0 / QPSK

N/A



Date: 2-JAN-2023 14:36:53






# Conducted Spurious Emission


## Band 23 SCS3.75kHz

### Lowest Channel / 1SC1 / BPSK




Date: 2.JAN.2023 13:13:08

### Lowest Channel / 1SC1 / QPSK




Date: 2.JAN.2023 13:14:03

### Middle Channel / 1SC1 / BPSK




Date: 2.JAN.2023 13:20:12

### Middle Channel / 1SC1 / QPSK




Date: 2.JAN.2023 13:19:13

### Highest Channel / 1SC1 / BPSK



Date: 2.JAN.2023 15:14:20

### Highest Channel / 1SC1 / QPSK



Date: 2.JAN.2023 15:12:58