



# FCC RF Test Report

**APPLICANT** : Bullitt Group  
**EQUIPMENT** : Rugged Smart Phone  
**BRAND NAME** : CAT  
**MODEL NAME** : S60  
**MARKETING NAME** : S60  
**FCC ID** : ZL5S60  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was received on Mar. 03, 2016 and testing was completed on May 30, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 5

    1.5 Modification of EUT ..... 6

    1.6 Testing Location ..... 6

    1.7 Applicable Standards ..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1 Carrier Frequency Channel ..... 8

    2.2 Pre-Scanned RF Power ..... 9

    2.3 Test Mode ..... 9

    2.4 Connection Diagram of Test System ..... 10

    2.5 Support Unit used in test configuration and system ..... 11

    2.6 EUT Operation Test Setup ..... 11

    2.7 Measurement Results Explanation Example ..... 11

**3 TEST RESULT ..... 12**

    3.1 6dB and 99% Bandwidth Measurement ..... 12

    3.2 Output Power Measurement ..... 14

    3.3 Power Spectral Density Measurement ..... 15

    3.4 Conducted Band Edges and Spurious Emission Measurement ..... 17

    3.5 Radiated Band Edges and Spurious Emission Measurement ..... 30

    3.6 AC Conducted Emission Measurement ..... 33

    3.7 Antenna Requirements ..... 38

**4 LIST OF MEASURING EQUIPMENT ..... 39**

**5 UNCERTAINTY OF EVALUATION ..... 40**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. RADIATED SPURIOUS EMISSION**

**APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR630110-01C	Rev. 01	Initial issue of report	Jun. 06, 2016



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.56 dB at 2483.600 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.90 dB at 2.262 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**Bullitt Group**

One Valpy, Valpy Street, Reading, Berkshire, RG1 1AR United Kingdom

## 1.2 Manufacturer

**Compal Electronics, INC.**

No. 385, Yangguang St. Neihu District, Taipei City 11491, Taiwan, R.O.C

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Rugged Smart Phone
Brand Name	CAT
Model Name	S60
Marketing Name	S60
Sample 1	EUT with Dual SIM
Sample 2	EUT with Single SIM
FCC ID	ZL5S60
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/NFC WLAN 11b/g/n HT20/HT40 Bluetooth v4.1 EDR/LE
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. All test items are performed on sample 1.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 19.50 dBm (0.0891 W) 802.11g : 20.58 dBm (0.1143 W) 802.11n HT20 : 19.15 dBm (0.0822 W) 802.11n HT40 : 19.81 dBm (0.0957 W)
99% Occupied Bandwidth	802.11b : 13.90MHz 802.11g : 18.35MHz 802.11n HT20 : 19.05MHz 802.11n HT40 : 36.70MHz
Antenna Type	802.11b/g/n : PIFA Antenna type with gain 0.41 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH10-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.



## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-





### 2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b mode				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	19.50	19.14	19.06	19.19

2.4GHz 802.11g mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	20.58	20.35	20.47	20.45	20.44	20.35	20.39	20.31

2.4GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	19.15	19.05	18.97	18.97	18.71	18.62	18.59	18.53

2.4GHz 802.11n HT40 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	19.81	19.55	19.41	19.47	19.36	19.34	19.04	19.10

### 2.3 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1: WCDMA Band II Idle + Bluetooth Link + WLAN Link + Camera (Rear) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1

## 2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>





## 2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	16G	FCC DoC	N/A	N/A
6.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8 m

## 2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, “QRCT” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

## 2.7 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


##### 3.1.4 Test Setup





### 3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A of this test report.



**Note :** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

### 3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


#### 3.3.4 Test Setup





### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.





## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges and Spurious Emission


Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	PH Yang

#### WLAN 802.11b Channel 01


##### 100kHz PSD reference Level




##### Low Channel Plot



##### Spurious Emission 30MHz~3GHz



##### Spurious Emission 2GHz~25GHz






Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	PH Yang

WLAN 802.11b Channel 06

100kHz PSD reference Level


Mid Channel Plot




Date: 16.MAY.2016 09:29:02

Spurious Emission 30MHz~3GHz

Spurious Emission 2GHz~25GHz



Date: 16.MAY.2016 09:29:36




Date: 16.MAY.2016 09:29:44




Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	PH Yang

WLAN 802.11b Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	PH Yang

WLAN 802.11g Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	PH Yang

WLAN 802.11g Channel 06



100kHz PSD reference Level

Mid Channel Plot



Spurious Emission 30MHz~3GHz

Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	PH Yang

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	PH Yang

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz








Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	PH Yang

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level


Mid Channel Plot




Date: 16.MAY.2016 10:20:06

Spurious Emission 30MHz~3GHz

Spurious Emission 2GHz~25GHz



Date: 16.MAY.2016 10:20:20




Date: 16.MAY.2016 10:20:28




Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	PH Yang

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	03	Test Engineer :	PH Yang

WLAN 802.11n HT40 Channel 03


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	PH Yang

WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level


Mid Channel Plot




Date: 16.MAY.2016 10:34:58

Spurious Emission 30MHz~3GHz

Spurious Emission 2GHz~25GHz



Date: 16.MAY.2016 10:35:13




Date: 16.MAY.2016 10:35:21




Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	09	Test Engineer :	PH Yang

WLAN 802.11n HT40 Channel 09


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz





### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


#### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:


- (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.
- For average measurement:
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
  - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


**For radiated emissions below 30MHz**



**For radiated emissions from 30MHz to 1GHz**



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C of this report.

### 3.5.7 Duty Cycle

Please refer to Appendix D of this report.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix B and C of this report.





### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~23°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	42~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + Bluetooth Link + WLAN Link + Camera (Rear) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1		




**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.502000	40.2	Off	L1	19.6	15.8	56.0
0.854000	40.3	Off	L1	19.6	15.7	56.0
1.006000	41.0	Off	L1	19.7	15.0	56.0
1.190000	35.2	Off	L1	19.7	20.8	56.0
2.054000	38.3	Off	L1	19.6	17.7	56.0
2.182000	38.4	Off	L1	19.6	17.6	56.0
2.262000	41.1	Off	L1	19.6	14.9	56.0
3.398000	37.3	Off	L1	19.7	18.7	56.0
18.030000	36.8	Off	L1	20.6	23.2	60.0
19.342000	37.9	Off	L1	20.7	22.1	60.0



Test Mode :	Mode 1	Temperature :	22~23°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	42~43%%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + Bluetooth Link + WLAN Link + Camera (Rear) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1		




Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.502000	31.0	Off	L1	19.6	15.0	46.0
0.854000	28.3	Off	L1	19.6	17.7	46.0
1.006000	28.4	Off	L1	19.7	17.6	46.0
1.190000	25.5	Off	L1	19.7	20.5	46.0
2.054000	28.3	Off	L1	19.6	17.7	46.0
2.182000	27.7	Off	L1	19.6	18.3	46.0
2.262000	29.5	Off	L1	19.6	16.5	46.0
3.398000	26.5	Off	L1	19.7	19.5	46.0
18.030000	26.4	Off	L1	20.6	23.6	50.0
19.342000	27.7	Off	L1	20.7	22.3	50.0



Test Mode :	Mode 1	Temperature :	22~23°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	42~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band II Idle + Bluetooth Link + WLAN Link + Camera (Rear) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1		



**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.502000	38.1	Off	N	19.6	17.9	56.0
1.054000	36.0	Off	N	19.6	20.0	56.0
2.158000	39.8	Off	N	19.6	16.2	56.0
3.398000	34.9	Off	N	19.7	21.1	56.0
16.422000	36.8	Off	N	20.5	23.2	60.0
17.726000	39.7	Off	N	20.6	20.3	60.0
19.062000	40.9	Off	N	20.7	19.1	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.502000	29.7	Off	N	19.6	16.3	46.0
1.054000	25.3	Off	N	19.6	20.7	46.0
2.158000	26.2	Off	N	19.6	19.8	46.0
3.398000	23.5	Off	N	19.7	22.5	46.0
16.422000	24.4	Off	N	20.5	25.6	50.0
17.726000	27.3	Off	N	20.6	22.7	50.0
19.062000	28.3	Off	N	20.7	21.7	50.0



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1132003	300MHz~40GHz	Aug. 12, 2015	May 12, 2016 ~ May 16, 2016	Aug. 11, 2016	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Aug. 12, 2015	May 12, 2016 ~ May 16, 2016	Aug. 11, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 23, 2015	May 12, 2016 ~ May 16, 2016	Nov. 22, 2016	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 11, 2016~ May 12, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	May 11, 2016~ May 12, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	May 11, 2016~ May 12, 2016	Dec. 01, 2016	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Mar. 27, 2016 ~ May 30, 2016	Sep. 01, 2016	Radiation (03CH10-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Nov. 16, 2015	Mar. 27, 2016 ~ May 30, 2016	Nov. 15, 2016	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D	35413	30MHz~1GHz	Jan. 13, 2016	Mar. 27, 2016 ~ May 30, 2016	Jan. 12, 2017	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Sep. 30, 2015	Mar. 27, 2016 ~ May 30, 2016	Sep. 29, 2016	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY53270078	1GHz~26.5GHz	Nov. 13, 2015	Mar. 27, 2016 ~ May 30, 2016	Nov. 12, 2016	Radiation (03CH10-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1902246	1GHz~18GHz	Nov. 16, 2015	Mar. 27, 2016 ~ May 30, 2016	Nov. 15, 2016	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 15, 2015	Mar. 27, 2016 ~ May 30, 2016	Oct. 14, 2016	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Mar. 27, 2016 ~ May 30, 2016	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Mar. 27, 2016 ~ May 30, 2016	N/A	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 15, 2016	Mar. 27, 2016 ~ May 30, 2016	Apr. 14, 2017	Radiation (03CH10-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY55420170	N/A	Mar. 10, 2016	Mar. 27, 2016 ~ May 30, 2016	Mar. 09, 2017	Radiation (03CH10-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Mar. 27, 2016 ~ May 30, 2016	Jun. 01, 2016	Radiation (03CH10-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
---	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.50
---	------





## **Appendix A. Conducted Test Results**

**A1 - DTS Part**

Test Engineer:	PHYang	Temperature:	21~25	°C
Test Date:	2015/5/12~5/16	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

2.4GHz Band								
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	13.90	9.04	0.50	Pass
11b	1Mbps	1	6	2437	13.90	9.00	0.50	Pass
11b	1Mbps	1	11	2462	13.85	8.56	0.50	Pass
11g	6Mbps	1	1	2412	18.25	16.42	0.50	Pass
11g	6Mbps	1	6	2437	18.35	16.44	0.50	Pass
11g	6Mbps	1	11	2462	18.30	16.44	0.50	Pass
HT20	MCS0	1	1	2412	18.95	17.64	0.50	Pass
HT20	MCS0	1	6	2437	19.00	17.64	0.50	Pass
HT20	MCS0	1	11	2462	19.05	17.64	0.50	Pass
HT40	MCS0	1	3	2422	36.70	35.60	0.50	Pass
HT40	MCS0	1	6	2437	36.50	35.20	0.50	Pass
HT40	MCS0	1	9	2452	36.60	35.28	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

2.4GHz Band										
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	19.50	30.00	0.41	19.91	36.00	Pass
11b	1Mbps	1	6	2437	19.22	30.00	0.41	19.63	36.00	Pass
11b	1Mbps	1	11	2462	19.16	30.00	0.41	19.57	36.00	Pass
11g	6Mbps	1	1	2412	20.58	30.00	0.41	20.99	36.00	Pass
11g	6Mbps	1	6	2437	20.45	30.00	0.41	20.86	36.00	Pass
11g	6Mbps	1	11	2462	20.37	30.00	0.41	20.78	36.00	Pass
HT20	MCS0	1	1	2412	19.15	30.00	0.41	19.56	36.00	Pass
HT20	MCS0	1	6	2437	18.82	30.00	0.41	19.23	36.00	Pass
HT20	MCS0	1	11	2462	19.02	30.00	0.41	19.43	36.00	Pass
HT40	MCS0	1	3	2422	19.46	30.00	0.41	19.87	36.00	Pass
HT40	MCS0	1	6	2437	19.81	30.00	0.41	20.22	36.00	Pass
HT40	MCS0	1	9	2452	19.35	30.00	0.41	19.76	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**  
***(Reporting Only)***

2.4GHz Band						
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.13	16.97
11b	1Mbps	1	6	2437	0.13	16.86
11b	1Mbps	1	11	2462	0.13	16.75
11g	6Mbps	1	1	2412	0.65	11.99
11g	6Mbps	1	6	2437	0.65	11.81
11g	6Mbps	1	11	2462	0.65	11.58
HT20	MCS0	1	1	2412	0.63	9.98
HT20	MCS0	1	6	2437	0.63	9.85
HT20	MCS0	1	11	2462	0.63	9.73
HT40	MCS0	1	3	2422	1.22	10.15
HT40	MCS0	1	6	2437	1.22	10.43
HT40	MCS0	1	9	2452	1.22	10.38

**TEST RESULTS DATA**  
**Peak Power Density**

2.4GHz Band								
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-5.99	0.41	8.00	Pass
11b	1Mbps	1	6	2437	-5.27	0.41	8.00	Pass
11b	1Mbps	1	11	2462	-5.51	0.41	8.00	Pass
11g	6Mbps	1	1	2412	-13.05	0.41	8.00	Pass
11g	6Mbps	1	6	2437	-13.52	0.41	8.00	Pass
11g	6Mbps	1	11	2462	-14.85	0.41	8.00	Pass
HT20	MCS0	1	1	2412	-14.97	0.41	8.00	Pass
HT20	MCS0	1	6	2437	-15.67	0.41	8.00	Pass
HT20	MCS0	1	11	2462	-16.37	0.41	8.00	Pass
HT40	MCS0	1	3	2422	-17.32	0.41	8.00	Pass
HT40	MCS0	1	6	2437	-18.15	0.41	8.00	Pass
HT40	MCS0	1	9	2452	-18.01	0.41	8.00	Pass



## Appendix B. Radiated Spurious Emission

Test Engineer :	Tsung Lee and Donny Tang	Temperature :	23~25°C
		Relative Humidity :	45~48%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11b CH 01 2412MHz		2364	51.35	-22.65	74	52.07	27.14	5.39	33.25	318	51	P	H	
		2390	40.69	-13.31	54	41.29	27.23	5.39	33.22	318	51	A	H	
	*	2412	105.35	-	-	105.87	27.28	5.42	33.22	318	51	P	H	
	*	2412	102.23	-	-	102.75	27.28	5.42	33.22	318	51	A	H	
													H	
														H
			2386.95	50.72	-23.28	74	51.34	27.23	5.39	33.24	123	58	P	V
			2388.75	40.67	-13.33	54	41.29	27.23	5.39	33.24	123	58	A	V
	*		2412	103.04	-	-	103.56	27.28	5.42	33.22	123	58	P	V
	*		2414	99.97	-	-	100.49	27.28	5.42	33.22	123	58	A	V
														V
														V
802.11b CH 06 2437MHz		2349.24	51.74	-22.26	74	52.56	27.1	5.33	33.25	321	53	P	H	
		2389.65	40.74	-13.26	54	41.36	27.23	5.39	33.24	321	53	A	H	
	*	2437	105.61	-	-	106.03	27.37	5.42	33.21	321	53	P	H	
	*	2437	102.37	-	-	102.79	27.37	5.42	33.21	321	53	A	H	
			2484.04	51.54	-22.46	74	51.8	27.46	5.46	33.18	321	53	P	H
			2483.8	41.29	-12.71	54	41.55	27.46	5.46	33.18	321	53	A	H
			2374.35	50.91	-23.09	74	51.57	27.19	5.39	33.24	151	55	P	V
			2358.33	40.67	-13.33	54	41.45	27.14	5.33	33.25	151	55	A	V
	*		2437	103.85	-	-	104.27	27.37	5.42	33.21	151	55	P	V
	*		2437	100.61	-	-	101.03	27.37	5.42	33.21	151	55	A	V
			2498.6	51.7	-22.3	74	51.91	27.5	5.46	33.17	151	55	P	V
			2483.52	41.11	-12.89	54	41.37	27.46	5.46	33.18	151	55	A	V



<b>802.11b</b> <b>CH 11</b> <b>2462MHz</b>	*	2462	101.88	-	-	102.23	27.41	5.44	33.2	279	351	P	H
	*	2462	98.64	-	-	98.99	27.41	5.44	33.2	279	351	A	H
		2497.56	52.48	-21.52	74	52.69	27.5	5.46	33.17	279	351	P	H
		2483.88	41.38	-12.62	54	41.64	27.46	5.46	33.18	279	351	A	H
													H
													H
	*	2462	103.3	-	-	103.65	27.41	5.44	33.2	100	58	P	V
	*	2462	100.07	-	-	100.42	27.41	5.44	33.2	100	58	A	V
		2487	52	-22	74	52.26	27.46	5.46	33.18	100	58	P	V
		2484.32	41.44	-12.56	54	41.7	27.46	5.46	33.18	100	58	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11b CH 01 2412MHz		4824	47.45	-26.55	74	69.02	31.46	7.58	60.61	100	0	P	H	
													H	
													H	
													H	
			4824	50.77	-23.23	74	72.34	31.46	7.58	60.61	100	0	P	V
														V
														V
802.11b CH 06 2437MHz		4872	44.98	-29.02	74	66.24	31.56	7.7	60.52	100	0	P	H	
		7309	40.82	-33.18	74	56.08	36.18	9.49	60.93	100	0	P	H	
													H	
													H	
			4872	48.24	-25.76	74	69.5	31.56	7.7	60.52	100	0	P	V
			7309	39.55	-34.45	74	54.81	36.18	9.49	60.93	100	0	P	V
														V
802.11b CH 11 2462MHz		4926	46.5	-27.5	74	67.33	31.66	7.93	60.42	100	0	P	H	
		7386	39.88	-34.12	74	55.17	36.37	9.53	61.19	100	0	P	H	
													H	
													H	
			4926	49.65	-24.35	74	70.48	31.66	7.93	60.42	100	0	P	V
			7386	39.8	-34.2	74	55.09	36.37	9.53	61.19	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz  
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11g CH 01 2412MHz		2389.74	51.24	-22.76	74	51.86	27.23	5.39	33.24	330	55	P	H	
		2389.92	41.86	-12.14	54	42.46	27.23	5.39	33.22	330	55	A	H	
	*	2412	101.93	-	-	102.45	27.28	5.42	33.22	330	55	P	H	
	*	2412	94.17	-	-	94.69	27.28	5.42	33.22	330	55	A	H	
													H	
													H	
			2326.38	51.45	-22.55	74	52.33	27.05	5.33	33.26	125	60	P	V
			2389.83	41.32	-12.68	54	41.92	27.23	5.39	33.22	125	60	A	V
	*		2412	99.53	-	-	100.05	27.28	5.42	33.22	125	60	P	V
	*		2412	91.82	-	-	92.34	27.28	5.42	33.22	125	60	A	V
													V	
													V	
802.11g CH 06 2437MHz		2353.83	52.02	-21.98	74	52.8	27.14	5.33	33.25	320	45	P	H	
		2385.06	41.19	-12.81	54	41.85	27.19	5.39	33.24	320	45	A	H	
	*	2437	101.55	-	-	101.97	27.37	5.42	33.21	320	45	P	H	
	*	2437	93.87	-	-	94.29	27.37	5.42	33.21	320	45	A	H	
			2499.6	51.83	-22.17	74	52.04	27.5	5.46	33.17	320	45	P	H
			2483.56	41.92	-12.08	54	42.18	27.46	5.46	33.18	320	45	A	H
			2357.16	51.25	-22.75	74	52.03	27.14	5.33	33.25	105	58	P	V
			2376.69	40.94	-13.06	54	41.6	27.19	5.39	33.24	105	58	A	V
	*		2437	100.48	-	-	100.9	27.37	5.42	33.21	105	58	P	V
	*		2437	92.75	-	-	93.17	27.37	5.42	33.21	105	58	A	V
			2486.68	51.17	-22.83	74	51.43	27.46	5.46	33.18	105	58	P	V
			2484.12	41.58	-12.42	54	41.84	27.46	5.46	33.18	105	58	A	V



<b>802.11g</b> <b>CH 11</b> <b>2462MHz</b>	*	2462	102.18	-	-	102.53	27.41	5.44	33.2	315	50	P	H
	*	2462	94.49	-	-	94.84	27.41	5.44	33.2	315	50	A	H
		2483.8	56.54	-17.46	74	56.8	27.46	5.46	33.18	315	50	P	H
		2483.68	44.34	-9.66	54	44.6	27.46	5.46	33.18	315	50	A	H
													H
													H
	*	2462	99.59	-	-	99.94	27.41	5.44	33.2	360	356	P	V
	*	2462	91.92	-	-	92.27	27.41	5.44	33.2	360	356	A	V
		2483.52	57.25	-16.75	74	57.51	27.46	5.46	33.18	360	356	P	V
		2483.56	43.13	-10.87	54	43.39	27.46	5.46	33.18	360	356	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11g CH 01 2412MHz		4824	39.19	-34.81	74	60.76	31.46	7.58	60.61	100	0	P	H	
													H	
													H	
													H	
			4822	41.75	-32.25	74	63.32	31.46	7.58	60.61	100	0	P	V
														V
														V
802.11g CH 06 2437MHz		4872	37.64	-36.36	74	58.9	31.56	7.7	60.52	100	0	P	H	
		7309	39.08	-34.92	74	54.34	36.18	9.49	60.93	100	0	P	H	
													H	
													H	
			4872	38.43	-35.57	74	59.69	31.56	7.7	60.52	100	0	P	V
			7309	39.97	-34.03	74	55.23	36.18	9.49	60.93	100	0	P	V
														V
802.11g CH 11 2462MHz		4926	36.7	-37.3	74	57.53	31.66	7.93	60.42	100	0	P	H	
		7386	39.47	-34.53	74	54.76	36.37	9.53	61.19	100	0	P	H	
													H	
													H	
			4926	38.33	-35.67	74	59.16	31.66	7.93	60.42	100	0	P	V
			7386	40.62	-33.38	74	55.91	36.37	9.53	61.19	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 01 2412MHz		2389.65	50.76	-23.24	74	51.38	27.23	5.39	33.24	300	50	P	H	
		2390	41.21	-12.79	54	41.81	27.23	5.39	33.22	300	50	A	H	
	*	2412	100.05	-	-	100.57	27.28	5.42	33.22	300	50	P	H	
	*	2412	92.15	-	-	92.67	27.28	5.42	33.22	300	50	A	H	
													H	
														H
			2361.84	50.9	-23.1	74	51.68	27.14	5.33	33.25	123	57	P	V
			2389.92	41.28	-12.72	54	41.88	27.23	5.39	33.22	123	57	A	V
		*	2412	97.9	-	-	98.42	27.28	5.42	33.22	123	57	P	V
		*	2412	90.16	-	-	90.68	27.28	5.42	33.22	123	57	A	V
													V	
													V	
802.11n HT20 CH 06 2437MHz		2389.02	52.09	-21.91	74	52.71	27.23	5.39	33.24	322	59	P	H	
		2388.12	41.17	-12.83	54	41.79	27.23	5.39	33.24	322	59	A	H	
	*	2437	100.68	-	-	101.1	27.37	5.42	33.21	322	59	P	H	
	*	2437	91.82	-	-	92.24	27.37	5.42	33.21	322	59	A	H	
			2496.68	51.43	-22.57	74	51.64	27.5	5.46	33.17	322	59	P	H
			2486	41.76	-12.24	54	42.02	27.46	5.46	33.18	322	59	A	H
			2333.85	51.09	-22.91	74	51.97	27.05	5.33	33.26	100	59	P	V
			2364.54	41.15	-12.85	54	41.86	27.14	5.39	33.24	100	59	A	V
		*	2437	99.06	-	-	99.48	27.37	5.42	33.21	100	59	P	V
		*	2437	91.25	-	-	91.67	27.37	5.42	33.21	100	59	A	V
		2485.44	51.4	-22.6	74	51.66	27.46	5.46	33.18	100	59	P	V	
		2487.24	41.69	-12.31	54	41.95	27.46	5.46	33.18	100	59	A	V	



<b>802.11n HT20 CH 11 2462MHz</b>	*	2462	100.04	-	-	100.39	27.41	5.44	33.2	315	52	P	H
	*	2462	92.32	-	-	92.67	27.41	5.44	33.2	315	52	A	H
		2483.76	55.09	-18.91	74	55.35	27.46	5.46	33.18	315	52	P	H
		2483.56	43.12	-10.88	54	43.38	27.46	5.46	33.18	315	52	A	H
													H
													H
	*	2462	98.01	-	-	98.36	27.41	5.44	33.2	100	60	P	V
	*	2462	90.31	-	-	90.66	27.41	5.44	33.2	100	60	A	V
		2484.28	53.93	-20.07	74	54.19	27.46	5.46	33.18	100	60	P	V
		2483.92	42.93	-11.07	54	43.19	27.46	5.46	33.18	100	60	A	V
												V	
												V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
802.11n HT20 CH 01 2412MHz		4824	34.97	-39.03	74	56.54	31.46	7.58	60.61	100	0	P	H	
													H	
													H	
													H	
			4824	38.32	-35.68	74	59.89	31.46	7.58	60.61	100	0	P	V
														V
														V
802.11n HT20 CH 06 2437MHz		4874	33.94	-40.06	74	55.2	31.56	7.7	60.52	100	0	P	H	
		7311	39.96	-34.04	74	55.22	36.18	9.49	60.93	100	0	P	H	
													H	
													H	
			4874	35	-39	74	56.26	31.56	7.7	60.52	100	0	P	V
			7311	40.15	-33.85	74	55.41	36.18	9.49	60.93	100	0	P	V
														V
802.11n HT20 CH 11 2462MHz		4924	35.4	-38.6	74	56.23	31.66	7.93	60.42	100	0	P	H	
		7386	39.88	-34.12	74	55.17	36.37	9.53	61.19	100	0	P	H	
													H	
													H	
			4924	36.29	-37.71	74	57.12	31.66	7.93	60.42	100	0	P	V
			7386	39.3	-34.7	74	54.59	36.37	9.53	61.19	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



**2.4GHz 2400~2483.5MHz  
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 03 2422MHz		2371.92	50.79	-23.21	74	51.45	27.19	5.39	33.24	323	57	P	H
		2333.49	41.84	-12.16	54	42.72	27.05	5.33	33.26	323	57	A	H
	*	2422	97.22	-	-	97.69	27.32	5.42	33.21	323	57	P	H
	*	2422	89.8	-	-	90.27	27.32	5.42	33.21	323	57	A	H
		2485.4	51.96	-22.04	74	52.22	27.46	5.46	33.18	323	57	P	H
		2484.56	42.78	-11.22	54	43.04	27.46	5.46	33.18	323	57	A	H
		2332.77	51.58	-22.42	74	52.46	27.05	5.33	33.26	108	58	P	V
		2327.73	41.81	-12.19	54	42.69	27.05	5.33	33.26	108	58	A	V
	*	2422	95.32	-	-	95.79	27.32	5.42	33.21	108	58	P	V
	*	2422	87.75	-	-	88.22	27.32	5.42	33.21	108	58	A	V
		2485.96	51.21	-22.79	74	51.47	27.46	5.46	33.18	108	58	P	V
		2485.4	42.65	-11.35	54	42.91	27.46	5.46	33.18	108	58	A	V
802.11n HT40 CH 06 2437MHz		2388.03	51.36	-22.64	74	51.98	27.23	5.39	33.24	320	51	P	H
		2358.87	42.05	-11.95	54	42.83	27.14	5.33	33.25	320	51	A	H
	*	2437	96.84	-	-	97.26	27.37	5.42	33.21	320	51	P	H
	*	2437	89.53	-	-	89.95	27.37	5.42	33.21	320	51	A	H
		2484.52	51.37	-22.63	74	51.63	27.46	5.46	33.18	320	51	P	H
		2483.56	43.53	-10.47	54	43.79	27.46	5.46	33.18	320	51	A	H
		2362.83	51.17	-22.83	74	51.95	27.14	5.33	33.25	100	58	P	V
		2381.55	42.19	-11.81	54	42.85	27.19	5.39	33.24	100	58	A	V
	*	2437	95.75	-	-	96.17	27.37	5.42	33.21	100	58	P	V
	*	2437	87.84	-	-	88.26	27.37	5.42	33.21	100	58	A	V
		2485.48	52.26	-21.74	74	52.52	27.46	5.46	33.18	100	58	P	V
		2483.8	42.85	-11.15	54	43.11	27.46	5.46	33.18	100	58	A	V





<b>802.11n</b>  <b>HT40</b>  <b>CH 09</b>  <b>2452MHz</b>		2324.49	51.07	-22.93	74	51.95	27.05	5.33	33.26	311	45	P	H
		2360.49	41.9	-12.1	54	42.68	27.14	5.33	33.25	311	45	A	H
	*	2452	96.96	-	-	97.35	27.37	5.44	33.2	311	45	P	H
	*	2452	89.46	-	-	89.85	27.37	5.44	33.2	311	45	A	H
		2484.08	59.01	-14.99	74	59.27	27.46	5.46	33.18	311	45	P	H
		2483.6	48.44	-5.56	54	48.7	27.46	5.46	33.18	311	45	A	H
		2386.68	50.85	-23.15	74	51.47	27.23	5.39	33.24	100	57	P	V
		2384.34	41.87	-12.13	54	42.53	27.19	5.39	33.24	100	57	A	V
	*	2452	95.93	-	-	96.32	27.37	5.44	33.2	100	57	P	V
	*	2452	88.23	-	-	88.62	27.37	5.44	33.2	100	57	A	V
		2483.68	58.04	-15.96	74	58.3	27.46	5.46	33.18	100	57	P	V
		2483.64	46.24	-7.76	54	46.5	27.46	5.46	33.18	100	57	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 03 2422MHz		4844	33.66	-40.34	74	55.05	31.49	7.7	60.58	100	0	P	H
		7266	39.32	-34.68	74	54.58	36.11	9.46	60.83	100	0	P	H
													H
													H
		4844	34.49	-39.51	74	55.88	31.49	7.7	60.58	100	0	P	V
		7266	39.65	-34.35	74	54.91	36.11	9.46	60.83	100	0	P	V
													V
													V
802.11n HT40 CH 06 2437MHz		4874	34.72	-39.28	74	55.98	31.56	7.7	60.52	100	0	P	H
		7311	38.78	-35.22	74	54.04	36.18	9.49	60.93	100	0	P	H
													H
													H
		4874	35.2	-38.8	74	56.46	31.56	7.7	60.52	100	0	P	V
		7311	39.89	-34.11	74	55.15	36.18	9.49	60.93	100	0	P	V
													V
													V
802.11n HT40 CH 09 2452MHz		4904	35.29	-38.71	74	56.3	31.63	7.82	60.46	100	0	P	H
		7356	39.89	-34.11	74	55.17	36.3	9.51	61.09	100	0	P	H
													H
													H
		4904	36.32	-37.68	74	57.33	31.63	7.82	60.46	100	0	P	V
		7356	39.93	-34.07	74	55.21	36.3	9.51	61.09	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz 802.11n HT40 LF		31.08	23.16	-16.84	40	29.79	25.54	0.65	32.82	-	-	P	H	
		162.03	20.95	-22.55	43.5	35.47	16.84	1.33	32.69	-	-	P	H	
		277.86	19.17	-26.83	46	30.82	19.32	1.76	32.73	-	-	P	H	
		601	26.37	-19.63	46	31.32	25.51	2.57	33.03	-	-	P	H	
		744.5	29.1	-16.9	46	31.75	27.38	2.91	32.94	-	-	P	H	
		941.9	31.52	-14.48	46	30.28	29.8	3.29	31.85	100	25	P	H	
														H
														H
														H
														H
														H
														H
			59.16	32.12	-7.88	40	51.62	12.32	0.93	32.75	100	57	P	V
			162.03	21.32	-22.18	43.5	35.84	16.84	1.33	32.69	-	-	P	V
			260.85	19.05	-26.95	46	30.26	19.76	1.76	32.73	-	-	P	V
			384	25.9	-20.1	46	34.57	22.02	2.13	32.82	-	-	P	V
			536.6	25.58	-20.42	46	31.65	24.42	2.47	32.96	-	-	P	V
			941.9	31.32	-14.68	46	30.08	29.8	3.29	31.85	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- 1. Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- 2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- 1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- 2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- 1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- 2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



## Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Tsung Lee and Donny Tang	Temperature :	23~25°C
		Relative Humidity :	45~48%





### Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 9</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 9</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 9</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 9</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : IO</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : IO</p>
Avg.	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : IO</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : IO</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : IO</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : IO</p>
Avg.	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:0.300KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : IO</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:0.300KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : IO</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak	<p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 11</p>	<p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 11</p>
Avg.	<p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:0.300KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 11</p>	<p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:0.300KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 11</p>







2.4GHz 2400~2483.5MHz





WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 630110-01 Mode : 12</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 630110-01 Mode : 12</p>
Avg.	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 630110-01 Mode : 12</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 630110-01 Mode : 12</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 13</p>	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 13</p>
Avg.	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 13</p>	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 13</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 13</p>	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 13</p>
Avg.	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 13</p>	 <p>Date: 2016-05-27</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 13</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 14</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 14</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 14</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 14</p>







2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 15</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 15</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 15</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 15</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 16</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 16</p>
Avg.	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 16</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 16</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 16</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 16</p>
Avg.	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 16</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:1.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 16</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 17</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 17</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 17</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:1000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 17</p>







2.4GHz 2400~2483.5MHz





WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 18</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 18</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 18</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 18</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 18</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 18</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 18</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 18</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>
Avg.	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 19</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1	Horizontal	Vertical
Peak	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 20</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 20</p>
Avg.	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 20</p>	 <p>Date: 2016-05-28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 630110-01            Mode : 20</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1	Horizontal	Vertical
Peak	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 20</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 20</p>
Avg.	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 20</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 630110-01            Mode : 20</p>







**2.4GHz 2400~2483.5MHz**



**WIFI 802.11b (Harmonic @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 9</p>	 <p>Site : 03CH10-VY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL            Detector : Peak            Project : 630110-01            Mode : 9</p>



WIFI	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
ANT	<b>802.11b CH06 2437MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH10-HY          Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL          Detector : Peak          Project : 630110-01          Mode : 10</p>	 <p>Site : 03CH10-HY          Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL          Detector : Peak          Project : 630110-01          Mode : 10</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH10-HY          Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL          Detector : Peak          Project : 630110-01          Mode : 11</p>	 <p>Site : 03CH10-HY          Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL          Detector : Peak          Project : 630110-01          Mode : 11</p>





**2.4GHz 2400~2483.5MHz**

**WIFI 802.11g (Harmonic @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
<b>Peak</b>  <b>Avg.</b>	<p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 12</p>	<p>Site : 03CH10-VY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL            Detector : Peak            Project : 630110-01            Mode : 12</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH10-HY  Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL  Detector : Peak  Project : 630110-01  Mode : 13</p>	 <p>Site : 03CH10-HY  Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL  Detector : Peak  Project : 630110-01  Mode : 13</p>





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak Project : 630110-01 Mode : 14</p>	<p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL Detector : Peak Project : 630110-01 Mode : 14</p>





2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak Project : 630110-01 Mode : 15</p>	 <p>Site : 03CH10-VY Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL Detector : Peak Project : 630110-01 Mode : 15</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak Project : 630110-01 Mode : 16</p>	 <p>Site : 03CH10-HY Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL Detector : Peak Project : 630110-01 Mode : 16</p>







WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 17</p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL            Detector : Peak            Project : 630110-01            Mode : 17</p>





**2.4GHz 2400~2483.5MHz**



**WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH03 2422MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 1B</p>	 <p>Site : 03CH10-VY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL            Detector : Peak            Project : 630110-01            Mode : 1B</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH06 2437MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Date: 2016.05.28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL            Detector : Peak            Project : 630110-01            Mode : 19</p>	 <p>Date: 2016.05.28</p> <p>Site : 03CH10-HY            Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL            Detector : Peak            Project : 630110-01            Mode : 19</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH09 2452MHz	
1	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	 <p>Site : 03CH10-HY          Condition : FCC CLASS-B 3m HORN_9170_406_0584 HORIZONTAL          Detector : Peak          Project : 630110-01          Mode : 20</p>	 <p>Site : 03CH10-HY          Condition : FCC CLASS-B 3m HORN_9170_406_0584 VERTICAL          Detector : Peak          Project : 630110-01          Mode : 20</p>



2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT40 LF	
1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH10-1Y Condition : FCC CLASS-B 3m BI-LOG 6111D-LF HORIZONTAL Detector : Peak Project : 630110-01 Mode : Z1</p>	<p>Site : 03CH10-1Y Condition : FCC CLASS-B 3m BI-LOG 6111D-LF VERTICAL Detector : Peak Project : 630110-01 Mode : Z1</p>




## Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
802.11b	97.14	8160	0.12	300Hz
802.11g	86.08	1360	0.74	1kHz
2.4GHz 802.11n HT20	86.49	1280	0.78	1kHz
2.4GHz 802.11n HT40	75.45	630	1.59	3kHz




802.11b



Date: 9.MAY.2016 16:08:16


802.11g



Date: 9.MAY.2016 16:14:16




802.11n HT20



Date: 9.MAY.2016 16:22:59

802.11n HT20



Date: 12.MAY.2016 17:09:43