

Bullitt Group

No. 4, The Aquarium, King Street, Reading, RG1 2AN, United Kingdom

Tel: +44 118 958 0449

Date: April 18, 2018

Federal Communications Commission
Office of Engineering and Technology Laboratory Division
7435 Oakland Mills Rd
Columbia MD 21046-1609


SUBJECT: FCC Application for FCC ID: ZL5S61

To Whom It May Concern:

We hereby attest that, LTE release 10 limitations and support restrictions of FCC ID: ZL5S61 are:

- a) LTE Rel 11 TS 36.521-1V 11.2.0
- b) Downlink and Uplink Carrier Aggregation (CA) are supported.
 - Downlink supported inter-band and intra-band CA. Uplink only supported intra-band CA.
 - Up to a maximum of 3 DL carriers paired with single UL carrier
 - Support CA Bandwidth Class A, B and C.
 - Max aggregate bandwidth supported is 60 MHz
- c) Power reduction applied when uplink CA supported.
- d) Power setting varied in different BW, modulation, RB allocation, channels with CA.
- e) Enhanced SC-FDMA is not supported.
- f) LTE uplink MIMO and other transmit diversity is not supported
- g) UE category Downlink Category 12/Uplink Category 13
- h) SON, EICIC are supported
- i) Wi-Fi 802.11 a/b/g/n/ac; Bluetooth v5.0 with LE, NFC transmitters are contained in this device.

Sincerely yours,



Wayne Huang
whuang@bullitt-group.com