


EMC TEST REPORT



Report No.: 17070605-FCC-E

Supersede Report No: N/A

Applicant	Power Idea Technology (Shenzhen) Co., Ltd.	
Product Name	GSM Digital Mobile Phone	
Model No.	RG129	
Serial No.	N/A	
Test Standard	FCC Part 15 Subpart B Class B:2016, ANSI C63.4: 2014	
Test Date	July 21 to August 23, 2017	
Issue Date	August 24, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
<i>Evans He</i>	<i>David Huang</i>	
Evans He Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070605-FCC-E
Page	3 of 36

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 AC POWER LINE CONDUCTED EMISSIONS.....	9
6.2 RADIATED EMISSIONS.....	15
ANNEX A. TEST INSTRUMENT.....	20
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	21
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	32
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	35
ANNEX E. DECLARATION OF SIMILARITY.....	36

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070605-FCC-E	NONE	Original	August 24, 2017

2. Customer information

Applicant Name	Power Idea Technology (Shenzhen) Co., Ltd.
Applicant Add	4th Floor, A Section , Languang Science&technology Building , No.7 Xinxi RD , Hi-Tech Industrial Park North , Nanshan District , ShenZhen , P.R.C.
Manufacturer	Power Idea Technology (Shenzhen) Co., Ltd.
Manufacturer Add	4th Floor, A Section , Languang Science&technology Building , No.7 Xinxi RD , Hi-Tech Industrial Park North , Nanshan District , ShenZhen , P.R.C.

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	GSM Digital Mobile Phone
Main Model:	RG129
Serial Model:	N/A
Antenna Gain:	GSM850: -2.02dBi PCS1900: -0.11dBi Bluetooth: -2.12dBi
Antenna Type:	GSM: PIFA antenna BT: Monopole antenna
Input Power:	Adapter: Model: STC-A22O501500USBA-Z Input: AC100-240V~50/60Hz,200mA Output: DC 5.0V,500mA Battery Model: BL100EI (ICP5/34/53) Spec: 3.7V/800mAh(2.96Wh) Limited charge voltage: 4.2V
Equipment Category :	JBP
Type of Modulation:	GSM / GPRS: GMSK Bluetooth: GFSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH Bluetooth: 79CH
Port:	USB Port, Earphone Port



Test Report	17070605-FCC-E
Page	7 of 36

Trade Name : N/A

FCC ID: ZLE-RG129

Date EUT received: July 20, 2017

Test Date(s): July 21 to August 23, 2017

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2014	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2014	Radiated Emissions	Compliance

Measurement Uncertainty

Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	±3.11dB
Radiated Emission(30MHz~1GHz)	±5.12dB
Radiated Emission(1GHz~6GHz)	±5.34dB


6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1005mbar
Test date :	August 01, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.107	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBµV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dBµV)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															

Test Setup	 <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	---

Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50Ω /50mH EUT LISN, connected to filtered mains.
-----------	--


Test Report	17070605-FCC-E
Page	10 of 36

	<ol style="list-style-type: none"> 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode :	USB Mode
--------------------	-----------------




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2787	23.59	QP	10.03	33.62	60.85	-27.23
2	L1	0.2787	5.15	AVG	10.03	15.18	50.85	-35.67
3	L1	0.5556	19.82	QP	10.03	29.85	56.00	-26.15
4	L1	0.5556	5.68	AVG	10.03	15.71	46.00	-30.29
5	L1	0.9807	19.69	QP	10.03	29.72	56.00	-26.28
6	L1	0.9807	12.11	AVG	10.03	22.14	46.00	-23.86
7	L1	2.7942	14.38	QP	10.05	24.43	56.00	-31.57
8	L1	2.7942	-1.20	AVG	10.05	8.85	46.00	-37.15
9	L1	12.9294	8.25	QP	10.19	18.44	60.00	-41.56
10	L1	12.9294	-2.14	AVG	10.19	8.05	50.00	-41.95
11	L1	21.6615	11.45	QP	10.33	21.78	60.00	-38.22
12	L1	21.6615	6.85	AVG	10.33	17.18	50.00	-32.82

Test Mode:	USB Mode
-------------------	-----------------




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1734	23.52	QP	10.02	33.54	64.80	-31.26
2	N	0.1734	-0.57	AVG	10.02	9.45	54.80	-45.35
3	N	0.2709	20.97	QP	10.02	30.99	61.09	-30.10
4	N	0.2709	13.40	AVG	10.02	23.42	51.09	-27.67
5	N	0.5556	18.33	QP	10.02	28.35	56.00	-27.65
6	N	0.5556	6.75	AVG	10.02	16.77	46.00	-29.23
7	N	0.7857	13.62	QP	10.03	23.65	56.00	-32.35
8	N	0.7857	3.47	AVG	10.03	13.50	46.00	-32.50
9	N	2.8098	13.41	QP	10.05	23.46	56.00	-32.54
10	N	2.8098	1.45	AVG	10.05	11.50	46.00	-34.50
11	N	21.6654	10.40	QP	10.29	20.69	60.00	-39.31
12	N	21.6654	6.44	AVG	10.29	16.73	50.00	-33.27

Test Mode :	USB Mode
--------------------	-----------------




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.5595	22.86	QP	10.03	32.89	56.00	-23.11
2	L1	0.5595	5.40	AVG	10.03	15.43	46.00	-30.57
3	L1	0.9807	18.58	QP	10.03	28.61	56.00	-27.39
4	L1	0.9807	9.15	AVG	10.03	19.18	46.00	-26.82
5	L1	1.1328	13.41	QP	10.03	23.44	56.00	-32.56
6	L1	1.1328	0.98	AVG	10.03	11.01	46.00	-34.99
7	L1	4.1388	14.60	QP	10.07	24.67	56.00	-31.33
8	L1	4.1388	-0.11	AVG	10.07	9.96	46.00	-36.04
9	L1	4.8369	12.88	QP	10.08	22.96	56.00	-33.04
10	L1	4.8369	0.58	AVG	10.08	10.66	46.00	-35.34
11	L1	19.1694	22.15	QP	10.29	32.44	60.00	-27.56
12	L1	19.1694	4.03	AVG	10.29	14.32	50.00	-35.68

Test Mode :	USB Mode
-------------	----------



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.1734	28.70	QP	10.02	38.72	64.80	-26.08
2	N	0.1734	3.78	AVG	10.02	13.80	54.80	-41.00
3	N	0.5673	22.30	QP	10.02	32.32	56.00	-23.68
4	N	0.5673	13.98	AVG	10.02	24.00	46.00	-22.00
5	N	0.9144	19.49	QP	10.03	29.52	56.00	-26.48
6	N	0.9144	11.10	AVG	10.03	21.13	46.00	-24.87
7	N	2.8176	18.89	QP	10.05	28.94	56.00	-27.06
8	N	2.8176	3.88	AVG	10.05	13.93	46.00	-32.07
9	N	3.9906	17.84	QP	10.06	27.90	56.00	-28.10
10	N	3.9906	4.20	AVG	10.06	14.26	46.00	-31.74
11	N	21.6654	9.96	QP	10.29	20.25	60.00	-39.75
12	N	21.6654	5.10	AVG	10.29	15.39	50.00	-34.61

6.2 Radiated Emissions

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1005mbar
Test date :	August 01, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.109(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	<input checked="" type="checkbox"/>										
		<table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength ($\mu\text{V/m}$)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 - 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>		Frequency range (MHz)	Field Strength ($\mu\text{V/m}$)	30 – 88	100	88 – 216	150	216 - 960	200	Above 960	500
		Frequency range (MHz)		Field Strength ($\mu\text{V/m}$)									
		30 – 88		100									
		88 – 216		150									
216 - 960	200												
Above 960	500												



Procedure	<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarization (whichever gave the higher emission level
-----------	---


	<p>over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <ul style="list-style-type: none"> ■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%) <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode :	USB Mode
-------------	----------

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	H	59.8588	49.71	QP	7.32	22.41	0.75	35.37	40.00	-4.63	100	164
2	H	131.7577	46.79	QP	13.14	22.39	1.21	38.75	43.50	-4.75	100	340
3	H	180.0165	50.10	QP	11.00	22.25	1.36	40.21	43.50	-3.29	100	114
4	H	276.1236	51.25	QP	12.55	22.29	1.75	43.26	46.00	-2.74	100	205
5	H	504.7062	44.39	QP	17.77	21.80	2.43	42.79	46.00	-3.21	100	321
6	H	827.4934	35.92	peak	21.70	21.08	2.91	39.45	46.00	-6.55	100	40

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	71.5806	49.04	QP	7.77	22.39	0.97	35.39	40.00	-4.61	100	330
2	V	132.2206	48.16	QP	13.11	22.39	1.22	40.10	43.50	-3.40	100	222
3	V	185.7882	50.11	QP	11.32	22.29	1.46	40.60	43.50	-2.90	100	154
4	V	276.1236	49.04	QP	12.55	22.29	1.75	41.05	46.00	-4.95	100	12
5	V	420.5803	43.72	peak	16.11	21.97	2.06	39.92	46.00	-6.08	100	193
6	V	833.3171	34.35	peak	21.77	21.06	2.90	37.96	46.00	-8.04	100	232

Above 1GHz

Frequency (MHz)	Read_level (dB μ V/m)	Azimuth	Height (cm)	Polarity (H/V)	Level (dB μ V/m)	Factors (dB)	Limit (dB μ V/m)	Margin (dB)	Detector (PK/AV)
1405.2	67.23	157	100	V	-18.97	48.26	74	-25.74	PK
1763.5	61.36	36	100	V	-16.74	44.62	74	-29.38	PK
2238.9	61.96	119	100	V	-14.35	47.61	74	-26.39	PK
1834.2	66.7	249	100	H	-16.39	50.31	74	-23.69	PK
2064.8	64.98	103	100	H	-14.7	50.28	74	-23.72	PK
2531.7	61.87	335	100	H	-13.52	48.35	74	-25.65	PK

*Note1: The highest frequency of the EUT is 2480 MHz, so the testing has been conformed to 5*2480MHz =12,400MHz.*

Note2: The frequency that above 3GHz is mainly from the environment noise.

Note3: The AV measurement performed, more than 20dB below limit so AV test data was not presented.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance Stabilization Network	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance Stabilization Network	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Label View




EUT - Front View




EUT - Rear View




EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Mainboard with Shielding – Rear View




Mainboard without Shielding – Rear View



LCD – Front View




LCD – Rear View




GSM/PCS Antenna View




BT - Antenna View




Annex B.iii. Photograph: Test Setup Photo



Conducted Emissions Test Setup – Front View



Conducted Emissions Test Setup – Side View



Radiated Emissions Test Setup Below 1GHz




Radiated Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
GOLDWEB	Router	R102	1202032094
Lenovo	AC Adapter	42T4416	21D9JU
HP	Printer	VCVRA-1003	CN36M19JWX
DELL	Mouse	E100	912NMTUT41481
BULL	Socket	GN-403	GN201203
Power Idea Technology (Shenzhen) Co., Ltd.	Earphone	RG129	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	2m	JX120051274
USB Cable	Un-shielding	No	2m	CBA3000AH0C1
RJ45 Cable	Un-shielding	No	2m	KX156327541
Router Power cable	Un-shielding	No	2m	13274630Z
Printer Power cable	Un-shielding	No	2m	127581031
Power Cable	Un-shielding	No	0.8m	GT211032

Test Report	17070605-FCC-E
Page	35 of 36

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	17070605-FCC-E
Page	36 of 36

Annex E. DECLARATION OF SIMILARITY

N/A