

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505	21.94	0.1	22.04	159.96	2
21100	2535	22	0.1	22.1	162.18	2
21400	2565	21.91	0.1	22.01	158.85	2

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	23.94	0.1	24.04	253.51	2
21100	2535.0	23.99	0.1	24.09	256.45	2
21375	2562.5	23.75	0.1	23.85	242.66	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	22.87	0.1	22.97	198.15	2
21100	2535.0	22.82	0.1	22.92	195.88	2
21375	2562.5	22.84	0.1	22.94	196.79	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	22.01	0.1	22.11	162.55	2
21100	2535	21.98	0.1	22.08	161.44	2
21375	2562.5	21.94	0.1	22.04	159.96	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	23.95	0.1	24.05	254.1	2
21100	2535.0	24.01	0.1	24.11	257.63	2
21350	2560.0	23.83	0.1	23.93	247.17	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	22.89	0.1	22.99	199.07	2
21100	2535.0	22.9	0.1	23	199.53	2
21350	2560.0	22.85	0.1	22.95	197.24	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510	22.02	0.1	22.12	162.93	2
21100	2535	22.04	0.1	22.14	163.68	2
21350	2560	21.96	0.1	22.06	160.69	2



BUREAU
VERITAS

Test Report No.: W7L-P22110001RF06

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23017	699.7	22.39	-3.5	16.74	47.21	3
23095	707.5	22.15	-3.5	16.5	44.67	3
23173	715.3	22.35	-3.5	16.7	46.77	3

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23017	699.7	21.58	-3.5	15.93	39.17	3
23095	707.5	21.23	-3.5	15.58	36.14	3
23173	715.3	21.55	-3.5	15.9	38.9	3

CHANNEL BANDWIDTH: 1.4MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23017	699.7	20.16	-3.5	14.51	28.25	3
23095	707.5	19.98	-3.5	14.33	27.1	3
23173	715.3	20.14	-3.5	14.49	28.12	3

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23025	700.5	22.41	-3.5	16.76	47.42	3
23095	707.5	22.17	-3.5	16.52	44.87	3
23165	714.5	22.34	-3.5	16.69	46.67	3

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23025	700.5	21.61	-3.5	15.96	39.45	3
23095	707.5	21.23	-3.5	15.58	36.14	3
23165	714.5	21.55	-3.5	15.9	38.9	3

CHANNEL BANDWIDTH: 3MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23025	700.5	20.17	-3.5	14.52	28.31	3
23095	707.5	19.92	-3.5	14.27	26.73	3
23165	714.5	20.08	-3.5	14.43	27.73	3

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23035	701.5	22.42	-3.5	16.77	47.53	3
23095	707.5	22.12	-3.5	16.47	44.36	3
23155	713.5	22.35	-3.5	16.7	46.77	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23035	701.5	21.61	-3.5	15.96	39.45	3
23095	707.5	21.23	-3.5	15.58	36.14	3
23155	713.5	21.54	-3.5	15.89	38.82	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23035	701.5	20.11	-3.5	14.46	27.93	3
23095	707.5	19.89	-3.5	14.24	26.55	3
23155	713.5	20.14	-3.5	14.49	28.12	3



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23060	704	22.47	-3.5	16.82	48.08	3
23095	707.5	22.19	-3.5	16.54	45.08	3
23130	711	22.4	-3.5	16.75	47.32	3

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23060	704	21.63	-3.5	15.98	39.63	3
23095	707.5	21.31	-3.5	15.66	36.81	3
23130	711	21.56	-3.5	15.91	38.99	3

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23060	704	20.18	-3.5	14.53	28.38	3
23095	707.5	19.94	-3.5	14.29	26.85	3
23130	711	20.16	-3.5	14.51	28.25	3

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

LTE BAND 13

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	21.29	-3.5	15.64	36.64	3
23230	782	21.33	-3.5	15.68	36.98	3
23255	784.5	21.32	-3.5	15.67	36.9	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	20.43	-3.5	14.78	30.06	3
23230	782	20.41	-3.5	14.76	29.92	3
23255	784.5	20.43	-3.5	14.78	30.06	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	19.59	-3.5	13.94	24.77	3
23230	782	19.56	-3.5	13.91	24.6	3
23255	784.5	19.56	-3.5	13.91	24.6	3



Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	21.37	-3.5	15.72	37.33	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	20.49	-3.5	14.84	30.48	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	19.61	-3.5	13.96	24.89	3
-	-	-	-	-	-	-

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).



Test Report No.: W7L-P22110001RF06

LTE BAND 17

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23755	706.5	22.23	-3.5	16.58	45.5	3
23790	710	22.18	-3.5	16.53	44.98	3
23825	713.5	22.37	-3.5	16.72	46.99	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23755	706.5	21.32	-3.5	15.67	36.9	3
23790	710	21.33	-3.5	15.68	36.98	3
23825	713.5	21.5	-3.5	15.85	38.46	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23755	706.5	20.17	-3.5	14.52	28.31	3
23790	710	20.12	-3.5	14.47	27.99	3
23825	713.5	20.17	-3.5	14.52	28.31	3

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23780	709	22.27	-3.5	16.62	45.92	3
23790	710	22.23	-3.5	16.58	45.5	3
23800	711	22.38	-3.5	16.73	47.1	3

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23780	709	21.39	-3.5	15.74	37.5	3
23790	710	21.38	-3.5	15.73	37.41	3
23800	711	21.52	-3.5	15.87	38.64	3

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23780	709	20.21	-3.5	14.56	28.58	3
23790	710	20.17	-3.5	14.52	28.31	3
23800	711	20.25	-3.5	14.6	28.84	3

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

LTE BAND 38

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37775	2572.5	23.3	0.1	23.4	218.78	2
38000	2595.0	23.43	0.1	23.53	225.42	2
38225	2617.5	23.51	0.1	23.61	229.61	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37775	2572.5	22.43	0.1	22.53	179.06	2
38000	2595.0	22.59	0.1	22.69	185.78	2
38225	2617.5	22.61	0.1	22.71	186.64	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37775	2572.5	21.12	0.1	21.22	132.43	2
38000	2595	21.18	0.1	21.28	134.28	2
38225	2617.5	21.21	0.1	21.31	135.21	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37800	2575.0	23.31	0.1	23.41	219.28	2
38000	2595.0	23.39	0.1	23.49	223.36	2
38200	2615.0	23.54	0.1	23.64	231.21	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37800	2575.0	22.42	0.1	22.52	178.65	2
38000	2595.0	22.56	0.1	22.66	184.5	2
38200	2615.0	22.64	0.1	22.74	187.93	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37800	2575	21.1	0.1	21.2	131.83	2
38000	2595	21.21	0.1	21.31	135.21	2
38200	2615	21.2	0.1	21.3	134.9	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37825	2577.5	23.32	0.1	23.42	219.79	2
38000	2595.0	23.36	0.1	23.46	221.82	2
38175	2612.5	23.54	0.1	23.64	231.21	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37825	2577.5	22.41	0.1	22.51	178.24	2
38000	2595.0	22.57	0.1	22.67	184.93	2
38175	2612.5	22.61	0.1	22.71	186.64	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37825	2577.5	21.15	0.1	21.25	133.35	2
38000	2595	21.21	0.1	21.31	135.21	2
38175	2612.5	21.21	0.1	21.31	135.21	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37850	2580.0	23.38	0.1	23.48	222.84	2
38000	2595.0	23.44	0.1	23.54	225.94	2
38150	2610.0	23.56	0.1	23.66	232.27	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37850	2580.0	22.49	0.1	22.59	181.55	2
38000	2595.0	22.61	0.1	22.71	186.64	2
38150	2610.0	22.66	0.1	22.76	188.8	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
37850	2580	21.16	0.1	21.26	133.66	2
38000	2595	21.23	0.1	21.33	135.83	2
38150	2610	21.23	0.1	21.33	135.83	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

LTE BAND 41

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39675	2498.5	22.92	0.1	23.02	200.45	2
40620	2593.0	23.07	0.1	23.17	207.49	2
41565	2687.5	23.05	0.1	23.15	206.54	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39675	2498.5	22.02	0.1	22.12	162.93	2
40620	2593.0	22.2	0.1	22.3	169.82	2
41565	2687.5	22.22	0.1	22.32	170.61	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39675	2498.5	20.74	0.1	20.84	121.34	2
40620	2593.0	20.86	0.1	20.96	124.74	2
41565	2687.5	20.91	0.1	21.01	126.18	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39700	2501.0	22.92	0.1	23.02	200.45	2
40620	2593.0	23.04	0.1	23.14	206.06	2
41540	2685.0	23.1	0.1	23.2	208.93	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39700	2501.0	22.07	0.1	22.17	164.82	2
40620	2593.0	22.23	0.1	22.33	171	2
41540	2685.0	22.21	0.1	22.31	170.22	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39700	2501.0	20.79	0.1	20.89	122.74	2
40620	2593.0	20.9	0.1	21	125.89	2
41540	2685.0	20.86	0.1	20.96	124.74	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39725	2503.5	22.95	0.1	23.05	201.84	2
40620	2593.0	23.04	0.1	23.14	206.06	2
41515	2682.5	23.1	0.1	23.2	208.93	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39725	2503.5	22.06	0.1	22.16	164.44	2
40620	2593.0	22.23	0.1	22.33	171	2
41515	2682.5	22.18	0.1	22.28	169.04	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39725	2503.5	20.8	0.1	20.9	123.03	2
40620	2593.0	20.87	0.1	20.97	125.03	2
41515	2682.5	20.91	0.1	21.01	126.18	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39750	2506.0	22.97	0.1	23.07	202.77	2
40620	2593.0	23.08	0.1	23.18	207.97	2
41490	2680.0	23.12	0.1	23.22	209.89	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39750	2506.0	22.1	0.1	22.2	165.96	2
40620	2593.0	22.25	0.1	22.35	171.79	2
41490	2680.0	22.23	0.1	22.33	171	2

CHANNEL BANDWIDTH: 20 MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
39750	2506.0	20.82	0.1	20.92	123.59	2
40620	2593.0	20.92	0.1	21.02	126.47	2
41490	2680.0	20.92	0.1	21.02	126.47	2

LTE BAND 66

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131979	1710.7	23.7	-1.5	22.2	165.96	1
132322	1745	24	-1.5	22.5	177.83	1
132665	1779.3	23.85	-1.5	22.35	171.79	1

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131979	1710.7	22.73	-1.5	21.23	132.74	1
132322	1745	23	-1.5	21.5	141.25	1
132665	1779.3	22.91	-1.5	21.41	138.36	1

CHANNEL BANDWIDTH: 1.4MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131979	1710.7	21.71	-1.5	20.21	104.95	1
132322	1745	21.94	-1.5	20.44	110.66	1
132665	1779.3	21.81	-1.5	20.31	107.4	1

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131987	1711.5	23.72	-1.5	22.22	166.72	1
132322	1745	23.99	-1.5	22.49	177.42	1
132657	1778.5	23.89	-1.5	22.39	173.38	1

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131987	1711.5	22.76	-1.5	21.26	133.66	1
132322	1745	22.99	-1.5	21.49	140.93	1
132657	1778.5	22.95	-1.5	21.45	139.64	1

CHANNEL BANDWIDTH: 3MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131987	1711.5	21.77	-1.5	20.27	106.41	1
132322	1745	21.97	-1.5	20.47	111.43	1
132657	1778.5	21.75	-1.5	20.25	105.93	1

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131997	1712.5	23.73	-1.5	22.23	167.11	1
132322	1745	23.97	-1.5	22.47	176.6	1
132647	1777.5	23.85	-1.5	22.35	171.79	1

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131997	1712.5	22.71	-1.5	21.21	132.13	1
132322	1745	23.02	-1.5	21.52	141.91	1
132647	1777.5	22.94	-1.5	21.44	139.32	1

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
131997	1712.5	21.71	-1.5	20.21	104.95	1
132322	1745	21.94	-1.5	20.44	110.66	1
132647	1777.5	21.81	-1.5	20.31	107.4	1

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132022	1715	23.75	-1.5	22.25	167.88	1
132322	1745	23.98	-1.5	22.48	177.01	1
132622	1775	23.88	-1.5	22.38	172.98	1

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132022	1715	22.71	-1.5	21.21	132.13	1
132322	1745	22.99	-1.5	21.49	140.93	1
132622	1775	22.9	-1.5	21.4	138.04	1

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132022	1715	21.7	-1.5	20.2	104.71	1
132322	1745	21.95	-1.5	20.45	110.92	1
132622	1775	21.78	-1.5	20.28	106.66	1

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132047	1717.5	23.72	-1.5	22.22	166.72	1
132322	1745	24.02	-1.5	22.52	178.65	1
132597	1772.5	23.84	-1.5	22.34	171.4	1

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132047	1715	22.7	-1.5	21.2	131.83	1
132322	1745	23.06	-1.5	21.56	143.22	1
132622	1775	22.94	-1.5	21.44	139.32	1

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132047	1715	21.77	-1.5	20.27	106.41	1
132322	1745	21.97	-1.5	20.47	111.43	1
132622	1775	21.75	-1.5	20.25	105.93	1

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132072	1720	23.78	-1.5	22.28	169.04	1
132322	1745	24.04	-1.5	22.54	179.47	1
132572	1770	23.9	-1.5	22.4	173.78	1

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132072	1720	22.78	-1.5	21.28	134.28	1
132322	1745	23.07	-1.5	21.57	143.55	1
132572	1770	22.96	-1.5	21.46	139.96	1

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
132072	1720	21.78	-1.5	20.28	106.66	1
132322	1745	21.99	-1.5	20.49	111.94	1
132572	1770	21.83	-1.5	20.33	107.89	1

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





Test Report No.: W7L-P22110001RF06

3.2.4 TEST RESULTS


Please Refer to Appendix Of this test report.

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.



Test Report No.: W7L-P22110001RF06

3.3.4 TEST RESULTS

Please Refer to Appendix Of this test report.

3.4 BAND EDGE MEASUREMENT

3.4.1 LIMITS OF BAND EDGE MEASUREMENT


According to FCC 27.53(c) specified that For operations in the 746-758 MHz band and the 776-788 MHz band , the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emission in a 6.25kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, $P(\text{dBW})$, by at least $65 + 10 \log 10p(P)$, dB, for mobile and portable equipment.

According to FCC 27.53(g) specified that For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

According to FCC 27.53(h) specified that For operations in the 1710-1755 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

According to FCC 27.53(m)(4) specified that For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. For mobile digital stations, in the 1 megahertz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed.

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 10kHz and VBW of the spectrum is 30kHz (LTE bandwidth for (1.4M/3M/5M/10M/15M/20M)1RB/0RB&1RB/MAXRB).
- c. The center frequency of spectrum is the band edge frequency and span is 2MHz. RBW of the spectrum is 51kHz and VBW of the spectrum is 150kHz (WCDMA).
- d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is $\geq 1\% \cdot \text{EBW}$ kHz and VBW of the spectrum is $3 \cdot \text{RBW}$ kHz. (LTE bandwidth 1.4M/3M/5M/10M/15M/20MHz).
- e. Record the max trace plot into the test report.



Test Report No.: W7L-P22110001RF06

3.4.4 TEST RESULTS

Please Refer to Appendix Of this test report.

3.5 CONDUCTED SPURIOUS EMISSIONS

3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .


For: LTE Band7

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -25dBm .

3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9kHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP





**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

3.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix Of this test report.



3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

For: LTE Band7/ Band41

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -25dBm .

3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G.
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$.


NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

3.6.3 DEVIATION FROM TEST STANDARD


No deviation

3.6.4 TEST SETUP


< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



3.6.5 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

LTE Band 13

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	56.198	-64.74	-46.66	-13.00	-51.74	-18.08	Peak	Horizontal
2	94.020	-64.71	-43.46	-13.00	-51.71	-21.25	Peak	Horizontal
3 PP	156.100	-57.32	-40.20	-13.00	-44.32	-17.12	Peak	Horizontal
4	195.870	-59.72	-41.73	-13.00	-46.72	-17.99	Peak	Horizontal
5	226.910	-61.96	-47.75	-13.00	-48.96	-14.21	Peak	Horizontal
6	335.550	-67.56	-55.96	-13.00	-54.56	-11.60	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	33.880	-65.04	-45.28	-13.00	-52.04	-19.76	Peak	Vertical
2 PP	99.840	-50.58	-44.07	-13.00	-37.58	-6.51	Peak	Vertical
3	156.100	-57.62	-40.27	-13.00	-44.62	-17.35	Peak	Vertical
4	242.430	-70.86	-56.59	-13.00	-57.86	-14.27	Peak	Vertical
5	334.580	-67.93	-57.74	-13.00	-54.93	-10.19	Peak	Vertical
6	421.880	-65.07	-56.27	-13.00	-52.07	-8.80	Peak	Vertical





BUREAU VERITAS

Test Report No.: W7L-P22110001RF06

ABOVE 1GHz


Note: For higher frequency, the emission is too low to be detected.

WCDMA Band IV:

CH 1312

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3424.800	-50.96	-58.18	-13.00	-37.96	7.22	Peak	Horizontal
2 PP	5134.000	-46.72	-56.62	-13.00	-33.72	9.90	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3418.000	-50.66	-57.85	-13.00	-37.66	7.19	Peak	Vertical
2 PP	5137.200	-47.00	-57.39	-13.00	-34.00	10.39	Peak	Vertical






Test Report No.: W7L-P22110001RF06

CH 1413

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3470.000	-50.79	-58.07	-13.00	-37.79	7.28	Peak	Horizontal
2 PP	5197.800	-46.39	-56.39	-13.00	-33.39	10.00	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3465.200	-52.22	-59.48	-13.00	-39.22	7.26	Peak	Vertical
2	PP 5186.000	-47.77	-58.21	-13.00	-34.77	10.44	Peak	Vertical






Test Report No.: W7L-P22110001RF06

CH 1513

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3496.000	-51.40	-58.72	-13.00	-38.40	7.32	Peak	Horizontal
2 PP	5264.000	-46.55	-56.65	-13.00	-33.55	10.10	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3505.200	-51.25	-58.58	-13.00	-38.25	7.33	Peak	Vertical
2	PP 5264.000	-47.63	-58.14	-13.00	-34.63	10.51	Peak	Vertical






Test Report No.: W7L-P22110001RF06

LTE Band 7
 CHANNEL BANDWIDTH: 5MHz / QPSK
 CH 21100

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5882.000	-50.42	-60.24	-25.00	-25.42	9.82	Peak	Horizontal
2	7605.000	-50.05	-62.23	-25.00	-25.05	12.18	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5070.000	-50.07	-60.40	-25.00	-25.07	10.33	Peak	Vertical
2 PP	7604.000	-49.93	-64.78	-25.00	-24.93	14.85	Peak	Vertical






Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 10MHz / QPSK
CH21100

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5082.000	-50.31	-60.13	-25.00	-25.31	9.82	Peak	Horizontal
2	7605.000	-52.27	-64.45	-25.00	-27.27	12.18	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5070.000	-49.52	-59.85	-25.00	-24.52	10.33	Peak	Vertical
2	PP 7604.000	-49.05	-63.90	-25.00	-24.05	14.85	Peak	Vertical






BUREAU VERITAS

Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5070.000	-49.84	-59.64	-25.00	-24.84	9.80	Peak	Horizontal
2	7604.000	-50.76	-62.93	-25.00	-25.76	12.17	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	Pol/Phase
1 PP 5056.000	-49.59	-59.91	-25.00	-24.59	10.32	Peak Vertical
2 7605.000	-49.87	-64.72	-25.00	-24.87	14.85	Peak Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

**CHANNEL BANDWIDTH: 20MHz / QPSK
CH20850**

MODE	TX channel 20850	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5030.000	-49.65	-59.39	-25.00	-24.65	9.74	Peak	Horizontal
2	7530.000	-53.18	-64.81	-25.00	-28.18	11.63	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 20850	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5020.000	-49.46	-59.75	-25.00	-24.46	10.29	Peak	Vertical
2 PP	7526.000	-47.68	-62.42	-25.00	-22.68	14.74	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CH21100

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5070.000	-50.26	-60.06	-25.00	-25.26	9.80	Peak	Horizontal
2	7604.000	-51.87	-64.04	-25.00	-26.87	12.17	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

MODE	TX channel 21100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5882.000	-49.74	-60.08	-25.00	-24.74	10.34	Peak	Vertical
2	PP 7605.000	-49.02	-63.87	-25.00	-24.02	14.85	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CH21350

MODE	TX channel 21350	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5108.000	-50.26	-60.12	-25.00	-25.26	9.86	Peak	Horizontal
2	7680.000	-51.29	-64.01	-25.00	-26.29	12.72	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 21350	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5108.000	-48.76	-59.13	-25.00	-23.76	10.37	Peak	Vertical
2	7680.000	-49.52	-64.48	-25.00	-24.52	14.96	Peak	Vertical





**BUREAU
VERITAS**


Test Report No.: W7L-P22110001RF06

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1416.000	-57.52	-56.88	-13.00	-44.52	-0.64	Peak	Horizontal
2	PP 2122.500	-55.17	-59.23	-13.00	-42.17	4.06	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1415.000	-57.46	-57.05	-13.00	-44.46	-0.41	Peak	Vertical
2	PP 2118.000	-54.24	-58.14	-13.00	-41.24	3.90	Peak	Vertical





BUREAU VERITAS


Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 3MHz / QPSK

CH23095

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1415.000	-47.10	-46.45	-13.00	-34.10	-0.65	Peak	Horizontal
2 PP	2118.000	-46.52	-50.57	-13.00	-33.52	4.05	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-49.60	-49.20	-13.00	-36.60	-0.40	Peak	Vertical
2	2122.500	-51.52	-55.44	-13.00	-38.52	3.92	Peak	Vertical






Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1416.000	-50.25	-49.61	-13.00	-37.25	-0.64	Peak	Horizontal
2 PP	2122.500	-47.69	-51.75	-13.00	-34.69	4.06	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1415.000	-50.47	-50.06	-13.00	-37.47	-0.41	Peak	Vertical
2	2118.000	-52.37	-56.27	-13.00	-39.37	3.90	Peak	Vertical






Test Report No.: W7L-P22110001RF06

CHANNEL BANDWIDTH: 10MHz / QPSK

CH23060

MODE	TX channel 23060	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1408.000	-51.92	-51.26	-13.00	-38.92	-0.66	Peak	Horizontal
2	2118.000	-53.63	-57.68	-13.00	-40.63	4.05	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 23060	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1416.000	-53.53	-53.13	-13.00	-40.53	-0.40	Peak	Vertical
2	PP 2112.000	-52.50	-56.39	-13.00	-39.50	3.89	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CH23095

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1415.000	-44.80	-44.15	-13.00	-31.80	-0.65	Peak	Horizontal
2 PP	2118.000	-37.23	-41.28	-13.00	-24.23	4.05	Peak	Horizontal






Test Report No.: W7L-P22110001RF06

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1416.000	-46.96	-46.56	-13.00	-33.96	-0.40	Peak	Vertical
2	PP 2122.500	-41.38	-45.30	-13.00	-28.38	3.92	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P22110001RF06

CH23130

MODE	TX channel 23130	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-53.06	-52.42	-13.00	-40.06	-0.64	Peak	Horizontal
2	2133.000	-54.22	-58.32	-13.00	-41.22	4.10	Peak	Horizontal





Test Report No.: W7L-P22110001RF06

MODE	TX channel 23130	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1422.000	-54.38	-54.00	-13.00	-41.38	-0.38	Peak	Vertical
2 PP	2144.000	-54.23	-58.20	-13.00	-41.23	3.97	Peak	Vertical

