

# RADIO TEST REPORT

## (FCC Part 15 Subpart C)



Applicant:	Power Idea Technology (Shenzhen) Co., Ltd.
Address:	4th Floor, A Section, Languang Science&technology Building, No.7 Xinxi RD, Hi-Tech Industrial Park North, Nanshan District, ShenZhen, P.R.C.

Manufacturer:	Power Idea Technology (Shenzhen) Co., Ltd.
Address:	4th Floor, A Section, Languang Science&technology Building, No.7 Xinxi RD, Hi-Tech Industrial Park North, Nanshan District, ShenZhen, P.R.C.
Product:	Smart Phone
Brand Name:	RugGear
Model Name:	PSM03G
Marketing name :	RG880
FCC ID:	ZLE-RG880
Date of tests:	Dec. 20, 2023 ~Mar. 20, 2024

The tests have been carried out according to the requirements of the following standard:

- Part 15 Subpart C §15. 225
- RSS-Gen Issue 5, Amendment 2 (February 2021)
- ANSI C63.10-2020

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
	
Date: Mar. 20, 2024	Date: Mar. 20, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL DESCRIPTION.....</b>	<b>6</b>
1.1	GENERAL DESCRIPTION OF EUT.....	6
1.2	MODIFICATION OF EUT .....	7
1.3	APPLICABLE STANDARDS .....	7
<b>2</b>	<b>TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
2.1	DESCRIPTIONS OF TEST MODE.....	8
2.2	TEST CONFIGURATIONS .....	9
2.3	SUPPORT EQUIPMENT .....	10
2.4	TEST SETUP.....	10
2.5	MEASUREMENT RESULTS EXPLANATION EXAMPLE.....	12
<b>3</b>	<b>TEST RESULT .....</b>	<b>13</b>
3.1	20DB AND 99% BANDWIDTH MEASUREMENT .....	13
3.1.1	LIMIT OF 20DB AND 99% BANDWIDTH.....	13
3.1.2	TEST PROCEDURES .....	13
3.1.3	TEST RESULT OF 20DB AND 99% BANDWIDTH .....	14
3.2	FREQUENCY STABILITY MEASUREMENT .....	16
3.2.1	LIMIT OF FREQUENCY STABILITY .....	16
3.2.2	TEST PROCEDURES .....	16
3.2.3	TEST RESULT OF FREQUENCY STABILITY .....	16
3.3	FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK MEASUREMENT .....	18
3.3.1	LIMIT OF FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK .....	18
3.3.2	TEST PROCEDURES .....	18
3.3.3	TEST RESULTS OF FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK (1.705 MHZ ~ 30 MHZ) .....	19
3.4	RADIATED EMISSIONS MEASUREMENT .....	20
3.4.1	LIMIT .....	20
3.4.2	MEASURING INSTRUMENT SETTING .....	20
3.4.3	TEST PROCEDURES .....	20
3.4.4	TEST RESULTS OF RADIATED EMISSIONS (9 KHZ ~ 30 MHZ).....	22
3.4.5	TEST RESULT OF RADIATED SPURIOUS EMISSION (30MHZ ~ 1GHZ) .....	24
3.5	AC CONDUCTED EMISSION MEASUREMENT .....	26
3.5.1	LIMIT OF AC CONDUCTED EMISSION .....	26
3.5.2	TEST PROCEDURES .....	26
3.5.3	TEST RESULT OF AC CONDUCTED EMISSION .....	27
3.6	ANTENNA REQUIREMENTS .....	29
3.6.1	STANDARD APPLICABLE.....	29
3.6.2	ANTENNA CONNECTED CONSTRUCTION .....	29



**BUREAU  
VERITAS**

**Test Report No.: PSU-QSU2312200110RF10**

3.6.3	ANTENNA GAIN .....	29
<b>4</b>	<b>LIST OF MEASURING EQUIPMENT .....</b>	<b>30</b>
<b>5</b>	<b>UNCERTAINTY OF EVALUATION.....</b>	<b>31</b>



Test Report No.: PSU-QSU2312200110RF10

## REPORT REVISE RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QSU2312200110RF10	Original release	Mar. 20, 2024

## SUMMARY OF TEST RESULT

FCC Rule	IC Rule	Description	Limit	Result	Remark
-	RSS-Gen 6.7	99% Bandwidth	-	Pass	-
15.225(a)(b)(c)	RSS-210 Annex B.6	Field Strength of Fundamental Emissions	15.225(a)(b)(c) RSS-210 Annex B.6	Pass	-
15.215	-	20dB Spectrum Bandwidth	15.215	Pass	-
15.225(d) 15.209	RSS-210 Annex B.6	Radiated Emission	15.225(d) & 15.209 RSS-210 Annex B.6	Pass	-
15.207	RSS-GEN 8.8	AC Conducted Emission	15.207(a)	Note	
15.225(e)	Annex B.6	Frequency Stability	< ±100 ppm	Pass	-
15.203	RSS-Gen 6.8	Antenna Requirement	N/A	Pass	-

### \*Test Lab Information Reference

**Lab A:**

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

**Lab Address:**

Tower N, Innovation Center, 88 Zhuyi Road, High-tech District, Suzhou City, Anhui Province

**Accredited Test Lab Cert 6613.01**

The FCC Site Registration No. is 434559; The Designation No. is CN1325.

# 1 GENERAL DESCRIPTION

## 1.1 GENERAL DESCRIPTION OF EUT

Items	Description
<b>Tx/Rx Frequency Range</b>	13.553MHz ~ 13.567MHz
<b>Channel Number</b>	1
<b>20dBW</b>	5.181 kHz
<b>99%OBW</b>	18.929 kHz
<b>Antenna Type</b>	LOOP Antenna
<b>Type of Modulation</b>	ASK
<b>HW Version</b>	MP619_MB_V1.02_PCB
<b>SW Version (FVIN)</b>	RG880_EEA_00.00_1_20240305

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

**NOTE:** Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.

### List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
CPU	QUALCOMM	N/A	SM6225	N/A
eMMC 1 (=ROM 1)	SAMSUNG	N/A	KM2L9001CM-B518	N/A
eMMC 2 (=ROM 2)	Hynix	N/A	H9QT0GECN6X145R	N/A
RAM 1	N/A	N/A	N/A	N/A
RAM 2	N/A	N/A	N/A	N/A
BT/WLAN Module	N/A	N/A	N/A	N/A
NFC chipset	NXP	N/A	N/A	N/A
Battery	N/A	N/A	BL450AGP	Power Rating: 4.4V 4500mAh
Adapter	N/A	SHENZHEN MERRYKING ELECTRONICS CO.. LTD	MK-Q181US	I/P: 100-240Vac, 50/60Hz, 0.5A, O/P:5.0V 3.0A or 9.0V 2.0A or 12.0V 1.5A
USB Cable	N/A	Huizhou Huating Technology Co., Ltd	USB1.0	Signal Line,1.0meter

## 1.2 MODIFICATION OF EUT

No modifications are made to the EUT during all test items.

## 1.3 APPLICABLE STANDARDS

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2020
- ♦ RSS-210 Issue 10
- ♦ RSS-Gen Issue 5

## 2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST

### 2.1 DESCRIPTIONS OF TEST MODE

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.


Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz
<p><b>Note:</b></p> <ol style="list-style-type: none"> <li>The EUT was programmed to be in continuously transmitting mode.</li> <li>The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.</li> <li>Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, work in modes and data rates. Selected for the final test as listed below.</li> </ol>	

Frequency	Work in Modes	Type	Data Rate (Kbps)
13.56 MHz	<input type="checkbox"/> Card Emulation <input checked="" type="checkbox"/> Reader/Writer <input type="checkbox"/> Peer-to-Peer	<input type="checkbox"/> A <input type="checkbox"/> B <input checked="" type="checkbox"/> F <input type="checkbox"/> V	<input type="checkbox"/> 106 <input checked="" type="checkbox"/> 212 <input type="checkbox"/> 424 <input type="checkbox"/> 848
<p><b>Remark:</b></p> <p>The mark "<input checked="" type="checkbox"/> " means is chosen for testing;          The mark "<input type="checkbox"/> " means is not chosen for testing.</p>			





## 2.2 TEST CONFIGURATIONS

### <AC Conducted Emissions>



### < For Fundamental Emissions and Mask and Radiated Emissions Measurement >



\* Kept in a remote area

## 2.3 SUPPORT EQUIPMENT


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A	N/A	N/A	N/A	N/A

## 2.4 TEST SETUP


The EUT is continuously communicating during the tests.

EUT was set in the Hidden menu mode to enable NFC communications.

### Setup diagram for Conducted Test




### Setup diagram for Radiation(9KHz~30MHz) Test





Setup diagram for Radiation(Below 1G) Test



## 2.5 MEASUREMENT RESULTS EXPLANATION EXAMPLE

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

### Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5 + 10 = 15 \text{ (dB)} \end{aligned}$$

### 3 TEST RESULT

#### 3.1 20DB AND 99% BANDWIDTH MEASUREMENT

##### 3.1.1 LIMIT OF 20DB AND 99% BANDWIDTH

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


##### 3.1.2 TEST PROCEDURES

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used. (Since the signal being measured is CW or CW-like, it is impractical to adjust RBW according to C63.10 because the bandwidth measured will always follow RBW and the result will be approximately twice as large as RBW.)
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

### 3.1.3 TEST RESULT OF 20DB AND 99% BANDWIDTH

Test Mode :	NFC	Temperature :	23°C	
Test Engineer :	Hanwen Xu	Relative Humidity :	50%	
<b>Mode</b>	<b>Frequency</b>	<b>20dB Bandwidth [kHz]</b>	<b>99% OBW[kHz]</b>	<b>Verdict</b>
NFC Type F_212 Kbps	13.56MHz	5.181	18.929	PASS


#### 20dB Bandwidth & 99% Bandwidth Plot





BUREAU VERITAS

Test Report No.: PSU-QSU2312200110RF10



NFC Type  
F\_  
212 Kbps

## 3.2 FREQUENCY STABILITY MEASUREMENT

### 3.2.1 LIMIT OF FREQUENCY STABILITY

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 3.2.2 TEST PROCEDURES

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c - f) / f_c \times 10^6$  ppm and the limit is less than  $\pm 100$ ppm.
6. Extreme temperature rule is -20°C~50°C.

### 3.2.3 TEST RESULT OF FREQUENCY STABILITY

The NFC Type F\_212 Kbps is the worst case, Only report worst mode data





NFC Type F\_212 Kbps

Voltage (Vdc)	Temperature (°C)	Measurement Frequency (MHz)	Frequency Tolerance(ppm)	Limit(ppm)	Result
10.2	20	13.55996	-0.72	±100	Pass
13.8		13.56024	20.64		Pass
12	-20	13.56012	10.35		Pass
	-10	13.56030	22.85		Pass
	0	13.55978	-17.73		Pass
	10	13.55984	-13.26		Pass
	20	13.56002	0.76		Pass
	30	13.55992	-7.36		Pass
	40	13.55975	-16.24		Pass
50	13.5603	7.36	Pass		

### 3.3 FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK MEASUREMENT

#### 3.3.1 LIMIT OF FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK

Rules and specifications	FCC CFR 47 Part 15 section 15.225 IC RSS-210 B.6			
	Description			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength ( $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 10m	Field Strength (dB $\mu$ V/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

#### 3.3.2 TEST PROCEDURES

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.

Note: Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).



### 3.3.3 TEST RESULTS OF FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK (1.705 MHz ~ 30 MHz)

<b>Test Mode :</b>	NFC (13.56 MHz)	<b>Temperature :</b>	23°C
<b>Test Engineer :</b>	Hanwen Xu	<b>Relative Humidity :</b>	50%
<b>Frequency Range</b>	13.11MHz~14.01MHz	<b>Polarization :</b>	Horizontal



Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+: QPK Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	13.560	39.01	124.00	84.99	20.26	H	160.6	1.00

## 3.4 RADIATED EMISSIONS MEASUREMENT

### 3.4.1 LIMIT

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 3.4.2 MEASURING INSTRUMENT SETTING

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

### 3.4.3 TEST PROCEDURES


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the

turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.

5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.

### 3.4.4 TEST RESULTS OF RADIATED EMISSIONS (9 KHZ ~ 30 MHZ)

<b>Test Mode :</b>	NFC (13.56 MHz)	<b>Temperature :</b>	23°C
<b>Test Engineer :</b>	Hanwen Xu	<b>Relative Humidity :</b>	50%
<b>Frequency Range</b>	9 KHz ~ 30 MHz	<b>Polarization :</b>	Horizontal




Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+: QPK Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	0.037	53.67	116.24	62.57	20.52	H	4.9	1.00
1	0.077	30.65	109.87	79.22	20.52	H	1	1.00
1	0.116	34.03	106.32	72.29	20.41	H	4.9	1.00
2	0.636	30.82	71.54	40.71	20.31	H	1	1.00
2	6.666	30.87	69.54	38.67	20.29	H	358.8	1.00
2	13.560	36.72	69.54	32.82	20.26	H	1	1.00



**BUREAU  
VERITAS**

**Test Report No.: PSU-QSU2312200110RF10**

<b>Test Mode :</b>	NFC (13.56 MHz)	<b>Temperature :</b>	23°C
<b>Test Engineer :</b>	Hanwen Xu	<b>Relative Humidity :</b>	50%
<b>Frequency Range</b>	9 KHz ~ 30 MHz	<b>Polarization :</b>	Vertical




Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+: QPK Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	0.030	48.53	118.06	69.53	20.48	V	5	1.00
1	0.059	35.95	112.19	76.24	20.56	V	359.1	1.00
1	0.125	26.14	105.67	79.52	20.41	V	5	1.00
2	1.113	31.67	66.67	35.01	20.45	V	358.9	1.00
2	6.891	30.85	69.54	38.69	20.32	V	1	1.00
2	13.560	40.59	69.54	28.95	20.26	V	359.1	1.00



### 3.4.5 TEST RESULT OF RADIATED SPURIOUS EMISSION (30MHZ ~ 1GHZ)

Test Mode :	NFC (13.56MHz)	Temperature :	23°C
Test Engineer :	Hanwen Xu	Relative Humidity :	50%
Frequency Range	30MHz~1GHz	Polarization :	Horizontal



Rg	Frequency [MHz]	QPK Level [dBµV/m]	QPK Limit [dBµV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	53.368	22.06	40.00	17.94	-9.71	H	355	2.00	120.000
1	100.105	20.56	43.50	22.94	-11.83	H	90.5	2.00	120.000
1	175.059	23.46	43.50	20.04	-13.74	H	90.5	2.00	120.000
1	291.768	26.15	46.00	19.85	-6.87	H	133.1	1.00	120.000
1	575.669	22.37	46.00	23.63	-3.17	H	269.4	1.00	120.000
1	746.433	24.68	46.00	21.32	-0.49	H	358.7	1.00	120.000






**BUREAU  
VERITAS**

**Test Report No.: PSU-QSU2312200110RF10**

<b>Test Mode :</b>	NFC (13.56MHz)	<b>Temperature :</b>	23°C
<b>Test Engineer :</b>	Hanwen Xu	<b>Relative Humidity :</b>	50%
<b>Frequency Range</b>	30MHz~1GHz	<b>Polarization :</b>	Vertical



Rg	Frequency [MHz]	QPK Level [dBµV/m]	QPK Limit [dBµV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	47.725	21.50	40.00	18.50	-10.47	V	92.8	2.00	120.000
1	96.621	16.78	43.50	26.72	-12.48	V	269.4	1.00	120.000
1	137.538	13.34	43.50	30.16	-14.41	V	0.9	2.00	120.000
1	252.130	15.10	46.00	30.90	-9.01	V	92.8	2.00	120.000
1	393.794	18.21	46.00	27.79	-3.36	V	0.9	2.00	120.000
1	534.488	20.25	46.00	25.75	-3.37	V	0.9	2.00	120.000

## 3.5 AC CONDUCTED EMISSION MEASUREMENT

### 3.5.1 LIMIT OF AC CONDUCTED EMISSION

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 3.5.2 TEST PROCEDURES

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.5.3 TEST RESULT OF AC CONDUCTED EMISSION

<b>Test Mode :</b>	NFC	<b>Temperature :</b>	26°C
<b>Test Engineer :</b>	Hanwen Xu	<b>Relative Humidity :</b>	51%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Line
<b>Function Type :</b>	NFC		




Rg	Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.429	50.06	57.27	7.21	40.31	47.27	6.96	11.76	L1	9.000
1	0.816	48.33	56.00	7.67	40.50	46.00	5.50	11.74	L1	9.000
1	1.802	45.05	56.00	10.95	37.91	46.00	8.09	11.76	L1	9.000
1	2.886	43.74	56.00	12.26	35.92	46.00	10.08	11.77	L1	9.000
1	5.334	41.11	60.00	18.89	33.20	50.00	16.80	11.79	L1	9.000
1	20.765	26.11	60.00	33.89	19.36	50.00	30.64	11.88	L1	9.000



BUREAU VERITAS

Test Report No.: PSU-QSU2312200110RF10

Test Mode :	NFC	Temperature :	26°C
Test Engineer :	Hanwen Xu	Relative Humidity :	51%
Test Voltage :	AC 120V/60Hz	Phase :	Neutral
Function Type :	NFC		



Rg	Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.177	50.58	64.63	14.05	43.81	54.63	10.82	12.22	N	9.000
1	0.524	42.32	56.00	13.68	30.80	46.00	15.20	12.77	N	9.000
1	0.816	41.93	56.00	14.07	30.39	46.00	15.61	12.74	N	9.000
1	4.025	36.06	56.00	19.94	24.91	46.00	21.09	12.75	N	9.000
1	7.328	33.37	60.00	26.63	24.28	50.00	25.72	12.78	N	9.000
1	25.386	24.01	60.00	35.99	12.91	50.00	37.09	12.87	N	9.000

## **3.6 ANTENNA REQUIREMENTS**

### **3.6.1 STANDARD APPLICABLE**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

### **3.6.2 ANTENNA CONNECTED CONSTRUCTION**

A LOOP Antenna design is used.

### **3.6.3 ANTENNA GAIN**

The antenna peak gain of EUT is less than 6 dBi.



## 4 LIST OF MEASURING EQUIPMENT

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
WIDEBANDRADIO COMMUNICATION TESTER	Rohde&Schwarz	CMW500	169399	Jun.27,22	Jun.26,24
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC- 02Chamber	Nov.24,22	Nov.23,25
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.28,22	Feb.27,24
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.27,24	Feb.26,26
Loop Antenna	R&S	HFH2-Z2/Z2 E	100976	Feb.23,22	Feb.22,24
Loop Antenna	R&S	HFH2-Z2/Z2 E	100976	Feb.24,24	Feb.23,26
Antenna Power Supply	RS	N/A	N/A	N/A	N/A
EMI Test Receiver	R&S	ESW44	101973	Feb.25,22	Feb.24,24
EMI Test Receiver	R&S	ESW44	101973	Feb.24,24	Feb.23,26
Measurement Software	R&S	ELEKTRA	N/A	N/A	N/A
Pre-Amplifier	R&S	SCU08F1	101028	Sep.16,22	Sep.15,24
CABLE	R&S	W13.01	N/A	Apr.28,23	Apr.27,24
CABLE	R&S	W13.02	N/A	Apr.28,23	Apr.27,24
CABLE	R&S	W12.14	N/A	Apr.28,23	Apr.27,24


- NOTE:**
1. The calibration interval of the above test instruments is 12/ 24/ 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Chamber.
  3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.

## 5 UNCERTAINTY OF EVALUATION

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Frequency Stability	$\pm 76.97\text{Hz}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

-----End of the report-----