Applicant/Grantee Fibocom Wireless Inc. /ZMO									
FCC ID: ZMOFG190WNA									
Section 15.212 Modular Transmitters									
Request for Modular Approval Request for Limited Modular Approval									
<u> </u>		Requirement		EUT Conditions	Comply (Y/N)				
Single Modular Approval Requirements									
1	The radio elements of the modular			The radio portion of this module is	Y				
	transmitter must have their own			shielded, please see exhibition external					
	shielding. The physical crystal and		ystal and	photos.					
	tuning capacitors may be located								
	external to the shielded radio elements.								
2	The modular transmitter must have			The module has buffer modulation/data	Y				
	buffered modulation/data inputs (if such			inputs.					
	inputs are provided) to ensure that the								
		comply with							
		s under condit							
	excessive data rates or over-modulation.								
3	The modular	transmitter n	nust have its	The module has its own power supply	Y				
	own power s	upply regulat	ion.	regulation. Please see the schem.pdf					
4	The modular	transmitter n	nust comply	The requirements of antenna connector	Y				
	with the ante	nna and trans	mission	and spurious emission have been					
	system requi	rements of Se	ections 15.203,	fulfilled. Please refer to the Test Report					
	15.204(b) an	d 15.204(c).	Γhe antenna	exhibition.					
	must either b	e permanentl	y attached or						
	employ a "ur	nique" antenn	a coupler (at						
	all connectio	ns between th	e module and						
		including the							
	-	l installation"	•						
		03 is not appl							
		can apply to l							
	* *	rovals under p	paragraph (b)						
		of this section.							
5		transmitter n		Please refer to the Setup Photo	Y				
		one configura		exhibition for the stand-alone test					
		t not be inside		configuration.					
	`	g testing for c	•						
		requirements							
		nodule will be							
	-	nust comply v							
		ed requiremen							
		07. AC or DC							
			s connected to						
		nust not conta	,						
	_	vill be market							
		Section 15.27							
	_	se lines shall	_						
	• •	tual use or, if	-						
		least 10 centi	oling between						
		-	•						
	me case of th	ne module and	ı supporung						

	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	The Module will be labeled with its own	Y
	equipped with either a permanently	FCC ID, and the instruction on the	
	affixed label or must be capable of	labeling rule of the end product has been	
	electronically displaying its FCC	stated in the User Manual of this	
	identification number.	module. Please refer to the Label and	
	(A) If using a permanently affixed label, the	User Manual exhibition.	
	modular transmitter must be labeled with its own		
	FCC identification number, and, if the FCC		
	identification number is not visible when the		
	module is installed inside another device, then the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use		
	wording such as the following: "Contains		
	Transmitter Module		
	FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate		
	instructions along with the module which explain this requirement. In the latter case, a copy of		
	these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and		
	visible on the modular transmitter or on the device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed		
	must display a label referring to the enclosed		
	module. This exterior label can use wording such		
	as the following: "Contains FCC cartified transmitter module(s)"		
	"Contains FCC certified transmitter module(s)." Any similar wording that expresses the same		
	meaning may be used. The user manual must		
	include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for		
7	equipment authorization. The modular transmitter must comply	The required FCC rule has been fulfilled	Y
'	with any specific rules or operating	and all the instructions for maintaining	1
		_	
	requirements that	compliance have been clearly stated in the User Manual.	
	ordinarily apply to a complete transmitter and the manufacturer must	the Oser Manual.	
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		

8	The modular transmitter must comply	Please refer exhibition RF Exposure for	Y
	with any applicable RF exposure	the compliance of MPE RF exposure	
	requirements in its final configuration.	rule.	

Patrick Ma

Contact Person: Patrick Ma E-mail: mapx@fibocom.com