Request for Modular/Limited Modular Approval

| Dat | e: December 17, 2021 | | | |
|-----|---|---------------|------------------|--|
| Sub | rject: Manufacturer's Declaration for - Modular Approval □ - Spli | t Modular A | Approval | |
| | □ - Limited Modular Approval □ - Limited Spli | t Modular A | Approval | |
| | · | | • • | |
| Cor | fidentiality Request for: <u>ZMOFM101GL</u> | | | |
| | | | | |
| | 8 Basic Requirements – FCC Part 15.212(a)(1) | | | |
| | For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the F | | nges ment Met | |
| 1 | Modular Approval Requirement The modular transmitter must have its own RF shielding. This is intended to ensure that the | Require | ment wet | |
| ٠. | module does not have to rely upon the shielding provided by the device into which it is | | | |
| | installed in order for all modular transmitter emissions to comply with FCC limits. It is also | _ | | |
| | intended to prevent coupling between the RF circuitry of the module and any wires or circuits | ∠ YES | ☐ - NO(*) | |
| | in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded | | | |
| | radio elements. 15.212(a)(1)(i) | | | |
| | | | | |
| | Details: <example -="" a="" all="" component<="" contains="" covers="" metal="" module="" rf="" shield="" td="" the="" which=""><td>s and circui</td><td>try. The</td></example> | s and circui | try. The | |
| 2 | shield is located on the top of the board next to antenna connector> The moduler transmitter must have buffered modulation/data inputs (if such inputs are | | | |
| ۷. | The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of | ⊠ - YES | □ - NO(*) | |
| | excessive data rates or over-modulation. 15.212(a)(1)(ii) | | □ - NO() | |
| | | | | |
| | Details: <example as="" buffered="" circuit="" data="" described="" description<="" in="" is="" modulation="" operational="" td="" the="" to="" –=""></example> | | | |
| 3 | provided with the application> The modular transmitter must have its own power supply regulation on the module. This is | | | |
| ٥. | intended to ensure that the module will comply with FCC requirements regardless of the | | | |
| | design of the power supplying circuitry in the device into which the module is installed. | ∠ YES | ☐ - NO(*) | |
| | 15.212(a)(1)(iii) | | | |
| | Details: <example contains="" its="" module="" own="" please="" power="" refer<="" regulation.="" supply="" td="" the="" –=""><td>to schomat</td><td>ic filed with</td></example> | to schomat | ic filed with | |
| | this application> | to scrieniat | ic mea with | |
| 4. | The modular transmitter must comply with the antenna and transmission system | | | |
| | requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna | | | |
| | must either be permanently attached or employ a "unique" antenna coupler (at all | ⊠ - YES | ☐ - NO(*) | |
| | connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited | | () | |
| | modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv) | | | |
| | | | | |
| | Details: <example an="" antenna="" connector="" connects="" its="" module="" td="" the="" to="" ufl="" using="" which<="" –=""><td></td><td></td></example> | | | |
| | standard connector. A list of antennas tested and approved with this device may be four provided with the application> | na in users i | manuai | |
| 5. | The modular transmitter must be tested in a stand-alone configuration, i.e., the module must | | | |
| | not be inside another device during testing. This is intended to demonstrate that the module | | | |
| | is capable of complying with Part 15 emission limits regardless of the device into which it is | | | |
| | eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and | | | |
| | data input/output lines connected to the module must not contain ferrites, unless they will be | ⊠ - YES | □ - NO(*) | |
| | marketed with the module (see Section 15.27(a)). The length of these lines shall be length | | □ NO() | |
| | typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there | | | |
| | is no coupling between the case of the module and supporting equipment. Any accessories, | | | |
| | peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v) | | | |
| | or commercially available (see Section 15.51(1)). 15.212(a)(1)(v) | | | |
| | Details: <example as="" in="" module="" photogra<="" setup="" shown="" stand-alone="" td="" test="" tested="" the="" was="" –=""><td>aphs filed w</td><td>ith this</td></example> | aphs filed w | ith this | |
| | application> | | | |

| | Modular Approval Requirement | Require | ment Met |
|----|--|--------------|-------------|
| 6. | The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: ZMOMC610LA" or "Contains FCC ID: ZMOMC610LA" Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the | ⊠ - YES | □ - NO(*) |
| | device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi) Details: <example -="" a="" application.<="" are="" as="" exhibit="" filed="" host="" in="" installation="" instructions="" is="" label="" labeling="" manual="" module="" on="" shown="" specific="" td="" the="" there="" this="" with=""><td></td><td>plication.</td></example> | | plication. |
| 7. | The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii) | ⊠ - YES | □ - NO(*) |
| | Details: <example 15c="" application.="" are="" complies="" fcc="" filed="" in="" installation="" instructions="" manual="" module="" part="" provided="" requirements.="" the="" this="" with="" –=""></example> | s to the OEN | l installer |
| 8. | The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii) | ⊠ - YES | □ - NO(*) |
| | Details: < The module meets RF exposure in mobile configuration.> | | |

Limited Module Description – When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

| Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied) | | | |
|--|--|--------------|--|
| Requirement | Requirement Met | | |
| For non-Software Defined Radio transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280. | ☐ - Provided in Separate Cover Letter | ⊠ - N/A | |
| Details: <example adju<br="" be="" can="" device="" firmware="" modified="" not="" of="" or="" the="" –="">a separate cover letter filed with this application. ></example> | usted by the end user as o | lescribed in | |
| For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812. | ☐ - Provided in Separate Cover Letter | ⊠ - N/A | |
| Details: <example a="" –n=""></example> | | | |

| | | nual |
|---|--|---------|
| For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. | ☐ - Provided in Separate Cover Letter | ⊠ - N/A |

OEM Integration Manual Guidance - KDB 996369 D03 Section 2

Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures for third-parties to use and/or integrate the module into a host device.

| Requirement | | | | | |
|--|--|---|--|--|--|
| Is this module intended for sale to third parties? | or ⊠ - YES | ☐ - No, If No, and LMA applies, the applicant of make the following detailed info purineeds to be basic integration instruct and the information below must stroperational description. If the application confidential, this will require a seletter explaining the module is not for that integration instructions are induced to the description of the description of the description instructions are induced the description of the des | ublic. However there still ions for a users manual iill be included in the ant wishes to keep this parate statement cover sale to third parties and | | |
| Item | s required to be in the manu | ıal – See KDB 996369 D03, Section 2 | | | |
| As of May 1, 2019, the FCC requires ALL the following information to be in the installation manual. Modular transmitter applicants should include information in their instructions for all these items indicating clearly when they are not applicable. For example information on trace antenna design could indicate "Not Applicable". Also if a module is limited to only a grantees own products and not intended for sale to third parties, the user instructions may not need to be detailed and the following items can be placed in the operational description, but this should include a cover letter as cited above. | | | | | |
| | es. KDB 996369 D03, Section | 2.2 | | | |
| a. Only list rule | es related to the transmitter. | | | | |
| a. Conditions s point systen | ns, professional installation info | ole loss, reduction of power for point to | | | |
| Limited Module Procedure | es. KDB 996369 D03, Section | 2.4 | | | |
| necessary li b. When RF exsuch that co 4. Trace antenna designs. I a. Layout of tratests for des compliance. identified ar 5. RF exposure consideration a. Clearly and module. Tw to define co text needed 6. Antennas. KDB 996369 D | miting conditions reposure evaluation is necessary mpliance is ensured, such as a MDB 996369 D03, Section 2.5 ace design, parts list, antenna, sign verification, and production of the confidential, the method used information provided in the constant of the confidential of the constant | connectors, isolation requirements, in test procedures for ensuring ed to keep confidential must be operational description. 2.6 allow host manufacturers to use the dessary: first to the host manufacturer cm from body) and second additional in the host product manuals. | □ - All Items shown to the left are provided in the Modular Integration Guide (or UM) for Full Modular Approval (MA) or LMA. □ - An LMA applies and is approved ONLY for use by the grantee in their own products, and not intended for sale to 3 rd | | |
| installer inst antenna typ considered | ructions when applicable. The es (monopole, PIFA, dipole, et a type) | n and all applicable professional antenna list shall also identify the c – note that "omni-directional" is not | parties as provided in a separate cover letter. Therefore the information shown to | | |
| a. Advice to ho "Contains F | CC ID: " with their finished pro- | provide a physical or e-label stating | the left is found in the theory of operation. | | |
| a. Test modes clarifications | that should be taken into cons | sideration by host integrators including dismultaneous configurations. | | | |
| | Subpart B disclaimer, KDB 99 | | | | |

Sincerely,

Lucy lou

Fibocom Wireless Inc. TEL: +86-755-26525092

070920-02b