

RF EXPOSURE REPORT

Report No.: SA160330W009

FCC ID: ZMOH380GL

Test Model: H380-GL

Received Date: Apr. 01, 2016

Test Date: Apr. 02, 2016 ~ Apr. 21, 2016

Issued Date: May. 09, 2016

Applicant: FIBOCOM Wireless Inc.

Address: 5/F, Tower A, Technology Building II, 1057 Nanhai Blvd,
Nanshan, Shenzhen, China

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd.,
Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Cau Vil., Lin Kou Dist., New Taipei
City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

TABLE OF CONTENTS

RF EXPOSURE REPORT	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATI	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	6
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA	6
3.3 CLASSIFICATION	6
3.4 CONDUCTED POWER	7
3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	8

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA160330W009	Original release	May. 09, 2016

1 Certificate of Conformity

Product: WCDMA module with GSM,GPRS,EDGE

Brand: FIBOCOM

Test Model: H380-GL

Sample Status: Identical Prototype

Applicant: FIBOCOM Wireless Inc.

Test Date: Apr. 02, 2016 ~ Apr. 21, 2016

Standards: **FCC Part 2 (Section 2.1091)**

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** May. 09, 2016

Amyee Qian / Engineer

Approved by :  , **Date:** May. 09, 2016

William Chung / Manager

2 GENERAL INFORMATI

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WCDMA module with GSM,GPRS,EDGE	
BRAND	FIBOCOM	
MODEL NAME	H380-GL	
POWER SUPPLY	3.3Vdc (adapter or host equipment)	
OPERATING TEMPERATURE RANGE	-20 ~ 65°C	
MODULATION TECHNOLOGY	DSSS, OFDM	
MODULATION TYPE	GPRS/EDGE	GMSK, 8PSK
	WCDMA	BPSK/QPSK
OPERATING FREQUENCY	GPRS/EDGE	824.2MHz ~ 848.8MHz (FOR GPRS 850) 1850.2MHz ~ 1909.8MHz (FOR PCS 1900)
	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA V) 826.4MHz ~ 846.6MHz (FOR WCDMA II)
ANTENNA TYPE	External Antenna	
ANTENNA GAIN	3dBi gain for GPRS850/WCDMA Band V 5dBi gain for PCS1900/WCDMA Band II	
HW VERSION	V1.0.2	
SW VERSION	H380_V2G.0C.00.02	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

a. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Module Approval**.

3.4 CONDUCTED POWER

GPRS & EDGE

Band	GPRS 850			PCS 1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GPRS 8	32.78	33.27	32.41	29.24	29.48	29.67
GPRS 10	30.66	31.12	30.30	27.04	27.30	27.53
GPRS 11	29.37	29.81	29.00	25.77	26.03	26.25
GPRS 12	27.75	28.21	27.39	24.28	24.51	24.74
EDGE 8 (MCS9)	26.95	27.42	26.62	25.24	25.54	25.77
EDGE 10 (MCS9)	24.94	25.48	24.63	22.98	23.24	23.48
EDGE 11 (MCS9)	23.77	24.22	23.46	22.23	22.52	22.75
EDGE 12 (MCS9)	22.23	22.84	21.92	20.67	20.97	21.22

WCDMA

BAND	WCDMA II			WCDMA V		
CHANNEL	9262	9400	9538	4132	4182	4233
FREQUENCY (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6
RMC 12.2K	23.04	22.98	23.18	23.19	23.37	22.81
HSPA						
HSDPA Subtest-1	22.97	22.92	23.17	23.06	23.30	22.71
HSDPA Subtest-2	22.06	21.98	22.22	22.23	22.37	21.82
HSDPA Subtest-3	21.77	21.74	22.01	21.97	22.09	21.53
HSDPA Subtest-4	21.60	21.50	21.75	21.69	21.85	21.28
HSUPA Subtest-1	22.04	21.95	22.16	22.17	22.36	21.76
HSUPA Subtest-2	20.01	19.98	20.17	20.19	20.33	19.81
HSUPA Subtest-3	20.86	20.82	21.00	21.00	21.13	20.64
HSUPA Subtest-4	20.17	20.15	20.33	20.26	20.41	20.04
HSUPA Subtest-5	22.25	22.17	22.39	22.53	22.57	22.09

3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

GPRS

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Conducted Time Average Power (dBm)	E.I.R.P Power (mW)/8	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
GPRS 850	836.4	GPRS12	3	33.27	529.554	0.105	0.56	PASS
PCS 1900	1909.8	GPRS12	5	29.67	366.362	0.073	1.00	PASS

WCDMA

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Conducted Time Average Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
WCDMA850	836.4	RMC12.2k	3	23.37	433.511	0.086	0.56	PASS
WCDMA1900	1852.4	RMC12.2k	5	23.18	657.658	0.131	1.00	PASS