



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

Project No: CB10501085

## Maximum Permissible Exposure Report

Applicant's company	MitraStar Technology Corporation
Applicant Address	No. 6, Innovation Rd II, Science-Based Industrial, Hsin-Chu, Taiwan
FCC ID	ZMYAM525
Manufacturer's company (1)	MitraStar Technology Corporation
Manufacturer Address	No. 6, Innovation Rd II, Hsinchu Science Park, Hsinchu 30076, Taiwan
Manufacturer's company (2)	WuXi MitraStar Technology Co. Ltd
Manufacturer Address	60#-E, Minshan Road, Wuxi New district Jangsu, P.R.C.

Product Name	MoCA to Wireless / Ethernet bridge
Brand Name	Pace
Model Name	AM525
Ref. Standard(s)	47 CFR FCC Part 2 Subpart J, section 2.1091
Received Date	Nov. 30, 2015
Final Test Date	Jan. 11, 2016
Submission Type	Original Equipment

Sam Chen

SPORTON INTERNATIONAL INC.



Testing Laboratory  
1190



## Table of Contents

<b>1. GENERAL DESCRIPTION.....</b>	<b>1</b>
1.1. EUT General Information .....	1
1.2. Testing Location.....	1
<b>2. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>2</b>
2.1. Limit of Maximum Permissible Exposure .....	2
2.2. MPE Calculation Method .....	2
2.3. Calculated Result and Limit.....	3



## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA5O2010	Rev. 01	Initial issue of report	Feb. 05, 2016

## 1. GENERAL DESCRIPTION

### 1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

### 1.2. Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456      FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065      FAX : 886-3-656-9085

## 2. MAXIMUM PERMISSIBLE EXPOSURE

### 2.1. Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2. MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

### 2.3. Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For 5GHz Band:

Antenna Type: Dipole Antenna

Conducted Power for IEEE 802.11ac MCS0/Nss2 (VHT40): 26.60 dBm

Distance (cm)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	5230	4.71	2.9549	26.6011	457.2074	0.268905	1	Complies

Note:  $Directional\ Gain = 10 \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left( \sum_{k=1}^{N_{ANT}} g_{j,k} \right)^2}{N_{ANT}} \right]$

For 2.4GHz Band:

Antenna Type: Dipole Antenna

Conducted Power for IEEE 802.11n MCS8 (HT20): 25.87 dBm

Distance (cm)	Test Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	2437	2.00	1.5849	25.8705	386.4101	0.121899	1	Complies

#### Conclusion:

Both of the WLAN 2.4GHz Band and WLAN 5GHz Band can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is  $0.121899 / 1 + 0.268905 / 1 = 0.390804$ , which is less than "1". This confirmed that the device complies.