

## EMI CERTIFICATION REPORT

**Applicant:**

LG Electronics Inc.

60-39, Gasan-dong, Gumchon-gu, Seoul  
153-023, Korea

**Date of Issue:** June 16, 2011

**Test Report No.:** HCTE1106FE17

**Test Site:** HCT CO., LTD.

**HCT FRN:** 0005-8664-21

**FCC ID:**

**ZNFC800**

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B  
Equipment Type : Cellular/PCS GSM/EDGE/AWS/WCDMA phone with Bluetooth & WLAN  
Trade Name : LG Electronics Inc  
Model(s) : LG-C800, C800, LGC800  
Port / Connector(s) : USB Data Port / Headset Port


The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862



Report prepared by  
: Doo Hwan Ryu  
Test Engineer of EMC Team



Approved by  
: Sang Jun Lee  
Manager of EMC Team

---

## TABLE OF CONTENTS

---

	<b>PAGE</b>
1. GENERAL INFORMATION	
1.1 Product description	3
1.2 Related submittal(s)/Grant(s)	3
1.3 Tested system details	4
1.4 Cable description	5
1.5 Noise suppression parts on cable. (I/O cable)	5
1.6 Test methodology	6
1.7 Test facility	6
1.8 Frequency Range of Radiated Measurements	6
2. SYSTEM TEST CONFIGURATION	
2.1 Configuration of tested system	7
3. PRELIMINARY TEST	
3.1 Conducted Emission test	8
3.2 Radiated Emission test	8
4. CONDUCTED AND RADIATED EMISSION TESTS SUMMARY	
4.1 Conducted Emission test	9
4.2 Radiated Emission test	14
5. FIELD STRENGTH CALCULATION	15
6. TEST EQUIPMENT	16
7. CONCLUSION	17

**ATTACHMENT: TEST SETUP PHOTOGRAPHS**

## 1. GENERAL INFORMATION

### 1.1 Product Description

Equipment Under Test (E.U.T) is **Cellular/PCS GSM/EDGE/AWS/WCDMA phone with Bluetooth & WLAN, Model: LG-C800** manufactured by **LG Electronics Inc.** Its basic purpose is used for communications.

<b>Model (s)</b>	LG-C800
<b>Additional Model</b>	C800, LGC800
<b>FCC ID</b>	ZNFC800
<b>E.U.T Type</b>	Cellular/PCS GSM/EDGE/AWS/WCDMA phone with Bluetooth & WLAN
<b>TX Frequency</b>	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 712.4 MHz to 1 752.5 MHz (WCDMA 1 700)
<b>RX Frequency</b>	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 2 112.4 MHz to 2 152.6 MHz (WCDMA 1 700)

### 1.2 Related Submittal(s) / Grant(s)

Original submittal only.

### 1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Manufacturer	Model Number	FCC ID / DoC	Connected To
Cellular/PCS GSM/ EDGE/AWS/WCDMA phone with Bluetooth & WLAN	LG	LG-C800	ZNFC800	Notebook PC
Notebook PC	LG	X140-02	DoC	E.U.T Notebook PC adaptor
Notebook PC adaptor	DELTA (JIANG SU)	ADP-40PH AD	-	Notebook PC
Mouse	Microsoft	Intellimouse optical USB and PS/2 compatible	DoC	Notebook PC
USB cable	KSD	SGDY0018501	-	E.U.T Notebook PC
SD card(2 GB)	SanDisk	-	-	E.U.T
Headset	-	-	-	E.U.T

### 1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
Cellular/PCS GSM/EDGE/AWS/WCDMA phone with Bluetooth & WLAN	Headset jack	-	N	(D)1.1
	USB data	Y	Y	(P,D)1.2
Notebook PC	USB (Mouse)	-	Y	(D)1.8

\* The marked "(D)" means the data cable and "(P)" means the power cable.

### 1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
Cellular/PCS GSM/EDGE/AWS/WCDMA phone with Bluetooth & WLAN	Headset jack	N	-	Y	E.U.T End
	USB data	N	-	Y	Both End
Notebook PC	USB (Mouse)	Y	Notebook PC End	Y	Notebook PC End

## 1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to E.U.T distance of 3 m

## 1.7 Test Facility

The 10 m semi anechoic chamber used to collect the Conducted and Radiated data is located at the 105-1, Jangam-Ri, Majang-Myeon, Icheon-Si, Kyoungki-Do, Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4.

Detailed description of test facilities was submitted to the Commission and accepted dated Sep. 03, 2010 (Registration Number: 90661)

## 1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower


## 2. SYSTEM TEST CONFIGURATION

### 2.1 Configuration of Test System

Power Line Conducted test : E.U.T was connected to LISN via Notebook PC adaptor.  
Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

Radiated Emission test : Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed in a 10 m semi-anechoic chamber.

[Configuration of Tested System]



Power Line: 110 VAC

### **3. PRELIMINARY TEST**

---

#### **3.1 Conducted Emission Test**

■ It was tested Data Communication mode, after connecting all peripheral devices.

<b>Operation Mode</b>	<b>The Worst Operating Condition</b>
Data Communication	○

#### **3. 2 Radiated Emission Test**

■ It was tested Data Communication mode, after connecting all peripheral devices.

<b>Operation Mode</b>	<b>The Worst Operating Condition</b>
Data Communication	○



## 4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

### 4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Temperature	: 24.9 °C
Humidity level	: 47.8 %
Test date	: June 07, 2011

※ **NOTE:** Refer to page 10 to page 13 for details.


**HCT**

**EMC**

EUT: LG-C800  
 Manufacturer: LG  
 Operating Condition: DATA MODE  
 Test Site: SHIELD ROOM  
 Operator: DH-RYU  
 Test Specification: H  
 Comment:

**SCAN TABLE: "FCC PART 15 B(H)"**

Short Description:			FCC PART 15 CLASS B			
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	1.0 kHz	MaxPeak	10.0 ms	9 kHz	None
500.0 kHz	5.0 MHz	4.0 kHz	Average			
			MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



**MEASUREMENT RESULT: "PHONE\_fin QP"**

6/7/2011 3:43PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.166010	54.20	10.1	65	11.0	---	---
0.168010	53.80	10.1	65	11.2	---	---
0.183010	49.50	10.1	64	14.8	---	---
0.512000	21.30	10.1	56	34.7	---	---
0.600000	21.80	10.1	56	34.2	---	---
0.660000	20.90	10.1	56	35.1	---	---
11.956000	23.10	11.1	60	36.9	---	---
12.036000	23.50	11.1	60	36.5	---	---
13.044000	22.40	11.2	60	37.6	---	---

**MEASUREMENT RESULT: "PHONE\_fin AV"**

6/7/2011 3:43PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.166010	21.30	10.1	55	33.9	---	---
0.168010	30.00	10.1	55	25.0	---	---
0.186010	27.30	10.1	54	26.9	---	---
0.504000	15.40	10.1	46	30.6	---	---
0.612000	9.60	10.1	46	36.4	---	---
0.668000	9.80	10.1	46	36.2	---	---
11.188000	15.80	11.0	50	34.2	---	---
12.516000	17.00	11.2	50	33.0	---	---
16.520000	14.90	11.5	50	35.1	---	---


**HCT**

**EMC**

EUT: LG-C800  
 Manufacturer: LG  
 Operating Condition: DATA MODE  
 Test Site: SHIELD ROOM  
 Operator: DH-RYU  
 Test Specification: N  
 Comment:

**SCAN TABLE: "FCC PART 15 B(N)"**

Short Description:			FCC PART 15 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



**MEASUREMENT RESULT: "PHONE\_fin QP"**

6/7/2011 3:46PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.170010	51.20	10.3	65	13.8	---	---
0.182010	49.00	10.3	64	15.4	---	---
0.238010	37.30	10.3	62	24.9	---	---
0.504000	24.50	10.3	56	31.5	---	---
0.720000	16.40	10.4	56	39.6	---	---
4.184000	22.20	10.6	56	33.8	---	---
11.548000	24.40	11.1	60	35.6	---	---
11.576000	24.20	11.1	60	35.8	---	---
12.328000	24.70	11.2	60	35.3	---	---

**MEASUREMENT RESULT: "PHONE\_fin AV"**

6/7/2011 3:46PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.186010	26.50	10.3	54	27.7	---	---
0.194010	27.60	10.3	54	26.2	---	---
0.434010	17.00	10.3	47	30.1	---	---
0.508000	14.60	10.3	46	31.4	---	---
0.608000	9.00	10.3	46	37.0	---	---
4.336000	14.60	10.6	46	31.4	---	---
11.544000	18.00	11.1	50	32.0	---	---
11.916000	18.30	11.2	50	31.7	---	---
16.976000	14.20	11.5	50	35.8	---	---

## 4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

Limit Apply to : FCC PART 15 Subpart B Class B

**-For measurement below 1 GHz**

Detector : Quasi-Peak (6 dB Bandwidth: 120 kHz)

**-For measurement above 1 GHz**

Setting : Peak mode: Detector- Peak(RBW: 1 MHz / VBW: 1 MHz)  
 : Average mode: Detector- Peak (RBW: 1 MHz / VBW: 10 Hz)

Temperature : 23.6 °C

Humidity Level : 49.5 %

Test Date : June 07, 2011

Frequency (MHz)	Reading (dBUV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBUV/m)	Level (dBUV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
129.2	18.16	V	1.0	11.88	1.96	43.5	32.0	11.5
142.2	12.02	V	1.0	12.62	2.06	43.5	26.7	16.8
151.2	16.40	V	1.1	12.88	2.12	43.5	31.4	12.1
368.6	13.76	H	3.0	14.94	3.39	46.0	32.1	13.9
384.0	21.05	H	1.2	15.28	3.47	46.0	39.8	6.2
763.7	7.45	H	3.0	22.14	5.01	46.0	34.6	11.4

**\* NOTE:**

1. Measurement above 1 GHz was performed from 1 GHz to the 5<sup>th</sup> harmonic of highest fundamental frequency. The highest fundamental frequency is GSM 1 900 center frequency.
2. For measurement above 1 GHz, Emission noise was not founded over the ambient noise.

## 5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.  
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB $\mu$ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB $\mu$ V/m value is mathematically converted to its corresponding level in  $\mu$ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

### [Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	$\mu$ V/m	dB $\mu$ V/m
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

## 6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Number</u>	<u>Serial Number</u>	<u>Next CAL Date</u>
<b><u>Conducted Emission</u></b>				
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100033	2012.02.15
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	2012.02.01
<input type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	2012.04.01
<input checked="" type="checkbox"/> Attenuator	Rohde & Schwarz	ESH3-Z2	375.8810.352	2011.10.25
<b><u>Radiated Emission</u></b>				
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	2011.10.29
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU26	100241	2011.09.01
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3125	2013.05.03
<input checked="" type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	-
<input checked="" type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	-
<input checked="" type="checkbox"/> Communication Antenna	Schwarzbeck	USLP9142	9142-248	-
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	-	2012.04.13
<input checked="" type="checkbox"/> Power Amplifier	Rohde & Schwarz	SCU-18	10094	2011.09.29
<input type="checkbox"/> Base Station	Rohde & Schwarz	CMU 200	1100000802	2012.02.16



## 7. CONCLUSION

---

The data collected shows that the **Cellular/PCS GSM/EDGE/AWS/WCDMA phone with Bluetooth & WLAN, Model: LG-C800, FCC ID: ZNFC800** complies with §15.107 and §15.109 of the FCC rules.