



HCT CO., LTD.

CERTIFICATE OF COMPLIANCE FCC Certification

Applicant Name:
LG Electronics MobileComm U.S.A., Inc.

Address:
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Issue:
July 01, 2014

Test Site/Location:
HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-
myeon, Icheon-si, Gyeonggi-do, Korea

Report No.: HCT-R-1407-F009

HCT FRN: 0005866421

FCC ID : ZNFD221C

APPLICANT : LG Electronics MobileComm U.S.A., Inc.

FCC Model(s): LG-D221c

Additional FCC Model(s): LGD221c, D221c

EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support

Peak RF Output Power: -2.145 dBm (0.6102 mW)

Frequency Range: 2402 MHz -2480 MHz(BT 4.0_Low Energy Mode)

Modulation type GFSK

FCC Classification: Digital Transmission System(DTS)

FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report prepared by
: Kyoung Houn Seo
Test Engineer of RF Team

Approved by
: Chang Seok Choi
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C



Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1407-F009	July 01, 2014	- First Approval Report

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WiFi802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNF0221C

Table of Contents

1. GENERAL INFORMATION		4
2. EUT DESCRIPTION		4
3. TEST METHODOLOGY		5
3.1 EUT CONFIGURATION		5
3.2 EUT EXERCISE		5
3.3 GENERAL TEST PROCEDURES		5
3.4 DESCRIPTION OF TEST MODES		5
4. INSTRUMENT CALIBRATION.....		6
5. FACILITIES AND ACCREDITATIONS		6
5.1 FACILITIES		6
5.2 EQUIPMENT		6
6. ANTENNA REQUIREMENTS		6
7. SUMMARY TEST OF RESULTS		7
8. TEST RESULT		8
8.1 DUTY CYCLE.....		8
8.2 6dB BANDWIDTH MEASUREMENT		9
8.3 OUTPUT POWER MEASUREMENT.....		1 2
8.4 POWER SPECTRAL DENSITY		1 9
8.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS ...		2 3
8.6 RADIATED MEASUREMENT.....		3 4
8.6.1 RADIATED SPURIOUS EMISSIONS.....		3 4
8.6.2 RADIATED RESTRICTED BAND EDGES		4 3
8.7 POWERLINE CONDUCTED EMISSIONS		4 5
9. LIST OF TEST EQUIPMENT		5 0
9.1 LIST OF TEST EQUIPMENT(Conducted Test)		5 0
9.2 LIST OF TEST EQUIPMENT(Radiated Test).....		5 1

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C



1. GENERAL INFORMATION

Applicant: LG Electronics MobileComm U.S.A., Inc.
Address: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
FCC ID: ZNFD221C
EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support
Model name(s): LG-D221c
Additional Model name(s): LGD221c, D221c
Date(s) of Tests: June 10, 2014 ~ June 23, 2014
Place of Tests: HCT Co., Ltd.
 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea
 (IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

FCC Model Name	LG-D221c	
Additional FCC Model Name	LGD221c, D221c	
EUT Type	GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	
Power Supply	DC 3.8 V	
Battery type	Li-ion Battery(Standard)	
Frequency Range	TX: 2402 MHz ~ 2480 MHz RX: 2402 MHz ~ 2480 MHz	
Max. RF Output Power	Peak	-2.145 dBm (0.6102 mW)
	Average	-2.580 dBm (0.5521 mW)
BT Operating Mode	BT 4.0_Low Energy Mode	
Modulation Type	GFSK	
Number of Channels	40 Channels	
Antenna Specification	Manufacturer: LS Mtron Co.Ltd. Antenna type: SHEET METAL Antenna Peak Gain : 0.3 dBi	



3. TEST METHODOLOGY

FCC KDB 558074 D01 DTS Meas Guidance v03r02 dated June 05, 2014 entitled “Guidance for Performing Compliance Measurements on Digital Transmission Systems(DTS) and the measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.4-2003) Operating Under §15.247” were used in the measurement.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

Conducted Antenna Terminal

See Section from 9.1 to 9.2.(KDB 558074)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated February 28, 2014 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C

7. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	CONDUCTED	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 8.7		PASS
Radiated Spurious Emissions	§15.205, 15.209	cf. Section 8.6.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.6.2		PASS


8. TEST RESULT

8.1 DUTY CYCLE

□ TEST PROCEDURE

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

□ TEST CONFIGURATION



□ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/05/2014)

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on}/T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

LE Mode	T_{on} (ms)	T_{total} (ms)	Duty Cycle	Duty Cycle Factor
		0.1120	0.6256	0.1790


8.2 6dB BANDWIDTH MEASUREMENT

Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

□ TEST CONFIGURATION



□ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Page 5 in KDB 558074, issued 06/05/2014)

RBW = 100 kHz

VBW \geq 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple


Allow the trace to stabilize

Note : We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.


FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C

□ RESULT PLOTS


6dB Bandwidth plot (Low-CH 0)



6dB Bandwidth plot (Mid-CH 19)



6dB Bandwidth plot (High-CH 39)



FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C


8.3 OUTPUT POWER MEASUREMENT

Test Requirements and limit, §15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of a Spectrum Analyzer. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

□ TEST CONFIGURATION



□ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We use the spectrum analyzer's integrated band power measurement function.

This EUT TX condition is actual operating mode by BT LE mode test program.

The Spectrum Analyzer is set to

- Peak Power(Procedure 9.1.1 in KDB 558074, issued 06/05/2014)
 - RBW ≥ DTS Bandwidth
 - VBW ≥ 3 x RBW
 - SPAN ≥ 3 x RBW
 - Detector Mode = Peak
 - Sweep = auto couple
 - Trace Mode = max hold
 - Allow trace to fully stabilize.
 - Use peak marker function to determine the peak amplitude level

- Average Power (Procedure 9.2.2.4 in KDB 558074, issued 06/05/2014)
 - Measure the duty cycle
 - Set span to at least 1.5 times the OBW
 - RBW = 1-5 % of the OBW, not to exceed 1 MHz.
 - VBW ≥ 3 x RBW.
 - Number of points in sweep ≥ 2 x span / RBW. (This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)
 - Sweep time = auto.
 - Detector = RMS(i.e., power averaging)
 - Do not use sweep triggering. Allow the sweep to “free run”.
 - Trace average at least 100 traces in power averaging(RMS) mode.
 - Compute power by integrating the spectrum across the OBW of the signal using the instrument's band

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C



power measurement function with band limits set equal to the OBW band edges.

Add 10 log (1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

□ Sample Calculation

Output Power = Reading Value + ATT loss + Cable loss(1 ea) + Duty Cycle Factor

Output Power = 10 dBm + 10 dB + 0.8 dB + 0.2 dB = 21.0 dBm

Note :

1. Spectrum reading values are not plot data. The power results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is offset for 2.4 GHz Band.

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C



□ TEST RESULTS-Peak

Conducted Output Power Measurements

LE Mode		Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.		
2402	0	-3.181	30
2440	19	-2.616	30
2480	39	-2.145	30


□ TEST RESULTS-Average

Conducted Output Power Measurements

LE Mode		Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency[MHz]	Channel No.				
2402	0	-10.66	7.47	-3.18	30
2440	19	-10.09	7.47	-2.62	30
2480	39	-10.05	7.47	-2.58	30

□ RESULT PLOTS-Peak

Conducted Output Power (Low-CH 0)




Conducted Output Power (Mid-CH 19)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C


Conducted Output Power (High-CH 39)




FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C

□ RESULT PLOTS-Average

Conducted Output Power (Low-CH 0)




Conducted Output Power (Mid-CH 19)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C

Conducted Output Power (High-CH 39)



FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C


8.4 POWER SPECTRAL DENSITY

Test Requirements and limit, §15.247(e)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

□ TEST CONFIGURATION



□ TEST PROCEDURE

We tested according to Procedure 10.2 in KDB 558074, issued 06/05/2014

The spectrum analyzer is set to :

Set analyzer center frequency to DTS channel center frequency.

Span = 1.5 times the DTS channel bandwidth.

RBW = 3 kHz ≤ RBW ≤ 100 kHz.

VBW ≥ 3 x RBW.

Sweep = auto couple

Detector = peak

Trace Mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

□ Sample Calculation

PSD = Reading Value + ATT loss + Cable loss(1 ea)

Output Power = -5 dBm + 10 dB + 0.8 dB = 5.8 dBm

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is offset for 2.4 GHz Band.

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C



□ TEST RESULTS


Conducted Power Density Measurements

Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/Fail
2402	0	LE	-17.352	8	Pass
2440	19		-16.832	8	Pass
2480	39		-16.402	8	Pass


FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WiFi802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C

RESULT PLOTS

Power Spectral Density (Low-CH 0)



Power Spectral Density (Mid-CH 19)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WiFi802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C

Power Spectral Density (High-CH 39)



FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C


8.5 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc

□ TEST CONFIGURATION



□ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. (Procedure 11.0 in KDB 558074, issued 04/09/2013)

RBW = 100 kHz

VBW \geq 3 x RBW

Set span to encompass the spectrum to be examined

Detector = Peak

Trace Mode = max hold

Sweep time = auto couple

Ensure that the number of measurement points \geq 2*Span/RBW

Allow trace to fully stabilize.

Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 10th harmonic range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C



offset for 2.4 GHz Band.

4. In case of conducted spurious emissions test, please check factors blow table.
5. In order to simplify the report, attached plots were only the worst case channel and data rate.

□ FACTORS FOR FREQUENCY

Freq(MHz)	Factor(dB)
30	9.95
100	10.01
200	10.03
300	10.04
400	10.05
500	10.04
600	10.03
700	10.09
800	10.10
900	10.08
1000	10.11
2000	10.25
2400*	10.19
2500*	10.26
3000	10.27
4000	10.22
5000	10.48
5700*	10.42
5800*	10.48
6000	10.48
7000	10.57
8000	10.45
9000	10.50
10000	10.64
11000	10.69
12000	10.75
13000	10.92
14000	11.90
15000	11.00
16000	11.03
17000	10.93
18000	10.96

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C




19000	10.85
20000	12.11
21000	11.17
22000	10.99
23000	11.12
24000	11.10
25000	11.42

Note : 1. ** is fundamental frequency range.
2. Factor = Cable loss + Attenuator loss


FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C

□ RESULT PLOTS

BandEdge (Low-CH 0)




BandEdge (High-CH 39)



FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C


30 MHz ~ 1 GHz

Conducted Spurious Emission (High-CH 39)



1 GHz ~ 3 GHz


Conducted Spurious Emission (High-CH 39)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C


3 GHz ~ 5 GHz

Conducted Spurious Emission (High-CH 39)



5 GHz ~ 7 GHz

Conducted Spurious Emission (High-CH 39)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C




7 GHz ~ 9 GHz

Conducted Spurious Emission (High-CH 39)



9 GHz ~ 11 GHz


Conducted Spurious Emission (High-CH 39)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C


11 GHz ~ 13 GHz

Conducted Spurious Emission (High-CH 39)



13 GHz ~ 15 GHz


Conducted Spurious Emission (High-CH 39)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C


15 GHz ~ 17 GHz

Conducted Spurious Emission (High-CH 39)



17 GHz ~ 19 GHz


Conducted Spurious Emission (High-CH 39)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C


19 GHz ~ 21 GHz

Conducted Spurious Emission (High-CH 39)




21 GHz ~ 23 GHz

Conducted Spurious Emission (High-CH 39)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C

Conducted Spurious Emission (High-CH 39)



FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C

8.6 RADIATED MEASUREMENT.


8.6.1 RADIATED SPURIOUS EMISSIONS.

Test Requirements and limit, §15.205, §15.209


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE USED

Method 12.1 in KDB 558074, issued 06/05/2014

Spectrum Setting

- Peak

Peak emission levels are measured by setting the instrument as follows:

RBW = cf. Table 1.

VBW $\geq 3 \times$ RBW.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes.

(Note that the required measurement time may be longer for low duty cycle applications).

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz



- Average

Set RBW = 1 MHz

Set VBW $\geq 1/T$. (at least 100 times less than the resolution bandwidth, but no less than 10 Hz.)

Select spectrum analyzer linear display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Note :

1. We are performed the RSE and radiated band edge using standard radiated method.
2. The actual setting value of VBW for BT LE mode.

BT LE Mode	T _{on} (ms)	T _{total} (ms)	Duty Cycle (%)	VBW(1/T) (Hz)	The actual setting value of VBW (Hz)
	0.1120	0.6256	17.90	8929	3000



TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V/m	dBm /m	dBm	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
4. Limit line = specific Limits (dBuV) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNF0221C



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V/m	dBm /m	dBm	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C



Above 1 GHz

Operation Mode: CH Low(LE Mode)

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	52.15	-4.32	V	47.83	73.98	26.15	PK
4804	38.51	-4.32	V	34.19	53.98	19.79	AV
7206	51.69	5.18	V	56.87	73.98	17.11	PK
7206	38.24	5.18	V	43.42	53.98	10.56	AV
4804	52.47	-4.32	H	48.15	73.98	25.83	PK
4804	39.35	-4.32	H	35.03	53.98	18.95	AV
7206	51.83	5.18	H	57.01	73.98	16.97	PK
7206	38.64	5.18	H	43.82	53.98	10.16	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C



Operation Mode: CH Mid(LE Mode)

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4880	49.58	-3.95	V	45.63	73.98	28.35	PK
4880	37.02	-3.95	V	33.07	53.98	20.91	AV
7320	51.46	5.46	V	56.92	73.98	17.07	PK
7320	38.68	5.46	V	44.14	53.98	9.85	AV
4880	49.69	-3.95	H	45.74	73.98	28.24	PK
4880	37.12	-3.95	H	33.17	53.98	20.81	AV
7320	51.39	5.46	H	56.85	73.98	17.14	PK
7320	38.77	5.46	H	44.23	53.98	9.76	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNF0221C

Operation Mode: CH High(LE Mode)

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	50.48	-3.49	V	46.99	73.98	26.99	PK
4960	37.81	-3.49	V	34.32	53.98	19.66	AV
7440	51.27	5.10	V	56.37	73.98	17.61	PK
7440	38.56	5.10	V	43.66	53.98	10.32	AV
4960	50.69	-3.49	H	47.20	73.98	26.78	PK
4960	37.96	-3.49	H	34.47	53.98	19.51	AV
7440	51.38	5.10	H	56.48	73.98	17.50	PK
7440	38.75	5.10	H	43.85	53.98	10.13	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

8.6.2 RADIATED RESTRICTED BAND EDGES

Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode	BT 4.0_LE
Operating Frequency	2402 MHz
Channel No	0 Ch

Frequency [MHz]	Reading [dBuV/m]	A.F.+CL [dBm]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	26.11	33.90	H	60.01	73.98	13.97	PK
2390.0	14.10	33.90	H	48.00	53.98	5.98	AV
2390.0	26.09	33.90	V	59.99	73.98	13.99	PK
2390.0	14.06	33.90	V	47.96	53.98	6.02	AV

Notes:

1. Frequency range of measurement = 2310 MHz ~ 2390 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The radiated restricted band edge measurements are measured with a spectrum analyzer connected to the receive antenna while the EUT is transmitting.



Operation Mode	BT 4.0_LE
Operating Frequency	2480 MHz
Channel No	39 Ch

Frequency [MHz]	Reading [dBUV/m]	A.F.+CL [dBm]	Ant. Pol. [H/V]	Total [dBUV/m]	Limit [dBUV/m]	Margin [dB]	Measurement Type
2483.5	26.95	33.99	H	60.94	73.98	13.04	PK
2483.5	14.85	33.99	H	48.84	53.98	5.15	AV
2483.5	26.57	33.99	V	60.56	73.98	13.42	PK
2483.5	14.77	33.99	V	48.76	53.98	5.22	AV

Notes:

1. Frequency range of measurement = 2483.5 MHz ~ 2500 MHz
2. Total = Reading Value + Antenna Factor + Cable Loss
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The radiated restricted band edge measurements are measured with a spectrum analyzer connected to the receive antenna while the EUT is transmitting.

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support		FCC ID: ZNFD221C



8.7 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. We are performed the AC Power Line Conducted Emission test for Ch.39 on BT 4.0 LE mode.
Because Ch.39 on BT 4.0 LE mode is worst case.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C

RESULT PLOTS


Conducted Emissions (Line 1)

HCT TEST Report

Common Information

EUT: LG-D221c
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: BT_LE MODE
 Operator Name: KH-SEO

FCC CLASS B



— FCCCLASS B_OP
 — FCCCLASS B_AV
 — Preview Result 1-PK
— Preview Result 2-AVG
 X Final Result 1-QPK
 X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.348000	42.1	9.000	Off	L1	9.7	16.9	59.0
0.433500	41.2	9.000	Off	L1	9.7	16.0	57.2
0.689000	38.6	9.000	Off	L1	9.7	17.4	56.0
0.792500	36.7	9.000	Off	L1	9.7	19.3	56.0
0.806000	37.8	9.000	Off	L1	9.7	18.2	56.0
0.837500	36.9	9.000	Off	L1	9.7	19.1	56.0
1.751000	42.3	9.000	Off	L1	9.8	13.7	56.0
1.809500	40.9	9.000	Off	L1	9.8	15.1	56.0
1.836500	43.5	9.000	Off	L1	9.8	12.5	56.0
1.845500	44.1	9.000	Off	L1	9.8	11.9	56.0
1.877000	42.4	9.000	Off	L1	9.8	13.6	56.0
1.886000	43.4	9.000	Off	L1	9.8	12.6	56.0
5.427500	28.7	9.000	Off	L1	10.1	31.3	60.0
5.441000	28.6	9.000	Off	L1	10.1	31.4	60.0
5.567000	29.0	9.000	Off	L1	10.1	31.0	60.0
5.594000	29.1	9.000	Off	L1	10.1	30.9	60.0

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
5.616500	29.0	9.000	Off	L1	10.1	31.0	60.0
6.953000	28.9	9.000	Off	L1	10.3	31.1	60.0

Final Result 2


Frequency (MHz)	CAverage (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.348000	34.4	9.000	Off	L1	9.7	14.6	49.0
0.433500	31.7	9.000	Off	L1	9.7	15.5	47.2
0.792500	26.4	9.000	Off	L1	9.7	19.6	46.0
0.837500	26.1	9.000	Off	L1	9.7	19.9	46.0
0.846500	25.3	9.000	Off	L1	9.7	20.7	46.0
0.864500	29.4	9.000	Off	L1	9.7	16.6	46.0
1.715000	30.8	9.000	Off	L1	9.8	15.2	46.0
1.791500	32.4	9.000	Off	L1	9.8	13.6	46.0
1.800500	32.7	9.000	Off	L1	9.8	13.3	46.0
1.836500	33.2	9.000	Off	L1	9.8	12.8	46.0
1.845500	32.8	9.000	Off	L1	9.8	13.2	46.0
1.863500	31.5	9.000	Off	L1	9.8	14.5	46.0
5.387000	17.4	9.000	Off	L1	10.1	32.6	50.0
5.567000	18.7	9.000	Off	L1	10.1	31.3	50.0
5.594000	19.1	9.000	Off	L1	10.1	30.9	50.0
5.621000	18.8	9.000	Off	L1	10.1	31.2	50.0
6.939500	20.0	9.000	Off	L1	10.3	30.0	50.0
6.953000	20.0	9.000	Off	L1	10.3	30.0	50.0

HCT TEST Report

Common Information

EUT: LG-D221c
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: BT_LE MODE
 Operator Name: KH-SEO

FCC CLASS B



— FCCCLASS B_OP — FCCCLASS B_AV — Preview Result 1-PR
— Preview Result 2-AVG x Final Result 1-QFK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.177000	39.5	9.000	Off	N	9.7	25.1	64.6
0.217500	37.0	9.000	Off	N	9.7	25.9	62.9
0.298500	34.2	9.000	Off	N	9.7	26.1	60.3
0.307500	36.6	9.000	Off	N	9.7	23.4	60.0
0.702500	33.8	9.000	Off	N	9.7	22.2	56.0
0.792500	33.5	9.000	Off	N	9.7	22.6	56.0
1.710500	35.3	9.000	Off	N	9.8	20.7	56.0
1.805000	35.8	9.000	Off	N	9.8	20.2	56.0
1.827500	35.5	9.000	Off	N	9.8	20.5	56.0
1.845500	37.4	9.000	Off	N	9.8	18.6	56.0
1.890500	36.5	9.000	Off	N	9.8	19.5	56.0
1.935500	34.6	9.000	Off	N	9.9	21.4	56.0
5.364500	22.7	9.000	Off	N	10.1	37.3	60.0
5.400500	22.7	9.000	Off	N	10.1	37.3	60.0
5.418500	22.8	9.000	Off	N	10.1	37.2	60.0
6.057500	22.5	9.000	Off	N	10.2	37.5	60.0

6/23/2014

11:08:31

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
6.984500	23.0	9.000	Off	N	10.3	37.0	60.0
7.115000	23.2	9.000	Off	N	10.3	36.8	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.177000	25.0	9.000	Off	N	9.7	29.6	54.6
0.217500	24.2	9.000	Off	N	9.7	28.7	52.9
0.262500	23.5	9.000	Off	N	9.7	27.9	51.4
0.303000	28.2	9.000	Off	N	9.7	22.0	50.2
0.348000	26.4	9.000	Off	N	9.7	22.6	49.0
0.792500	21.2	9.000	Off	N	9.7	24.8	46.0
1.710500	25.3	9.000	Off	N	9.8	20.7	46.0
1.782500	26.7	9.000	Off	N	9.8	19.3	46.0
1.827500	27.3	9.000	Off	N	9.8	18.7	46.0
1.836500	27.4	9.000	Off	N	9.8	18.6	46.0
1.890500	25.4	9.000	Off	N	9.8	20.6	46.0
1.926500	25.5	9.000	Off	N	9.9	20.5	46.0
5.364500	15.5	9.000	Off	N	10.1	34.5	50.0
5.400500	15.1	9.000	Off	N	10.1	34.9	50.0
6.057500	16.5	9.000	Off	N	10.2	33.5	50.0
6.984500	17.2	9.000	Off	N	10.3	32.8	50.0
7.115000	17.3	9.000	Off	N	10.3	32.7	50.0
7.803500	17.2	9.000	Off	N	10.3	32.8	50.0



9. LIST OF TEST EQUIPMENT

9.1 LIST OF TEST EQUIPMENT(Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ENV216/ LISN	01/29/2014	Annual	01/29/2015	100073
Agilent	E4440A/ Spectrum Analyzer	04/09/2014	Annual	04/09/2015	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	05/23/2014	Annual	05/23/2015	MY51110063
Agilent	N1911A/Power Meter	01/24/2014	Annual	01/24/2015	MY45100523
Agilent	N1921A /POWER SENSOR	07/11/2013	Annual	07/11/2014	MY45241059
Hewlett Packard	11636B/Power Divider	10/22/2013	Annual	10/22/2014	11377
Agilent	87300B/Directional Coupler	12/18/2013	Annual	12/18/2014	3116A03621
Hewlett Packard	11667B / Power Splitter	01/27/2014	Annual	01/27/2015	10545
DIGITAL	EP-3010 /DC POWER SUPPLY	10/29/2013	Annual	10/29/2014	3110117
ITECH	IT6720 / DC POWER SUPPLY	11/05/2013	Annual	11/05/2014	0100021562870011 99
TESCOM	TC-3000C / BLUETOOTH TESTER	04/11/2014	Annual	04/11/2015	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/07/2014	Annual	05/07/2015	100422
Agilent	8493C / Attenuator(10 dB)	07/24/2013	Annual	07/24/2014	76649
WEINSCHEL	2-3 / Attenuator(3 dB)	10/28/2013	Annual	10/28/2014	BR0617

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R-1407-F009	Date of Issue: July 01, 2014	EUT Type: GSM/WCDMA Phone with Bluetooth4.0, WIFI802.11 b/g/n(2.4GHz_HT20&HT40), VoIP, Hotspot support	FCC ID: ZNFD221C

9.2 LIST OF TEST EQUIPMENT(Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Calibration Due	Serial No.
Schwarzbeck	VULB 9160/ TRILOG Antenna	12/17/2012	Biennial	12/17/2014	3150
Rohde & Schwarz	ESCI / EMI TEST RECEIVER	01/24/2014	Annual	01/24/2015	100584
HD	MA240/ Antenna Position Tower	N/A	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	09/10/2013	Annual	09/10/2014	10094
CERNEK	CBL18265035 / POWER AMP	07/24/2013	Annual	07/24/2014	22966
CERNEK	CBL26405040 / POWER AMP	04/04/2014	Annual	04/04/2015	19660
Schwarzbeck	BBHA 9120D/ Horn Antenna	07/05/2013	Biennial	07/05/2015	1151
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	10/30/2012	Biennial	10/30/2014	BBHA9170124
Rohde & Schwarz	FSP / Spectrum Analyzer	01/24/2014	Annual	01/24/2015	839117/011
Wainwright Instrument	WHF3.0/18G-10EF / High Pass Filter	02/03/2014	Annual	02/03/2015	F6
Wainwright Instrument	WHNX6.0/26.5G-6SS / High Pass Filter	04/09/2014	Annual	04/09/2015	1
Wainwright Instrument	WHNX7.0/18G-8SS / High Pass Filter	04/04/2014	Annual	04/04/2015	29
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	06/24/2014	Annual	06/17/2015	1
TESCOM	TC-3000C / BLUETOOTH TESTER	04/11/2014	Annual	04/11/2015	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/07/2014	Annual	05/07/2015	100422
Rohde & Schwarz	LOOP ANTENNA	08/14/2012	Biennial	08/14/2014	100179
CERNEK	CBL06185030 / POWER AMP	07/24/2013	Annual	07/24/2014	22965
CERNEK	CBLU1183540 / POWER AMP	07/24/2013	Annual	07/24/2014	22964