




PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com



MEASUREMENT REPORT FCC PART 15.407 / IC RSS-210 802.11a/n/ac (UNII)

Applicant Name:
LG Electronics MobileComm U.S.A
60-39, Gasan-dong, Gumchon-gu,
Seoul, Korea

Date of Testing:
7/16 - 8/6/2013
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0Y1307011142.ZNF

FCC ID:	ZNFD803
IC CERTIFICATION NO.:	2703C-D803
APPLICANT:	LG Electronics MobileComm U.S.A

Application Type: Certification
Model(s): LG-D803, LGD803, D803
EUT Type: Portable Handset
FCC Classification: Unlicensed National Information Infrastructure (UNII)
FCC Rule Part(s): Part 15.407 (UNII Band 1-4), 15.247 (UNII Band 4, 802.11ac)
Test Procedure(s): KDB 789033 v01r03, KDB 644545 D02 v01 Alternative Guidance.

Mode	UNII Band	Channel Bandwidth (MHz)	Tx Frequency (MHz)	Conducted Power	
				Max. Power (mW)	Max. Power (dBm)
802.11a	1	20	5180 - 5240	12.274	10.89
	2	20	5260 - 5320	12.274	10.89
	3	20	5500 - 5700	11.641	10.66
	4	20	5745 - 5825	9.661	9.85
802.11n	1	20	5180 - 5240	11.482	10.60
	2	20	5260 - 5320	11.940	10.77
	3	20	5500 - 5700	11.143	10.47
	4	20	5745 - 5825	9.616	9.83
802.11n	1	40	5190 - 5230	11.695	10.68
	2	40	5270 - 5310	12.531	10.98
	3	40	5510 - 5670	11.967	10.78
	4	40	5755 - 5795	9.750	9.89
802.11ac	1	80	5210	9.638	9.84
	2	80	5290	9.333	9.70
	3	80	5530	9.886	9.95
	4	80	5775	8.035	9.05

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033. Test results reported herein relate only to the item(s) tested. I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortencz
President




FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 1 of 104	

TABLE OF CONTENTS


FCC PART 15.407 MEASUREMENT REPORT		3
1.0 INTRODUCTION.....		4
1.1 SCOPE.....		4
1.2 PCTEST TEST LOCATION.....		4
2.0 PRODUCT INFORMATION		5
2.1 EQUIPMENT DESCRIPTION.....		5
2.2 DEVICE CAPABILITIES.....		5
2.3 TEST CONFIGURATION.....		5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....		5
2.5 LABELING REQUIREMENTS.....		5
3.0 DESCRIPTION OF TEST		6
3.1 EVALUATION PROCEDURE.....		6
3.2 AC LINE CONDUCTED EMISSIONS.....		6
3.3 RADIATED EMISSIONS		7
4.0 ANTENNA REQUIREMENTS.....		8
5.0 TEST EQUIPMENT CALIBRATION DATA.....		9
6.0 TEST RESULTS		10
6.1 SUMMARY.....		10
6.2 26DB BANDWIDTH MEASUREMENT – 802.11A/N/AC		11
6.3 UNII OUTPUT POWER MEASUREMENT – 802.11A/N/AC		34
6.4 PEAK POWER SPECTRAL DENSITY – 802.11A/N/AC		37
6.5 PEAK EXCURSION RATIO – 802.11A/N/AC.....		58
6.6 FREQUENCY STABILITY.....		62
6.7 RADIATED SPURIOUS EMISSION MEASUREMENTS.....		66
6.8 RADIATED BAND EDGE MEASUREMENTS (20MHZ BW)		75
6.9 RADIATED BAND EDGE MEASUREMENTS (40MHZ BW)		82
6.10 RADIATED BAND EDGE MEASUREMENTS (80MHZ BW)		89
6.11 LINE-CONDUCTED TEST DATA.....		96
7.0 CONCLUSION		104

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 2 of 104	



MEASUREMENT REPORT

FCC Part 15.407



§ 2.1033 General Information

APPLICANT: LG Electronics MobileComm U.S.A

APPLICANT ADDRESS: 60-39, Gasan-dong, Gumchon-gu,
Seoul, Korea,

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA

FCC RULE PART(S): Part 15.407

IC SPECIFICATION(S): RSS-210 Issue 8

MODEL NAME: LG-D803

FCC ID: ZNFD803

Test Device Serial No.: BT/WIFI Conduction, Production Pre-Production Engineering
BT/WIFI Radiation


FCC CLASSIFICATION: Unlicensed National Information Infrastructure (UNII)

DATE(S) OF TEST: 7/16 - 8/6/2013

TEST REPORT S/N: 0Y1307011142.ZNF



Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 3 of 104	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'tl (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.






Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 4 of 104

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFD803**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Band 4, 7, 17 LTE, 802.11a/b/g/n/ac WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC

Note: 5GHz WLAN (DTS/NII) operation is possible in 20MHz, 40MHz, and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of KDB 789033. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The maximum achievable duty cycles are as follows:

- 802.11a/n 20MHz Bandwidth – 95.5%
- 802.11n 40MHz Bandwidth – 90.1%
- 802.11ac 80MHz Bandwidth – 83.4%

2.3 Test Configuration

The LG Portable Handset FCC ID: ZNFD803 was tested per the guidance of KDB 789033. ANSI C63.10-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. U-NII procedures and limits were applied for operations in the frequency band from 5.725-5.850 GHz in accordance with KDB 644545 D02 v01 to demonstrate compliance with 15.247 requirements. See Sections 3.2, 3.3, and 6.1 of this test report for a description of the AC line conducted emissions, radiated emissions, and antenna port conducted emissions test setups, respectively.

2.4 EMI Suppression Device(s)/Modifications



No EMI suppression device(s) were added and/or no modifications were made during testing.

2.5 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5).

Please see attachment for FCC ID label and label location.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 5 of 104	

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009) and the guidance provided in KDB 789033 were used in the measurement of **LG Portable Handset FCC ID: ZNFD803**.

Deviation from measurement procedure.....None



3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 6.9. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 8.51.0.



FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 6 of 104	

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by varying: the mode of operation or resolution, clock or data rate, scrolling H pattern to the EUT and/or support equipment, and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 7 of 104	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **LG Portable Handset FCC ID: ZNFD803** unit complies with the requirement of §15.203.

Band 1		Band 2		Band 3		Band 4	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
:	:	:	:	:	:	:	:
42	5210	56	5280	116	5580	157	5785
:	:	:	:	:	:	:	:
48	5240	64	5320	144	5720	165	5825



Table 4-1. 802.11a / 802.11n (20MHz) Frequency / Channel Operations

Band 1		Band 2		Band 3		Band 4	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
:	:	:	:	:	:	:	:
46	5230	62	5310	110	5550	159	5795
				:	:		
				142	5710		

Table 4-2. 802.11n (40MHz BW) Frequency / Channel Operations

Band 1		Band 2		Band 3		Band 4	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
42	5210	58	5290	106	5530	155	5755

Table 4-3. 802.11ac (80MHz BW) Frequency / Channel Operations

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 8 of 104	

5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/29/2013	Annual	3/29/2014	N/A
-	WL25-1	Conducted Cable Set (25GHz)	1/16/2013	Annual	1/16/2014	N/A
-	WL40-1	Conducted Cable Set (40GHz)	1/17/2013	Annual	1/17/2014	N/A
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Agilent	N9030A	PXA Signal Analyzer (44GHz)	1/11/2013	Annual	1/11/2014	MY52350166
Anritsu	MA2411B	Pulse Sensor	9/19/2012	Annual	9/19/2013	1027293
Anritsu	ML2495A	Power Meter	10/11/2012	Annual	10/11/2013	1039008
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Biennial	7/22/2013	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/30/2012	Biennial	5/30/2014	135427
ETS Lindgren	3160-10	26.5-40 GHz Standard Gain Horn	6/6/2012	Biennial	6/6/2014	130993
Mini-Circuits	VHF-3100+	High Pass Filter	1/17/2013	Annual	1/17/2014	30841
Mini-Circuits	VHF-8400+	3.4GHz - 9.9GHz High Pass Filter	1/17/2013	Annual	1/17/2014	31048
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	5/31/2013	Annual	5/31/2014	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/31/2013	Annual	5/31/2014	100040
Rohde & Schwarz	ESU26	EMI Test Receiver	2/25/2013	Annual	2/25/2014	100342
Rohde & Schwarz	TS-PR40	26.5-40 GHz Pre-Amplifier	6/6/2012	Biennial	6/6/2014	100037
Solar Electronics	8012-50-R-24-BNC	LISN	6/20/2013	Biennial	6/20/2015	310233
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 5-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration due date that falls within the test date range, care was taken to ensure that this equipment was utilized prior to the calibration due date.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 9 of 104

6.0 TEST RESULTS

6.1 Summary



Company Name: LG Electronics MobileComm U.S.A
 FCC ID: ZNFD803
 Method/System: Unlicensed National Information Infrastructure (UNII)
 Data Rate(s) Tested: 6, 9, 12, 18, 24, 36, 48, 54Mbps (802.11a)
6.5/7.2, 13/14.4, 19.5/21.7, 26/28.9, 39/43.3, 52/57.8, 58.5/65, 65/72.2 (n – 20MHz)
13.5/15, 27/30, 40.5/45, 54/60, 81/90, 108/120, 121.5/135, 135/150 (n – 40MHz BW)
29.3/32.5Mbps, 58.5/65Mbps, 87.8/97.5Mbps, 117/130Mbps, 175.5/195Mbps,
234/260Mbps, 263.3/292.5Mbps, 292.5/325Mbps, 351/390Mbps, 390/433.3Mbps
(ac – 80MHz BW)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
N/A	RSS-210 [A9.2]	26dB Bandwidth [FCC] Occupied Bandwidth [IC]	N/A	CONDUCTED	PASS	Section 6.2
15.407 (a)(1)	RSS-210 [A9.2]	Maximum Conducted Output Power	< 4 + 10log ₁₀ (BW) dBm (5150-5250MHz) [FCC] < 10 + 10log ₁₀ (BW) dBm (5150-5250MHz) [IC] < 11 + 10log ₁₀ (B) dBm (5250-5350MHz, 5470 – 5725MHz)		PASS	Section 6.3
15.407 (a)(1), (5)	RSS-210 [A9.2]	Peak Power Spectral Density	< 4 dBm/MHz (5150-5250) [FCC] < 10dBm/MHz (5150-5250) [IC] < 11dBm/MHz (5250-5350) < 11dBm/MHz (5470-5725)		PASS	Section 6.4
15.407(a)(6)	N/A	Peak Excursion	< 13 dB/MHz maximum difference		PASS	Section 6.5
15.407(g)	N/A	Frequency Stability	N/A		PASS	Section 6.6
15.407(h)	RSS-210 [A9.3]	Dynamic Frequency Selection	See DFS Test Report		PASS	See DFS Test Report
15.407(b)(1), (2),(3)	RSS-210 [A9.2]	Undesirable Emissions	< -27 dBm/MHz EIRP (5150-5350MHz, 5470-5725MHz)	RADIATED	PASS	Section 6.7, 6.8
15.205, 15.407(b)(1), (5), (6)	RSS-Gen [7.2.3.2]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)		PASS	Section 6.9
15.207	RSS-Gen [7.2.2]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.11

Table 6-1. Summary of Test Results

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "UNII Automation", Version 2.0.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 10 of 104	

6.2 26dB Bandwidth Measurement – 802.11a/n/ac

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

The 26dB bandwidth is used to determine the conducted power limits.

Test Procedure Used

KDB 789033 v01r03 – Section D

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-1. Test Instrument & Measurement Setup



Test Notes


None

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 11 of 104	


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured 26dB Bandwidth [MHz]		Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured 26dB Bandwidth [MHz]
Band I	5180	36	a	6	20.43	Band III	5500	100	a	6	20.16
	5200	40	a	6	20.44		5580	116	a	6	20.29
	5240	48	a	6	20.21		5720	144	a	6	20.40
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	20.70		5500	100	n (20MHz)	6.5/7.2 (MCS0)	20.67
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	20.78		5580	116	n (20MHz)	6.5/7.2 (MCS0)	20.70
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	20.61		5720	144	n (20MHz)	6.5/7.2 (MCS0)	20.65
	5190	38	n (40MHz)	13.5/15 (MCS0)	39.80		5510	102	n (40MHz)	13.5/15 (MCS0)	39.66
	5230	46	n (40MHz)	13.5/15 (MCS0)	39.40		5550	110	n (40MHz)	13.5/15 (MCS0)	39.57
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	82.47		5710	142	n (40MHz)	13.5/15 (MCS0)	39.63
								5530	106	ac (80MHz)	29.3/32.5 (MCS0)
Band II	5260	52	a	6	20.35	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	82.18	
	5280	56	a	6	20.30	Band IV	5745	149	a	6	20.44
	5320	64	a	6	20.25		5785	157	a	6	20.17
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	20.73		5825	165	a	6	20.24
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	20.76		5745	149	n (20MHz)	6.5/7.2 (MCS0)	20.42
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	20.65		5785	157	n (20MHz)	6.5/7.2 (MCS0)	20.82
	5270	54	n (40MHz)	13.5/15 (MCS0)	39.57		5825	165	n (20MHz)	6.5/7.2 (MCS0)	20.58
	5310	62	n (40MHz)	13.5/15 (MCS0)	39.75		5755	151	n (40MHz)	13.5/15 (MCS0)	39.66
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	81.76		5795	159	n (40MHz)	13.5/15 (MCS0)	39.58
								5775	155	ac (80MHz)	29.3/32.5 (MCS0)

Table 6-2. Conducted Bandwidth Measurements

FCC ID: ZNFD803	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 12 of 104




Plot 6-1. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-2. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 13 of 104




Plot 6-3. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-4. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 14 of 104




Plot 6-5. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 6-6. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 15 of 104




Plot 6-7. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 6-8. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 16 of 104




Plot 6-9. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 6-10. 26dB Bandwidth Plot (802.11a (UNII Band 2) – Ch. 52)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 17 of 104




Plot 6-11. 26dB Bandwidth Plot (802.11a (UNII Band 2) – Ch. 56)




Plot 6-12. 26dB Bandwidth Plot (802.11a (UNII Band 2) – Ch. 64)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 18 of 104




Plot 6-13. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 52)




Plot 6-14. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 56)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 19 of 104




Plot 6-15. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 64)




Plot 6-16. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 54)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 20 of 104




Plot 6-17. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 62)




Plot 6-18. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2) – Ch. 58)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 21 of 104




Plot 6-19. 26dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 100)




Plot 6-20. 26dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 116)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 22 of 104




Plot 6-21. 26dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 144)




Plot 6-22. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 100)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 23 of 104




Plot 6-23. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 116)




Plot 6-24. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 144)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 24 of 104




Plot 6-25. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 102)




Plot 6-26. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 110)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 25 of 104




Plot 6-27. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 142)




Plot 6-28. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 106)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 26 of 104




Plot 6-29. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 138)




Plot 6-30. 26dB Bandwidth Plot (20MHz BW 802.11a (UNII Band 4) – Ch. 149)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 27 of 104




Plot 6-31. 26dB Bandwidth Plot (20MHz BW 802.11a (UNII Band 4) – Ch. 157)




Plot 6-32. 26dB Bandwidth Plot (20MHz BW 802.11a (UNII Band 4) – Ch. 165)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 28 of 104




Plot 6-33. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 4) – Ch. 149)




Plot 6-34. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 4) – Ch. 157)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 29 of 104




Plot 6-35. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 4) – Ch. 165)




Plot 6-36. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 4) – Ch. 151)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 30 of 104




Plot 6-37. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 4) – Ch. 159)




Plot 6-38. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 4) – Ch. 155)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 31 of 104




Plot 6-39. 20dB Bandwidth Plot (20MHz BW 802.11a (UNII Band 2) – Ch. 52)



Plot 6-40. 20dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 52)

Note: The 20dB bandwidth plot of the UNII Band 2 low channel for both 802.11a and 802.11n was found to be within 20MHz and is, therefore, operating solely within the UNII Band 2 frequencies as per KDB 644545 v01r01.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 32 of 104



Plot 6-41. 20dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2) – Ch. 58)

Note: The 20dB bandwidth plot of the UNII Band 2 low channel was found to be within 80MHz and is, therefore, operating solely within the UNII Band 2 frequencies as per KDB 644545 v01r01.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 33 of 104

6.3 UNII Output Power Measurement – 802.11a/n/ac §15.407 (a); RSS-210 [A9.2]

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033, and at the appropriate frequencies.

In the 5.15 – 5.25GHz band, the maximum permissible conducted output power is the lesser of 50mW (16.99dBm) and $4 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 4 \text{ dBm} + 10\log_{10}(20.21) = 17.06\text{dBm}$.

In the 5.25 – 5.35GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(20.25) = 24.06\text{dBm}$.

In the 5.47 – 5.725GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(20.16) = 24.04\text{dBm}$.

In the 5.725 – 5.825GHz band, the maximum permissible conducted output power is the lesser of 1000mW (30dBm) and $17 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 17 \text{ dBm} + 10\log_{10}(20.17) = 30.05\text{dBm}$.

Test Procedure Used

KDB 789033 v01r03 – Section E)3)b) Method PM-G
KDB 644545 D02 v01

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-2. Test Instrument & Measurement Setup

Test Notes

In the conducted power tables below, channels that straddle the upper UNII-3 and UNII-4 Band Edge at 5725MHz are highlighted in orange. These channels were evaluated in accordance with requirements of KDB 644545 D01 Section F(3). Accordingly, the power for the portion of the emission occurring within each UNII Band must comply with that particular power limit (i.e. UNII-3 = 250mW, UNII-4 = 1Watt). The powers shown in the tables that follow are the powers for the entire channel bandwidth. It is confirmed that the maximum conducted output power of the entire signal complies with the limits of the respective Band of operation. Therefore the portion of the signal within each band also complies with the limits for that band. Thus the highlighted channels comply with Part 15.407(a).



FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 34 of 104	

Mode	Freq [MHz]	Channel	Detector	802.11a Conducted Power [dBm]								
				Data Rate [Mbps]								
				6	9	12	18	24	36	48	54	
802.11a	5180	36	AVG	10.52	10.58	10.67	10.59	10.69	10.64	10.67	10.63	
802.11a	5200	40	AVG	10.65	10.87	10.80	10.89	10.79	10.81	10.86	10.41	
802.11a	5220	44	AVG	10.50	10.61	10.68	10.54	10.61	10.54	10.54	10.36	
802.11a	5240	48	AVG	10.48	10.42	10.46	10.45	10.45	10.48	10.49	10.25	
802.11a	5260	52	AVG	10.58	10.79	10.61	10.73	10.74	10.70	10.89	10.50	
802.11a	5280	56	AVG	10.73	10.76	10.76	10.70	10.70	10.65	10.80	10.55	
802.11a	5300	60	AVG	10.64	10.62	10.72	10.72	10.61	10.57	10.68	10.47	
802.11a	5320	64	AVG	10.66	10.65	10.62	10.65	10.60	10.52	10.60	10.43	
802.11a	5500	100	AVG	10.57	10.53	10.58	10.66	10.53	10.51	10.54	10.25	
802.11a	5520	104	AVG	10.44	10.40	10.56	10.46	10.49	10.32	10.43	10.29	
802.11a	5540	108	AVG	10.44	10.34	10.39	10.38	10.30	10.24	10.42	9.94	
802.11a	5560	112	AVG	9.94	9.92	9.97	9.92	10.02	9.82	10.05	9.85	
802.11a	5580	116	AVG	10.11	10.12	10.29	10.16	10.06	10.09	10.22	9.98	
802.11a	5660	132	AVG	9.89	9.87	9.94	9.84	9.81	9.91	9.93	9.71	
802.11a	5680	136	AVG	9.74	9.80	9.84	9.85	9.74	9.71	10.02	9.62	
802.11a	5700	140	AVG	9.63	9.75	9.71	9.69	9.66	9.73	9.89	9.45	
802.11a	5720	144	AVG	9.68	9.71	9.75	9.70	9.62	9.63	9.64	9.72	
802.11a	5745	149	AVG	9.63	9.84	9.84	9.76	9.73	9.60	9.71	9.48	
802.11a	5765	153	AVG	9.66	9.58	9.64	9.71	9.58	9.64	9.54	9.59	
802.11a	5785	157	AVG	9.20	9.58	9.50	9.60	9.18	9.70	9.85	9.64	
802.11a	5805	161	AVG	9.73	9.69	9.72	9.24	9.36	9.44	9.56	9.42	
802.11a	5825	165	AVG	9.44	9.45	9.50	9.57	9.67	9.49	9.70	9.34	

Table 6-3. 802.11a (UNII) Maximum Conducted Output Power

Mode	Freq [MHz]	Channel	Detector	20MHz BW 802.11n (5GHz) Conducted Power [dBm]								
				Data Rate [Mbps]								
				6.5/7.2	13/14.4	19.5/21.7	26/28.9	39/43.4	52/57.8	58.5/65	65/72.2	
802.11n	5180	36	AVG	10.57	10.60	10.54	10.51	10.47	10.47	10.42	10.46	
802.11n	5200	40	AVG	10.54	10.46	10.40	10.47	10.43	10.30	10.39	10.34	
802.11n	5220	44	AVG	10.41	10.43	10.48	10.35	10.27	10.27	10.35	10.29	
802.11n	5240	48	AVG	10.26	10.30	10.41	10.26	10.33	10.22	10.30	10.27	
802.11n	5260	52	AVG	10.77	10.62	10.68	10.64	10.60	10.62	10.60	10.62	
802.11n	5280	56	AVG	10.57	10.62	10.53	10.69	10.65	10.41	10.58	10.49	
802.11n	5300	60	AVG	10.52	10.52	10.53	10.53	10.52	10.51	10.49	10.43	
802.11n	5320	64	AVG	10.49	10.58	10.48	10.40	10.50	10.38	10.45	10.45	
802.11n	5500	100	AVG	10.36	10.29	10.33	10.43	10.42	10.28	10.43	10.38	
802.11n	5520	104	AVG	10.47	10.31	10.40	10.36	10.29	10.28	10.28	10.33	
802.11n	5540	108	AVG	10.31	10.35	10.37	10.27	10.36	10.33	10.32	10.31	
802.11n	5560	112	AVG	10.25	10.29	10.24	10.30	10.26	10.23	10.20	10.16	
802.11n	5580	116	AVG	10.19	10.26	10.14	10.15	10.19	10.19	10.20	10.11	
802.11n	5660	132	AVG	9.90	9.89	9.91	9.95	9.80	9.89	9.77	9.80	
802.11n	5680	136	AVG	9.82	9.81	9.75	9.82	9.74	9.83	9.73	9.72	
802.11n	5700	140	AVG	9.72	9.79	9.82	9.73	9.72	9.78	9.72	9.72	
802.11n	5720	144	AVG	9.76	9.72	9.78	9.71	9.64	9.69	9.66	9.67	
802.11n	5745	149	AVG	9.76	9.67	9.65	9.83	9.83	9.70	9.73	9.71	
802.11n	5765	153	AVG	9.78	9.71	9.66	9.51	9.64	9.61	9.56	9.50	
802.11n	5785	157	AVG	9.63	9.69	9.83	9.74	9.52	9.55	9.61	9.53	
802.11n	5805	161	AVG	9.64	9.53	9.48	9.58	9.53	9.54	9.48	9.54	
802.11n	5825	165	AVG	9.47	9.51	9.49	9.48	9.40	9.34	9.34	9.42	

Table 6-4. 20MHz BW 802.11n (UNII) Maximum Conducted Output Power

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 35 of 104	

Mode	Freq [MHz]	Channel	Detector	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
				Data Rate [Mbps]							
				13.5/15	27/30	40.5/45	54/60	81/90	108/120	121.5/135	135/150
802.11n	5190	38	AVG	10.68	10.39	10.38	10.61	10.42	10.66	10.36	10.38
802.11n	5230	46	AVG	10.65	10.19	10.54	10.41	9.95	10.41	10.57	10.54
802.11n	5270	54	AVG	10.94	10.56	10.71	10.98	10.75	10.62	10.98	10.97
802.11n	5310	62	AVG	10.59	10.40	10.80	10.89	10.37	10.82	10.51	10.35
802.11n	5510	102	AVG	10.62	10.43	10.57	10.48	10.49	10.40	10.43	10.36
802.11n	5550	110	AVG	10.78	10.47	10.45	10.42	10.33	10.57	10.27	10.26
802.11n	5670	134	AVG	10.11	10.07	9.89	10.14	9.82	9.86	10.13	9.76
802.11n	5710	142	AVG	10.01	10.06	10.00	9.97	9.97	9.96	10.03	10.00
802.11n	5755	151	AVG	9.31	9.08	9.25	9.41	9.39	9.30	9.39	9.25
802.11n	5795	159	AVG	9.89	9.31	9.19	9.23	9.29	9.83	9.60	9.79

Table 6-5. 40MHz BW 802.11n (UNII) Maximum Conducted Output Power

Mode	Freq [MHz]	Channel	Data Rate
			6.5Mbps
			MCS0
802.11ac	5180	36*	9.31
802.11ac	5200	40	9.38
802.11ac	5240	48*	9.42
802.11ac	5260	52*	9.77
802.11ac	5280	56	9.54
802.11ac	5320	64*	9.54
802.11ac	5500	100	9.51
802.11ac	5580	116*	9.20
802.11ac	5700	140	8.58
802.11ac	5720	144	9.19
802.11ac	5745	149*	8.61
802.11ac	5785	157*	8.46
802.11ac	5825	165	8.22



Table 6-6. 20MHz BW 802.11ac (UNII) Maximum Conducted Output Power

Mode	Freq [MHz]	Channel	Data Rate
			13.5Mbps
			MCS0
802.11ac	5190	38	9.66
802.11ac	5230	46	9.19
802.11ac	5270	54	9.56
802.11ac	5310	62	9.37
802.11ac	5510	102	9.49
802.11ac	5550	110	9.24
802.11ac	5670	134	8.86
802.11ac	5710	142	8.84
802.11ac	5755	151	8.12
802.11ac	5795	159	8.24

Table 6-7. 40MHz BW 802.11ac (UNII) Maximum Conducted Output Power

Mode	Freq [MHz]	Channel	Detector	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]									
				Data Rate [Mbps]									
				29.3/32.5	58.5/65	87.8/97.5	117/130	175.5/195	234/260	263.3/292.5	292.5/325	351/390	390/433.3
802.11ac	5210	42	AVG	9.75	9.73	9.63	9.68	9.74	9.69	9.84	9.69	9.69	9.59
802.11ac	5290	58	AVG	9.70	9.54	9.60	9.50	9.63	9.52	9.60	9.58	9.50	9.58
802.11ac	5530	106	AVG	9.83	9.80	9.73	9.72	9.70	9.82	9.95	9.78	9.72	9.70
802.11ac	5690	138	AVG	9.15	9.13	9.05	9.07	9.14	9.10	9.02	9.06	9.11	9.05
802.11ac	5775	155	AVG	9.04	8.94	8.95	8.98	9.01	8.99	9.02	9.05	8.96	8.84

Table 6-8. 80MHz BW 802.11ac (UNII) Maximum Conducted Output Power

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 36 of 104	

6.4 Peak Power Spectral Density – 802.11a/n/ac §15.407 (a)(1),(5) / RSS-210 [A9.2]

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033, and at the appropriate frequencies. Method SA-2, as defined in KDB 789033, was used to measure the power spectral density.

Test Procedure Used

KDB 789033 v01r03 – Section F
KDB 644545 D02 v01

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times$ (span/RBW)
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run.
9. Reference level offset = $10 \cdot \log(1/\text{duty cycle})$ was applied.
 - a. 802.11a/n (20MHz BW): $10 \cdot \log(1/95.5\%) = 0.20 \text{ dB}$
 - b. 802.11n (40MHz BW): $10 \cdot \log(1/90.1\%) = 0.41 \text{ dB}$
 - c. 802.11ac (80MHz BW): $10 \cdot \log(1/83.4\%) = 0.79 \text{ dB}$
10. Trace was averaged over 100 sweeps
11. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.









Figure 6-3. Test Instrument & Measurement Setup

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 37 of 104	


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density	Margin [dB]		Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density	Margin [dB]
Band I	5180	36	a	6	-0.107	4.0	-4.11	Band III	5500	100	a	6	-0.320	11.0	-11.32
	5200	40	a	6	-0.107	4.0	-4.11		5580	116	a	6	-0.426	11.0	-11.43
	5240	48	a	6	0.147	4.0	-3.85		5720	144	a	6	-0.850	11.0	-11.85
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	-0.524	4.0	-4.52		5500	100	n (20MHz)	6.5/7.2 (MCS0)	-0.688	11.0	-11.69
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	-0.568	4.0	-4.57		5580	116	n (20MHz)	6.5/7.2 (MCS0)	-0.702	11.0	-11.70
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	-0.347	4.0	-4.35		5720	144	n (20MHz)	6.5/7.2 (MCS0)	-0.970	11.0	-11.97
	5190	38	n (40MHz)	13.5/15 (MCS0)	-3.174	4.0	-7.17		5510	102	n (40MHz)	13.5/15 (MCS0)	-3.374	11.0	-14.37
	5230	46	n (40MHz)	13.5/15 (MCS0)	-3.506	4.0	-7.51		5550	110	n (40MHz)	13.5/15 (MCS0)	-3.505	11.0	-14.51
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-6.988	4.0	-10.99		5710	142	n (40MHz)	13.5/15 (MCS0)	-3.570	11.0	-14.57
	5260	52	a	6	0.151	11.0	-10.85		5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-7.106	11.0	-18.11
Band II	5280	56	a	6	0.079	11.0	-10.92	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	-8.340	11.0	-19.34	
	5320	64	a	6	0.038	11.0	-10.96	5745	149	a	6	-0.630	11.0	-11.63	
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	-0.375	11.0	-11.38	5785	157	a	6	-2.000	11.0	-13.00	
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	0.000	11.0	-11.00	5825	165	a	6	-2.380	11.0	-13.38	
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	-0.142	11.0	-11.14	5745	149	n (20MHz)	6.5/7.2 (MCS0)	-1.560	11.0	-12.56	
	5270	54	n (40MHz)	13.5/15 (MCS0)	-2.831	11.0	-13.83	5785	157	n (20MHz)	6.5/7.2 (MCS0)	-2.080	11.0	-13.08	
	5310	62	n (40MHz)	13.5/15 (MCS0)	-3.279	11.0	-14.28	5825	165	n (20MHz)	6.5/7.2 (MCS0)	-2.700	11.0	-13.70	
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-7.102	11.0	-18.10	5755	151	n (40MHz)	13.5/15 (MCS0)	-4.670	11.0	-15.67	
								5795	159	n (40MHz)	13.5/15 (MCS0)	-4.680	11.0	-15.68	
								5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-9.110	11.0	-20.11	

Table 6-9. Conducted Power Spectral Density Measurements

FCC ID: ZNFD803	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 38 of 104




Plot 6-42. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-43. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 39 of 104




Plot 6-44. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-45. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 40 of 104




Plot 6-46. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 6-47. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 41 of 104




Plot 6-48. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 6-49. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 42 of 104




Plot 6-50. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 6-51. Peak Power Spectral Density Plot (802.11a (UNII Band 2) – Ch. 52)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 43 of 104




Plot 6-52. Peak Power Spectral Density Plot (802.11a (UNII Band 2) – Ch. 56)




Plot 6-53. Peak Power Spectral Density Plot (802.11a (UNII Band 2) – Ch. 64)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 44 of 104




Plot 6-54. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 52)




Plot 6-55. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 56)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 45 of 104




Plot 6-56. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 64)




Plot 6-57. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 54)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 46 of 104




Plot 6-58. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 62)




Plot 6-59. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2) – Ch. 58)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 47 of 104




Plot 6-60. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 100)




Plot 6-61. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 116)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 48 of 104




Plot 6-62. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 144)




Plot 6-63. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 100)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 49 of 104




Plot 6-64. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 116)




Plot 6-65. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 144)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 50 of 104




Plot 6-66. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 102)




Plot 6-67. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 110)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 51 of 104




Plot 6-68. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 142)




Plot 6-69. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 106)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 52 of 104




Plot 6-70. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 138)




Plot 6-71. Peak Power Spectral Density Plot (20MHz BW 802.11a (UNII Band 4) – Ch. 149)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 53 of 104




Plot 6-72. Peak Power Spectral Density Plot (20MHz BW 802.11a (UNII Band 4) – Ch. 157)




Plot 6-73. Peak Power Spectral Density Plot (20MHz BW 802.11a (UNII Band 4) – Ch. 165)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 54 of 104




Plot 6-74. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 4) – Ch. 149)




Plot 6-75. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 4) – Ch. 157)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 55 of 104




Plot 6-76. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 4) – Ch. 165)




Plot 6-77. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 4) – Ch. 151)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 56 of 104



Plot 6-78. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 4) – Ch. 159)



Plot 6-79. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 4) – Ch. 155)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 57 of 104

6.5 Peak Excursion Ratio – 802.11a/n/ac §15.407(a)(6)

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033, and at the appropriate frequencies. Method SA-2, as defined in KDB 789033, was used to capture the average trace used to make the peak excursion measurement.

The largest permissible difference between the modulation envelope (measured using a peak hold function) and the maximum power spectral density is 13 dBm/MHz.

Test Procedure Used

KDB 789033 v01r03 – Section G
KDB 644545 D02 v01

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize
8. The peak search function of the spectrum analyzer was used to find the peak of the spectrum. This level was compared to the peak power density level found from the previous section to determine the peak excursion.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-4. Test Instrument & Measurement Setup


Test Notes

The peak excursion was investigated for all signal types, modulation types, channel bandwidths, and variations in signal parameters and the worst case data is shown below. Only the worst case modulation mode on a single channel among all bands is reported since that is sufficient to demonstrate compliance to the peak excursion requirement per KDB 789033 v01r03.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 58 of 104	


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Peak Excursion Ratio [dBm]	Max Permissible Peak Excursion Ratio [dBm/MHz]	Margin [dB]
5240	48	a	6	7.76	13.0	-5.24
5500	100	n (20MHz)	6.5/7.2 (MCS0)	8.35	13.0	-4.65
5510	102	n (40MHz)	13.5/15 (MCS0)	7.95	13.0	-5.05
5530	106	ac (80MHz)	29.3/32.5 (MCS0)	8.03	13.0	-4.97

Table 6-10. Conducted Peak Excursion Ratio Measurements




Plot 6-80. Peak Excursion Ratio Plot (802.11a)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 59 of 104




Plot 6-81. Peak Excursion Ratio Plot (20MHz BW 802.11n)



Plot 6-82. Peak Excursion Ratio Plot (40MHz BW 802.11n)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 60 of 104



Plot 6-83. Peak Excursion Ratio Plot (80MHz BW 802.11ac)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 61 of 104

6.6 Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,180,000,000 Hz
 CHANNEL: 36
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,180,000,026	26	0.00000050
100 %		- 30	5,180,000,005	5	0.00000010
100 %		- 20	5,180,000,003	3	0.00000005
100 %		- 10	5,180,000,010	10	0.00000020
100 %		0	5,180,000,014	14	0.00000028
100 %		+ 10	5,180,000,021	21	0.00000040
100 %		+ 20	5,180,000,006	6	0.00000011
100 %		+ 30	5,180,000,015	15	0.00000029
100 %		+ 40	5,180,000,019	19	0.00000037
100 %		+ 50	5,180,000,012	12	0.00000024
115 %	4.37	+ 20	5,180,000,011	11	0.00000020
BATT. ENDPOINT	3.40	+ 20	5,180,000,026	26	0.00000051

Table 6-11. Frequency Stability Measurements for UNII Band 1 (Ch. 36)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 62 of 104	

Frequency Stability (Cont'd)

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,260,000,000 Hz
 CHANNEL: 52
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,260,000,019	19	0.00000036
100 %		- 30	5,260,000,029	29	0.00000055
100 %		- 20	5,260,000,012	12	0.00000024
100 %		- 10	5,260,000,004	4	0.00000008
100 %		0	5,260,000,004	4	0.00000008
100 %		+ 10	5,260,000,001	1	0.00000002
100 %		+ 20	5,260,000,013	13	0.00000024
100 %		+ 30	5,260,000,005	5	0.00000010
100 %		+ 40	5,260,000,019	19	0.00000036
100 %		+ 50	5,260,000,025	25	0.00000048
115 %	4.37	+ 20	5,260,000,008	8	0.00000015
BATT. ENDPOINT	3.40	+ 20	5,260,000,029	29	0.00000055

Table 6-12. Frequency Stability Measurements for UNII Band 2 (Ch. 52)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 63 of 104	

Frequency Stability (Cont'd)

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,500,000,000 Hz
 CHANNEL: 100
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,500,000,020	20	0.00000036
100 %		- 30	5,500,000,021	21	0.00000038
100 %		- 20	5,500,000,029	29	0.00000052
100 %		- 10	5,500,000,027	27	0.00000048
100 %		0	5,500,000,004	4	0.00000007
100 %		+ 10	5,500,000,019	19	0.00000035
100 %		+ 20	5,500,000,023	23	0.00000042
100 %		+ 30	5,500,000,019	19	0.00000034
100 %		+ 40	5,500,000,014	14	0.00000026
100 %		+ 50	5,500,000,006	6	0.00000011
115 %		4.37	+ 20	5,500,000,007	7
BATT. ENDPOINT	3.40	+ 20	5,500,000,002	2	0.00000003

Table 6-13. Frequency Stability Measurements for UNII Band 3 (Ch. 100)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 64 of 104	

Frequency Stability (Cont'd)

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.



OPERATING FREQUENCY: 5,745,000,000 Hz
 CHANNEL: 149
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,745,000,010	10	0.00000018
100 %		- 30	5,745,000,018	18	0.00000032
100 %		- 20	5,745,000,016	16	0.00000027
100 %		- 10	5,745,000,008	8	0.00000013
100 %		0	5,745,000,013	13	0.00000023
100 %		+ 10	5,745,000,015	15	0.00000026
100 %		+ 20	5,745,000,012	12	0.00000021
100 %		+ 30	5,745,000,005	5	0.00000009
100 %		+ 40	5,745,000,015	15	0.00000027
100 %		+ 50	5,745,000,003	3	0.00000006
115 %	4.37	+ 20	5,745,000,014	14	0.00000024
BATT. ENDPOINT	3.40	+ 20	5,745,000,001	1	0.00000001

Table 6-14. Frequency Stability Measurements for UNII Band 4 (Ch. 149)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 65 of 104	

6.7 Radiated Spurious Emission Measurements

§15.407(b)(1), (6), §15.205, §15.209; RSS-210 [A9.2]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20/40 MHz BW), and 802.11ac (20/40/80 MHz BW)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-15 per Section 15.209.

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-15. Radiated Limits

Test Procedures Used



KDB 789033 v01r03 – Section H

KDB 644545 D02 v01

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 66 of 104	

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-5. Test Instrument & Measurement Setup

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 67 of 104	

Test Notes

1. All radiated spurious emissions levels were measured in a radiated test setup per the guidance of KDB 789033 v01r03 Section H.
2. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-11. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. Average levels at -135dBm and peak levels at -125dBm represent the analyzer noise floor and signify that no emission was detected.
8. No radiated spurious emissions were detected in Band 1 from 5150 – 5250MHz while the EUT was transmitting in Band 2.

Sample Calculations



Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 6.8 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + 10 \text{ dB Attenuator}) - \text{Preamplifier Gain}$$
- A duty cycle correction equal to $10 \cdot \log(1/\text{duty cycle})$ was added to the formula above for average measurements.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 68 of 104	

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10360.00	-97.89	Peak	H	48.17	0.00	57.28	68.20	-10.92
* 15540.00	-135.00	Average	H	54.56	0.00	26.56	53.98	-27.42
* 15540.00	-125.00	Peak	H	54.56	0.00	36.56	73.98	-37.42
* 20720.00	-101.48	Average	H	44.53	-9.54	40.51	53.98	-13.47
* 20720.00	-100.37	Peak	H	44.53	-9.54	41.62	73.98	-32.36
25900.00	-125.00	Peak	H	43.10	0.00	25.10	68.20	-43.10

Table 6-16. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10400.00	-97.80	Peak	H	48.09	0.00	57.29	68.20	-10.91
* 15600.00	-135.00	Average	H	54.42	0.00	26.42	53.98	-27.56
* 15600.00	-125.00	Peak	H	54.42	0.00	36.42	73.98	-37.56
* 20800.00	-103.21	Average	H	44.49	-9.54	38.74	53.98	-15.24
* 20800.00	-100.69	Peak	H	44.49	-9.54	41.26	73.98	-32.72
26000.00	-125.00	Peak	H	42.76	0.00	24.76	68.20	-43.44

Table 6-17. Radiated Measurements

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10480.00	-97.77	Peak	H	48.03	0.00	57.26	68.20	-10.94
* 15720.00	-135.00	Average	H	54.45	0.00	26.45	53.98	-27.53
* 15720.00	-125.00	Peak	H	54.45	0.00	36.45	73.98	-37.53
* 20960.00	-104.80	Average	H	44.47	-9.54	37.13	53.98	-16.85
* 20960.00	-101.37	Peak	H	44.47	-9.54	40.56	73.98	-33.42
26200.00	-125.00	Peak	H	42.71	0.00	24.71	68.20	-43.49

Table 6-18. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10520.00	-97.77	Peak	H	48.18	0.00	57.40	68.20	-10.80
* 15780.00	-135.00	Average	H	54.53	0.00	26.53	53.98	-27.45
* 15780.00	-125.00	Peak	H	54.53	0.00	36.53	73.98	-37.45
* 21040.00	-104.48	Average	H	44.53	-9.54	37.51	53.98	-16.47
* 21040.00	-102.82	Peak	H	44.53	-9.54	39.17	73.98	-34.81
26300.00	-125.00	Peak	H	43.10	0.00	25.10	68.20	-43.10

Table 6-19. Radiated Measurements

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10560.00	-98.02	Peak	H	48.49	0.00	57.47	68.20	-10.73
* 15840.00	-135.00	Average	H	54.66	0.00	26.66	53.98	-27.32
* 15840.00	-125.00	Peak	H	54.66	0.00	36.66	73.98	-37.32
* 21120.00	-104.55	Average	H	44.49	-9.54	37.40	53.98	-16.58
* 21120.00	-102.52	Peak	H	44.49	-9.54	39.43	73.98	-34.55
26400.00	-125.00	Peak	H	42.76	0.00	24.76	68.20	-43.44

Table 6-20. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 10640.00	-106.30	Average	H	49.07	0.00	49.76	53.98	-4.22
* 10640.00	-96.17	Peak	H	49.07	0.00	59.89	73.98	-14.09
* 15960.00	-135.00	Average	H	54.99	0.00	26.99	53.98	-26.99
* 15960.00	-125.00	Peak	H	54.99	0.00	36.99	73.98	-36.99
* 21280.00	-105.34	Average	H	44.47	-9.54	36.59	53.98	-17.39
* 21280.00	-101.66	Peak	H	44.47	-9.54	40.27	73.98	-33.71
26600.00	-125.00	Peak	H	42.71	0.00	24.71	68.20	-43.49

Table 6-21. Radiated Measurements

Radiated Spurious Emission Measurements (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100



Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11000.00	-106.92	Average	H	49.89	0.00	49.97	53.98	-4.01
* 11000.00	-98.03	Peak	H	49.89	0.00	58.86	73.98	-15.12
16500.00	-125.00	Peak	H	56.14	0.00	38.14	68.20	-30.06
22000.00	-101.19	Peak	H	44.53	-9.54	40.80	68.20	-27.40
27500.00	-125.00	Peak	H	43.10	0.00	25.10	68.20	-43.10

Table 6-22. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5580MHz
 Channel: 116

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11160.00	-106.21	Average	H	50.05	0.00	50.84	53.98	-3.14
* 11160.00	-97.37	Peak	H	50.05	0.00	59.68	73.98	-14.30
16740.00	-125.00	Peak	H	56.20	0.00	38.20	68.20	-30.00
* 22320.00	-104.63	Average	H	44.49	-9.54	37.32	53.98	-16.66
* 22320.00	-102.21	Peak	H	44.49	-9.54	39.74	73.98	-34.24
27900.00	-125.00	Peak	H	42.76	0.00	24.76	68.20	-43.44

Table 6-23. Radiated Measurements

FCC ID: ZNFD803	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 72 of 104

Radiated Spurious Emission Measurements (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5700MHz
 Channel: 140



Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11400.00	-106.29	Average	H	49.82	0.00	50.53	53.98	-3.45
* 11400.00	-98.26	Peak	H	49.82	0.00	58.56	73.98	-15.42
17100.00	-125.00	Peak	H	57.45	0.00	39.45	68.20	-28.75
* 22800.00	-105.47	Average	H	44.47	-9.54	36.46	53.98	-17.52
* 22800.00	-101.93	Peak	H	44.47	-9.54	40.00	73.98	-33.98
28500.00	-125.00	Peak	H	42.71	0.00	24.71	68.20	-43.49

Table 6-24. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11490.00	-112.86	Avg	H	50.95	0.00	45.09	53.98	-8.89
* 11490.00	-101.09	Peak	H	50.95	0.00	56.86	73.98	-17.12
17235.00	-125.00	Peak	H	59.91	0.00	41.91	68.20	-26.29
* 22980.00	-114.87	Avg	H	63.39	-9.54	45.98	53.98	-8.00
* 22980.00	-103.06	Peak	H	63.39	-9.54	57.79	73.98	-16.19
287235.00	-125.00	Peak	H	43.10	0.00	25.10	68.20	-43.10

Table 6-25. Radiated Measurements

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 73 of 104

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11570.00	-112.86	Avg	H	50.24	0.00	44.39	53.98	-9.59
* 11570.00	-100.60	Peak	H	50.24	0.00	56.65	73.98	-17.33
17355.00	-125.00	Peak	H	59.73	0.00	41.73	68.20	-26.47
23140.00	-125.00	Peak	H	44.49	0.00	26.49	68.20	-41.71
28925.00	-125.00	Peak	H	42.76	0.00	24.76	68.20	-43.44

Table 6-26. Radiated Measurements


Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
* 11650.00	-112.82	Avg	H	50.33	0.00	44.51	53.98	-9.47
* 11650.00	-100.87	Peak	H	50.33	0.00	56.46	73.98	-17.52
17475.00	-125.00	Peak	H	59.67	0.00	41.67	68.20	-26.53
23300.00	-125.00	Peak	H	44.47	0.00	26.47	68.20	-41.73
29125.00	-125.00	Peak	H	42.71	0.00	24.71	68.20	-43.49

Table 6-27. Radiated Measurements

6.8 Radiated Band Edge Measurements (20MHz BW) §15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36



Date: 17.JUL.2013 15:51:37


Plot 6-84. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 75 of 104	

Radiated Band Edge Measurements (20MHz BW) (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]



*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz 58.39 dBμV
SWT 20 ms 5.148910256 GHz




Date: 17.JUL.2013 15:52:18

Plot 6-85. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 76 of 104

Radiated Band Edge Measurements (20MHz BW) (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64




Date: 17.JUL.2013 16:23:08

Plot 6-86. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 77 of 104	

Radiated Band Edge Measurements (20MHz BW) (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]



Date: 17.JUL.2013 16:24:35


Plot 6-87. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 78 of 104	

Radiated Band Edge Measurements (20MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100




Date: 17.JUL.2013 16:29:22

Plot 6-88. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 3)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 79 of 104	

Radiated Band Edge Measurements (20MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]




Date: 17.JUL.2013 16:31:30

Plot 6-89. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 3)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 80 of 104	

Radiated Band Edge Measurements (20MHz BW) (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (20MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Date: 6.AUG.2013 21:06:04

Plot 6-90. Radiated Non-restricted Upper Band Edge Plot (Peak – UNII Band 4)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 81 of 104	

6.9 Radiated Band Edge Measurements (40MHz BW) §15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38




Date: 17.JUL.2013 16:01:15

Plot 6-91. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 82 of 104	

Radiated Band Edge Measurements (40MHz BW) (Cont'd) §15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]



Date: 17.JUL.2013 16:00:27


Plot 6-92. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 83 of 104	

Radiated Band Edge Measurements (40MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5310MHz
 Channel: 62




Date: 17.JUL.2013 16:18:00

Plot 6-93. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2)

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 84 of 104

Radiated Band Edge Measurements (40MHz BW) (Cont'd) §15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]



Date: 17.JUL.2013 16:17:24


Plot 6-94. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 85 of 104	

Radiated Band Edge Measurements (40MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102




Date: 17.JUL.2013 16:37:33

Plot 6-95. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 3)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 86 of 104	

Radiated Band Edge Measurements (40MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]




Date: 17.JUL.2013 16:35:51

Plot 6-96. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 3)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 87 of 104

Radiated Band Edge Measurements (40MHz BW) (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159




Date: 6.AUG.2013 21:09:13

Plot 6-97. Radiated Non-restricted Upper Band Edge Plot (Peak – UNII Band 4)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 88 of 104	

6.10 Radiated Band Edge Measurements (80MHz BW) §15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42




Date: 17.JUL.2013 16:05:48

Plot 6-98. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 89 of 104	

Radiated Band Edge Measurements (80MHz BW) (Cont'd) §15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]



Date: 17.JUL.2013 16:06:55


Plot 6-99. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 90 of 104	

Radiated Band Edge Measurements (80MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58




Date: 17.JUL.2013 16:11:52

Plot 6-100. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 91 of 104	

Radiated Band Edge Measurements (80MHz BW) (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]



Date: 17.JUL.2013 16:13:42


Plot 6-101. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 92 of 104

Radiated Band Edge Measurements (80MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106




Date: 17.JUL.2013 16:48:57

Plot 6-102. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 3)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 93 of 104	

Radiated Band Edge Measurements (80MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]




Date: 17.JUL.2013 16:51:33

Plot 6-103. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 3)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 94 of 104

Radiated Band Edge Measurements (80MHz BW) (Cont'd)
§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11ac (80MHz)
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155




Date: 6.AUG.2013 21:10:27

Plot 6-104. Radiated Non-restricted Upper Band Edge Plot (Peak – UNII Band 4)

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 95 of 104

6.11 Line-Conducted Test Data

§15.207; RSS-Gen [7.2.2]



Plot 6-105. Line Conducted Plot with 802.11a UNII Band 1 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.294	L1	0.1	46.50	60.40	13.90	40.60	50.40	9.80
0.436	L1	0.0	41.10	57.10	16.00	27.90	47.10	19.20
0.524	L1	0.0	41.50	56.00	14.50	27.30	46.00	18.70
0.591	L1	0.0	41.00	56.00	15.00	31.90	46.00	14.10
0.974	L1	0.1	37.10	56.00	18.90	22.20	46.00	23.80
1.667	L1	0.2	43.80	56.00	12.20	28.70	46.00	17.30

Table 6-28. Line Conducted Data with 802.11a UNII Band 1 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 96 of 104

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



— FCC Part 15 Class B Voltage on Mains QP.LimitLine — FCC Part 15 Class B Voltage on Mains AV.LimitLine — Preview Result 1-PK+
▼ Final Result 1-QPK ◆ Final Result 2-AVG

Plot 6-106. Line Conducted Plot with 802.11a UNII Band 1 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.589	N	0.1	41.40	56.00	14.60	31.80	46.00	14.20
1.615	N	0.2	40.20	56.00	15.80	28.00	46.00	18.00
1.658	N	0.2	41.60	56.00	14.40	28.20	46.00	17.80
1.703	N	0.2	38.90	56.00	17.10	27.40	46.00	18.60
1.745	N	0.2	38.60	56.00	17.40	27.60	46.00	18.40
1.788	N	0.2	38.30	56.00	17.70	27.00	46.00	19.00

Table 6-29. Line Conducted Data with 802.11a UNII Band 1 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 97 of 104

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-107. Line Conducted Plot with 802.11a UNII Band 2 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.294	L1	0.1	46.30	60.40	14.10	41.10	50.40	9.30
0.454	L1	0.0	39.10	56.80	17.70	21.10	46.80	25.70
0.809	L1	0.1	40.30	56.00	15.70	24.80	46.00	21.20
1.660	L1	0.2	44.00	56.00	12.00	30.30	46.00	15.70
4.632	L1	0.3	33.90	56.00	22.10	25.10	46.00	20.90
7.546	L1	0.4	39.50	60.00	20.50	33.70	50.00	16.30

Table 6-30. Line Conducted Data with 802.11a UNII Band 2 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 98 of 104

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-108. Line Conducted Plot with 802.11a UNII Band 2 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
1.577	N	0.2	38.30	56.00	17.70	26.30	46.00	19.70
1.619	N	0.2	39.50	56.00	16.50	27.40	46.00	18.60
1.660	N	0.2	39.50	56.00	16.50	28.10	46.00	17.90
1.703	N	0.2	39.30	56.00	16.70	27.50	46.00	18.50
1.745	N	0.2	38.60	56.00	17.40	27.60	46.00	18.40
1.788	N	0.2	38.50	56.00	17.50	27.30	46.00	18.70

Table 6-31. Line Conducted Data with 802.11a UNII Band 2 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 99 of 104

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-109. Line Conducted Plot with 802.11a UNII Band 3 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.296	L1	0.1	45.80	60.30	14.50	40.00	50.30	10.30
0.445	L1	0.0	40.30	57.00	16.70	25.90	47.00	21.10
0.789	L1	0.1	41.90	56.00	14.10	29.80	46.00	16.20
1.664	L1	0.2	44.70	56.00	11.30	31.60	46.00	14.40
4.562	L1	0.3	34.20	56.00	21.80	25.10	46.00	20.90
7.580	L1	0.4	39.50	60.00	20.50	33.40	50.00	16.60

Table 6-32. Line Conducted Plot with 802.11a UNII Band 3 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 100 of 104

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-110. Line Conducted Plot with 802.11a UNII Band 3 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
1.586	N	0.2	38.60	56.00	17.40	26.70	46.00	19.30
1.622	N	0.2	39.80	56.00	16.20	27.80	46.00	18.20
1.664	N	0.2	39.50	56.00	16.50	28.00	46.00	18.00
1.709	N	0.2	40.30	56.00	15.70	27.60	46.00	18.40
1.752	N	0.2	39.00	56.00	17.00	27.60	46.00	18.40
1.797	N	0.2	38.70	56.00	17.30	27.30	46.00	18.70

Table 6-33. Line Conducted Data with 802.11a UNII Band 3 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AV Limit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 101 of 104

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



— FCC Part 15 Class B Voltage on Mains QP.LimitLine
 — FCC Part 15 Class B Voltage on Mains AV.LimitLine
 — Preview Result 1-PK+
 ▲ Final Result 1-QPK
 ◆ Final Result 2-AVG

Plot 6-111. Line Conducted Plot with 802.11a UNII Band 4 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.294	L1	0.1	46.60	60.40	13.80	40.70	50.40	9.70
0.454	L1	0.0	42.10	56.80	14.70	29.10	46.80	17.70
0.715	L1	0.1	37.30	56.00	18.70	24.10	46.00	21.90
1.664	L1	0.2	43.70	56.00	12.30	29.30	46.00	16.70
2.582	L1	0.2	41.60	56.00	14.40	28.50	46.00	17.50
4.583	L1	0.3	35.40	56.00	20.60	25.70	46.00	20.30

Table 6-34. Line Conducted Data with 802.11a UNII Band 4 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 157. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBµV) – QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 102 of 104

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-112. Line Conducted Plot with 802.11a UNII Band 4 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
1.586	N	0.2	38.60	56.00	17.40	26.70	46.00	19.30
1.622	N	0.2	39.80	56.00	16.20	27.80	46.00	18.20
1.664	N	0.2	39.50	56.00	16.50	28.00	46.00	18.00
1.709	N	0.2	40.30	56.00	15.70	27.60	46.00	18.40
1.752	N	0.2	39.00	56.00	17.00	27.60	46.00	18.40
1.797	N	0.2	38.70	56.00	17.30	27.30	46.00	18.70

Table 6-35. Line Conducted Data with 802.11a UNII Band 4 (N)



Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 157. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBµV) – QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFD803	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset		Page 103 of 104

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFD803** is in compliance with Part 15E of the FCC Rules.

FCC ID: ZNFD803		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307011142.ZNF	Test Dates: 7/16 - 8/6/2013	EUT Type: Portable Handset	Page 104 of 104	