



# SAR TEST REPORT

HCT CO., LTD

EUT Type:	Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN
FCC ID:	ZNFE425J
Model:	LG-E425j
Additional Model	LG-E425J, LGE425J, E425J, E425j, LGE425j
Date of Issue:	Apr.03, 2013
Test report No.:	HCTA1303FS01
Test Laboratory:	<b>HCT CO., LTD.</b> 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea TEL: +82 31 645 6300 FAX: +82 31 645 6401
Applicant :	<b>LG Electronics, MobileComm U.S.A., Inc.</b> 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
Testing has been carried out in accordance with:	RSS-102 Issue 4; Health Canada Safety Code 6 47CFR §2.1093 FCC OET Bulletin 65(Edition 97-01), Supplement C (Edition 01-01) ANSI/ IEEE C95.1 – 1992 IEEE 1528-2003
Test result:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.
Signature	 
	<hr/> <p>Report prepared by : Young-Soo Jang Test Engineer of SAR Part</p> <hr/> <p>Approved by : Jae-Sang So Manager of SAR Part</p>

---

## Table of Contents

---

<b><u>1. INTRODUCTION</u></b> .....	4
<b><u>2. TEST METHODOLOGY</u></b> .....	5
<b><u>3. DESCRIPTION OF DEVICE</u></b> .....	6
<b><u>4. DESCRIPTION OF TEST EQUIPMENT</u></b> .....	7
<b><u>5. SAR MEASUREMENT PROCEDURE</u></b> .....	14
<b><u>6. DESCRIPTION OF TEST POSITION</u></b> .....	16
<b><u>7. MEASUREMENT UNCERTAINTY</u></b> .....	18
<b><u>8. ANSI/ IEEE C95.1 - 1992 RF EXPOSURE LIMITS</u></b> .....	19
<b><u>9. SAR SYSTEM VALIDATION</u></b> .....	20
<b><u>10. SYSTEM VERIFICATION</u></b> .....	21
<b><u>11. RF CONDUCTED POWER MEASUREMENT</u></b> .....	23
<b><u>12. SAR Test configuration &amp; Antenna Information</u></b> .....	32
<b><u>13. SAR TEST DATA SUMMARY</u></b> .....	33
13.1 Measurement Results (GSM 850 Head SAR) .....	33
13.2 Measurement Results (GSM 1 900 Head SAR) .....	34
13.3 Measurement Results (WCDMA 1 900 Head SAR) .....	35
13.4 Measurement Results (802.11b/g/n Head SAR) .....	36
13.5 Measurement Results (GSM850 Hotspot SAR) .....	37
13.6 Measurement Results (GSM1900 Hotspot SAR) .....	38
13.9 Measurement Results (WCDMA 1 900 Hotspot SAR) .....	39
13.10 Measurement Results (802.11b/g/n Hotspot SAR) .....	40
13.11 Measurement Results (Body-worn SAR) .....	41
<b><u>14. SAR Measurement Variability and Uncertainty</u></b> .....	42
<b><u>15. SAR Summation Scenario</u></b> .....	43
<b><u>16. CONCLUSION</u></b> .....	46
<b><u>17. REFERENCES</u></b> .....	47
<b>Attachment 1. – SAR Test Plots</b> .....	48
<b>Attachment 2. – Dipole Verification Plots</b> .....	105
<b>Attachment 3. – Probe Calibration Data</b> .....	112
<b>Attachment 4. – Dipole Calibration Data</b> .....	124

## **Version**

Rev	DATE	DESCRIPTION
	Mar. 27, 2013	First Approval Report
1	Apr. 3, 2013	Page 43, 44 is reviewed

## 1. INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017. The measurement procedure described in IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

### SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative of the incremental electromagnetic energy ( $dW$ ) absorbed by (dissipated in) an incremental mass ( $dm$ ) contained in a volume element ( $dV$ ) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body.

$$S A R = \frac{d}{d t} \left( \frac{d U}{d m} \right) = \frac{d}{d t} \left( \frac{d U}{\rho d v} \right)$$

**Figure 2. SAR Mathematical Equation**

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$S A R = \sigma E^2 / \rho$$

where:

$\sigma$  = conductivity of the tissue-simulant material (S/m)

$\rho$  = mass density of the tissue-simulant material (kg/m<sup>3</sup>)

$E$  = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

## **2. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with FCC OET Bulletin 65 Supplement C 01-01, IEEE Standard 1528-2003 & IEEE 1528a-2005 and the following published KDB procedures.

- FCC KDB Publication 941225 D01 SAR test for 3G devices v02
- FCC KDB Publication 941225 D02 Guidance for 3GPP R6 and R7 HSPA v02v01
- FCC KDB Publication 941225 D03 SAR Test Reduction GSM GPRS EDGE v01
- FCC KDB Publication 941225 D04 SAR for GSM E GPRS Dual Xfer Mode v01
- FCC KDB Publication 941225 D06 Hot Spot SAR v01
- FCC KDB Publication 248227 D01v01r02(SAR Considerationa for 802.11 Devices)
- FCC KDB Publication 447498 D01v05 (General SAR Guidance)
- FCC KDB Publication 648474 D04 SAR Handsets Multi Xmter and Ant v01
- FCC KDB Publication 865664 D01 SAR measurement 100 MHz to 6 GHz v01
- FCC KDB Publication 865664 D02 SAR Reporting v01

### 3. DESCRIPTION OF DEVICE

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

EUT Type	Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN					
FCC ID:	ZNFE425J					
Model:	LG-E425j, LG-E425J, LGE425J, E425J, E425j, LGE425j					
Trade Name	LG Electronics, MobileComm U.S.A., Inc.					
Application Type	Certification					
Mode(s) of Operation	GSM850/GSM1900 /WCDMA1900 /802.11b/g/n					
Tx Frequency	824.20 - 848.80 MHz (GSM850) / 1 850.20 – 1 909.80 MHz (GSM1900) 1852.4 – 1 907.6 MHz (WCDMA1900)/ 2 412- 2 462 MHz (802.11b/g/n)					
Production Unit or Identical Prototype	Prototype					
Max SAR	Band	Tx Frequency (MHz)	Equipment Class	Reported 1 g SAR (W/kg)		
	GSM850	824.20 - 848.80	PCE	0.773	0.699	0.974
	GSM1900	1 850.20 - 1 909.80	PCE	0.650	0.371	0.481
	WCDMA1900	1 852.4 – 1 907.6	PCE	0.751	0.668	0.668
	Bluetooth	2 402 - 2 480	DSS	-		
	802.11b	2 412- 2 462	DTS	0.302	0.080	0.080
Simultaneous SAR per KDB 690783 D01				1.075	0.849	1.054
Date(s) of Tests	Mar.18, 2013 ~ Mar.21, 2013					
Antenna Type	Integral Antenna					
GRPS	Multislot Class: 12					
Key Feature(s)	This device supports Mobile Hotspot.					

## **4. DESCRIPTION OF TEST EQUIPMENT**

### **4.1 SAR MEASUREMENT SETUP**

These measurements are performed using the DASY4 automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure.4.1).

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the HP Pentium IV 3.0 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 4.1 HCT SAR Lab. Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in.

## **4.2 DASY4 E-FIELD PROBE SYSTEM**

### **4.2.1 ET3DV6 Probe Specification**

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection System Built-in shielding against static charges
Calibration	In air from 10 MHz to 2.5 GHz In brain and muscle simulating tissue at Frequencies of 450 MHz, 900 MHz and 1.8 GHz (accuracy: 8 %)
Frequency	10 MHz to > 3 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)
Directivity	$\pm 0.2$ dB in brain tissue (rotation around probe axis) $\pm 0.4$ dB in brain tissue (rotation normal probe axis)
Dynamic	5 $\mu\text{W}/\text{g}$ to > 100 mW/g;
Range Linearity:	$\pm 0.2$ dB
Surface Detection	$\pm 0.2$ mm repeatability in air and clear liquids over diffuse reflecting surfaces.
Dimensions	Overall length: 337 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application	General dissymmetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms



Figure 4.2 Photograph of the probe and the Phantom




Figure 4.3 ET3DV6 E-field Probe

The SAR measurements were conducted with the dosimetric probe

ET3DV6, designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches a maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2<sup>nd</sup> order fitting. The approach is stopped at reaching the maximum.

## 4.3 PROBE CALIBRATION PROCESS

### 4.3.1 E-Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with an accuracy better than  $\pm 10\%$ . The spherical isotropy was evaluated with the proper procedure and found to be better than  $\pm 0.25$  dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe is tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies bellow 1 GHz, and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

where:

$\Delta t$  = exposure time (30 seconds),

$C$  = heat capacity of tissue (brain or muscle),

$\Delta T$  = temperature increase due to RF exposure.

SAR is proportional to  $\Delta T / \Delta t$ , the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E-field;




Figure 4.4 E-Field and Temperature measurements at 900 MHz

$$\text{SAR} = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

$\sigma$  = simulated tissue conductivity,

$\rho$  = Tissue density (1.25 g/cm³ for brain tissue).




Figure 4.5 E-Field and temperature measurements at 1.8 GHz

### 4.3.2 Data Extrapolation

The DASY4 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given like below:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with       $V_i$     = compensated signal of channel i    ( $i=x,y,z$ )  
 $U_i$     = input signal of channel i                        ( $i=x,y,z$ )  
 $cf$     = crest factor of exciting field                        (DASY parameter)  
 $dcp_i$  = diode compression point                                (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

with       $V_i$     = compensated signal of channel i ( $i = x,y,z$ )  
 $Norm_i$  = sensor sensitivity of channel i    ( $i = x,y,z$ )  
 $\mu\text{V}/(\text{V}/\text{m})^2$  for E-field probes  
 $ConvF$  = sensitivity of enhancement in solution  
 $E_i$     = electric field strength of channel i in V/m

The RSS value of the field components gives the total field strength (Hermetian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with      SAR    = local specific absorption rate in W/g  
 $E_{tot}$     = total field strength in V/m  
 $\sigma$     = conductivity in [mho/m] or [Siemens/m]  
 $\rho$     = equivalent tissue density in g/cm<sup>3</sup>

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770}$$

with       $P_{pwe}$     = equivalent power density of a plane wave in W/cm<sup>2</sup>  
 $E_{tot}$     = total electric field strength in V/m

## 4.4 SAM Phantom

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.



Shell Thickness	2.0 mm $\pm$ 0.2 mm (6 $\pm$ 0.2 mm at ear point)
Filling Volume	about 25 L
Dimensions	810 mm x 1 000 mm x 500 mm (H x L x W)

Figure 4.6 SAM Phantom

Triple Modular Phantom consists of tree identical modules which can be installed and removed separately without emptying the liquid. It includes three reference points for phantom installation. Covers prevent evaporation of the liquid. Phantom material is resistant to DGBE based tissue simulating liquids. The MFP V5.1 will be delivered including wooden support only (**non**-standard SPEAG support).

Applicable for system performance check from 700 MHz to 6 GHz (MFP V5.1C) or 800 MHz - 6 GHz (MFP V5.1A) as well as dosimetric evaluations for body-worn operation.



Shell Thickness	2.0 mm $\pm$ 0.2 mm
Filling Volume	approx. 9.2 L
Dimensions	830 mm x 500 mm (L x W)

Figure 4.7 Triple Modular Phantom

## 4.5 Device Holder for Transmitters

In combination with the SAM Phantom V 4.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatable positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations.

To produce the Worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



Figure 4.8 Device Holder

## 4.6 Brain & Muscle Simulating Mixture Characterization

The brain and muscle mixtures consist of a viscous gel using hydrox-ethyl cellulose (HEC) gelling agent and saline solution (see Table 3.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrove.

Ingredients (% by weight)	Frequency (MHz)					
	835		1 900		2 450 - 2700	
Tissue Type	Head	Body	Head	Body	Head	Body
Water	40.45	53.06	54.9	70.17	71.88	73.2
Salt (NaCl)	1.45	0.94	0.18	0.39	0.16	0.1
Sugar	57.0	44.9	0.0	0	0.0	0.0
HEC	1.0	1.0	0.0	0	0.0	0.0
Bactericide	0.1	0.1	0.0	0	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	19.97	0.0
DGBE	0.0	0.0	44.92	29.44	7.99	26.7
Diethylene glycol hexyl ether	-	-	-	-	-	-

Salt: 99 % Pure Sodium Chloride      Sugar: 98 % Pure Sucrose  
 Water: De-ionized, 16M resistivity      HEC: Hydroxyethyl Cellulose  
 DGBE: 99 % Di(ethylene glycol) butyl ether,[2-(2-butoxyethoxy) ethanol]  
 Triton X-100(ultra pure): Polyethylene glycol mono[4-(1,1,3,3-tetramethylbutyl)phenyl] ether

**Table 4.1 Composition of the Tissue Equivalent Matter**

## 4.7 SAR TEST EQUIPMENT

Manufacturer	Type / Model	S/N	Calib. Date	Calib.Interval	Calib.Due
SPEAG	SAM Phantom	-	N/A	N/A	N/A
Staubli	Robot RX90L	F01/5K09A1/A/01	N/A	N/A	N/A
Staubli	Robot ControllerCS7MB	F99/5A82A1/C/01	N/A	N/A	N/A
HP	Pavilion t000_puffer	KRJ51201TV	N/A	N/A	N/A
SPEAG	Light Alignment Sensor	265	N/A	N/A	N/A
Staubli	Teach Pendant (Joystick)	D221340.01	N/A	N/A	N/A
SPEAG	DAE3	466	Feb. 21, 2013	Annual	Feb. 21, 2014
SPEAG	E-Field Probe ET3DV6	1605	Apr. 26, 2012	Annual	Apr. 26, 2013
SPEAG	Validation Dipole D835V2	441	May 16, 2012	Annual	May 16, 2013
SPEAG	Validation Dipole D1900V2	5d032	July 20, 2012	Annual	July 20, 2013
SPEAG	Validation Dipole D2450V2	743	Aug. 23, 2012	Annual	Aug. 23, 2013
Agilent	Power Meter(F) E4419B	MY41291386	Nov. 02, 2012	Annual	Nov. 02, 2013
Agilent	Power Sensor(G) 8481	MY41090870	Nov. 02, 2012	Annual	Nov. 02, 2013
HP	Dielectric Probe Kit 85070C	00721521	CBT		
HP	Dual Directional Coupler	16072	Nov. 02, 2012	Annual	Nov. 02, 2013
R&S	Base Station CMW500	1201.0002K50_116858	Jan. 17,2013	Annual	Jan. 17,2014
HP	Base Station E5515C	GB44400269	Feb. 14, 2013	Annual	Feb. 14, 2014
HP	Signal Generator 8664A	3744A02069	Nov. 02, 2012	Annual	Nov. 02, 2013
Hewlett Packard	11636B/Power Divider	11377	Nov. 11. 2012	Annual	Nov. 11. 2013
Agilent	N9020A/ SIGNAL	MY51110020	Jul. 31.2012	Annual	Jul. 31.2013
TESCOM	TC-3000C / BLUETOOTH	3000C000276	Jul. 11, 2012	Annual	Jul. 11, 2013

## NOTE:

1. The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Verification measurement is performed by HCT Lab. before each test. The brain/body simulating material is calibrated by HCT using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain/body-equivalent material.
2. CBT(Calibrating Before Testing). Prior to testing, the dielectric probe kit was calibrated via the network analyzer, with the specified procedure(calibrated in pure water) and calibration kit(standard) short circuit, before the dielectric measurement. The specific procedure and calibration kit are provided by Agilent

## 5. SAR MEASUREMENT PROCEDURE

The evaluation was performed with the following procedure:

1. The SAR value at a fixed location above the ear point was measured and was used as a reference value for assessing the power drop.
2. The SAR distribution at the exposed side of the head was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15 mm x 15 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.
3. Around this point, a volume of 32 mm x 32 mm x 30 mm was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:
  - a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
  - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR value, at the same location as procedure #1, was re-measured. If the value changed by more than 5 %, the evaluation is repeated.




Figure 5.1 SAR Measurement Point in Area Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extend, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SASR-distribution over 10g.

Area scan and zoom scan resolution setting follow KDB 865664 D01v01 quoted below

		$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		$5 \pm 1$ mm	$\frac{1}{4} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
		$\leq 2$ GHz: $\leq 15$ mm $2 - 3$ GHz: $\leq 12$ mm	$3 - 4$ GHz: $\leq 12$ mm $4 - 6$ GHz: $\leq 10$ mm
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}$ , $\Delta y_{\text{Area}}$		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}$ , $\Delta y_{\text{Zoom}}$		$\leq 2$ GHz: $\leq 8$ mm $2 - 3$ GHz: $\leq 5$ mm*	$3 - 4$ GHz: $\leq 5$ mm* $4 - 6$ GHz: $\leq 4$ mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$	$\leq 5$ mm	$3 - 4$ GHz: $\leq 4$ mm $4 - 5$ GHz: $\leq 3$ mm $5 - 6$ GHz: $\leq 2$ mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm
		$\Delta z_{\text{Zoom}}(n > 1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	$3 - 4$ GHz: $\geq 28$ mm $4 - 5$ GHz: $\geq 25$ mm $5 - 6$ GHz: $\geq 22$ mm

Note:  $\delta$  is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

\* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is  $\leq 1.4$  W/kg,  $\leq 8$  mm,  $\leq 7$  mm and  $\leq 5$  mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

## 6. DESCRIPTION OF TEST POSITION

### 6.1 HEAD POSITION

The device was placed in a normal operating position with the Point A on the device, as illustrated in following drawing, aligned with the location of the RE(ERP) on the phantom. With the ear-piece pressed against the head, the vertical center line of the body of the handset was aligned with an imaginary plane consisting of the RE, LE and M. While maintaining these alignments, the body of the handset was gradually moved towards the cheek until any point on the mouth-piece or keypad contacted the cheek. This is a cheek/touch position. For ear/tilt position, while maintain the device aligned with the BM and FN lines, the device was pivot against ERP back for 15° or until the device antenna touch the phantom. Please refer to IEEE 1528-2003 illustration below.




Figure 6.1 Side view of the phantom




Figure 6.2 Handset vertical and horizontal reference lines

## **6.2 Body Holster/Belt Clip Configurations**

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with each accessory. If multiple accessory share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some Devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used.

Since this EUT does not supply any body worn accessory to the end user a distance of 1.0 cm from the EUT back surface to the liquid interface is configured for the generic test.

"See the Test SET-UP Photo"

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), Including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worstcase positioning is then documented and used to perform Body SAR testing.

## 7. MEASUREMENT UNCERTAINTY

---

Error Description	Tol (± %)	Prob. dist.	Div.	c <sub>i</sub>	Standard Uncertainty (± %)	v <sub>eff</sub>
<b>1. Measurement System</b>						
Probe Calibration	6.00	N	1	1	6.00	∞
Axial Isotropy	4.70	R	1.73	0.7	1.90	∞
Hemispherical Isotropy	9.60	R	1.73	0.7	3.88	∞
Boundary Effects	1.00	R	1.73	1	0.58	∞
Linearity	4.70	R	1.73	1	2.71	∞
System Detection Limits	1.00	R	1.73	1	0.58	∞
Readout Electronics	0.30	N	1.00	1	0.30	∞
Response Time	0.8	R	1.73	1	0.46	∞
Integration Time	2.6	R	1.73	1	1.50	∞
RF Ambient Conditions	3.00	R	1.73	1	1.73	∞
Probe Positioner	0.40	R	1.73	1	0.23	∞
Probe Positioning	2.90	R	1.73	1	1.67	∞
Max SAR Eval	1.00	R	1.73	1	0.58	∞
<b>2. Test Sample Related</b>						
Device Positioning	2.90	N	1.00	1	2.90	145
Device Holder	3.60	N	1.00	1	3.60	5
Power Drift	5.00	R	1.73	1	2.89	∞
<b>3. Phantom and Setup</b>						
Phantom Uncertainty	4.00	R	1.73	1	2.31	∞
Liquid Conductivity(target)	5.00	R	1.73	0.64	1.85	∞
Liquid Conductivity(meas.)	2.07	N	1	0.64	1.32	9
Liquid Permitivity(target)	5.00	R	1.73	0.6	1.73	∞
Liquid Permitivity(meas.)	5.02	N	1	0.6	3.01	9
<b>Combind Standard Uncertainty</b>						
<b>Coverage Factor for 95 %</b>						
<b>Expanded STD Uncertainty</b>						

**Table 7.1 Uncertainty (800 MHz- 2450 MHz)**

## **8. ANSI/ IEEE C95.1 - 1992 RF EXPOSURE LIMITS**

HUMAN EXPOSURE	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT Occupational (W/kg) or (mW/g)
SPATIAL PEAK SAR * (Brain)	1.60	8.00
SPATIAL AVERAGE SAR ** (Whole Body)	0.08	0.40
SPATIAL PEAK SAR *** (Hands / Feet / Ankle / Wrist)	4.00	20.00

**Table 8.1 Safety Limits for Partial Body Exposure**

**NOTES:**

\* The Spatial Peak value of the SAR averaged over any 1 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

\*\* The Spatial Average value of the SAR averaged over the whole-body.

\*\*\* The Spatial Peak value of the SAR averaged over any 10 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

## **9. SAR SYSTEM VALIDATION**

Per FCC KCB 865664 D02v01, SAR system validation status should be document to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue-equivalent media for system validation, according to the procedures outlined in IEEE 1528-2003 and FCC KDB 865664 D01 v01. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

### **SAR System Validation Summary**

SAR System #	Probe	probe Type	Probe Calibration Point		Dipole	Date	Dielectric Parameters		CW Validation			Modulation Validation		
							Measured Permittivity	Measured conductivity	Sensitivity	Probe Linearity	Probe Isotropy	MOD. Type	Duty Factor	PAR
4	1605	ET3DV6	Head	835	441	Dec.22,2012	42.1	0.88	PASS	PASS	PASS	GMSK	PASS	N/A
4	1605	ET3DV6	Head	1900	5d032	Dec.22,2012	38.7	1.42	PASS	PASS	PASS	GMSK	PASS	N/A
4	1605	ET3DV6	Head	2450	743	Dec.22,2012	40.1	1.79	PASS	PASS	PASS	OFDM	N/A	PASS
4	1605	ET3DV6	Body	835	441	Dec.23,2012	55.4	0.96	PASS	PASS	PASS	GMSK	PASS	N/A
4	1605	ET3DV6	Body	1900	5d032	Dec.23,2012	52.5	1.57	PASS	PASS	PASS	GMSK	PASS	N/A
4	1605	ET3DV6	Body	2450	743	Dec.23,2012	53.1	1.91	PASS	PASS	PASS	OFDM	N/A	PASS

## 10. SYSTEM VERIFICATION

### 10.1 Tissue Verification

Freq. [MHz]	Date	Probe	Dipole	Liquid	Liquid Temp.[°C]	Parameters	Target Value	Measured Value	Deviation [%]	Limit [%]	
835	Mar. 18, 2013	3797	441	Head	21.4	$\epsilon_r$	41.5	40.4	- 2.65	$\pm 5$	
835						$\sigma$	0.90	0.919	+ 2.11	$\pm 5$	
1 900	Mar. 19, 2013		5d032	Body	21.4	$\epsilon_r$	55.2	56.8	+ 2.90	$\pm 5$	
1 900						$\sigma$	0.97	0.985	+ 1.55	$\pm 5$	
2 450	Mar. 21, 2013		743	Head	21.2	$\epsilon_r$	40.0	40.9	+ 2.25	$\pm 5$	
2 450						$\sigma$	1.40	1.37	- 2.14	$\pm 5$	
2 450				Body	21.2	$\epsilon_r$	53.3	52.3	- 1.88	$\pm 5$	
2 450						$\sigma$	1.52	1.56	+ 2.63	$\pm 5$	
2 450				Body	21.2	$\epsilon_r$	39.2	38.4	- 2.04	$\pm 5$	
2 450						$\sigma$	1.80	1.84	+ 2.22	$\pm 5$	
2 450						$\epsilon_r$	52.7	53.6	+ 1.71	$\pm 5$	
2 450						$\sigma$	1.95	1.99	+ 2.05	$\pm 5$	

The Tissue dielectronic parameters were measured prior to the SAR evaluation using an Agilent 85070C Dielectronic Probe Kit and Agilent Network Analyzer.

### 10.2 System Verification

Prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at 835 MHz / 1 900 MHz / 2 450 MHz by using the system Verification kit. (Graphic Plots Attached)

Freq. [MHz]	Date	Probe (SN)	Dipole (SN)	Liquid	Amb. Temp. [°C]	Liquid Temp. [°C]	1 W Target SAR <sub>1g</sub> (SPEAG) (mW/g)	Measured SAR <sub>1g</sub> (mW/g)	1 W Normalized SAR <sub>1g</sub> (mW/g)	Deviation [%]	Limit [%]	
835	Mar. 18, 2013	3797	441	Head	21.4	21.6	9.43	0.934	9.34	- 0.95	$\pm 10$	
835				Body	21.4	21.6	9.50	0.954	9.54	+ 0.42	$\pm 10$	
1 900	Mar. 19, 2013		5d032	Head	21.4	21.6	39.0	4.03	40.3	+ 3.33	$\pm 10$	
1 900				Body	21.4	21.6	39.9	3.9	39.0	- 2.26	$\pm 10$	
2 450	Mar. 21, 2013		743	Head	21.2	21.4	52.7	5.34	53.4	+ 1.33	$\pm 10$	
2 450				Body	21.2	21.4	51.2	5.2	52.0	+ 1.56	$\pm 10$	

## **10.3 System Verification Procedure**

SAR measurement was prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at each frequency band by using the system Verification kit. (Graphic Plots Attached)

- Cabling the system, using the Verification kit equipments.
- Generate about 100 mW Input Level from the Signal generator to the Dipole Antenna.
- Dipole Antenna was placed below the Flat phantom.
- The measured one-gram SAR at the surface of the phantom above the dipole feed-point should be within 10 % of the target reference value.
- The results are normalized to 1 W input power.

## **11. RF CONDUCTED POWER MEASUREMENT**

Power measurements were performed using a base station simulator under digital average power. The handset was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluation SAR. SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, this was configured with the base station simulator. The SAR measurement Software calculates a reference point at the start and end of the test to check for power drifts. If conducted Power deviations of more than 5 % occurred, the tests were repeated.

### **11.1 GSM**

Conducted output power measurements were performed using a base station simulator under digital average power.



SAR Test for WWAN were performed with a base station simulator Agilent E5515C. Communication between the device and the emulator was established by air link. Set base station emulator to allow DUT to radiate maximum output power during all tests. Please refer to the below worst case SAR operation setup.

- GSM voice: Head SAR
- GPRS Multi-slots : Body SAR with GPRS Multi-slot Class12 with CS 1 (GMSK)

**Note:**

CS1/MCS7 coding scheme was used in GPRS/EDGE output power measurements and SAR Testing, as a condition where GMSK/8PSK modulation was ensured. Investigation has shown that CS1 - CS4/ MCS5 – MCS9 settings do not have any impact on the output levels in the GPRS/EDGE modes.

**GSM850**

Target Power : 32.7 dBm

**GSM1900**

Target Power : 29.7 dBm

**GPRS850**

GPRS 1tx : 32.7 dBm

**PCS1900**

GPRS 2tx : 30.2 dBm

GPRS 1tx : 29.7 dBm

GPRS 3tx : 28.7 dBm

GPRS 2tx : 27.2 dBm

GPRS 4tx : 27.2 dBm

GPRS 3tx : 25.7 dBm

Tune-up Tolerance : -1.5dB/ +0.5dB

GPRS 4tx : 24.2 dBm

Tune-up Tolerance : -1.5dB/ +0.5dB

## GSM Conducted output powers (Burst-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)
GSM 850	128	32.78	32.77	30.28	28.80	27.36
	190	32.76	32.76	30.23	28.75	27.30
	251	32.73	32.72	30.15	28.65	27.21
GSM 1900	512	29.57	29.57	27.16	25.69	24.21
	661	29.70	29.70	27.31	25.83	24.34
	810	29.84	29.83	27.48	26.00	24.51

## GSM Conducted output powers (Frame-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)
GSM 850	128	23.75	23.74	24.26	24.54	24.35
	190	23.73	23.73	24.21	24.49	24.29
	251	23.7	23.69	24.13	24.39	24.2
GSM 1900	512	20.54	20.54	21.14	21.43	21.2
	661	20.67	20.67	21.29	21.57	21.33
	810	20.81	20.8	21.46	21.74	21.5

**Note:**

Time slot average factor is as follows:

1 Tx slot = 9.03 dB, Frame-Average output power = Burst-Average output power – 9.03 dB

2 Tx slot = 6.02 dB, Frame-Average output power = Burst-Average output power – 6.02 dB

3 Tx slot = 4.26 dB, Frame-Average output power = Burst-Average output power – 4.26 dB

4 Tx slot = 3.01 dB, Frame-Average output power = Burst-Average output power – 3.01 dB

## **10.5 WCDMA**

Body SAR is not required for handsets with HSDPA capabilities when the maximum average output of each RF channel with HSDPA active is less than  $\frac{1}{4}$  dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Otherwise, SAR is Measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that results in the highest SAR in 12.2 kbps RMC for that RF channel.

### **10.5.1 Output Power Verification**

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3 GPP TS 34.121, using the appropriate RMC or AMR with TPC(transmit power control) set to all "1s".

### **10.5.2 Head SAR Measurements**

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than  $\frac{1}{4}$  dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer using the exposure configuration that results in the highest SAR for that RF channel in 12.2 RMC.

### **10.5.3 Body SAR Measurement**

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s".

### **10.5.4 Handsets with Release 5 HSDPA**

Body SAR is not required for handsets with HSDPA capabilities when the maximum average output of each RF channel with HSDPA active is less than  $\frac{1}{4}$  dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Otherwise, SAR is Measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that results in the highest SAR in 12.2 kbps RMC for that RF channel.

**Sub-Test 1 Setup for Release 5 HSDPA**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	CM (dB) <sup>(2)</sup>
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	12/15 <sup>(3)</sup>	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ .

Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

## 10.5.5 Handsets with Release 6 HSPA (HSDPA/HSUPA)

Body SAR is not required for handsets with HSPA capabilities when the maximum average output of each RF channel with HSUPA/HSDPA active is less than  $\frac{1}{4}$  dB higher than that measured without HSUPA/HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2, according to the highest body SAR configuration in 12.1 kbps RMC without HSPA. When VOIP is applicable for head exposure, SAR is not required when the maximum output of each RF channel with HSPA is less than  $\frac{1}{4}$  dB higher than that measured using 12.2 kbps RMC; otherwise, the same HSPA configuration used for body measurement should be used to test for head exposure.

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM <sup>(2)</sup> (dB)	MPR (dB)	AG <sup>(4)</sup> Index	E-TFCI
1	11/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	11/15 <sup>(3)</sup>	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 <sup>(4)</sup>	15/15 <sup>(4)</sup>	64	15/15 <sup>(4)</sup>	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

WCDMA 1900

Target Power : 22.7 dBm

Tune-up Tolerance : -1.5 dB/ +0.5 dB

3GPP	Mode	3GPP 34.121	Cellular Band [dBm]					MPR Target
Release		Subtest	4132	Power reduction (dB)	4183	Power reduction (dB)	4233	
Version								
99	WCDMA	12.2 kbps RMC	22.50	-	22.52	-	22.58	-
99	WCDMA	12.2 kbps AMR	22.62	-	22.60	-	22.45	-
5	HSDPA	Subtest 1	22.39	-	22.40	-	22.31	-
5		Subtest 2	22.32	0.07	22.35	0.05	22.23	0.08
5		Subtest 3	21.97	0.42	21.91	0.49	21.89	0.42
5		Subtest 4	21.96	0.43	21.90	0.5	21.86	0.45

## WCDMA Average Conducted output powers

## 11.2 WiFi

### 11.2.1 SAR Testing for 802.11b/g/n modes

#### **General Device Setup**

Normal Network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

#### **Frequency Channel Configurations**

802.11 a/b/g and 4.9 GHz operating modes are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; Channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz § 15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. 4.9 GHz is tested on channels 1, 10 and 5 or 6, whichever has the higher output power, for 5 MHz channels; channels 11, 15 and 19 for 10 MHz channels; and channels 21 and 25 for 20 MHz channels.

These are referred to as the "default test channels". 802.11g mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.

Mode	GHz	Channel	Turbo Channel	"Default Test Channels"		
				515.247	802.11b	802.11g
802.11 b/g	2.412	1		✓	✗	
	2.437	6	6	✓	✗	
	2.462	11		✓	✗	
802.11a	5.18	36			✓	
	5.20	40	42 (5.21 GHz)			*
	5.22	44			✓	*
	5.24	48	50 (5.25 GHz)		✓	
	5.26	52			✓	
	5.28	56	58 (5.29 GHz)			*
	5.30	60			✓	*
	5.32	64			✓	
	5.500	100				*
	5.520	104			✓	
	5.540	108				*
	5.560	112				*
	5.580	116			✓	
	5.600	120	Unknown		✓	*
	5.620	124			✓	
	5.640	128				*
	5.660	132				*
	5.680	136			✓	
	5.700	140				*
	5.745	149		✓	✓	
	5.765	153			*	*
UNII or §15.247	5.785	157		✓		*
	5.805	161			*	*
	5.825	165		✓		
	§15.247					

802.11 Test Channels per FCC Requirements

2.4GHz

802.11b : 15.3 dBm    802.11g : 13.5 dBm    802.11n : 12.7 dBm

Tune-up Tolerance : -1.5dB/ +0.7 dB

## TEST RESULTS-Average

### Conducted Output Power Measurements (802.11b Mode)

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	1 Mbps	14.72	30
		2 Mbps	14.54	30
		5.5 Mbps	14.70	30
		11 Mbps	14.21	30
2437	6	1 Mbps	14.79	30
		2 Mbps	14.50	30
		5.5 Mbps	14.72	30
		11 Mbps	14.21	30
2462	11	1 Mbps	15.02	30
		2 Mbps	15.22	30
		5.5 Mbps	15.09	30
		11 Mbps	14.93	30

### Conducted Output Power Measurements (802.11g Mode)

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6 Mbps	13.29	30
		9 Mbps	12.59	30
		12 Mbps	12.91	30
		18 Mbps	12.60	30
		24 Mbps	12.65	30
		36 Mbps	11.90	30
		48 Mbps	11.86	30
		54 Mbps	11.71	30
2437	6	6 Mbps	13.44	30
		9 Mbps	13.15	30
		12 Mbps	13.02	30
		18 Mbps	12.74	30
		24 Mbps	13.15	30
		36 Mbps	12.68	30
		48 Mbps	12.40	30
		54 Mbps	11.56	30
2462	11	6 Mbps	13.63	30
		9 Mbps	13.17	30
		12 Mbps	12.95	30
		18 Mbps	13.44	30
		24 Mbps	13.22	30
		36 Mbps	12.41	30
		48 Mbps	12.47	30
		54 Mbps	12.20	30

**Conducted Output Power Measurements (802.11n Mode)**


802.11n Mode		Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.		
2412	1	6.5 Mbps	11.84
		13 Mbps	11.93
		19.5 Mbps	11.78
		26 Mbps	11.53
		39 Mbps	11.59
		52 Mbps	10.97
		58.5 Mbps	10.83
		65 Mbps	10.38
2437	6	6.5 Mbps	12.77
		13 Mbps	12.51
		19.5 Mbps	12.50
		26 Mbps	12.46
		39 Mbps	11.80
		52 Mbps	11.86
		58.5 Mbps	11.01
		65 Mbps	11.40
2462	11	6.5 Mbps	12.93
		13 Mbps	12.43
		19.5 Mbps	12.50
		26 Mbps	12.33
		39 Mbps	12.39
		52 Mbps	11.64
		58.5 Mbps	11.63
		65 Mbps	11.43

Note:

SAR testing was performed according to the FCC KDB 248227.

## 11. 3 Bluetooth Average Power

### Test Configuration



### TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the average detector mode. This test is performed with hopping off.

1. Span = 2 MHz (GFSK) / 5 MHz ( $\pi/4$ DQPSK and 8DPSK)
2. RBW = auto (GFSK) / auto ( $\pi/4$ DQPSK and 8DPSK)
3. VBW = auto (GFSK) / auto ( $\pi/4$ DQPSK and 8DPSK)
4. Sweep = 1 s
5. Packet type= DH5 (GFSK) / 2-DH5 ( $\pi/4$ DQPSK) / 3-DH5 (8DPSK)

Model	Channel	Frequency (MHz)	BT Average Power (dBm)		
			GFSK	8DPSK	$\pi/4$ DQPSK
LG-E425j	0	2402	4.94	3.52	3.5
	39	2440	9.12	7.59	7.56
	78	2480	8.98	7.59	7.59

Target Power :8.5 dBm


Power Tolerance: + 0.7dB

## 12. SAR Test configuration & Antenna Information

### 12.1 SAR Test configurations

Mode	Rear	Front	Left	Right	Bottom	Top
GSM 850	Yes	Yes	Yes	Yes	Yes	No
GSM 1 900	Yes	Yes	Yes	Yes	Yes	No
WCDMA 1 900	Yes	Yes	Yes	Yes	Yes	No
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes

### 12.2 Antenna and Device Information



[Front side View]

**Note:**

Per FCC KDB Publication 941225 D06, we performed the SAR testing at 1 cm from the top & bottom surfaces and also from side edges with a transmitting antenna  $\leq$  2.5 cm from an edge.

## 13. SAR TEST DATA SUMMARY

### 13.1 Measurement Results (GSM 850 Head SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Battery	Phantom Position	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
836.6	190 (Mid)	GSM850	32.76	-0.144	Standard	Left Ear	0.403	0.446	1
			32.76	-0.112	Standard	Left Tilt 15°	0.208	0.230	2
			32.76	-0.194	Standard	Right Ear	0.433	0.479	3
			32.76	-0.091	Standard	Right Tilt 15°	0.194	0.215	4
836.6	190 (Mid)	GPRS 3Tx	28.80	-0.107	Standard	Left Ear	0.674	0.739	5
			28.80	-0.121	Standard	Left Tilt 15°	0.379	0.416	6
			28.80	-0.197	Standard	Right Ear	0.705	0.773	7
			28.80	0.145	Standard	Right Tilt 15°	0.306	0.336	8
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population</b>						<b>Head 1.6 W/kg (mW/g) Averaged over 1 gram</b>			

#### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode       Manual Test cord       Base Station Simulator
- According to KDB 447498, Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz.
- For Head SAR testing, the EUT was set in GPRS multi-slot class12 with 3uplink slots for GSM850 due to maximum source-based time-averaged output power.  
According to the KDB 941225 D03 SAR test reduction GSM/GPRS/EDGE, the maximum output power configuration were chosen for Body SAR testing.

## 13.2 Measurement Results (GSM 1900 Head SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Battery	Phantom Position	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
1 880.0	661 (Mid)	GSM1900	29.7	-0.077	Standard	Left Ear	0.534	0.599	9
			29.7	-0.028	Standard	Left Tilt 15°	0.135	0.151	10
			29.7	-0.04	Standard	Right Ear	0.317	0.356	11
			29.7	0.086	Standard	Right Tilt 15°	0.091	0.102	12
1 880.0	661 (Mid)	GPRS 3Tx	25.83	-0.073	Standard	Left Ear	0.597	0.650	13
			25.83	-0.028	Standard	Left Tilt 15°	0.161	0.175	14
			25.83	-0.032	Standard	Right Ear	0.38	0.414	15
			25.83	-0.006	Standard	Right Tilt 15°	0.102	0.111	16
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit</b> <b>Spatial Peak</b> <b>Uncontrolled Exposure/ General Population</b>						<b>Head</b> <b>1.6 W/kg (mW/g)</b> <small>Averaged over 1 gram</small>			

### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode       Manual Test cord       Base Station Simulator
- According to KDB 447498, Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz.
- For Head SAR testing, the EUT was set in GPRS multi-slot class12 with 3uplink slots for GSM1900 due to maximum source-based time-averaged output power.  
According to the KDB 941225 D03 SAR test reduction GSM/GPRS/EDGE, the maximum output power configuration were chosen for Body SAR testing.

### 13.3 Measurement Results (WCDMA 1 900 Head SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Battery	Phantom Position	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
1880	9400 (Mid)	WCDMA 1 900	22.52	-0.156	Standard	Left Ear	0.642	0.751	17
			22.52	-0.063	Standard	Left Tilt 15°	0.188	0.220	18
			22.52	-0.122	Standard	Right Ear	0.537	0.628	19
			22.52	0.042	Standard	Right Tilt 15°	0.161	0.188	20
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit</b> <b>Spatial Peak</b> <b>Uncontrolled Exposure/ General Population</b>						<b>Head</b> <b>1.6 W/kg (mW/g)</b> <small>Averaged over 1 gram</small>			

#### NOTES:

- 1 The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- 2 All modes of operation were investigated and the worst-case are reported.
- 3 Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- 4 Tissue parameters and temperatures are listed on the SAR plot.
- 5 Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- 6 Test Signal Call Mode       Manual Test cord       Base Station Simulator
- 7 According to KDB 447498, Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz.
- 8 WCDMA Mode was tested under RMC 12.2 kbps and HSPA Inactive.

## 13.4 Measurement Results (802.11b/g/n Head SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Battery	Phantom Position	Data Rate	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel									
2.462	11 (High)	802.11b	15.02	-0.088	Standard	Left Ear	1Mbps	0.108	0.135	21
			15.02	-0.035	Standard	Left Tilt 15°	1Mbps	0.093	0.117	22
			15.02	-0.136	Standard	Right Ear	1Mbps	0.241	0.302	23
			15.02	0.135	Standard	Right Tilt 15	1Mbps	0.121	0.152	24
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population</b>						<b>Head</b> <b>1.6 W/kg (mW/g)</b> <small>Averaged over 1 gram</small>				

**NOTES:**

- 1 The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- 2 All modes of operation were investigated and the worst-case are reported.
- 3 Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- 4 Tissue parameters and temperatures are listed on the SAR plot.
- 5 Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- 6 Test Signal Call Mode       Manual Test cord       Base Station Simulator
- 7 IEEE 802.11g(including 802.11n) SAR testing is required when the conducted powers are equal to or greater than 0.25 dB Than the conducted powers in IEEE 802.11b.
- 8 For 2.4GHz WLAN, Highest average power channel for the lowest data rate was selected for SAR evaluation based on KDB 248227. Other channels are not necessary because 1g-average SAR < 0.8 W/Kg and peak SAR < 1.6W/Kg per KDB 248227.

## 13.5 Measurement Results (GSM850 Hotspot SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Configuration	Separation Distance	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
824.2	128 (Low)	GPRS 3Tx	28.80	0.195	Rear	1.0 cm	0.874	0.958	25
836.6	190 (Mid)		28.80	-0.123	Rear	1.0 cm	0.888	0.974	26
848.8	251 (High)		28.80	0.149	Rear	1.0 cm	0.815	0.894	27
836.6	190 (Mid)		28.80	0.129	Front	1.0 cm	0.583	0.639	28
836.6	190 (Mid)		28.80	-0.018	Left	1.0 cm	0.308	0.338	29
836.6	190 (Mid)		28.80	-0.061	Right	1.0 cm	0.472	0.518	30
836.6	190 (Mid)		28.80	-0.188	Bottom	1.0 cm	0.087	0.095	31
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population</b>						<b>Body 1.6 W/kg (mW/g)</b> <small>Averaged over 1 gram</small>			

**NOTES:**

- 1 The test data reported are the worst-case SAR value with the antenna-body position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- 2 All modes of operation were investigated and the worst-case are reported.
- 3 Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- 4 Tissue parameters and temperatures are listed on the SAR plot.
- 5 Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- 6 Test Signal Call Mode       Manual Test cord       Base Station Simulator
- 7 Test Configuration       With Holster       Without Holster
- 8 According to KDB 447498, Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz.
- 9 For body SAR testing, the EUT was set in GPRS multi-slot class12 with 3uplink slots for GSM850 due to maximum source-based time-averaged output power.  
According to the KDB 941225 D03 SAR test reduction GSM/GPRS/EDGE, the maximum output power configuration were chosen for Body SAR testing.

## 13.6 Measurement Results (GSM1900 Hotspot SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Configuration	Separation Distance	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
1 880	661 (Mid)	GPRS 3Tx	25.83	0.062	Rear	1.0 cm	0.442	0.481	32
			25.83	0.18	Front	1.0 cm	0.271	0.295	33
			25.83	0.037	Left	1.0 cm	0.127	0.138	34
			25.83	0.116	Right	1.0 cm	0.136	0.148	35
			25.83	-0.131	Bottom	1.0 cm	0.367	0.400	36
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population</b>						<b>Body 1.6 W/kg (mW/g)</b> <small>Averaged over 1 gram</small>			

**NOTES:**

- 1 The test data reported are the worst-case SAR value with the antenna-body position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- 2 All modes of operation were investigated and the worst-case are reported.
- 3 Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- 4 Tissue parameters and temperatures are listed on the SAR plot.
- 5 Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- 6 Test Signal Call Mode       Manual Test cord       Base Station Simulator
- 7 Test Configuration       With Holster       Without Holster
- 8 According to KDB 447498, Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz.
- 9 For body SAR testing, the EUT was set in GPRS multi-slot class12 with 3uplink slots for GSM1900 due to maximum source-based time-averaged output power.  
According to the KDB 941225 D03 SAR test reduction GSM/GPRS/EDGE, the maximum output power configuration were chosen for Body SAR testing.

### 13.9 Measurement Results (WCDMA 1900 Hotspot SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Configuration	Separation Distance	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
1880	9400 (Mid)	WCDMA 1900	22.52	0.136	Rear	1.0 cm	0.571	0.668	37
			22.52	0.029	Front	1.0 cm	0.364	0.426	38
			22.52	0.137	Left	1.0 cm	0.211	0.247	39
			22.52	0.181	Right	1.0 cm	0.199	0.233	40
			22.52	-0.016	Bottom	1.0 cm	0.468	0.547	41
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population</b>						<b>Body 1.6 W/kg (mW/g)</b> <small>Averaged over 1 gram</small>			

**NOTES:**

- 1 The test data reported are the worst-case SAR value with the antenna-Body position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- 2 All modes of operation were investigated and the worst-case are reported.
- 3 Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- 4 Tissue parameters and temperatures are listed on the SAR plot.
- 5 Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- 6 Test Signal Call Mode       Manual Test cord       Base Station Simulator
- 7 Test Configuration       With Holster       Without Holster
- 8 According to KDB 447498, Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz.
- 9 WCDMA Mode was tested under RMC 12.2 kbps and HSPA Inactive.

## 13.10 Measurement Results (802.11b/g/n Hotspot SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Configuration	Data Rate	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
2.462	11 (High)	802.11b	15.02	0.126	Rear	1Mbps	0.064	0.080	42
			15.02	0.189	Front	1Mbps	0.045	0.056	43
			15.02	-0.101	Left	1Mbps	0.054	0.068	44
			15.02	-0.133	Top	1Mbps	0.047	0.059	45
<b>ANSI/ IEEE C95.1 - 1992– Safety Limit</b> <b>Spatial Peak</b> <b>Uncontrolled Exposure/ General Population</b>						<b>Body</b> <b>1.6 W/kg (mW/g)</b> <small>Averaged over 1 gram</small>			

**NOTES:**

- 1 The test data reported are the worst-case SAR value with the antenna-body position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- 2 All modes of operation were investigated and the worst-case are reported.
- 3 Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- 4 Tissue parameters and temperatures are listed on the SAR plot.
- 5 Battery Type       Standard       Extended       Slim  
Batteries are fully charged for all readings.
- 6 Test Signal Call Mode       Manual Test code       Base Station Simulator
- 7 IEEE 802.11g(including 802.11n) SAR testing is required when the conducted powers are equal to or greater than 0.25 dB Than the conducted powers in IEEE 802.11b.
- 8 For 2.4GHz WLAN, Highest average power channel for the lowest data rate was selected for SAR evaluation based on KDB 248227. Other channels are not necessary because 1g-average SAR < 0.8 W/Kg and peak SAR < 1.6W/Kg per KDB 248227.

## 13.11 Measurement Results (Body-worn SAR)

Frequency		Modulation	Conducted Power (dBm)	Power Drift (dB)	Configuration	Separation Distance	Measured SAR(mW/g)	Scaled SAR(mW/g)	Plot No.
MHz	Channel								
836.6	190 (Mid)	GPRS 850	32.76	0.06	Rear	1.0 cm	0.632	0.699	46
1880	661 (Mid)	GPRS 1900	30.20	-0.033	Rear	1.0 cm	0.331	0.371	47
1880	9400 (Mid)	WCDMA 1900	22.52	0.136	Rear	1.0 cm	0.571	0.668	37
2462	11 (High)	802.11b (1 Mbps)	15.02	0.126	Rear	1.0 cm	0.064	0.080	42

**ANSI/ IEEE C95.1 - 1992– Safety Limit**

**Spatial Peak**

**Uncontrolled Exposure/ General Population**

**Body**

**1.6 W/kg (mW/g)**

Averaged over 1 gram

**NOTES:**

- 1 The test data reported are the worst-case SAR value with the antenna-body position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- 2 All modes of operation were investigated and the worst-case are reported.
- 3 Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- 4 Tissue parameters and temperatures are listed on the SAR plot.
- 5 According to KDB 447498, Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz.
- 6 Body-Worn accessory testing is typically associated with voice operation. Therefore, GSM voice was evaluated for body-worn SAR.

## **14. SAR Measurement Variability and Uncertainty**

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01.

These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

Frequency		Modulation	Battery	Phantom Position	Original SAR(mW/g)	Repeated SAR(mW/g)	Largest to Smallest SAR Ratio	Plot No.
MHz	Channel							
836.6	190 (Mid.)	GSM850	Standard	Rear	0.888	0.87	1.021	48

**Note(s):**

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not  $> 1.20$ .
2. Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg.

## 15. SAR Summation Scenario

	Position	Applicable Combination
Simultaneous Transmission	Head	GSM 850 Voice + 2.4 GHz WiFi
		GSM 1900 Voice + 2.4 GHz WiFi
		WCDMA 850 Voice + 2.4 GHz WiFi
		GPRS 850 Data + 2.4 GHz WiFi
		GPRS 1900 Data + 2.4 GHz WiFi
	Hotspot	GPRS 850 Data + 2.4 GHz WiFi
		GPRS 1900 Data + 2.4 GHz WiFi
		WCDMA 850 Data + 2.4 GHz WiFi
	Body-worn	GSM850 Voice + 2.4 GHz WiFi
		GSM1900 Voice + 2.4 GHz WiFi
		GSM850 Voice + 2.4 GHz Bluetooth
		GSM1900 Voice + 2.4 GHz Bluetooth
		WCDMA 850 Voice + 2.4 GHz WiFi
		WCDMA 850 Voice + 2.4 GHz Bluetooth

\* BT and WLAN are not simultaneous transmission.

Per FCC KDB 447498 D01v05, The SAR exclusion threshold for distance < 50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel(mW)}}{\text{Test Separation Dist(mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

. Mode	Frequency	Maximum Allowed Power	Separatuin Distance	$\leq 3.0$
	[MHz]	[mW]	[mm]	
Bluetooth	2440	8	10	1.30

Based on the maximum conducted power of Bluetooth and antenna to use separation distance, Bluetooth SAR was not required  $[(8/10)*\sqrt{2.440}] = 1.30 < 3.0$ .

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1iii, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is  $\leq 1.6\text{W/kg}$ . When standalone SAR is not required to be measured per FCC KDB 447498 D01v05 4.3.22, the following equation must be used to estimate the standalone 1-g SAR for simultaneous transmission assessment involving that transmitter

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel,mW})}{\text{Min.Separation Distance}}$$

. Mode	Frequency	Maximum Allowed Power	Separatuin Distance (Body)	Estimated SAR (Body)
	[MHz]	[mW]	[mm]	[W/kg]
Bluetooth	2440	8	10	0.17

Note : Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. The Estimated SAR results were determined according to FCC KDB447498 D01v05

### Simultaneous Transmission Summation for Held to Ear

Band	configuration	Scaled SAR(W/kg)	2.4 GHz WIFI Scaled SAR (W/kg)	$\Sigma$ 1-g SAR (W/kg)
GSM 850	Left Cheek	0.446	0.135	0.581
	Left Tilt	0.23	0.117	0.347
	Right Cheek	0.479	0.302	0.781
	Right Tilt	0.215	0.152	0.367
GSM 1900	Left Cheek	0.599	0.135	0.734
	Left Tilt	0.151	0.117	0.268
	Right Cheek	0.356	0.302	0.658
	Right Tilt	0.102	0.152	0.254
GSM 850	Left Cheek	0.739	0.135	0.874
	Left Tilt	0.416	0.117	0.533
	Right Cheek	0.773	0.302	1.075
	Right Tilt	0.336	0.152	0.488
GSM 1900	Left Cheek	0.65	0.135	0.785
	Left Tilt	0.175	0.117	0.292
	Right Cheek	0.414	0.302	0.716
	Right Tilt	0.111	0.152	0.263
WCDMA 1900	Left Cheek	0.751	0.135	0.886
	Left Tilt	0.22	0.117	0.337
	Right Cheek	0.628	0.302	0.93
	Right Tilt	0.188	0.152	0.34

### Simultaneous Transmission Summation for Body-Worn (1 cm)

Band	configuration	Scaled SAR(W/kg)	2.4 GHz WIFI Scaled SAR (W/kg)	BT SAR (W/kg)	$\Sigma$ 1-g SAR (W/kg)
GSM 850	Rear	0.699	0.068		0.767
				0.17	0.869
GSM 1900	Rear	0.371	0.068		0.439
				0.17	0.541
WCDMA 850	Rear	0.668	0.068		0.736
				0.17	0.838

**Simultaneous Transmission Summation for Hotspot (1 cm)**

Band	configuration	Scaled SAR(W/kg)	2.4 GHz WIFI Scaled SAR (W/kg)	$\Sigma$ 1-g SAR (W/kg)
GPRS 850	Rear	0.974	0.08	1.054
	Front	0.639	0.056	0.695
	Left	0.338	0.068	0.406
	Right	0.518		0.577
	Bottom	0.095		0.095
	Top		0.059	0.059
GPRS 1900	Rear	0.481	0.08	0.561
	Front	0.295	0.056	0.351
	Left	0.138	0.068	0.206
	Right	0.148		0.148
	Bottom	0.400		0.400
	Top		0.059	0.059
WCDMA 850	Rear	0.668	0.08	0.748
	Front	0.426	0.056	0.482
	Left	0.247	0.068	0.315
	Right	0.233		0.233
	Bottom	0.547		0.547
	Top		0.059	0.059

## 16. CONCLUSION

---

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the ANSI/IEEE C95.1 1992.

These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests.

## 17. REFERENCES

---

- [1] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields, July 2001.
- [2] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, IEE Recommended Practice or Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body from Wireless Communications Devices.
- [3] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio frequency Radiation, Aug. 1996.
- [4] ANSI/IEEE C95.1 - 1991, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 kHz to 100 GHz, New York: IEEE, Aug. 1992
- [5] ANSI/IEEE C95.3 - 1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, 1992.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Pokovi<sup>o</sup>, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300 MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectro magnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computer mathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [18] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10 kHz-300 GHz, Jan. 1995.
- [20] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [21] SAR Evaluation of Handsets with Multiple Transmitters and Antennas #648474.
- [22] SAR Measurement Procedure for 802.11 a/b/g Transmitters #KDB 248227.

## Attachment 1. – SAR Test Plots

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 1

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Left Touch 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.445 mW/g

**Left Touch 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 4.38 V/m; Power Drift = -0.144 dB  
Peak SAR (extrapolated) = 0.561 W/kg  
**SAR(1 g) = 0.403 mW/g; SAR(10 g) = 0.280 mW/g**  
Maximum value of SAR (measured) = 0.429 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 2

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Left tilt 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.220 mW/g


**Left tilt 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.98 V/m; Power Drift = -0.112 dB

Peak SAR (extrapolated) = 0.265 W/kg

**SAR(1 g) = 0.208 mW/g; SAR(10 g) = 0.151 mW/g**

Maximum value of SAR (measured) = 0.220 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 3

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Right touch 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.460 mW/g


**Right touch 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.51 V/m; Power Drift = -0.194 dB

Peak SAR (extrapolated) = 0.574 W/kg

**SAR(1 g) = 0.433 mW/g; SAR(10 g) = 0.301 mW/g**

Maximum value of SAR (measured) = 0.467 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 4

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Right tilt 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.207 mW/g


**Right tilt 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.54 V/m; Power Drift = -0.091 dB

Peak SAR (extrapolated) = 0.254 W/kg

**SAR(1 g) = 0.194 mW/g; SAR(10 g) = 0.138 mW/g**

Maximum value of SAR (measured) = 0.209 mW/g



0 dB = 0.209mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 5

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Left Touch GPRS 3Tx 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.787 mW/g

**Left Touch GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 5.58 V/m; Power Drift = -0.107 dB  
Peak SAR (extrapolated) = 0.966 W/kg  
**SAR(1 g) = 0.674 mW/g; SAR(10 g) = 0.450 mW/g**  
Maximum value of SAR (measured) = 0.737 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 6

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Left Tilt GPRS 3Tx 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.380 mW/g


**Left Tilt GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.83 V/m; Power Drift = -0.121 dB

Peak SAR (extrapolated) = 1.07 W/kg

**SAR(1 g) = 0.379 mW/g; SAR(10 g) = 0.265 mW/g**

Maximum value of SAR (measured) = 0.395 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 7

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Right touch GPRS 3Tx 190ch/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.753 mW/g


**Right touch GPRS 3Tx 190ch/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.11 V/m; Power Drift = -0.197 dB

Peak SAR (extrapolated) = 0.933 W/kg

**SAR(1 g) = 0.705 mW/g; SAR(10 g) = 0.496 mW/g**

Maximum value of SAR (measured) = 0.755 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 8

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 40.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.64, 6.64, 6.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 835/900 Phamtom ; Type: SAM

**Right tilt GPRS 3Tx 190ch/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.324 mW/g


**Right tilt GPRS 3Tx 190ch/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.9 V/m; Power Drift = 0.145 dB

Peak SAR (extrapolated) = 0.395 W/kg

**SAR(1 g) = 0.306 mW/g; SAR(10 g) = 0.222 mW/g**

Maximum value of SAR (measured) = 0.322 mW/g



0 dB = 0.322mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 9

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

**Left Touch 661/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.552 mW/g

**Left Touch 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 10.5 V/m; Power Drift = -0.077 dB  
Peak SAR (extrapolated) = 0.814 W/kg  
**SAR(1 g) = 0.534 mW/g; SAR(10 g) = 0.321 mW/g**  
Maximum value of SAR (measured) = 0.557 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 10

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

**Left tilt 661 GPRS 3Tx/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.161 mW/g

**Left tilt 661 GPRS 3Tx/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.13 V/m; Power Drift = -0.028 dB  
Peak SAR (extrapolated) = 0.189 W/kg  
**SAR(1 g) = 0.135 mW/g; SAR(10 g) = 0.088 mW/g**  
Maximum value of SAR (measured) = 0.145 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 11

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

**Right Touch 661/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.377 mW/g


**Right Touch 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.49 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 0.438 W/kg

**SAR(1 g) = 0.317 mW/g; SAR(10 g) = 0.205 mW/g**

Maximum value of SAR (measured) = 0.344 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 12

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

**Right Tilt 661/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.102 mW/g


**Right Tilt 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.21 V/m; Power Drift = 0.086 dB

Peak SAR (extrapolated) = 0.146 W/kg

**SAR(1 g) = 0.091 mW/g; SAR(10 g) = 0.056 mW/g**

Maximum value of SAR (measured) = 0.097 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 13

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

**Left Touch 661 GPRS 3Tx/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.632 mW/g

**Left Touch 661 GPRS 3Tx/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 7.52 V/m; Power Drift = -0.073 dB  
Peak SAR (extrapolated) = 0.920 W/kg  
**SAR(1 g) = 0.597 mW/g; SAR(10 g) = 0.356 mW/g**  
Maximum value of SAR (measured) = 0.632 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 14

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

**Left Tilt 661 GPRS 3Tx/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.198 mW/g

**Left Tilt 661 GPRS 3Tx/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.75 V/m; Power Drift = -0.028 dB  
Peak SAR (extrapolated) = 0.217 W/kg  
**SAR(1 g) = 0.161 mW/g; SAR(10 g) = 0.103 mW/g**  
Maximum value of SAR (measured) = 0.179 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 15

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$


Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

**Right Touch 661 GPRS 3Tx/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.450 mW/g

**Right Touch 661 GPRS 3Tx/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 7.06 V/m; Power Drift = -0.032 dB  
Peak SAR (extrapolated) = 0.530 W/kg  
**SAR(1 g) = 0.380 mW/g; SAR(10 g) = 0.234 mW/g**  
Maximum value of SAR (measured) = 0.413 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 16

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$


Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 800/900 Phantom; Type: SAM

Right Tilt 661 GPRS 3Tx/Area Scan (61x91x1): Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.114 mW/g

Right Tilt 661 GPRS 3Tx/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.86 V/m; Power Drift = -0.006 dB  
Peak SAR (extrapolated) = 0.168 W/kg  
**SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.065 mW/g**  
Maximum value of SAR (measured) = 0.107 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 17

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 9400/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.786 mW/g

**Left touch 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.06 V/m; Power Drift = -0.156 dB  
Peak SAR (extrapolated) = 1.02 W/kg  
**SAR(1 g) = 0.642 mW/g; SAR(10 g) = 0.374 mW/g**  
Maximum value of SAR (measured) = 0.688 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 18

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left tilt 9400/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.223 mW/g

**Left tilt 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.11 V/m; Power Drift = -0.063 dB  
Peak SAR (extrapolated) = 0.287 W/kg  
**SAR(1 g) = 0.188 mW/g; SAR(10 g) = 0.116 mW/g**  
Maximum value of SAR (measured) = 0.197 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 19

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 9400/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.602 mW/g

**Right touch 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.62 V/m; Power Drift = -0.122 dB  
Peak SAR (extrapolated) = 0.786 W/kg  
**SAR(1 g) = 0.537 mW/g; SAR(10 g) = 0.326 mW/g**  
Maximum value of SAR (measured) = 0.578 mW/g

**Right touch 9400/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.62 V/m; Power Drift = -0.122 dB  
Peak SAR (extrapolated) = 0.703 W/kg  
**SAR(1 g) = 0.482 mW/g; SAR(10 g) = 0.308 mW/g**  
Maximum value of SAR (measured) = 0.522 mW/g



0 dB = 0.522mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 20

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.35 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(5.26, 5.26, 5.26); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 9400/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.179 mW/g

**Right touch 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 11.0 V/m; Power Drift = 0.042 dB  
Peak SAR (extrapolated) = 0.260 W/kg  
**SAR(1 g) = 0.161 mW/g; SAR(10 g) = 0.097 mW/g**  
Maximum value of SAR (measured) = 0.171 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 21

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.86 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.59, 4.59, 4.59); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 1800/1900 Phantom; Type: SAM

**Left touch 11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.123 mW/g


**Left touch 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.84 V/m; Power Drift = -0.088 dB

Peak SAR (extrapolated) = 0.202 W/kg

**SAR(1 g) = 0.108 mW/g; SAR(10 g) = 0.058 mW/g**

Maximum value of SAR (measured) = 0.118 mW/g



0 dB = 0.118mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 22

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.86 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.59, 4.59, 4.59); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 1800/1900 Phantom; Type: SAM

**Left tilt 11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 0.104 mW/g

**Left tilt 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 6.69 V/m; Power Drift = -0.035 dB  
Peak SAR (extrapolated) = 0.180 W/kg  
**SAR(1 g) = 0.093 mW/g; SAR(10 g) = 0.049 mW/g**  
Maximum value of SAR (measured) = 0.101 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 23

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.86 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.59, 4.59, 4.59); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 1800/1900 Phantom; Type: SAM

**Right touch 11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.282 mW/g


**Right touch 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.1 V/m; Power Drift = -0.136 dB

Peak SAR (extrapolated) = 0.601 W/kg

**SAR(1 g) = 0.241 mW/g; SAR(10 g) = 0.111 mW/g**

Maximum value of SAR (measured) = 0.261 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 24

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.86 \text{ mho/m}$ ;  $\epsilon_r = 38.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.59, 4.59, 4.59); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: 1800/1900 Phantom; Type: SAM

**Right tilt 11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.142 mW/g


**Right tilt 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.66 V/m; Power Drift = 0.135 dB

Peak SAR (extrapolated) = 0.283 W/kg

**SAR(1 g) = 0.121 mW/g; SAR(10 g) = 0.058 mW/g**

Maximum value of SAR (measured) = 0.135 mW/g



0 dB = 0.135mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 25  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:2.77

Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 0.978 \text{ mho/m}$ ;  $\epsilon_r = 56.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear GPRS 3Tx 128/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.920 mW/g

**Body rear GPRS 3Tx 128/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.76 V/m; Power Drift = 0.195 dB

Peak SAR (extrapolated) = 1.16 W/kg

**SAR(1 g) = 0.874 mW/g; SAR(10 g) = 0.623 mW/g**

Maximum value of SAR (measured) = 0.923 mW/g


**Body rear GPRS 3Tx 128/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.76 V/m; Power Drift = 0.195 dB

Peak SAR (extrapolated) = 1.12 W/kg

**SAR(1 g) = 0.781 mW/g; SAR(10 g) = 0.536 mW/g**

Maximum value of SAR (measured) = 0.859 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 26  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.987 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear GPRS 3Tx 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.978 mW/g

**Body rear GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.25 V/m; Power Drift = -0.123 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.888 mW/g; SAR(10 g) = 0.633 mW/g

Maximum value of SAR (measured) = 0.943 mW/g


**Body rear GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.25 V/m; Power Drift = -0.123 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.794 mW/g; SAR(10 g) = 0.548 mW/g

Maximum value of SAR (measured) = 0.853 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 27  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 848.8 \text{ MHz}$ ;  $\sigma = 0.998 \text{ mho/m}$ ;  $\epsilon_r = 56.7$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear GPRS 3Tx 251/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.863 mW/g

**Body rear GPRS 3Tx 251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.21 V/m; Power Drift = 0.149 dB

Peak SAR (extrapolated) = 1.13 W/kg

**SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.504 mW/g**


Maximum value of SAR (measured) = 0.790 mW/g

**Body rear GPRS 3Tx 251/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.21 V/m; Power Drift = 0.149 dB

Peak SAR (extrapolated) = 1.08 W/kg

**SAR(1 g) = 0.815 mW/g; SAR(10 g) = 0.576 mW/g**

Maximum value of SAR (measured) = 0.868 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 28  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.987 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body front GPRS 3Tx 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.617 mW/g


**Body front GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.18 V/m; Power Drift = 0.129 dB

Peak SAR (extrapolated) = 0.755 W/kg

SAR(1 g) = 0.583 mW/g; SAR(10 g) = 0.417 mW/g

Maximum value of SAR (measured) = 0.617 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 29  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1


Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.987 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body left GPRS 3Tx 190/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.330 mW/g

**Body left GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 9.13 V/m; Power Drift = -0.018 dB  
Peak SAR (extrapolated) = 0.435 W/kg  
**SAR(1 g) = 0.308 mW/g; SAR(10 g) = 0.208 mW/g**  
Maximum value of SAR (measured) = 0.334 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 30  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.987 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body right GPRS 3Tx 190/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.509 mW/g


**Body right GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.1 V/m; Power Drift = -0.061 dB

Peak SAR (extrapolated) = 0.654 W/kg

SAR(1 g) = 0.472 mW/g; SAR(10 g) = 0.326 mW/g

Maximum value of SAR (measured) = 0.503 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 31  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.77

Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.987 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body bottom GPRS 3Tx 190/Area Scan (61x41x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.099 mW/g


**Body bottom GPRS 3Tx 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.2 V/m; Power Drift = -0.188 dB

Peak SAR (extrapolated) = 0.162 W/kg

SAR(1 g) = 0.087 mW/g; SAR(10 g) = 0.055 mW/g

Maximum value of SAR (measured) = 0.092 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 32  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:


- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear 661/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.609 mW/g

**Body rear 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.63 V/m; Power Drift = 0.062 dB

Peak SAR (extrapolated) = 0.697 W/kg  
**SAR(1 g) = 0.442 mW/g; SAR(10 g) = 0.259 mW/g**

Maximum value of SAR (measured) = 0.476 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 33  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:


- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body front 661/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.302 mW/g

**Body front 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 5.07 V/m; Power Drift = 0.180 dB

Peak SAR (extrapolated) = 0.428 W/kg  
 $\text{SAR}(1 \text{ g}) = 0.271 \text{ mW/g}$ ;  $\text{SAR}(10 \text{ g}) = 0.164 \text{ mW/g}$

Maximum value of SAR (measured) = 0.293 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 34  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body left 661/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.140 mW/g

**Body left 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.58 V/m; Power Drift = 0.037 dB

Peak SAR (extrapolated) = 0.209 W/kg  
**SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.073 mW/g**  
Maximum value of SAR (measured) = 0.140 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 35  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body right 661/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.151 mW/g


**Body right 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.90 V/m; Power Drift = 0.116 dB

Peak SAR (extrapolated) = 0.206 W/kg

SAR(1 g) = 0.136 mW/g; SAR(10 g) = 0.084 mW/g

Maximum value of SAR (measured) = 0.149 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 36  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body bottom 661ch/Area Scan (61x41x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.442 mW/g


**Body bottom 661ch/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.5 V/m; Power Drift = -0.131 dB

Peak SAR (extrapolated) = 0.573 W/kg

SAR(1 g) = 0.367 mW/g; SAR(10 g) = 0.214 mW/g

Maximum value of SAR (measured) = 0.398 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 37  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear 9400/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.678 mW/g

**Body rear 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 8.14 V/m; Power Drift = 0.136 dB  
Peak SAR (extrapolated) = 0.921 W/kg

SAR(1 g) = 0.571 mW/g; SAR(10 g) = 0.330 mW/g  
Maximum value of SAR (measured) = 0.618 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 38  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body front 9400/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.403 mW/g

**Body front 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.61 V/m; Power Drift = 0.029 dB  
Peak SAR (extrapolated) = 0.580 W/kg

SAR(1 g) = 0.364 mW/g; SAR(10 g) = 0.220 mW/g  
Maximum value of SAR (measured) = 0.396 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 39  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body left 9400/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.229 mW/g


**Body left 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.82 V/m; Power Drift = 0.137 dB

Peak SAR (extrapolated) = 0.322 W/kg

**SAR(1 g) = 0.211 mW/g; SAR(10 g) = 0.131 mW/g**

Maximum value of SAR (measured) = 0.230 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 40  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body right 9400/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.221 mW/g

**Body right 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.90 V/m; Power Drift = 0.181 dB  
Peak SAR (extrapolated) = 0.309 W/kg

SAR(1 g) = 0.199 mW/g; SAR(10 g) = 0.121 mW/g  
Maximum value of SAR (measured) = 0.218 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 41  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body bottom 9400/Area Scan (61x41x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.573 mW/g


**Body bottom 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.5 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 0.733 W/kg

**SAR(1 g) = 0.468 mW/g; SAR(10 g) = 0.273 mW/g**

Maximum value of SAR (measured) = 0.508 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 42  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 2 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1605; ConvF(4.07, 4.07, 4.07); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear 11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.073 mW/g


**Body rear 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.91 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.137 W/kg

**SAR(1 g) = 0.064 mW/g; SAR(10 g) = 0.034 mW/g**

Maximum value of SAR (measured) = 0.070 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 43  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 2 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:


- Probe: ET3DV6 - SN1605; ConvF(4.07, 4.07, 4.07); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body front 11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 0.046 mW/g

**Body front 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 3.05 V/m; Power Drift = 0.189 dB

Peak SAR (extrapolated) = 0.090 W/kg  
 $\text{SAR}(1 \text{ g}) = 0.045 \text{ mW/g}$ ;  $\text{SAR}(10 \text{ g}) = 0.022 \text{ mW/g}$

Maximum value of SAR (measured) = 0.049 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 44  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 2 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.07, 4.07, 4.07); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body left 11/Area Scan (41x111x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 0.061 mW/g

**Body left 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 5.43 V/m; Power Drift = -0.101 dB  
Peak SAR (extrapolated) = 0.126 W/kg

SAR(1 g) = 0.054 mW/g; SAR(10 g) = 0.024 mW/g  
Maximum value of SAR (measured) = 0.060 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.21, 2013  
Plot NO. 45  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 2 \text{ mho/m}$ ;  $\epsilon_r = 53.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.07, 4.07, 4.07); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body top 11/Area Scan (71x51x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 0.051 mW/g

**Body top 11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 4.72 V/m; Power Drift = -0.133 dB  
Peak SAR (extrapolated) = 0.092 W/kg

SAR(1 g) = 0.047 mW/g; SAR(10 g) = 0.025 mW/g  
Maximum value of SAR (measured) = 0.050 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.2 °C  
Ambient Temperature: 21.4 °C  
Test Date: Mar.18, 2013  
Plot NO. 46  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: #1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.987 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:


- Probe: ET3DV6 - SN1605; ConvF(6.52, 6.52, 6.52); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear 190/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.678 mW/g

**Body rear 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 12.5 V/m; Power Drift = 0.060 dB  
Peak SAR (extrapolated) = 0.834 W/kg

SAR(1 g) = 0.632 mW/g; SAR(10 g) = 0.452 mW/g  
Maximum value of SAR (measured) = 0.669 mW/g

**Body rear 190/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 12.5 V/m; Power Drift = 0.060 dB  
Peak SAR (extrapolated) = 0.832 W/kg  
SAR(1 g) = 0.580 mW/g; SAR(10 g) = 0.408 mW/g  
Maximum value of SAR (measured) = 0.632 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular /PCS GSM/GPRS/EDGE(RX Only) /WCDMA /HSDPA Phone with Bluetooth, WLAN  
Liquid Temperature: 21.4 °C  
Ambient Temperature: 21.6 °C  
Test Date: Mar.19, 2013  
Plot NO. 47  
Separation Distance 1.0 cm

DUT: LG-E425J; Type: bar; Serial: # 1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.64, 4.64, 4.64); Calibrated: 2012-04-26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn466; Calibrated: 2013-02-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA

**Body rear 661/Area Scan (61x91x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.366 mW/g

**Body rear 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.83 V/m; Power Drift = -0.033 dB

Peak SAR (extrapolated) = 0.649 W/kg

SAR(1 g) = 0.331 mW/g; SAR(10 g) = 0.169 mW/g

Maximum value of SAR (measured) = 0.357 mW/g

