

PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



HEARING AID COMPATIBILITY

Applicant Name:

LG Electronics MobileComm U.S.A. Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 **United States**

Date of Testing: 04/14/2018 - 04/18/2018 Test Site/Location: PCTEST Lab, Columbia, MD, USA

Test Report Serial No.: 1M1804030060-13-R2.ZNF

FCC ID: ZNFG710TM

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A. INC.

Audio Band Magnetic Testing (T-Coil) Scope of Test:

Application Type: Class II Permissive Change

CFR §20.19(b) FCC Rule Part(s): **HAC Standard:** ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

DUT Type: Portable Handset Model: LM-G710TM

Additional Model(s): LMG710TM, G710TM, LM-G710AWM, LMG710AWM, G710AWM,

LM-G710RM, LMG710RM, G710RM Pre-Production Sample [S/N: 09753]

Class II Permissive Change(s): See FCC Change Document

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

Note: This revised Test Report (S/N: 1M1804030060-13-R2.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Test Device Serial No.:





FCC ID: ZNFG710TM	POTEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 1 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 1 of 76

TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	6
4.	METHOD OF MEASUREMENT	8
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	18
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	21
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	24
8.	FCC 3G MEASUREMENTS	27
9.	T-COIL TEST SUMMARY	28
10.	MEASUREMENT UNCERTAINTY	39
11.	EQUIPMENT LIST	40
12.	TEST DATA	41
13.	CALIBRATION CERTIFICATES	64
14.	CONCLUSION	71
15.	REFERENCES	72
16.	TEST SETUP PHOTOGRAPHS	74

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 2 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Fage 2 01 76

1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFG710TM	INCIRCLAND LANDS TO 1, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 2 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 3 of 76

2. DUT DESCRIPTION



FCC ID: ZNFG710TM

Applicant: LG Electronics MobileComm U.S.A. Inc.

1000 Sylvan Avenue

Englewood Cliffs, NJ 07632

United States

Model: LM-G710TM

Additional Model(s): LMG710TM, G710TM, LM-G710AWM, LMG710AWM,

G710AWM, LM-G710RM, LMG710RM, G710RM

Serial Number: 09753
HW Version: Rev.1.0
SW Version: G710TM07y
Antenna: Internal Antenna
DUT Type: Portable Handset

I. LTE Band Selection

This device supports the following pairs of LTE bands with similar frequencies: LTE B12 & B17, LTE B66 & B4, and LTE B25 & B2. Each of these pairs of LTE bands has the same target power and shares the same transmission path. Since the supported frequency spans for the smaller LTE bands are completely covered by the larger LTE bands, only the larger LTE bands (LTE B12, B66, and B25) were evaluated for hearing-aid compliance.

FCC ID: ZNFG710TM	POTEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 4 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 4 of 76

Table 2-1 **ZNFG710TM HAC Air Interfaces**

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service	
	850	VO	Yes	Yes: WIFI or BT	CMRS Voice*	
GSM	1900				Google Duo**	
	GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo**	
	850	-				
UMTS	1700	VD	Yes	Yes: WIFI or BT	CMRS Voice*	
	1900					
	HSPA	VD	Yes	Yes: WIFI or BT	Google Duo**	
	680 (B71)	1	Yes ¹			
	700 (B12)	1				
	700 (B17)	<u> </u>		Yes: WIFI or BT	VoLTE*, Google Duo**	
	780 (B13)	1	Yes			
LTE (FDD)	850 (B5)					
	1700 (B4)	VD				
	1700 (B66)					
	1900 (B2)					
	1900 (B25)					
	2300 (B30)					
	2500 (B7)					
LTE (TDD)	2600 (B41)	VD	Yes	Yes: WIFI or BT	VoLTE*, Google Duo**	
	2450					
	5200 (U-NII 1)					
WIFI	5300 (U-NII 2A)	VD	Yes	Yes: GSM, UMTS, or LTE	VoWIFI**, Google Duo**	
	5500 (U-NII 2C)					
	5800 (U-NII 3)					
ВТ	2450	DT	No	Yes: GSM, UMTS, or LTE	N/A	
DT = Digital Data - Not intended for CMRS Service Interpre VD = CMRS and IP Voice over Data Transport ** Refe 1. LTE B			* Reference le Interpretation ** Reference 1. LTE B71, wh	evel in accordance with 7.4.2.1 of ANSI C63.19-20 level is -20dBm0 in accordance with FCC KDB 285 inlie outside the scope of ANSI C63.19 and FCC HA	5076 D02	

to the existing HAC procedures.

FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg F of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 5 of 76

3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

I. MAGNETIC COUPLING

Axial and Radial Field Intensity

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be \geq -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz




Figure 3-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds
-15 dB(A/m) at 1 kHz

FCC ID: ZNFG710TM	PETEST VINCIALISM LABORATORY, LAC	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo C of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 6 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

Signal Quality

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Catagoni	Telephone RF Parameters		
Category	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]		
T1	0 to 10 dB		
T2	10 to 20 dB		
Т3	20 to 30 dB		
T4	> 30 dB		
Table 3-1 Magnetic Coupling Parameters			

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFG710TM	INCREES CARDES ON THE	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 7 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 7 of 76

4. METHOD OF MEASUREMENT

I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:





Figure 4-1
Validation Setup with Helmholtz Coil



FCC ID: ZNFG710TM	PETEST INCHESCO LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 0 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 8 of 76

T-Coil Test Setup

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size: 0.1 mm

Maximum speed 6.1 cm/sec
Line Voltage: 115 VAC
Line Frequency: 60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T

Active Frequency 100 Hz – 8 kHz

Range:
Stimulus Type:
Male and Female, no spaces

Single Sample 20.96 seconds

Duration: 20.90 seco

Activity Level: 100%






Figure 4-4
Spectral Characteristic of full P.50



Temporal Characteristic of full P.50

FCC ID: ZNFG710TM	INCHEST OF LANDSTON, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo O of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 9 of 76



ABM2 Measurement Block Diagram:



Figure 4-6 Magnetic Measurement Processing Steps

IV. Test Procedure

- 1. Ambient Noise Check per C63.19 §7.3.1
 - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
 - b. "A-weighting" and Half-Band Integration was applied to the measurements.
 - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation(See Figure 4-1)
 - The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
 - b. ABM1 Validation

The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where H_c = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.08m; R=10.2Ω and using V=18mV:

Coil, N=20; r=0.08m; R=10.20 and using V=18mV:
$$H_c = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of -10 dB(A/m) in the center of the Helmholtz coil which was used to validate the probe measurement at -10dB(A/m). This was verified to be within \pm 0.5 dB of the -10dB(A/m) value (see Page 37).

FCC ID: ZNFG710TM	PETEST EXCHANGE CARRETON, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 10 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 10 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

c. Frequency Response Validation

The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:



Figure 4-7 Frequency Response Validation


d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 11 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 11 of 76







Figure 4-8
ABM2 Frequency Response Validation

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2
ABM2 Power Sum Validation

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFG710TM	PETEST EXCHANGE CARRETON, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 10 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 12 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M





Figure 4-10
ABM2 Power Sum Validation

3. Measurement Test Setup

- a. Fine scan above the WD (TEM)
 - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):



- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-15 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator

Measurement Distance

i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN™	TDMA (22 and 11 Hz)	-18

FCC ID: ZNFG710TM	PETEST VINGHEEF ON LABORATORY, LAC	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 12 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 13 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

(5.2,5.2)

Measurement Grid

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- iii. See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.
- c. Real-Time Analyzer (RTA)
 - i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.
- d. WD Radio Configuration Selection
 - i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 8 for more information regarding worst-case configurations for UMTS. LTE configuration information can be found in Section 5. WIFI configuration information can be found in Section 6 and 7):




Figure 4-13 Vocoder Analysis for ABM Noise for GSM

- Signal Quality Data Analysis
 - a. Narrow-band Magnetic Intensity
 - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.
 - b. Frequency Response
 - i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
 - ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
 - iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.

FCC ID: ZNFG710TM	INCREES CARDES ON THE	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 14 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 14 of 76

c. Signal Quality Index

- i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz -10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
- ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
- iii. This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

٧. **Test Setup**




Figure 4-14 **Audio Magnetic Field Test Setup**

VI. **Deviation from C63.19 Test Procedure**

Non-conducted RF connection due to inaccessible RF ports.

VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 15 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 15 of 76

VIII. Wireless Device Channels and Frequencies

1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes since circuit-switched voice modes were worst-case.

> Table 4-3 Center Channels and Frequencies

ochici onamicio una i requencies				
Test frequencies & associated channels				
Channel	Frequency (MHz)			
Cellular 850				
190 (GSM)	836.60			
4183 (UMTS)	836.60			
AWS 1750				
1412 (UMTS)	1730.40			
PCS 1900				
661 (GSM)	1880			
9400 (UMTS)	1880			

2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. Low-mid and mid-high channels are additionally tested for LTE TDD. The middle channel and supported bandwidths from the worst-case band according to Table 7-5 was additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-4 to 9-12 as well as 9-19 to 9-20 for LTE bandwidths and channels.

3. WIFI

The middle channel for each 802.11 standard was tested for each probe orientation. The 2.4GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. The 5GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested on higher U-NII bands as well as applicable low and high channels. See Tables 9-13 to 9-16 as well as 9-21 to 9-24 for WIFI standards and channels.

FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 16 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 16 of 76

IX. Test Flow

The flow diagram below was followed (From C63.19):




Figure 4-15 C63.19 T-Coil Signal Test Process

FCC ID: ZNFG710TM	INCHEST OF LANDSTON, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 17 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 17 of 76

5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoLTE over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1
Test Setup for VoLTE over IMS T-Coil Measurements

2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

* http://c63.org/documents/misc/posting/new_interpretations.htm

FCC ID: ZNFG710TM	PETEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 10 of 76
1M1804030060-13-R2 7NF	04/14/2018 - 04/18/2018	Portable Handset		Page 18 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. DUT Configuration for VoLTE over IMS T-coil Testing

1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. 16QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

Table 5-1
VoLTE over IMS SNNR by Radio Configuration

		VOLILO	LEI IIAIO OIA	INIX Dy I	laulo oo	inigaratio		
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
1882.5	26365	20	QPSK	1	0	-3.31	-54.59	51.28
1882.5	26365	20	QPSK	1	25	-2.88	-50.69	47.81
1882.5	26365	20	QPSK	1	49	-3.18	-51.67	48.49
1882.5	26365	20	QPSK	25	0	-3.17	-52.96	49.79
1882.5	26365	20	QPSK	25	12	-2.74	-55.28	52.54
1882.5	26365	20	QPSK	25	25	-3.26	-57.01	53.75
1882.5	26365	20	QPSK	50	0	-3.06	-52.65	49.59
1882.5	26365	20	16QAM	1	0	-3.19	-48.40	45.21
1882.5	26365	20	16QAM	1	25	-3.29	-49.32	46.03
1882.5	26365	20	16QAM	1	49	-3.26	-48.96	45.70
1882.5	26365	20	16QAM	25	0	-3.18	-51.21	48.03
1882.5	26365	20	16QAM	25	12	-2.98	-52.97	49.99
1882.5	26365	20	16QAM	25	25	-2.89	-52.17	49.28
1882.5	26365	20	16QAM	50	0	-2.93	-51.79	48.86
1882.5	26365	20	64QAM	1	0	-3.09	-49.22	46.13
1882.5	26365	20	64QAM	1	25	-3.15	-48.50	45.35
1882.5	26365	20	64QAM	1	49	-2.79	-48.92	46.13
1882.5	26365	20	64QAM	25	0	-2.80	-53.89	51.09
1882.5	26365	20	64QAM	25	12	-2.76	-49.73	46.97
1882.5	26365	20	64QAM	25	25	-3.16	-50.76	47.60
1882.5	26365	20	64QAM	50	0	-3.10	-50.70	47.60


2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 5-2
AMR Codec Investigation – VoLTE over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	-2.03	-3.24	-1.46	-1.56		LTE Band 12 10MHz	23095
ABM2 (dBA/m)	-48.56	-48.40	-48.39	-49.77	Axial		
Frequency Response	Pass	Pass	Pass	Pass	Axiai		
S+N/N (dB)	46.53	45.16	46.93	48.21			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFG710TM	POTEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 10 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 19 of 76

3. LTE TDD Uplink-Downlink Configuration Investigation for VoLTE over IMS

An investigation was performed to determine the worst-case Uplink-Downlink configuration for VoLTE over IMS T-Coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length $T_f = 307200 \cdot T_s$ = 10 ms, where T_s is a number of time units equal to 1/(15000 x 2048) seconds. Additionally, each radio frame consists of 10 subframes, each of length 30720 · T_s = 1 ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is 2192 · Ts which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

> Table 5-3 **Uplink-Downlink Configurations for Type 2 Frame Structures**

Uplink-downlink configuration	Downlink-to-Uplink Subframe number Switch-point periodicity								Calculated Transmission			
configuration	Switch-point periodicity	0	1	2	3	4	5	6	7	8	9	Duty Cycle (%)
0	5 ms	D	S	U	J	U	D	S	J	J	J	61.4%
1	5 ms	D	S	U	U	D	D	S	U	U	D	41.4%
2	5 ms	D	S	U	D	D	D	S	J	D	D	21.4%
3	10 ms	D	S	U	J	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	J	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	Ū	U	D	S	U	U	D	51.4%

a. Power Class 3 Uplink-Downlink Configuration Investigation

Power class 3 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 0RB Offset. For Power Class 3, all configurations (0-6) are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 6 was used as the worst-case configuration for Power Class 3 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-4 Power Class 3 VolTE over IMS SNNR by UL-DL Configuration

	I Ower Class 3 Vol IL Over INO SHARE by OL-DL Configuration											
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]			
2593.0	40620	20	16QAM	1	0	0	-3.24	-44.64	41.40			
2593.0	40620	20	16QAM	1	0	1	-3.61	-44.87	41.26			
2593.0	40620	20	16QAM	1	0	2	-3.37	-45.39	42.02			
2593.0	40620	20	16QAM	1	0	3	-3.29	-46.80	43.51			
2593.0	40620	20	16QAM	1	0	4	-3.57	-46.39	42.82			
2593.0	40620	20	16QAM	1	0	5	-3.64	-46.52	39.75			
2593.0	40620	20	16QAM	1	0	6	-3.30	-40.73	37.43			

b. Conclusion

Per the investigations above, UL-DL Configuration 6 was used to evaluate Power Class 3 VoLTE over IMS.

FCC ID: ZNFG710TM	EXPLANATION LABORATORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 20 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Fage 20 01 76

VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION 6.

I. Test System Setup for VoWIFI over IMS T-coil Testing

Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1 Test Setup for VoWIFI over IMS T-Coil Measurements

2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level2. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

² FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

	TCC Office of Engineering and Technology RDB, 263076 D02 T-Coli Testing for Civil 7 F V03, September 13, 2017									
FCC ID: ZNFG710TM	INCIRERATE LADDRESON, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager						
Filename:	Test Dates:	DUT Type:		Page 21 of 76						
1M1804030060-13-R2 ZNF	04/14/2018 - 04/18/2018	Portable Handset		1 490 21 01 70						

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

DUT Configuration for VoWIFI over IMS T-coil Testing II.

1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each 802.11 standard:

> Table 6-1 802.11b SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11b	6	DSSS	1	-7.06	-38.96	31.90
802.11b	6	DSSS	2	-7.23	-40.22	32.99
802.11b	6	CCK	5.5	-7.01	-39.26	32.25
802.11b	6	CCK	11	-6.75	-39.43	32.68

Table 6-2 802.11g/a SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11g	6	BPSK	6	-7.29	-43.57	36.28
802.11g	6	BPSK	9	-6.72	-42.42	35.70
802.11g	6	QPSK	12	-6.77	-44.30	37.53
802.11g	6	QPSK	18	-7.09	-45.47	38.38
802.11g	6	16-QAM	24	-6.70	-46.59	39.89
802.11g	6	16-QAM	36	-6.66	-46.51	39.85
802.11g	6	64-QAM	48	-7.10	-46.71	39.61
802.11g	6	64-QAM	54	-6.64	-47.48	40.84

Table 6-3 802.11n/ac 20MHz BW SNNR by Radio Configuration

	Bandwidth			Data Rate	ABM1	ABM2	SNNR
Mode	[MHz]	Channel	Modulation	[Mbps]	[dB(A/m)]	[dB(A/m)]	GNNK [dB]
802.11n	20	40	BPSK	6.5	-7.01	-53.28	46.27
802.11n	20	40	QPSK	13	-7.05	-54.60	47.55
802.11n	20	40	QPSK	19.5	-7.22	-54.83	47.61
802.11n	20	40	16-QAM	26	-6.66	-53.15	46.49
802.11n	20	40	16-QAM	39	-6.80	-54.74	47.94
802.11n	20	40	64-QAM	52	-7.14	-55.41	48.27
802.11n	20	40	64-QAM	58.5	-6.85	-54.40	47.55
802.11n	20	40	64-QAM	65	-7.01	-54.84	47.83
802.11ac	20	40	256-QAM	78	-6.85	-55.75	48.90

FCC ID: ZNFG710TM	POTEST VIXENCE LABORATORY, NE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 22 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 22 01 76

Table 6-4 802.11n/ac 40MHz BW SNNR by Radio Configuration

	002.1 m/ac 40minz BW Olding By Radio Configuration								
Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]		
802.11n	40	38	BPSK	13.5	-7.17	-53.81	46.64		
802.11n	40	38	QPSK	27	-6.82	-54.36	47.54		
802.11n	40	38	QPSK	40.5	-7.30	-55.04	47.74		
802.11n	40	38	16-QAM	54	-7.22	-54.69	47.47		
802.11n	40	38	16-QAM	81	-6.73	-53.57	46.84		
802.11n	40	38	64-QAM	108	-6.64	-54.80	48.16		
802.11n	40	38	64-QAM	121.5	-6.70	-54.53	47.83		
802.11n	40	38	64-QAM	135	-7.04	-55.05	48.01		
802.11ac	40	38	256-QAM	162	-6.87	-54.14	47.27		
802.11ac	40	38	256-QAM	180	-7.16	-55.09	47.93		

2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 6-5 AMR Codec Investigation - VoWIFI over IMS

AMIX Codec investigation – vovni rover imo									
Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel	
ABM1 (dBA/m)	-5.83	-7.34	-5.24	-5.20					
ABM2 (dBA/m)	-39.03	-39.09	-39.19	-39.00	Axial	2.4GHz			
Frequency Response	Pass	Pass	Pass	Pass	Axiai	2.4GHZ	802.11b	6	
S+N/N (dB)	33.20	31.75	33.95	33.80					

Mute on; Backlight off; Max Volume; Max Contrast




Figure 6-2 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 22 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 23 of 76

7. OTT VOIP TEST SYSTEM AND DUT CONFIGURATION

I. Test System Setup for OTT VolP T-Coil Testing

1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 64kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation³. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

II. DUT Configuration for OTT VoIP T-Coil Testing

1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 6kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

Table 7-1
Codec Investigation – OTT VoIP (EDGE)

Codec Setting:	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	8.29	8.38		
ABM2 (dBA/m)	-37.25	-35.59	Axial	661
Frequency Response	Pass	Pass	Axiai	
S+N/N (dB)	45.54	43.97		

³ FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFG710TM	PCTEST INCIDENCE LABORATORS, INC.	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 24 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Fage 24 01 70

Table 7-2 Codec Investigation - OTT VoIP (HSPA)

Couce investigation of the (not A)							
Codec Setting:	64kbps	64kbps 6kbps		Channel			
ABM1 (dBA/m)	8.89	9.06					
ABM2 (dBA/m)	-53.79	-52.64	Axial	9400			
Frequency Response	Pass	Pass	Axiai				
S+N/N (dB)	62.68	61.70					

Table 7-3 Codec Investigation - OTT VoIP (LTE)

				<u> </u>	
Codec Setting:	64kbps	6kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	8.89	9.06			
ABM2 (dBA/m)	-46.36	-45.83	Axial	LTE Band 13	23230
Frequency Response	Pass	Pass	Axidi	10MHz	
S+N/N (dB)	55.25	54.89			

Table 7-4 Codec Investigation - OTT VoIP (WIFI)

Oddec investigation – OTT voir (vvir)										
Codec Setting:	64kbps	6kbps	Orientation	Band	Standard	Channel				
ABM1 (dBA/m)	10.20	9.43			2.4GHz 802.11b	6				
ABM2 (dBA/m)	-34.55	-34.64	Axial	2.401.1-						
Frequency Response	Pass	Pass	Axiai	2.4GHz						
S+N/N (dB)	44.75	44.07								

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.G




Figure 7-1 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFG710TM	ENGINEER C LADDETON, INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 05 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 25 of 76

2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE band to be used for OTT VoIP testing. LTE Band 13 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE bands:

Table 7-5
OTT VoIP (LTE) SNNR by LTE Band

			<u> </u>	· <u> </u>					
Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
71	680.5	133297	20	16QAM	1	0	9.24	-46.46	55.70
12	707.5	23095	10	16QAM	1	0	9.02	-49.60	58.62
13	782.0	23230	10	16QAM	1	0	9.20	-46.48	55.68
5	836.5	20525	10	16QAM	1	0	9.22	-48.08	57.30
66	1732.5	132322	20	16QAM	1	0	9.27	-49.11	58.38
25	1882.5	26365	20	16QAM	1	0	9.13	-47.47	56.60
7	2535.0	21100	20	16QAM	1	0	9.07	-48.45	57.52
30	2310.0	27710	10	16QAM	1	0	9.20	-48.29	57.49

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 26 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 20 01 70

FCC 3G MEASUREMENTS 8.

I. **UMTS Test Configurations**

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:




Figure 8-1 **UMTS Audio Band Magnetic Noise**

Table 8-1 **Codec Investigation - UMTS**

Codec investigation - On 10							
Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel		
ABM1 (dBA/m)	-1.49	-1.45	-1.64		9400		
ABM2 (dBA/m)	-58.58	-58.74	-58.91	Axial			
Frequency Response	Pass	Pass	Pass	Axiai			
S+N/N (dB)	57.09	57.29	57.27				

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC="All 1s"




Figure 8-2 Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 27 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Fage 27 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

9. T-COIL TEST SUMMARY

Table 9-1 Consolidated Tabled Results

Consolidated Tabled Results												
			esponse rgin	•	netic / Verdict		SNNR dict	Margin from FCC Limit	C63.19-2011			
		8.3	3.2	8.3	3.1	8.3	3.4	(dB)	Rating			
C63.19	9 Section	Axial	Radial	Axial	Radial	Axial	Radial					
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-5.01	Т3			
	PCS	PASS	NA	PASS	PASS	PASS	PASS		. •			
EDGE (OTT VoIP)	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-15.97	T4			
(OTT VOIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS					
	Cellular	PASS	NA	PASS	PASS	PASS	PASS					
UMTS	AWS	PASS	NA	PASS	PASS	PASS	PASS	-22.72	T4			
	PCS	PASS	NA	PASS	PASS	PASS	PASS					
HSPA	Cellular	PASS	NA	PASS	PASS	PASS	PASS					
(OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS	-32.39	T4			
	PCS	PASS	NA	PASS	PASS	PASS	PASS					
	B71	PASS	NA	PASS	PASS	PASS	PASS					
	B12	PASS	NA	PASS	PASS	PASS	PASS					
	B13	PASS	NA	PASS	PASS	PASS	PASS					
LTE FDD	B5	PASS	NA	PASS	PASS	PASS	PASS	-16.70	T4			
212100	B66	PASS	NA	PASS	PASS	PASS	PASS		1.4			
	B25	PASS	NA	PASS	PASS	PASS	PASS					
	B30	PASS	NA	PASS	PASS	PASS	PASS					
	В7	PASS	NA	PASS	PASS	PASS	PASS					
LTE FDD (OTT VoIP)	B13	PASS	NA	PASS	PASS	PASS	PASS	-28.12	Т4			
LTE TDD	B41	PASS	NA	PASS	PASS	PASS	PASS	-10.00	Т3			
LTE TDD (OTT VoIP)	B41	PASS	NA	PASS	PASS	PASS	PASS	-20.84	Т4			
	802.11b	PASS	NA	PASS	PASS	PASS	PASS					
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	6 96	Т3			
WLAN	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-6.86	13			
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS					
	802.11b	PASS	NA	PASS	PASS	PASS	PASS					
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	10.26	Т4			
(OTT VoIP)	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-19.36	14			
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS					
	802.11a	PASS	NA	PASS	PASS	PASS	PASS					
U-NII	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-14.41	T4			
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS					
	802.11a	PASS	NA	PASS	PASS	PASS	PASS					
U-NII (OTT VoIP)	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-26.59	T4			
(OTT VOIE)	802.11ac	PASS	NA	PASS	PASS	PASS	PASS					

FCC ID: ZNFG710TM	PETEST:	HAC (T-COIL) TEST REPORT	1 LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 20 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 28 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

I. **Raw Handset Data**

Table 9-2 **Raw Data Results for GSM**

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates			
		128	-0.21	-31.20		1.25	30.99	20.00	-10.99	T4				
	Axial	190	-0.34	-30.87	-60.17	1.24	30.53	20.00	-10.53	T4	2.6, 3.2			
GSM850		251	-0.27	-30.72		1.21	30.45	20.00	-10.45	T4				
GSIVIOSU		128	-6.42	-32.12			25.70	20.00	-5.70	T3				
	Radial	190	-6.36	-31.70	-59.87	-59.87 N/A	N/A	25.34	20.00	-5.34	Т3	2.4, 2.2		
		251	-6.47	-31.48			25.01	20.00	-5.01	T3				
		512	-0.29	-31.52		1.23	31.23	20.00	-11.23	T4				
	Axial	661	-0.30	-32.83	-60.17	1.26	32.53	20.00	-12.53	T4	2.6, 3.2			
GSM1900		810	-0.36	-33.96		1.26	33.60	20.00	-13.60	T4				
G3W1900		512	-6.41	-32.47			26.06	20.00	-6.06	T3				
	Radial	661	-6.70	-33.80	-59.87	-59.87	-59.87	-59.87	N/A	27.10	20.00	-7.10	T3	2.4, 2.2
		810	-6.38	-35.04			28.66	20.00	-8.66	T3				

Table 9-3 **Raw Data Results for UMTS**

	Raw Data Results for UM15												
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
		4132	-1.40	-58.96		2.00	57.56	20.00	-37.56	T4			
	Axial	4183	-1.39	-58.96	-60.17	2.00	57.57	20.00	-37.57	T4	2.6, 3.2		
UMTS V		4233	-1.38	-58.76		2.00	57.38	20.00	-37.38	T4			
OWI S V		4132	-8.60	-51.32			42.72	20.00	-22.72	T4			
	Radial	4183	-8.59	-52.98	-59.87	N/A	44.39	20.00	-24.39	T4	2.4, 2.2		
		4233	-8.62	-51.63			43.01	20.00	-23.01	T4			
		1312	-1.54	-58.89		2.00	57.35	20.00	-37.35	T4			
	Axial	1412	-1.46	-58.86	-60.17	2.00	57.40	20.00	-37.40	T4	2.6, 3.2		
UMTS IV		1513	-1.38	-58.84		2.00	57.46	20.00	-37.46	T4			
UNITSIV		1312	-8.64	-51.85			43.21	20.00	-23.21	T4			
	Radial	1412	-8.65	-51.96	-59.87	N/A	43.31	20.00	-23.31	T4	2.4, 2.2		
		1513	-8.67	-51.98			43.31	20.00	-23.31	T4			
		9262	-1.45	-58.72		2.00	57.27	20.00	-37.27	T4			
	Axial	9400	-1.40	-58.87	-60.17	2.00	57.47	20.00	-37.47	T4	2.6, 3.2		
LIMTE		9538	-1.43	-58.61		2.00	57.18	20.00	-37.18	T4			
UMTS II		9262	-8.61	-52.01			43.40	20.00	-23.40	T4			
	Radial	9400	-8.60	-53.10	-59.87	-59.87	N/A	44.50	20.00	-24.50	T4	2.4, 2.2	
		9538	-8.58	-53.22			44.64	20.00	-24.64	T4			

Table 9-4 **Raw Data Results for LTE B71**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	133297	-3.48	-47.74		2.00	44.26	20.00	-24.26	T4	
	Axial	15MHz	133297	-3.27	-47.66	-60.17	2.00	44.39	20.00	-24.39	T4	2.6, 3.2
	Axiai	10MHz	133297	-3.30	-46.63	-00.17	2.00	43.33	20.00	-23.33	T4	2.0, 3.2
LTE Band		5MHz	133297	-3.23	-47.75		2.00	44.52	20.00	-24.52	T4	
71		20MHz	133297	-9.87	-47.44			37.57	20.00	-17.57	T4	
	Radial	15MHz	133297	-9.91	-47.10	-59.87	N/A	37.19	20.00	-17.19	T4	2.4, 2.2
	Naulai	10MHz	133297	-9.91	-46.73	-58.67	IN/A	36.82	20.00	-16.82	T4	2.4, 2.2
	5MHz	133297	-9.82	-46.84		37.02	20.00	-17.02	T4			

FCC ID: ZNFG710TM	POTEST VIXENCE LABORATORY, NE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 20 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 29 of 76

Table 9-5 Raw Data Results for LTE B12

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		10MHz	23095	-3.06	-48.56		2.00	45.50	20.00	-25.50	T4	
	Axial	5MHz	23095	-3.24	-48.17	-60.17	2.00	44.93	20.00	-24.93	T4	2.6, 3.2
Axiai	3MHz	23095	-2.98	-47.97	-00.17	1.99	44.99	20.00	-24.99	T4	2.0, 3.2	
LTE Band	LTE Band	1.4MHz	23095	-3.00	-47.99		1.95	44.99	20.00	-24.99	T4	
12		10MHz	23095	-9.80	-48.85			39.05	20.00	-19.05	T4	
	Radial	5MHz	23095	-9.85	-48.09	-59.87	N/A	38.24	20.00	-18.24	T4	2.4, 2.2
	Naulai	3MHz	23095	-10.16	-47.92	-59.07	IN/A	37.76	20.00	-17.76	T4	2.4, 2.2
		1.4MHz	23095	-9.75	-47.34			37.59	20.00	-17.59	T4	

Table 9-6 Raw Data Results for LTE B13

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		Axial	10MHz	23230	-2.96	-46.10	-60.17	2.00	43.14	20.00	-23.14	T4	2.6, 3.2
L	TE Band	Axiai	5MHz	23230	-3.08	-47.98	-60.17	2.00	44.90	20.00	-24.90	T4	2.0, 3.2
	13	Radial	10MHz	23230	-9.90	-46.60	-59.87	N/A	36.70	20.00	-16.70	T4	2422
		Radiai	5MHz	23230	-10.16	-47.74	-59.67	N/A	37.58	20.00	-17.58	T4	2.4, 2.2

Table 9-7 Raw Data Results for LTE B5

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
			10MHz	20525	-3.09	-48.02		2.00	44.93	20.00	-24.93	T4	
		Axial	5MHz	20525	-3.19	-48.28	-60.17	2.00	45.09	20.00	-25.09	T4	2.6, 3.2
		Axiai	3MHz	20525	-3.31	-47.12	-00.17	2.00	43.81	20.00	-23.81	T4	2.0, 3.2
١.	TE Band 5		1.4MHz	20525	-3.20	-46.98		2.00	43.78	20.00	-23.78	T4	
ľ	. I E Ballu 3		10MHz	20525	-10.09	-47.70			37.61	20.00	-17.61	T4	
		Radial	5MHz	20525	-10.00	-48.12	-59.87	N/A	38.12	20.00	-18.12	T4	2.4, 2.2
		Naulai	3MHz	20525	-9.91	-47.95	-59.67	IWA	38.04	20.00	-18.04	T4	2.4, 2.2
			1.4MHz	20525	-9.93	-47.64			37.71	20.00	-17.71	T4	

Table 9-8 Raw Data Results for LTE B66

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	132322	-3.48	-48.58		2.00	45.10	20.00	-25.10	T4	
		15MHz	132322	-3.53	-49.03		1.98	45.50	20.00	-25.50	T4	
	Axial	10MHz	132322	-3.63	-48.60	60.17	2.00	44.97	20.00	-24.97	T4	2.6, 3.2
Axial	5MHz	132322	-3.41	-48.60	-60.17	2.00	45.19	20.00	-25.19	T4	2.6, 3.2	
		3MHz	132322	-3.37	-49.00		2.00	45.63	20.00	-25.63	T4	
LTE Band		1.4MHz	132322	-3.62	-48.03		2.00	44.41	20.00	-24.41	T4	
66		20MHz	132322	-10.19	-48.22			38.03	20.00	-18.03	T4	
		15MHz	132322	-9.73	-48.66	1		38.93	20.00	-18.93	T4	
	Radial	10MHz	132322	-10.04	-48.31	-59.87	N/A	38.27	20.00	-18.27	T4	0400
	Radiai	5MHz	132322	-9.76	-48.96	-59.87	IWA	39.20	20.00	-19.20	T4	2.4, 2.2
		3MHz	132322	-9.80	-48.62			38.82	20.00	-18.82	T4	
		1.4MHz	132322	-10.02	-47.81			37.79	20.00	-17.79	T4	1

FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 20 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 30 of 76

Table 9-9 **Raw Data Results for LTE B25**

						counto io						
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	26365	-3.14	-48.61		2.00	45.47	20.00	-25.47	T4	
		15MHz	26365	-3.24	-48.42		2.00	45.18	20.00	-25.18	T4	
	Axial	10MHz	26365	-3.62	-49.49	-60.17	2.00	45.87	20.00	-25.87	T4	2.6, 3.2
	Axiai	5MHz	26365	-3.61	-48.34	-00.17	2.00	44.73	20.00	-24.73	T4	2.0, 3.2
		3MHz	26365	-3.31	-48.62		2.00	45.31	20.00	-25.31	T4	
LTE Band		1.4MHz	26365	-3.25	-47.95		1.92	44.70	20.00	-24.70	T4	
25		20MHz	26365	-10.19	-48.49			38.30	20.00	-18.30	T4	
		15MHz	26365	-9.86	-48.58			38.72	20.00	-18.72	T4	
	Radial	10MHz	26365	-9.77	-48.64	-59.87	N/A	38.87	20.00	-18.87	T4	2.4, 2.2
	Radiai	5MHz	26365	-9.77	-47.61	-59.67	IN/A	37.84	20.00	-17.84	T4	2.4, 2.2
		3MHz	26365	-10.20	-48.99			38.79	20.00	-18.79	T4	
		1.4MHz	26365	-9.97	-47.92			37.95	20.00	-17.95	T4	

Table 9-10 Raw Data Results for LTE B30

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
		Avial	10MHz	27710	-3.41	-49.01	-60.17	2.00	45.60	20.00	-25.60	T4	2.6, 3.2
L	LTE Band 30	Axial	5MHz	27710	-3.20	-47.18	-60.17	2.00	43.98	20.00	-23.98	T4	2.0, 3.2
		Radial	10MHz	27710	-9.92	-48.23	-59.87	N/A	38.31	20.00	-18.31	T4	2.4. 2.2
			5MHz	27710	-10.13	-47.34		IV/A	37.21	20.00	-17.21	T4	2.4, 2.2

Table 9-11 Raw Data Results for LTE B7

					Data II			-				
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	21100	-3.46	-48.29		2.00	44.83	20.00	-24.83	T4	
	Avial	15MHz	21100	-3.50	-47.92	-60.17	2.00	44.42	20.00	-24.42	T4	2.6, 3.2
	Axial	10MHz	21100	-3.67	-48.66	-60.17	2.00	44.99	20.00	-24.99	T4 2.0, 3.2	2.0, 3.2
LTE Band 7		5MHz	21100	-3.14	-48.29		2.00	45.15	20.00	-25.15	T4	
LIE Ballu 7		20MHz	21100	-9.91	-47.60			37.69	20.00	-17.69	T4	
	Radial	15MHz	21100	-10.21	-47.58	50.07	N/A	37.37	20.00	-17.37	T4	2.4. 2.2
	Naulai	10MHz	21100	-10.17	-48.54	-59.87	IN/A	38.37	20.00	-18.37	T4	2.4, 2.2
		5MHz	21100	-9.91	-47.99			38.08	20.00	-18.08	T4	

Table 9-12 Raw Data Results for LTE B41 Power Class 3

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	41490	-3.64	-40.68		2.00	37.04	20.00	-17.04	T4	
		20MHz	41055	-3.22	-38.83		2.00	35.61	20.00	-15.61	T4	
		20MHz	40620	-3.56	-40.76		2.00	37.20	20.00	-17.20	T4	
	Axial	20MHz	40185	-3.67	-39.91	-60.17	1.98	36.24	20.00	-16.24	T4	2.6, 3.2
	Axiai	20MHz	39750	-3.61	-39.21	-60.17	2.00	35.60	20.00	-15.60	T4	2.6, 3.2
		15MHz	40620	-3.39	-40.74		2.00	37.35	20.00	-17.35	T4	
		10MHz	40620	-3.26	-41.04		2.00	37.78	20.00	-17.78	T4	
LTE Band		5MHz	40620	-3.63	-40.89		1.95	37.26	20.00	-17.26	T4	
41		20MHz	40620	-9.91	-41.95			32.04	20.00	-12.04	T4	
		15MHz	40620	-10.19	-41.82			31.63	20.00	-11.63	T4	
		10MHz	41490	-9.85	-41.42			31.57	20.00	-11.57	T4	
	Radial	10MHz	41055	-9.60	-39.60	-59.87	N/A	30.00	20.00	-10.00	Т3	2.4, 2.2
	Radiai	10MHz	40620	-10.10	-41.30	-59.87	IWA	31.20	20.00	-11.20	T4	2.4, 2.2
		10MHz	40185	-9.59	-40.83			31.24	20.00	-11.24	T4	
		10MHz	39750	-10.04	-40.44			30.40	20.00	-10.40	T4	
		5MHz	40620	-10.03	-41.50			31.47	20.00	-11.47	T4	

FCC ID: ZNFG710TM	V IXORETAGE LABORETOR, INC		LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 31 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		rage 31 01 76

Table 9-13
Raw Data Results for 2.4GHz WIFI

	Frague Margin from												
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
		1	-7.23	-40.92		2.00	33.69	20.00	-13.69	T4			
	Axial	6	-7.31	-39.39	-60.17	1.98	32.08	20.00	-12.08	T4	2.6, 3.2		
WLAN		11	-7.38	-40.26		2.00	32.88	20.00	-12.88	T4			
802.11b		1	-14.93	-42.54			27.61	20.00	-7.61	T3			
	Radial	6	-14.84	-41.70	-59.87	N/A	26.86	20.00	-6.86	Т3	2.4, 2.2		
		11	-15.05	-42.48			27.43	20.00	-7.43	T3			
WLAN	Axial	6	-6.90	-43.47	-60.17	2.00	36.57	20.00	-16.57	T4	2.6, 3.2		
802.11g	Radial	6	-15.08	-44.46	-59.87	N/A	29.38	20.00	-9.38	Т3	2.4, 2.2		
WLAN	Axial	6	-6.99	-46.58	-60.17	2.00	39.59	20.00	-19.59	T4	2.6, 3.2		
802.11n	Radial	6	-14.99	-47.44	-59.87	N/A	32.45	20.00	-12.45	T4	2.4, 2.2		
WLAN	Axial	6	-7.04	-47.59	-60.17	2.00	40.55	20.00	-20.55	T4	2.6, 3.2		
802.11ac	Radial	6	-15.25	-46.96	-59.87	N/A	31.71	20.00	-11.71	T4	2.4, 2.2		

Table 9-14
Raw Data Results for 5GHz WIFI 802.11a

					Juliu 110	<u> </u>	71 00112						
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	1	40	-7.44	-53.70		1.99	46.26	20.00	-26.26	T4	
		20MHz	2A	56	-7.00	-52.70		1.96	45.70	20.00	-25.70	T4	
	Axial	20MHz	2C	120	-6.95	-52.41	-60.17	2.00	45.46	20.00	-25.46	T4	2.6, 3.2
	Axidi	20MHz	3	149	-6.98	-52.32	-00.17	2.00	45.34	20.00	-25.34	T4	2.0, 3.2
		20MHz	3	157	-7.42	-52.44		2.00	45.02	20.00	-25.02	T4	
		20MHz	3	165	-7.42	-53.79		2.00	46.37	20.00	-26.37	T4	
802.11a	802.11a												
		20MHz	1	40	-15.00	-50.40			35.40	20.00	-15.40	T4	
	Radial	20MHz	2A	56	-15.06	-49.73			34.67	20.00	-14.67	T4	
		20MHz	2C	120	-15.12	-50.34	-59.87	N/A	35.22	20.00	-15.22	T4	2,4, 2,2
	Naulai	20MHz	3	149	-15.36	-50.15	-09.67	IN/A	34.79	20.00	-14.79	T4	2.4, 2.2
		20MHz	3	157	-15.12	-49.53			34.41	20.00	-14.41	T4	
		20MHz	3	165	-15.01	-49.70			34.69	20.00	-14.69	T4	

Table 9-15 Raw Data Results for 5GHz WIFI 802.11n

	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
ſ		Axial	40MHz	1	38	-6.97	-53.59	-60.17	2.00	46.62	20.00	-26.62	T4	2.6, 3.2
ı		Axiai	20MHz	1	40	-7.13	-54.15	-00.17	2.00	47.02	20.00	-27.02	T4	2.0, 3.2
	802.11n	802.11n												
ı			40MHz	1	38	-14.79	-50.97	F0.07	NI/A	36.18	20.00	-16.18	T4	2.4. 2.2
l		Raulai	20MHz	1	40	-15.13	-50.62	-59.87	.87 N/A	35.49	20.00	-15.49	T4	2.4, 2.2

Table 9-16 Raw Data Results for 5GHz WIFI 802.11ac

	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
		Axial	40MHz	1	38	-6.82	-54.86	-60.17	2.00	48.04	20.00	-28.04	T4	2.6. 3.2
		Axidi	20MHz	1	40	-6.90	-53.41	-00.17	2.00	46.51	20.00	-26.51	T4	2.0, 0.2
	802.11ac													
		Radial	40MHz	1	38	-15.37	-51.86	50.07	NIΔ	36.49	20.00	-16.49	T4	2,4, 2,2
		Radiai	20MHz	1	40	-15.26	-50.77	-59.87	N/A	35.51	20.00	-15.51	T4	2.4, 2.2

FCC ID: ZNFG710TM	V IXCHEELING LABORETON, INC.		LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 32 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		rage 32 01 76

Table 9-17 Raw Data Results for EDGE (OTT VoIP)

						oouito ioi	\	O	,			
	Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
	EDCE950	Axial	190	6.44	-35.12	-60.17	1.56	41.56	20.00	-21.56	T4	2.6, 3.2
	EDGE850	Radial	190	2.36	-33.61	-59.87	N/A	35.97	20.00	-15.97	T4	2.4, 2.2
_	DGE1900	Axial	661	7.06	-36.95	-60.17	1.66	44.01	20.00	-24.01	T4	2.6, 3.2
_	EDGE1900	Radial	661	2.16	-35.09	-59.87	N/A	37.25	20.00	-17.25	T4	2.4, 2.2

Table 9-18 Raw Data Results for HSPA (OTT VoIP)

	Naw Data Nesdits 101 1101 A (011 Voil)													
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates			
HSPA V	Axial	4183	8.77	-54.24	-60.17	1.49	63.01	20.00	-43.01	T4	2.6, 3.2			
пора V	Radial	4183	2.60	-51.25	-59.87	N/A	53.85	20.00	-33.85	T4	2.4, 2.2			
HSPA IV	Axial	1412	8.95	-54.88	-60.17	1.57	63.83	20.00	-43.83	T4	2.6, 3.2			
порату	Radial	1412	2.58	-51.77	-59.87	N/A	54.35	20.00	-34.35	T4	2.4, 2.2			
HSPA II	Axial	9400	9.13	-53.32	-60.17	1.37	62.45	20.00	-42.45	T4	2.6, 3.2			
HOPAII	Radial	9400	2.07	-50.32	-59.87	N/A	52.39	20.00	-32.39	T4	2.4, 2.2			

Table 9-19 Raw Data Results for LTE FDD B13 (OTT VoIP)

								\	•				
	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
		Axial	10MHz	23230	9.29	-46.65	-60.17	1.77	55.94	20.00	-35.94	T4	2.6, 3.2
	LTE Band		5MHz	23230	9.18	-48.03		1.79	57.21	20.00	-37.21	T4	2.0, 3.2
	13	Radial -	10MHz	23230	2.00	-46.12	-59.87	N/A	48.12	20.00	-28.12	T4	2.4. 2.2
			5MHz	23230	2.29	-46.91	-59.67		49.20	20.00	-29.20	T4	2.4, 2.2

Table 9-20 Raw Data Results for LTE TDD B41 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	41490	9.39	-38.82		1.72	48.21	20.00	-28.21	T4	
		20MHz	41055	9.15	-38.09		1.77	47.24	20.00	-27.24	T4	
		20MHz	40620	9.17	-38.81		1.66	47.98	20.00	-27.98	T4	
	Axial	20MHz	40185	9.04	-38.94	-60.17	1.73	47.98	20.00	-27.98	T4	2.6, 3.2
	Axiai	20MHz	39750	9.09	-38.39	-60.17	1.69	47.48	20.00	-27.48	T4	2.0, 3.2
		15MHz	40620	9.11	-39.89		1.76	49.00	20.00	-29.00	T4	
		10MHz	40620	9.22	-40.33		1.76	49.55	20.00	-29.55	T4	
LTE Band		5MHz	40620	9.08	-40.43		1.80	49.51	20.00	-29.51	T4	
41		20MHz	40620	2.45	-40.95			43.40	20.00	-23.40	T4	
		15MHz	40620	2.47	-40.96			43.43	20.00	-23.43	T4	
		10MHz	41490	2.41	-40.97			43.38	20.00	-23.38	T4	
	Dodial	10MHz	41055	2.33	-39.03	50.07	N/A	41.36	20.00	-21.36	T4	2.4, 2.2
	Radial	10MHz	40620	2.11	-38.73	-59.87	IVA	40.84	20.00	-20.84	T4	2.4, 2.2
		10MHz	40185	2.42	-40.11			42.53	20.00	-22.53	T4	
		10MHz	39750	2.59	-39.94			42.53	20.00	-22.53	T4	
		5MHz	40620	2.56	-39.60			42.16	20.00	-22.16	T4	

FCC ID: ZNFG710TM	PETEST EXCHAGAGE LABORTORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 22 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 33 of 76

Table 9-21
Raw Data Results for 2.4GHz WIFI (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	9.51	-35.68		1.56	45.19	20.00	-25.19	T4	
	Axial	6	9.42	-33.95	-60.17	1.62	43.37	20.00	-23.37	T4	2.6, 3.2
WLAN		11	8.97	-38.19		1.70	47.16	20.00	-27.16	T4	
802.11b		1	1.56	-38.23			39.79	20.00	-19.79	T4	
	Radial	6	1.68	-37.68	-59.87	N/A	39.36	20.00	-19.36	T4	2.4, 2.2
		11	1.86	-39.50			41.36	20.00	-21.36	T4	
WLAN	Axial	6	9.52	-39.75	-60.17	1.69	49.27	20.00	-29.27	T4	2.6, 3.2
802.11g	Radial	6	2.32	-40.88	-59.87	N/A	43.20	20.00	-23.20	T4	2.4, 2.2
WLAN	Axial	6	9.30	-43.78	-60.17	1.44	53.08	20.00	-33.08	T4	2.6, 3.2
802.11n	Radial	6	1.41	-44.20	-59.87	N/A	45.61	20.00	-25.61	T4	2.4, 2.2
WLAN	Axial	6	9.47	-42.19	-60.17	1.70	51.66	20.00	-31.66	T4	2.6, 3.2
802.11ac	Radial	6	1.65	-41.35	-59.87	N/A	43.00	20.00	-23.00	T4	2.4, 2.2

Table 9-22 Raw Data Results for 5GHz WIFI 802.11a (OTT VoIP)

				- Data I	oouito i		12 **** 1 C	· · · ·	(011 40	, <i>,</i>			
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	1	40	9.90	-48.66		1.57	58.56	20.00	-38.56	T4	
		20MHz	2A	56	8.79	-49.34		1.66	58.13	20.00	-38.13	T4	
	Axial	20MHz	2C	120	9.23	-49.25	-60.17	1.50	58.48	20.00	-38.48	T4	2.6, 3.2
	Axiai	20MHz	3	149	9.37	-49.29	-00.17	1.57	58.66	20.00	-38.66	T4	2.0, 3.2
		20MHz	3	157	9.48	-47.50		1.63	56.98	20.00	-36.98	T4	
		20MHz	3	165	9.64	-48.34		1.59	57.98	20.00	-37.98	T4	
802.11a													
		20MHz	1	40	1.77	-46.03			47.80	20.00	-27.80	T4	
		20MHz	2A	56	2.01	-44.88			46.89	20.00	-26.89	T4	
	Radial	20MHz	2C	120	2.06	-45.83	-59.87	N/A	47.89	20.00	-27.89	T4	2.4, 2.2
	Natilal	20MHz	3	149	1.94	-46.84	-09.67	IWA	48.78	20.00	-28.78	T4	2.4, 2.2
		20MHz	3	157	1.61	-44.98			46.59	20.00	-26.59	T4	
		20MHz	3	165	1.80	-45.80			47.60	20.00	-27.60	T4	

Table 9-23 Raw Data Results for 5GHz WIFI 802.11n (OTT VoIP)

	Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
ſ		Avial	40MHz	1	38	9.64	-50.50	-60.17	1.48	60.14	20.00	-40.14	T4	2.6, 3.2
ı	Axial	Axiai	20MHz	1	40	9.62	-48.99	-00.17	1.44	58.61	20.00	-38.61	T4	2.0, 3.2
ı	802.11n													
ı		Radial	40MHz	1	38	1.82	-49.97	-59.87	NI/A	51.79	20.00	-31.79	T4	2,4, 2,2
L		Raulai	20MHz	1	40	1.54	-48.87	-59.67	59.87 N/A	50.41	20.00	-30.41	T4	2.4, 2.2

Table 9-24 Raw Data Results for 5GHz WIFI 802.11ac (OTT VoIP)

				Data i i	Journey 1	J. J			,				
Mode	Orientation	Bandwidth	U-NII	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
	Axial	40MHz	1	38	9.00	-50.19	-60.17	1.46	59.19	20.00	-39.19	T4	2.6, 3.2
	Axidi	20MHz	1	40	9.33	-50.70	-00.17	1.47	60.03	20.00	-40.03	T4	2.0, 5.2
802.11ac													
	Radial	40MHz	1	38	1.65	-48.52	-59.87	N/A	50.17	20.00	-30.17	T4	2.4, 2.2
	Naulai	20MHz	1	40	1.81	-48.63	-59.67	IVA	50.44	20.00	-30.44	T4	2.4, 2.2

FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 24 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 34 of 76

II. Test Notes

A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- 3. Hearing Aid Mode (Phone→Call Settings→Additional settings→Hearing aids) as well as Noise Suppression Mode (Phone→Call Settings→Additional settings→Noise suppression) were set to ON for Frequency Response compliance
- 4. Speech Signal: ITU-T P.50 Artificial Voice
- 5. Bluetooth and WIFI were disabled while testing 2G/3G/4G modes.
- 6. Licensed data modes and Bluetooth were disabled while testing WIFI modes.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

B. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

C. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

D. LTE FDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 0RB offset
- 3. Vocoder Configuration: WB AMR 6.60kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 13 at 10MHz is the worst-case for both the Axial and Radial probe orientations, but that configuration supports only one channel. Therefore, no additional testing was performed.

E. LTE TDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 0RB offset
- 3. Power Class 3 Uplink-Downlink configuration: 6
- 4. Vocoder Configuration: WB AMR 6.60kbps
- 5. Speech Signal: ITU-T P.50 Artificial Voice
- 6. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, mid-high and high channels for those combinations. LTE Band 41 at 20MHz is the worst-case for the Axial probe orientation. LTE Band 41 at 10MHz bandwidth is the worst-case for the Radial probe orientation.

F. WIFI

- 1. Radio Configuration
 - a. 802.11b: DSSS, 1Mbps
 - b. 802.11g/a: BPSK, 9Mbps
 - c. 802.11n/ac 20MHz: BPSK, 6.5Mbps
 - d. 802.11n/ac 40MHz: BPSK, 13.5Mbps
- 2. Vocoder Configuration: WB AMR 6.60kbps
- The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both the Axial and Radial probe orientations.
- 4. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11a (U-NII 3) is the worst-case for both the Axial and Radial probe orientations.


FCC ID: ZNFG710TM	POTEST VIXENCE LABORATORY, NE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 25 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 35 of 76

G. OTT VoIP


- 1. Vocoder Configuration: 6kbps
- 2. EDGE Configuration
 - a. MCS Index: 7
 - b. Number of TX slots: 2
- 3. HSPA Configuration:
 - a. Release: 6
 - b. 3GPP 34.121 Subtest 1
- 4. LTE FDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 0RB offset
 - c. LTE Band 13 was the worst-case band from Table 7-5 and was used to test both Axial and Radial probe orientations.
 - d. The worst-case bandwidth for each probe orientation is additionally tested on the low and high channels for those bandwidths. LTE Band 13 at 10MHz is the worst-case for both the Axial and Radial probe orientations, but that configuration supports only one channel. Therefore, no additional testing was performed.
- 5. LTE TDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 0RB offset
 - c. Power Class 3 Uplink-Downlink configuration: 6
 - d. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those combinations. LTE Band 41 at 20MHz is the worst-case for the Axial probe orientation. LTE Band 41 at 10MHz is the worst-case for the Radial probe orientation.
- 6. WIFI Configuration:
 - a. Radio Configuration
 - i. 802.11b: DSSS, 1Mbps
 - ii. 802.11g/a: BPSK, 9Mbps
 - iii. 802.11n/ac 20MHz: BPSK, 6.5Mbps
 - iv. 802.11n/ac 40MHz: BPSK, 13.5Mbps
 - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both the Axial and Radial probe orientations.
 - c. The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11a (U-NII 3) is the worst-case for both the Axial and Radial probe orientations.

FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 26 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 36 of 76

III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.


IV. T-Coil Validation Test Results

Table 9-25
Helmholtz Coil Validation Table of Results

Item	Target	Result	Verdict
Axial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.175	PASS
Environmental Noise	< -58 dBA/m	-60.17	PASS
Frequency Response, from limits	> 0 dB	0.80	PASS
Radial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.265	PASS
Environmental Noise	< -58 dBA/m	-59.87	PASS
Frequency Response, from limits	> 0 dB	0.80	PASS

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 37 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		raye 37 01 76

٧. **ABM1 Magnetic Field Distribution Scan Overlays**



Axial Radial (Transverse)

Figure 9-1 **T-Coil Scan Overlay Magnetic Field Distributions**

Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFG710TM	PCTEST HAC (T-COIL) TEST REPORT		① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 38 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

10. MEASUREMENT UNCERTAINTY

Table 10-1
Uncertainty Estimation Table

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1)						17.7%	0.71
Expanded uncertainty (k=2), 95% confidence level						35.3%	1.31

Notes:

- 1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 20 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 39 of 76

11. EQUIPMENT LIST

Table 11-1 Equipment List

Equipment List							
Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number	
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/11/2017	Biennial	4/11/2019	7BFNM32	
Listen	SoundConnect	Microphone Power Supply	N/A		N/A	0899-PS150	
Listen	SoundConnect	Microphone Power Supply	12/2/2016	Biennial	12/2/2018	PS2612	
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/11/2017	Biennial	4/11/2019	23528889	
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/19/2018	Annual	1/19/2019	162125	
Rohde & Schwarz	CMW500	Radio Communication tester	7/14/2017	Annual	7/14/2018	140144	
Seekonk	NC-100	Torque Wrench (8" lb)	9/1/2016	Biennial	9/1/2018	21053	
TEM	C63.19	Helmholtz Coil	12/7/2016	Biennial	12/7/2018	925	
TEM	Radial T-Coil Probe	Radial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1130	
TEM	Axial T-Coil Probe	Axial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1124	
TEM		HAC System Controller with Software	N/A		N/A	N/A	
TEM		HAC Positioner	N/A		N/A	N/A	

FCC ID: ZNFG710TM	POTEST VIXENCE LABORATORY, NEC	PCTEST HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 40 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 40 of 76

12. TEST DATA

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		raye 41 01 76



DUT: HH Coil - SN: 925

Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011

Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum -50.0 -55.0 -60.0 -70.0 -豊 -75.0 -80.0 -85,0 -90.0 10k 100 1k [Hz] Frequency Response 3.0 -2.0 o.0 [m] B -1.0 -2.0--3.0-3k [Hz] Results Verification 1kHz Intensity -10.175 dB Max/Min -9.5/-10.5 -58.0 Verification ABM2 -60.17 dB Maximum Aligned Data Frequency Response Margin 800m dB Tolerance curves

FCC ID: ZNFG710TM	PETEST VENCIALES ON CARDENTON, INC.	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 40 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 42 of 76



DUT: HH Coil - SN: 925

Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011

Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum -50.0 -55.0 -60.0 -70.0 -豊 -75.0 -80.0 -85,0 -90.0 10k 100 1k [Hz] Frequency Response 3.0 -2.0 o.0 [m] B -1.0 -2.0--3.0-3k [Hz] Results Verification 1kHz Intensity -10.265 dB Max/Min -9.5/-10.5 -58.0 Verification ABM2 -59.87 dB Maximum Aligned Data

PCTEST 2018

FCC ID: ZNFG710TM	EXPLANTAGE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 43 01 70

Tolerance curves

800m dB

Frequency Response Margin



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- Mode: GSM850
- Channel: 251
- · Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	INCHEST OF LANDSTON, INC.	TAC (I-CUIL) IEST REPURT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 44 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 44 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- Mode: GSM1900
- Channel: 512
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 45 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 45 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- Mode: UMTS VChannel: 4233
- · Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	EXPLANTAGE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 46 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 46 of 76



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IVChannel: 1312

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	INCREES CARDES ON THE	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 47 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 47 of 76



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IIChannel: 9538

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	SECULIAR SECULAR SECU	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 49 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 48 of 76



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE FDD Band 13
Bandwidth: 10MHz

Channel: 23230

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 40 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 49 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe - SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- Mode: LTE TDD Band 41 (Power Class 3)
- Bandwidth: 20MHz
- Channel: 39750
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg FO of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 50 of 76



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe - SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

· Channel: 6

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	PETEST VINGING CADDETON, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags E1 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 51 of 76



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016


Test Configuration:

Mode: 5GHz WIFI (U-NII 3)

Standard: IEEE 802.11a
Bandwidth: 20MHz

· Channel: 157

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg FO of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 52 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- VolP Application: Google Duo
- Mode: EDGE850
- Channel: 190
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFG710TM	PETEST EXCHAGAGE LABORTORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 52 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 53 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM850Channel: 251



FCC ID: ZNFG710TM	PETEST VINCHESCO LABORATORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 54 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 54 01 70



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM1900Channel: 512



FCC ID: ZNFG710TM	PETEST VINCHESCO LABORATORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 55 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 55 01 70



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS VChannel: 4132



FCC ID: ZNFG710TM	SCHEER LASSET INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg FG of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 56 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IVChannel: 1312



FCC ID: ZNFG710TM	PETEST EXCHANGE CARRETON, INC.	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo F7 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 57 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IIChannel: 9262



FCC ID: ZNFG710TM	PETEST VINCIAL LABORATORY, LAC	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 59 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 58 of 76



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE FDD Band 13Bandwidth: 10MHzChannel: 23230



FCC ID: ZNFG710TM	PETEST VINGEREGGE LABORATORS, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 50 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 59 of 76



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63,19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE TDD Band 41(Power Class 3)

Bandwidth: 10MHz
Channel: 41055



FCC ID: ZNFG710TM	PETEST VINCHERGE LABORATORS, INC.	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 60 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		rage 60 01 70



Type: Portable Handset Serial: 09753


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

- Mode: 2.4GHz WIFI
- Standard: IEEE 802.11b
- Channel: 6



FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORS, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 61 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 61 of 76



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: 5GHz WIFI (U-NII 3)
Standard: IEEE 802.11a
Bandwidth: 20MHz
Channel: 157

Noise Spectrum



FCC ID: ZNFG710TM	PETEST VINGERSON LABORATORY, LAC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 62 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Fage 02 01 70



Type: Portable Handset Serial: 09753

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

VolP Application: Google Duo


Mode: EDGE850Channel: 190



FCC ID: ZNFG710TM	PETEST VINCIAL LABORATORY, LAC	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 62 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 63 of 76

13. CALIBRATION CERTIFICATES

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 64 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		rage 04 01 76



FCC ID: ZNFG710TM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		rage 05 01 70

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

HCATEMC_TEM 1124_Dec-07-2016



ISO/IEC 17025: 2005 Caustation Las. Cert. # 1533.01


Rev. 7.0 Jan. 24, 2014 Day # 1038 HCATEMO

1575 State Route 96, Victor NY 14564


REPORT OF CALIBRATION

TEM Consulting LP Axial T Coil Probe Model No.: Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab. I. D. No: 80578



Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC Calibration Laboratories Inc. procedure :

Collegation was performed by Wase Coldwell Collegation Laboratories Inc. under Operating Procedures intended to implement the requirements of (SO10012-1, IEC Guige 25, ANSI/NCSL Z540 1, (MIL STD 45662A) and ISO 9001 2008, ISO 17025

Cat. Date: 7-Dec-2016 Felix Christopher Calibrated on WCCL system type 9700

This designant chair net be reproduced, except in full, without the written approved from West Calebrait Car. Lake The

Page 1 of 2

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 66 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		rage 00 01 76

© 2018 PCTEST Engineering Laboratory, Inc.

HCATEMC_TEM 1124_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Raute 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Axial T Coil Probe

Model No.: Axial T Coil Probe

Serial No.: TEM 1124

Company: PCTEST Engineering Lab.

Test	Function	Tolera	Measured values			
				Before	Out	Remocke
10	Prons Sanalelyisy as	1000 H ₊ .	a BV/A/m	-60.23		-
			øB			
2 0	Proba Loval Linearity		6	6.03		
		R+r. (0 «B)	0 -6	0.00		
			-6	-6.03		
			-12	-12.05		
	- 2 5 Ar - 3 7 - 1		Ha.			
3.0	Probe Frequency Response		100	-19.8		
			126	-18.0		
			158	-16.0		
			200	-13.9		
			251	-12.0		
			316	-9.9		
			398	-8.0		
			501	-6.0		
			631	-4.0		
		200	794	-2.0		
		Ror, (0 a B)	1000	0.0		
			1259	2.0		
			1585	4.0		
			1995	6.0		
			2512	7.9		
			3162	9.9		
			3981	11.9		
			5012	13.9		
			6310	15.9		
			7943	18.0		
			10000	20.2		

PATRUMANTS USED FOR CANDIDERS	n.			Date or Cal	Trecostity No.	Due Dete
HP	34401A	S/N	36064102	1-O=1-2018	,287708	1-Oor-2017
HP	34401A	S/N	36102471	1-Oct-2016	.287708	1-Oct-2017
HP	33120A	S/N	36043716	1 Oct 2015	.287708	1 Oct 2017
B&K	2133	S/N	1583254	1-0 2016	683/284413-14	1-Oot-2017

Cal: Date: 7-Dec-2016 Calibrated on WCCL system type 9700

Tested by: Felle Christopher


Ray 7.0 Jan 24. 2014 Day # 1038 HCATEMC

Page 2 of 2

FCC ID: ZNFG710TM	PETEST INCIRCLASCE LASCETORY, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 67 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 67 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M



FCC ID: ZNFG710TM	PETEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 60 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 68 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

HCRTEMC TEM-1130 Dec-07-2016




ACCREDITED
Causeration Lab. Cert. #1533.01

1575 State Route 96, Victor NY 14564


REPORT OF CALIBRATION

TEM Consulting LP Radial T Coil Probe Model No.: Radial T Coil Probe Serial No.: TEM-1130

Company: PCTEST Engineering Lab. I. D. No: 80579



Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell

Calibration Laboratories Inc, procedure : Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Collection was performed by Weat Collection I Collection Laboration Laboration line, under Obstating Proceedings.

Internal Internal International Proceedings of SO 10012/1, IEC Guige 25, ANS/INCSL Z540 1. (MIL STD 45682A) and ISO 9001 2008, ISO 17025

Cet. Detc: 7-Dec-2016 (ML STD-45052A) and ISO 9001 2008, ISO 17025

Calibrated on WCCL system type 9700 Felix Christopher
This seement shall not be represented in the source of the West Carpoint Calibrated in the State of the Sta

Page 1 of 2

FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 60 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 69 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

HCRTEMC_TEM-1130_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Raute 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Radial T Coil Probe

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

Company: PCTEST Engineering Lab.

Test	Function	Function Tolerand			Measured values		
				Betore	Out	Remarks	
Τ.Ο	Probe Sensitivity es	1000 Hz.	a BV/A/m	-60.27			
	- 6. (1.0)		₽B			*	
2.0	Probe Lavel Linearity		6	6.03			
		R. (0 a B)	0	0.00			
			-6	-6,03			
			-12	-12.06			
			H.				
3.0	Praba Frequency Response		100	-19.9			
			126	-18.0			
			158	-16.0			
			200	-13.9			
			251	-12.0			
			316	-10.0			
			398	-8.0			
			501	-6.0			
			631	-4.0			
		2.00	794	-2.0			
		Rer. (0 a B)	1000	0.0			
			1259	2.0			
			1585	4.0			
			1995	6.0			
			2512	7.9			
			3162	9,9			
			3981	11.9			
			5012	13.9			
			6310	15.9			
			7943 10000	18.0 20.2			
			10000	20,2			

Inatrumante used for cellbre	tian			Date or Cal	Tracadallity No.	Due Date
HP	34401A	S/N	36064102	1-Oas-2016	,287708	1-Oer-2017
HP	34401A	S/N	35102471	1-Oct-2016	.287708	1-Oct-2017
HP	33120A	5/N	36043716	1 Oct 2015	.287708	1 Oct 2017
B&K	2133	S/N	1583254	1-Oce-2016	683/284413-14	1-Oot-2017

Cat. Data: 7-Dac-2016 Cellerated on WCGL system type 9700

Tasted by: Falls Christopher

R. 7.0 Jan 24, 2014 Day # 1038 HORTEMO

Page 2 of 2

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORS, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 70 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 70 of 76

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFG710TM	PETEST INCIDENCE LABORATORY, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 71 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 71 of 76

15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017
- FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 5. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
- Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- 8. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, " IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, " U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
- 13. EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
- 14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- 16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.

FCC ID: ZNFG710TM	PETEST VEXISTATION (NE	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 70 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 72 of 76

- Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- 19. Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- 20. Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.
- 22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- 24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 25. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- 28. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
- 29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFG710TM	INCIRCLASCIANT INC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 72 of 76
1M1804030060-13-R2.ZNF	04/14/2018 - 04/18/2018	Portable Handset		Page 73 of 76