



Maximum Power Spectral Density

Test Mode: TM 3 & ANT 1 & Ch.102




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 1 & Ch.118



Maximum Power Spectral Density

Test Mode: TM 3 & ANT 1 & Ch.142




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 1 & Ch.151




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 1 & Ch.159




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 1 & Ch.42



Maximum Power Spectral Density

Test Mode: TM 4 & ANT 1 & Ch.58



Maximum Power Spectral Density

Test Mode: TM 4 & ANT 1 & Ch.106




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 1 & Ch.122




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 1 & Ch.138



Maximum Power Spectral Density


Test Mode: TM 4 & ANT 1 & Ch.155



- Power spectral density: Antenna 2


Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.36




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.40



Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.48





Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.52




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.60




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.64




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.100




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.120




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.144




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.149




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.157




Maximum Power Spectral Density

Test Mode: TM 1 & ANT 2 & Ch.165




Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.36




Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.40



Maximum Power Spectral Density


Test Mode: TM 2 & ANT 2 & Ch.48






Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.52




Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.60



Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.64




Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.100




Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.120



Maximum Power Spectral Density


Test Mode: TM 2 & ANT 2 & Ch.144






Maximum Power Spectral Density

Test Mode: TM 2 & ANT 2 & Ch.165




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.38




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.46




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.54



Maximum Power Spectral Density


Test Mode: TM 3 & ANT 2 & Ch.62






Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.102




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.118




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.142




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.151




Maximum Power Spectral Density

Test Mode: TM 3 & ANT 2 & Ch.159




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 2 & Ch.42




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 2 & Ch.58




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 2 & Ch.106




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 2 & Ch.122




Maximum Power Spectral Density

Test Mode: TM 4 & ANT 2 & Ch.138



Maximum Power Spectral Density

Test Mode: TM 4 & ANT 2 & Ch.155



## 8.5 Radiated Spurious Emission Measurements

### ■ Test Requirements

#### • FCC Part 15.209(a) and (b)

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

#### • FCC Part 15.205 (a): Only spurious emissions are permitted in any of the frequency bands listed below:


MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.52025	160.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	12.57675 ~	160.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	12.57725	160.7 ~ 160.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	13.36 ~ 13.41	162.0125 ~ 167.17	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.42 ~ 16.423	167.72 ~ 173.2	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	16.69475 ~	240 ~ 285	2655 ~ 2900		
8.291 ~ 8.294	16.69525	322 ~ 335.4	3260 ~ 3267		
8.362 ~ 8.366	16.80425 ~	399.90 ~ 410	3332 ~ 3339		
8.37625 ~ 8.38675	16.80475	608 ~ 614	3345.8 ~ 3358		
	25.5 ~ 25.67	960 ~ 1240	3600 ~ 4000		
	37.5 ~ 38.25				
	73 ~ 74.6				
	74.8 ~ 75.2				

• **FCC Part 15.205(b):** The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

• **FCC Part 15.407 (b):** Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the **5.15-5.25 GHz band**: all emissions outside of the **5.15-5.35 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (2) For transmitters operating in the **5.25-5.35 GHz band**: all emissions outside of the **5.15-5.35 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (3) For transmitters operating in the **5.47-5.725 GHz band**: all emissions outside of the **5.47-5.725 GHz band** shall not exceed an **EIRP of -27 dBm/MHz**.
- (4) For transmitters operating in the **5.725-5.85 GHz band**: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions **below 1 GHz** must comply with the general field strength limits set forth in **Section 15.209**. Further, any U-NII devices using an **AC power line** are required to comply also with the conducted limits set forth in **Section 15.207**.
- (7) The provisions of §15.205 apply to intentional radiators operating under this section
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

## ■ Test Configuration



## ■ Test Procedure

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m.
2. The turn table shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 1m or 3 m away from the receiving antenna, which is varied from 1m to 4 m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

Radiated spurious emission measured using following Measurement Procedure of **KDB789033 D02v02r01**

### ► General Requirements for Unwanted Emissions Measurements

The following requirements apply to all unwanted emissions measurements, both in and outside of the restricted bands:

#### ▪ EUT Duty Cycle

- (1) The EUT shall be configured or modified to **transmit continuously** except as stated in (ii), below. The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (**to no lower than 98 percent**) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.
- (2) If **continuous transmission (or at least 98 percent duty cycle) cannot be achieved** due to hardware limitations of the EUT (e.g., overheating), the following additions to the measurement and reporting procedures are required:
  - The EUT shall be configured to operate at the maximum achievable duty cycle.
  - Measure the duty cycle, x, of the transmitter output signal.
  - Adjustments to measurement procedures (e.g., increasing test time and number of traces averaged) shall be performed as described in the procedures below.
  - The test report shall include the following additional information:
    - The reason for the duty cycle limitation.
    - The duty cycle achieved for testing and the associated transmit duration and interval between transmissions.
    - The sweep time and the amount of time used for trace stabilization during max-hold measurements for peak emission measurements.
- (3) Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.



**► Measurements below 1000 MHz**

- a) Follow the requirements in section II.G.3, "General Requirements for Unwanted Emissions Measurements".
- b) Compliance shall be demonstrated using **CISPR quasi-peak detection**; however, **peak detection** is permitted as an alternative to quasi-peak detection.

**► Measurements Above 1000 MHz (Peak)**

- a) Follow the requirements in section II.G.3, "General Requirements for Unwanted Emissions Measurements".
- b) Peak emission levels are measured by setting the analyzer as follows:
  - (i) **RBW = 1 MHz.**
  - (ii) **VBW ≥ 3 MHz.**
  - (iii) **Detector = Peak.**
  - (iv) Sweep time = Auto.
  - (v) Trace mode = Max hold.
  - (vi) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately  $1/x$ , where  $x$  is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

**► Measurements Above 1000 MHz (Method AD)**

- (i) **RBW = 1 MHz.**
- (ii) **VBW ≥ 3 MHz.**
- (iii) **Detector = RMS**, if  $\text{span} / (\# \text{ of points in sweep}) \leq \text{RBW} / 2$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, the detector mode shall be set to peak.
- (iv) Averaging type = power (i.e., RMS)
  - As an alternative, the detector and averaging type may be set for linear voltage averaging. Some analyzers require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- (v) Sweep time = Auto.
- (vi) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, the number of traces shall be increased by a factor of  $1/x$ , where  $x$  is the duty cycle. For example, with 50 percent duty cycle, at least 200 traces shall be averaged.
- (vii) If tests are performed with the EUT transmitting at a duty cycle less than 98 percent, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
  - **If power averaging (RMS) mode was used in step (iv) above, the correction factor is  $10 \log(1/x)$ , where  $x$  is the duty cycle.** For example, if the transmit duty cycle was 50 percent, then 3 dB must be added to the measured emission levels.
  - If linear voltage averaging mode was used in step (iv) above, the correction factor is  $20 \log(1/x)$ , where  $x$  is the duty cycle. For example, if the transmit duty cycle was 50 percent, then 6 dB must be added to the measured emission levels.
  - If a specific emission is demonstrated to be continuous (100 percent duty cycle) rather than turning on and off with the transmit cycle, no duty cycle correction is required for that emission.

Please refer to Appendix II for the duty correction factor

## Test Results

### Test Notes

1. No other spurious and harmonic emissions were found greater than listed emissions on below table.

2. Sample Calculation.

$$\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{T.F} + \text{DCCF} + \text{DCF} \quad / \quad \text{T.F} = \text{AF} + \text{CL} - \text{AG}$$

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,

DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor

3. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor =  $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

4. The limit is converted to field strength.

$$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 \text{ dB} = -27 \text{ dBm} + 95.2 = 68.2 \text{ dBuV/m}$$

### Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM1 Normal

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	36 (5180 MHz)	5148.34	V	X	PK	51.83	1.78	N/A	N/A	53.61	74.00	20.39
		5148.79	V	X	AV	42.72	1.79	0.11	N/A	44.62	54.00	9.38
		10360.35	V	X	PK	43.53	10.68	N/A	N/A	54.21	68.20	13.99
	40 (5200 MHz)	10399.86	V	X	PK	44.16	10.73	N/A	N/A	54.89	68.20	13.31
	48 (5240 MHz)	10480.12	V	X	PK	44.10	10.72	N/A	N/A	54.82	68.20	13.38
U-NII 2A	52 (5260 MHz)	10520.25	V	X	PK	45.60	10.78	N/A	N/A	56.38	68.20	11.82
		10600.14	V	X	PK	44.58	10.84	N/A	N/A	55.42	74.00	18.58
	60 (5300 MHz)	10600.17	V	X	AV	33.73	10.84	0.11	N/A	44.68	54.00	9.32
		5351.42	V	X	PK	50.80	3.33	N/A	N/A	54.13	74.00	19.87
		5351.59	V	X	AV	41.02	3.33	0.11	N/A	44.46	54.00	9.54
		10639.70	V	X	PK	43.28	10.84	N/A	N/A	54.12	74.00	19.88
64 (5320 MHz)	10639.60	V	X	AV	32.55	10.84	0.11	N/A	43.50	54.00	10.50	
	U-NII 2C	100 (5500 MHz)	5458.29	V	X	PK	51.31	3.43	N/A	N/A	54.74	74.00
5458.38			V	X	AV	40.86	3.43	0.11	N/A	44.40	54.00	9.60
5469.51			V	X	PK	50.99	3.43	N/A	N/A	54.42	68.20	13.78
10999.62			V	X	PK	43.79	10.95	N/A	N/A	54.74	74.00	19.26
10999.53			V	X	AV	33.32	10.95	0.11	N/A	44.38	54.00	9.62
120 (5600 MHz)	11200.34	V	X	PK	44.26	10.97	N/A	N/A	55.23	74.00	18.77	
	11200.25	V	X	AV	34.04	10.97	0.11	N/A	45.12	54.00	8.88	
	144 (5720 MHz)	11440.43	V	X	PK	43.99	11.06	N/A	N/A	55.05	74.00	18.95
11440.23		V	X	AV	33.48	11.06	0.11	N/A	44.65	54.00	9.35	
U-NII 3	149 (5745 MHz)	5714.27	V	X	PK	51.38	3.30	N/A	N/A	54.68	68.20	13.52
		5722.29	V	X	PK	53.75	3.17	N/A	N/A	56.92	78.20	21.28
		11490.06	V	X	PK	44.07	11.14	N/A	N/A	55.21	74.00	18.79
		11490.05	V	X	AV	33.81	11.14	0.11	N/A	45.06	54.00	8.94
	157 (5785 MHz)	11569.71	V	X	PK	44.64	11.53	N/A	N/A	56.17	74.00	17.83
		11569.88	V	X	AV	33.92	11.53	0.11	N/A	45.56	54.00	8.44
	165 (5825 MHz)	5851.35	V	X	PK	52.48	3.69	N/A	N/A	56.17	78.20	22.03
		5861.60	V	X	PK	51.29	3.73	N/A	N/A	55.02	68.20	13.18
		11649.52	V	X	PK	43.85	11.85	N/A	N/A	55.70	74.00	18.30
		11649.82	V	X	AV	34.10	11.85	0.11	N/A	46.06	54.00	7.94

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM2 Normal**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	36 (5180 MHz)	5147.71	V	X	PK	50.39	1.78	N/A	N/A	52.17	74.00	21.83
		5147.74	V	X	AV	41.88	1.78	0.19	N/A	43.85	54.00	10.15
		10360.17	V	X	PK	44.62	10.68	N/A	N/A	55.30	68.20	12.90
	40 (5200 MHz)	10400.04	V	X	PK	43.74	10.73	N/A	N/A	54.47	68.20	13.73
	48 (5240 MHz)	10480.08	V	X	PK	43.68	10.72	N/A	N/A	54.40	68.20	13.80
U-NII 2A	52 (5260 MHz)	10520.32	V	X	PK	43.38	10.78	N/A	N/A	54.16	68.20	14.04
	60 (5300 MHz)	10600.32	V	X	PK	44.29	10.84	N/A	N/A	55.13	74.00	18.87
		10600.13	V	X	AV	33.53	10.84	0.19	N/A	44.56	54.00	9.44
	64 (5320 MHz)	5352.26	V	X	PK	51.19	3.33	N/A	N/A	54.52	74.00	19.48
		5352.43	V	X	AV	41.20	3.33	0.19	N/A	44.72	54.00	9.28
		10639.52	V	X	PK	42.76	10.84	N/A	N/A	53.60	74.00	20.40
		10639.63	V	X	AV	32.53	10.84	0.19	N/A	43.56	54.00	10.44
U-NII 2C	100 (5500 MHz)	5459.20	V	X	PK	50.68	3.43	N/A	N/A	54.11	74.00	19.89
		5458.94	V	X	AV	40.89	3.43	0.19	N/A	44.51	54.00	9.49
		5468.48	V	X	PK	50.47	3.43	N/A	N/A	53.90	68.20	14.30
		11000.11	V	X	PK	43.63	10.95	N/A	N/A	54.58	74.00	19.42
		11000.03	V	X	AV	33.56	10.95	0.19	N/A	44.70	54.00	9.30
	120 (5600 MHz)	11200.14	V	X	PK	44.03	10.97	N/A	N/A	55.00	74.00	19.00
		11200.32	V	X	AV	33.98	10.97	0.19	N/A	45.14	54.00	8.86
	144 (5720 MHz)	11439.85	V	X	PK	43.89	11.06	N/A	N/A	54.95	74.00	19.05
		11439.51	V	X	AV	33.62	11.06	0.19	N/A	44.87	54.00	9.13
U-NII 3	149 (5745 MHz)	5713.05	V	X	PK	51.95	3.29	N/A	N/A	55.24	68.20	12.96
		5721.64	V	X	PK	52.01	3.18	N/A	N/A	55.19	78.20	23.01
		11490.26	V	X	PK	44.67	11.14	N/A	N/A	55.81	74.00	18.19
		11490.14	V	X	AV	33.86	11.14	0.19	N/A	45.19	54.00	8.81
	157 (5785 MHz)	11570.32	V	X	PK	44.18	11.53	N/A	N/A	55.71	74.00	18.29
		11570.34	V	X	AV	34.14	11.53	0.19	N/A	45.86	54.00	8.14
	165 (5825 MHz)	5850.61	V	X	PK	51.42	3.68	N/A	N/A	55.10	78.20	23.10
		5860.73	V	X	PK	50.84	3.75	N/A	N/A	54.59	68.20	13.61
		11649.55	V	X	PK	44.81	11.85	N/A	N/A	56.66	74.00	17.34
		11649.54	V	X	AV	34.03	11.85	0.19	N/A	46.07	54.00	7.93

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM3 Normal**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	38 (5190 MHz)	5149.30	V	X	PK	54.89	1.79	N/A	N/A	56.68	74.00	17.32
		5149.56	V	X	AV	44.42	1.79	0.26	N/A	46.47	54.00	7.53
		10379.83	V	X	PK	43.20	10.70	N/A	N/A	53.90	68.20	14.30
	46 (5230 MHz)	10460.09	V	X	PK	43.64	10.69	N/A	N/A	54.33	68.20	13.87
U-NII 2A	54 (5270 MHz)	10540.47	V	X	PK	43.51	10.82	N/A	N/A	54.33	68.20	13.87
	62 (5310 MHz)	5352.33	V	X	PK	51.94	3.33	N/A	N/A	55.27	74.00	18.73
		5352.17	V	X	AV	42.39	3.33	0.26	N/A	45.98	54.00	8.02
		10619.52	V	X	PK	43.50	10.84	N/A	N/A	54.34	74.00	19.66
		10620.10	V	X	AV	32.90	10.84	0.26	N/A	44.00	54.00	10.00
U-NII 2C	102 (5510 MHz)	5458.61	V	X	PK	49.38	3.43	N/A	N/A	52.81	74.00	21.19
		5458.75	V	X	AV	39.10	3.43	0.26	N/A	42.79	54.00	11.21
		5468.02	V	X	PK	49.12	3.43	N/A	N/A	52.55	68.20	15.65
		11019.60	V	X	PK	44.26	10.94	N/A	N/A	55.20	74.00	18.80
		11019.92	V	X	AV	33.90	10.94	0.26	N/A	45.10	54.00	8.90
	118 (5590 MHz)	11180.29	V	X	PK	44.77	10.98	N/A	N/A	55.75	74.00	18.25
		11180.31	V	X	AV	33.73	10.98	0.26	N/A	44.97	54.00	9.03
	142 (5710 MHz)	11419.90	V	X	PK	44.76	11.03	N/A	N/A	55.79	74.00	18.21
11419.76		V	X	AV	34.07	11.03	0.26	N/A	45.36	54.00	8.64	
U-NII 3	151 (5755 MHz)	5712.98	V	X	PK	52.97	3.29	N/A	N/A	56.26	68.20	11.94
		5723.46	V	X	PK	58.54	3.15	N/A	N/A	61.69	78.20	16.51
		11510.23	V	X	PK	44.83	11.21	N/A	N/A	56.04	74.00	17.96
		11510.50	V	X	AV	33.89	11.22	0.26	N/A	45.37	54.00	8.63
	159 (5795 MHz)	5851.47	V	X	PK	51.53	3.69	N/A	N/A	55.22	78.20	22.98
		5861.73	V	X	PK	51.73	3.73	N/A	N/A	55.46	68.20	12.74
		11589.81	V	X	PK	44.68	11.64	N/A	N/A	56.32	74.00	17.68
		11589.81	V	X	AV	33.89	11.64	0.26	N/A	45.79	54.00	8.21

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM4 Normal**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	42 (5210 MHz)	5148.47	V	X	PK	56.29	1.78	N/A	N/A	58.07	74.00	15.93
		5149.50	V	X	AV	46.88	1.79	0.16	N/A	48.83	54.00	5.17
		10419.69	V	X	PK	43.93	10.71	N/A	N/A	54.64	68.20	13.56
U-NII 2A	58 (5290 MHz)	5351.10	V	X	PK	52.41	3.33	N/A	N/A	55.74	74.00	18.26
		5350.30	V	X	AV	44.70	3.33	0.16	N/A	48.19	54.00	5.81
		10579.65	V	X	PK	44.65	10.84	N/A	N/A	55.49	68.20	12.71
U-NII 2C	106 (5530 MHz)	5458.57	V	X	PK	49.40	3.43	N/A	N/A	52.83	74.00	21.17
		5458.24	V	X	AV	39.15	3.43	0.16	N/A	42.74	54.00	11.26
		5468.27	V	X	PK	48.58	3.43	N/A	N/A	52.01	68.20	16.19
		11059.87	V	X	PK	45.38	10.93	N/A	N/A	56.31	74.00	17.69
	122 (5610 MHz)	11059.91	V	X	AV	33.92	10.93	0.16	N/A	45.01	54.00	8.99
		11219.54	V	X	PK	44.14	10.93	N/A	N/A	55.07	74.00	18.93
	138 (5690 MHz)	11219.95	V	X	AV	33.81	10.93	0.16	N/A	44.90	54.00	9.10
		11379.87	V	X	PK	44.66	10.97	N/A	N/A	55.63	74.00	18.37
U-NII 3	155 (5775 MHz)	11379.87	V	X	AV	33.74	10.97	0.16	N/A	44.87	54.00	9.13
		5714.22	V	X	PK	53.21	3.30	N/A	N/A	56.51	68.20	11.69
		5720.45	V	X	PK	53.58	3.20	N/A	N/A	56.78	78.20	21.42
		5853.87	V	X	PK	54.62	3.71	N/A	N/A	58.33	78.20	19.87
		5861.93	V	X	PK	51.29	3.72	N/A	N/A	55.01	68.20	13.19
		11550.19	V	X	PK	44.62	11.43	N/A	N/A	56.05	74.00	17.95
		11550.22	V	X	AV	33.74	11.43	0.16	N/A	45.33	54.00	8.67

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 4 & With Wireless charging pad**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	42 (5210 MHz)	5149.21	V	X	PK	55.72	1.79	N/A	N/A	57.51	74.00	16.49
		5149.65	V	X	AV	46.13	1.79	0.16	N/A	48.08	54.00	5.92
		10420.45	H	X	PK	44.22	10.71	N/A	N/A	54.93	68.20	13.27

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 4 & With Wireless charging pad**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2A	58 (5290 MHz)	5350.56	V	X	PK	52.78	3.33	N/A	N/A	56.11	74.00	17.89
		5350.82	V	X	AV	42.67	3.33	0.16	N/A	46.16	54.00	7.84
		10580.03	H	X	PK	44.57	10.84	N/A	N/A	55.41	68.20	12.79

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 3 & With Wireless charging pad**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	142 (5710 MHz)	11420.30	H	X	PK	44.41	11.03	N/A	N/A	55.44	74.00	18.56
		11420.05	H	X	AV	34.04	11.03	0.26	N/A	45.33	54.00	8.67

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 2 & With Wireless charging pad**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 3	165 (5825 MHz)	5852.85	V	X	PK	51.46	3.70	N/A	N/A	55.16	78.20	23.04
		5860.87	V	X	PK	50.52	3.75	N/A	N/A	54.27	68.20	13.93
		11649.63	H	X	PK	44.05	11.85	N/A	N/A	55.90	74.00	18.10
		11649.68	H	X	AV	33.88	11.85	0.19	N/A	45.92	54.00	8.08

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 4 & With Dual display**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	42 (5210 MHz)	5142.95	V	X	PK	59.02	1.76	N/A	N/A	60.78	74.00	13.22
		5142.60	V	X	AV	47.66	1.76	0.16	N/A	49.58	54.00	4.42
		10420.14	V	X	PK	43.62	10.71	N/A	N/A	54.33	68.20	13.87
		15629.92	V	X	PK	44.01	13.07	N/A	N/A	57.08	74.00	16.92
		15629.64	V	X	AV	33.63	13.07	0.16	N/A	46.86	54.00	7.14

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 4 & With Dual display**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2A	58 (5290 MHz)	5350.93	V	X	PK	53.47	3.33	N/A	N/A	56.80	74.00	17.20
		5350.44	V	X	AV	45.43	3.33	0.16	N/A	48.92	54.00	5.08
		10580.45	V	X	PK	44.41	10.84	N/A	N/A	55.25	68.20	12.95
		15870.48	V	X	PK	43.89	14.19	N/A	N/A	58.08	74.00	15.92
		15870.10	V	X	AV	33.66	14.18	0.16	N/A	48.00	54.00	6.00

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 3 & With Dual display**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	102 (5510 MHz)	5459.29	V	X	PK	48.45	3.43	N/A	N/A	51.88	74.00	22.12
		5459.45	V	X	AV	38.12	3.43	0.26	N/A	41.81	54.00	12.19
		5467.34	V	X	PK	48.40	3.43	N/A	N/A	51.83	68.20	16.37
		11020.00	V	X	PK	44.71	10.94	N/A	N/A	55.65	74.00	18.35
		11020.17	V	X	AV	33.66	10.94	0.26	N/A	44.86	54.00	9.14
		16529.90	V	X	PK	43.80	16.97	N/A	N/A	60.77	68.20	7.43

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 3 & With Dual display**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	142 (5710 MHz)	11419.70	V	X	PK	44.15	11.03	N/A	N/A	55.18	74.00	18.82
		11419.53	V	X	AV	34.02	11.03	0.26	N/A	45.31	54.00	8.69
		17129.57	V	X	PK	41.08	21.10	N/A	N/A	62.18	68.20	6.02

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 2 & With Dual display**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 3	165 (5825 MHz)	5850.44	V	X	PK	52.32	3.68	N/A	N/A	56.00	78.20	22.20
		5860.13	V	X	PK	50.83	3.77	N/A	N/A	54.60	68.20	13.60
		11649.91	V	X	PK	44.94	11.85	N/A	N/A	56.79	74.00	17.21
		11649.83	V	X	AV	34.11	11.85	0.19	N/A	46.15	54.00	7.85
		17474.65	V	X	PK	40.73	23.70	N/A	N/A	64.43	68.20	3.77

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 4 & With Dual Display + WCP**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 1	42 (5210 MHz)	5149.18	V	X	PK	55.63	1.79	N/A	N/A	57.42	74.00	16.58
		5149.18	V	X	AV	45.37	1.79	0.16	N/A	47.32	54.00	6.68
		10420.02	V	X	PK	44.15	10.71	N/A	N/A	54.86	68.20	13.34
		15630.16	V	X	PK	43.94	13.07	N/A	N/A	57.01	74.00	16.99
		15630.10	V	X	AV	34.08	13.07	0.16	N/A	47.31	54.00	6.69

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 4 & With Dual Display + WCP**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2A	58 (5290 MHz)	5351.21	V	X	PK	51.98	3.33	N/A	N/A	55.31	74.00	18.69
		5350.72	V	X	AV	42.73	3.33	0.16	N/A	46.22	54.00	7.78
		10579.68	V	X	PK	43.85	10.84	N/A	N/A	54.69	68.20	13.51
		15870.06	V	X	PK	43.90	14.18	N/A	N/A	58.08	74.00	15.92
		15870.61	V	X	AV	33.65	14.19	0.16	N/A	48.00	54.00	6.00

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 3 & With Dual Display + WCP**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	102 (5510 MHz)	5458.68	V	X	PK	48.32	3.43	N/A	N/A	51.75	74.00	22.25
		5458.50	V	X	AV	38.30	3.43	0.26	N/A	41.99	54.00	12.01
		5469.42	V	X	PK	48.23	3.43	N/A	N/A	51.66	68.20	16.54
		11020.34	V	X	PK	44.49	10.94	N/A	N/A	55.43	74.00	18.57
		11020.11	V	X	AV	34.00	10.94	0.26	N/A	45.20	54.00	8.80
		16529.55	V	X	PK	43.39	16.97	N/A	N/A	60.36	68.20	7.84

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 3 & With Dual Display + WCP**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 2C	142 (5710 MHz)	11419.70	V	X	PK	44.78	11.03	N/A	N/A	55.81	74.00	18.19
		11419.64	V	X	AV	33.90	11.03	0.26	N/A	45.19	54.00	8.81
		17129.73	V	X	PK	41.15	21.11	N/A	N/A	62.26	68.20	5.94

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) : TM 2 & With Dual Display + WCP**

Band	Tested Channel	Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
U-NII 3	165 (5825 MHz)	5850.70	V	X	PK	50.67	3.68	N/A	N/A	54.35	78.20	23.85
		5861.74	V	X	PK	51.02	3.73	N/A	N/A	54.75	68.20	13.45
		11650.43	V	X	PK	44.35	11.86	N/A	N/A	56.21	74.00	17.79
		11650.23	V	X	AV	33.88	11.86	0.19	N/A	45.93	54.00	8.07
		17474.95	V	X	PK	40.70	23.71	N/A	N/A	64.41	68.20	3.79



### - WiFi DBS(Dual-Band Simultaneous) Test Results

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) :**  
***Simultaneously transmission - Normal***

	Antenna	Band	Mode	TX Frequency(MHz)
Transmitting Configuration	1	2.4GHz	802.11g	2462 MHz
	2	U-NII 1	802.11ac(VHT80)	5210 MHz

Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.63	V	Z	PK	61.41	5.25	N/A	N/A	66.66	74.00	7.34
2483.59	V	Z	AV	44.23	5.25	0.60	N/A	50.08	54.00	3.92
4924.26	V	Y	PK	49.81	1.45	N/A	N/A	51.26	74.00	22.74
4924.42	V	Y	AV	39.12	1.45	0.60	N/A	41.17	54.00	12.83
5148.67	V	X	PK	49.61	1.78	N/A	N/A	51.39	74.00	22.61
5148.46	V	X	AV	41.06	1.78	0.16	N/A	43.00	54.00	11.00
10419.57	V	X	PK	43.57	10.71	N/A	N/A	54.28	68.20	13.92

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) :**  
***Simultaneously transmission - With Wireless charging pad***

	Antenna	Band	Mode	TX Frequency(MHz)
Transmitting Configuration	1	2.4GHz	802.11g	2462 MHz
	2	U-NII 1	802.11ac(VHT80)	5210 MHz

Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.57	H	X	PK	57.43	5.25	N/A	N/A	62.68	74.00	11.32
2483.72	H	X	AV	40.54	5.25	0.60	N/A	46.39	54.00	7.61
4923.71	V	X	PK	49.52	1.44	N/A	N/A	50.96	74.00	23.04
4923.57	V	X	AV	39.21	1.44	0.60	N/A	41.25	54.00	12.75
5148.95	V	X	PK	49.35	1.79	N/A	N/A	51.14	74.00	22.86
5149.09	V	X	AV	39.90	1.79	0.16	N/A	41.85	54.00	12.15
10419.98	H	X	PK	43.74	10.71	N/A	N/A	54.45	68.20	13.75

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) :**  
**Simultaneously transmission - With Dual Display**

	Antenna	Band	Mode	TX Frequency(MHz)
Transmitting Configuration	1	2.4GHz	802.11g	2462 MHz
	2	U-NII 1	802.11ac(VHT80)	5210 MHz

Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.82	V	Z	PK	57.45	5.26	N/A	N/A	62.71	74.00	11.29
2483.63	V	Z	AV	42.28	5.25	0.60	N/A	48.13	54.00	5.87
4924.43	V	Y	PK	49.99	1.45	N/A	N/A	51.44	74.00	22.56
4924.08	V	Y	AV	39.11	1.45	0.60	N/A	41.16	54.00	12.84
5148.11	V	X	PK	51.78	1.78	N/A	N/A	53.56	74.00	20.44
5147.88	V	X	AV	41.47	1.78	0.16	N/A	43.41	54.00	10.59
10419.74	V	X	PK	43.73	10.71	N/A	N/A	54.44	68.20	13.76

**Radiated Spurious Emissions data(9 kHz ~ 40 GHz) :**  
**Simultaneously transmission - With Dual Display + Wireless charging pad**

	Antenna	Band	Mode	TX Frequency(MHz)
Transmitting Configuration	1	2.4GHz	802.11g	2462 MHz
	2	U-NII 1	802.11ac(VHT80)	5210 MHz

Freq. (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.78	H	X	PK	60.94	5.26	N/A	N/A	66.20	74.00	7.80
2483.83	H	X	AV	44.06	5.26	0.60	N/A	49.92	54.00	4.08
4923.62	V	X	PK	49.65	1.44	N/A	N/A	51.09	74.00	22.91
4924.03	V	X	AV	39.23	1.45	0.60	N/A	41.28	54.00	12.72
5149.18	V	X	PK	50.46	1.79	N/A	N/A	52.25	74.00	21.75
5149.00	V	X	AV	40.58	1.79	0.16	N/A	42.53	54.00	11.47
10419.60	H	X	PK	43.95	10.71	N/A	N/A	54.66	68.20	13.54

## 8.6 AC Conducted Emissions

### ■ Test Requirements and limit, §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### ■ Test Configuration

See test photographs for the actual connections between EUT and support equipment.

### ■ Test Procedure

Conducted emissions from the EUT were measured according to the ANSI C63.10-2013.

1. The test procedure is performed in a 6.5 m  $\times$  3.5 m  $\times$  3.5 m (L  $\times$  W  $\times$  H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W)  $\times$  1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

### ■ Test Results: **Comply**

Note 1: See next pages for actual measured spectrum plots and data for worst case result.

**AC Line Conducted Emissions (Graph)**

Test Mode: U-NII 1 & TM 1 & MIMO(CDD) & 5240 MHz

**Results of Conducted Emission**

DTNC



Date 2020-05-08

Order No. DTNC2004-03119  
 Model No. LM-G910HMW  
 Serial No.  
 Test Condition 5.1GHz

Reference No.  
 Power Supply 120 V, 60 Hz  
 Temp/Humi. 23 °C / 42 %  
 Operator InHee Bae

Memo

LIMIT : FCC P15.207 QP  
 FCC P15.207 AV



**AC Line Conducted Emissions (Data List)**

Test Mode: U-NII 1 & TM 1 & MIMO(CDD) & 5240 MHz

**Results of Conducted Emission**

DTNC Date 2020-05-08

Order No.	DTNC2004-03119	Reference No.	
Model No.	LM-G910HMW	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 °C / 42 %
Test Condition	5.1GHz	Operator	InHee Bae

Memo

LIMIT : FCC P15.207 QP  
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]			
1	0.15378	16.13	5.82	10.00	26.13	15.82	65.79	55.79	39.66	39.97	N
2	0.16547	18.42	6.40	10.02	28.44	16.42	65.18	55.18	36.74	38.76	N
3	0.18033	17.13	5.71	10.02	27.15	15.73	64.47	54.47	37.32	38.74	N
4	0.18062	17.42	5.91	10.02	27.44	15.93	64.46	54.46	37.02	38.53	N
5	0.19573	16.64	5.12	10.02	26.66	15.14	63.79	53.79	37.13	38.65	N
6	0.32795	17.55	7.48	10.04	27.59	17.52	59.50	49.50	31.91	31.98	N
7	0.39673	19.65	12.01	10.06	29.71	22.07	57.92	47.92	28.21	25.85	N
8	0.46539	17.12	8.21	10.06	27.18	18.27	56.60	46.60	29.42	28.33	N
9	0.57287	18.66	6.19	10.06	25.72	16.25	56.00	46.00	30.28	29.75	N
10	0.61798	18.27	9.58	10.05	28.32	19.63	56.00	46.00	27.68	26.37	N
11	0.84029	20.75	7.84	10.06	30.81	17.90	56.00	46.00	25.19	28.10	N
12	0.99300	17.59	8.20	10.06	27.65	18.26	56.00	46.00	28.35	27.74	N
13	1.24308	22.21	10.77	10.07	32.28	20.84	56.00	46.00	23.72	25.16	N
14	1.27309	20.38	10.64	10.07	30.45	20.71	56.00	46.00	25.55	25.29	N
15	1.75103	19.22	8.11	10.09	29.31	18.20	56.00	46.00	26.69	27.80	N
16	1.96174	18.78	9.98	10.10	28.88	20.08	56.00	46.00	27.12	25.92	N
17	3.31809	18.41	9.28	10.17	28.58	19.45	56.00	46.00	27.42	26.55	N
18	4.59845	18.43	9.08	10.21	28.64	19.29	56.00	46.00	27.36	26.71	N
19	9.77478	13.03	4.23	10.35	23.38	14.58	60.00	50.00	36.62	35.42	N
20	16.03923	11.02	1.32	10.46	21.48	11.78	60.00	50.00	38.52	38.22	N
21	16.44154	10.52	0.95	10.47	20.99	11.42	60.00	50.00	39.01	38.58	N
22	17.69102	10.37	1.75	10.49	20.86	12.24	60.00	50.00	39.14	37.76	N
23	19.59390	10.97	3.00	10.53	21.50	13.53	60.00	50.00	38.50	36.47	N
24	0.15500	14.41	6.79	10.01	24.42	16.80	65.73	55.73	41.31	38.93	L
25	0.16500	16.86	6.22	10.01	26.87	16.23	65.21	55.21	38.34	38.98	L
26	0.18210	15.72	5.55	10.01	25.73	15.56	64.39	54.39	38.66	38.83	L
27	0.39984	22.26	11.56	10.04	32.30	21.60	57.86	47.86	25.56	26.26	L
28	0.62979	19.69	8.81	10.05	29.74	18.86	56.00	46.00	26.26	27.14	L
29	0.78889	24.41	12.98	10.06	34.47	23.04	56.00	46.00	21.53	22.96	L
30	0.83477	20.33	9.39	10.06	30.39	19.45	56.00	46.00	25.61	26.55	L
31	0.98513	24.88	14.55	10.06	34.94	24.61	56.00	46.00	21.06	21.39	L
32	0.98028	23.28	13.82	10.06	33.34	23.88	56.00	46.00	22.66	22.12	L
33	1.69113	23.66	13.06	10.10	33.76	23.16	56.00	46.00	22.24	22.84	L
34	2.17627	25.57	13.96	10.12	35.69	24.08	56.00	46.00	20.31	21.92	L
35	3.80285	22.95	12.44	10.18	33.13	22.62	56.00	46.00	22.87	23.38	L
36	4.13353	21.51	11.09	10.18	31.69	21.27	56.00	46.00	24.31	24.73	L
37	4.16387	21.45	11.12	10.18	31.63	21.30	56.00	46.00	24.37	24.70	L
38	5.84465	19.31	8.69	10.24	29.55	18.93	60.00	50.00	30.45	31.07	L
39	6.07081	19.87	8.53	10.24	30.11	18.77	60.00	50.00	29.89	31.23	L
40	10.21683	13.82	5.43	10.34	24.16	15.77	60.00	50.00	35.84	34.23	L
41	20.55578	15.80	3.78	10.50	26.30	14.28	60.00	50.00	33.70	35.72	L
42	20.83332	13.90	2.30	10.51	24.41	12.81	60.00	50.00	35.59	37.19	L

**AC Line Conducted Emissions (Graph)**

Test Mode: U-NII 2A & TM 1 & MIMO(CDD) & 5320 MHz

**Results of Conducted Emission**

DTNC



Date 2020-05-08

Order No. DTNC2004-03119  
 Model No. LM-G910HMW  
 Serial No.  
 Test Condition 5.3GHz

Reference No.  
 Power Supply 120 V, 60 Hz  
 Temp/Humi. 23 °C / 42 %  
 Operator InHee Bae

Memo

LIMIT : FCC P15.207 QP  
 FCC P15.207 AV



**AC Line Conducted Emissions (Data List)**

Test Mode: U-NII 2A & TM 1 & MIMO(CDD) & 5320 MHz

**Results of Conducted Emission**

DTNC

Date 2020-05-08

Order No.	DTNC2004-03119	Reference No.	
Model No.	LM-G910HMW	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 °C / 42 %
Test Condition	5.3GHz	Operator	InHee Bae

Memo

LIMIT : FCC P15.207 QP  
FCC P15.207 AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.15458	14.21	5.61	10.00	24.21	15.61	65.75	55.75	41.54	40.14	N
2	0.15787	14.48	5.56	10.00	24.48	15.56	65.58	55.58	41.10	40.02	N
3	0.18058	15.42	5.30	10.02	25.44	15.32	64.46	54.46	39.02	39.14	N
4	0.19798	14.02	4.22	10.02	24.04	14.24	63.70	53.70	39.66	39.46	N
5	0.21334	12.67	3.56	10.02	22.69	13.58	63.07	53.07	40.38	39.49	N
6	0.23012	12.34	3.65	10.02	22.36	13.67	62.45	52.45	40.09	38.78	N
7	0.25033	11.70	3.11	10.03	21.73	13.14	61.75	51.75	40.02	38.61	N
8	0.31496	14.71	4.38	10.04	24.75	14.42	59.84	49.84	35.09	35.42	N
9	0.39850	20.08	10.82	10.06	30.14	20.88	57.88	47.88	27.74	27.00	N
10	0.43460	17.44	7.43	10.06	27.50	17.49	57.16	47.16	29.66	29.67	N
11	0.45967	18.57	9.01	10.05	28.62	19.06	56.70	46.70	28.08	27.64	N
12	0.49845	17.96	7.63	10.06	28.02	17.69	56.03	46.03	28.01	28.34	N
13	0.78189	22.93	10.46	10.06	32.99	20.52	56.00	46.00	23.01	25.48	N
14	1.05689	19.04	8.91	10.06	29.10	18.97	56.00	46.00	26.90	27.03	N
15	1.12932	18.76	7.81	10.06	28.82	17.87	56.00	46.00	27.18	28.13	N
16	1.34669	19.34	8.96	10.07	29.41	19.03	56.00	46.00	26.59	26.97	N
17	2.29122	18.67	9.91	10.13	28.80	20.04	56.00	46.00	27.20	25.96	N
18	3.44215	17.61	9.44	10.17	27.78	19.61	56.00	46.00	28.22	26.39	N
19	4.70031	16.89	8.33	10.21	27.10	18.54	56.00	46.00	28.90	27.46	N
20	7.21928	12.94	4.73	10.27	23.21	15.00	60.00	50.00	36.79	35.00	N
21	7.84733	10.74	2.74	10.29	21.03	13.03	60.00	50.00	38.97	36.97	N
22	9.30246	12.78	4.38	10.33	23.11	14.71	60.00	50.00	36.89	35.29	N
23	10.06299	12.35	3.37	10.35	22.70	13.72	60.00	50.00	37.30	36.28	N
24	21.22709	7.84	0.70	10.55	18.39	11.25	60.00	50.00	41.61	38.75	N
25	0.15777	14.43	6.90	10.01	24.44	16.91	65.58	55.58	41.14	38.67	L
26	0.16565	16.36	6.04	10.01	26.37	16.05	65.18	55.18	38.81	39.13	L
27	0.17893	16.22	6.09	10.01	26.23	16.10	64.54	54.54	38.31	38.44	L
28	0.19974	13.50	4.24	10.02	23.52	14.26	63.62	53.62	40.10	39.36	L
29	0.21689	13.71	4.16	10.02	23.73	14.18	62.94	52.94	39.21	38.76	L
30	0.25427	12.16	3.50	10.02	22.18	13.52	61.62	51.62	39.44	38.10	L
31	0.39900	22.44	12.23	10.04	32.48	22.27	57.87	47.87	25.39	25.60	L
32	0.45628	22.68	11.90	10.05	32.73	21.95	56.76	46.76	24.03	24.81	L
33	0.47012	20.67	9.93	10.06	30.73	19.99	56.51	46.51	25.78	26.52	L
34	0.56177	18.76	7.99	10.07	28.83	18.06	56.00	46.00	27.17	27.94	L
35	0.59550	19.17	9.03	10.07	29.24	19.10	56.00	46.00	26.76	26.90	L
36	0.98073	24.04	14.14	10.06	34.10	24.20	56.00	46.00	21.90	21.80	L
37	1.01797	22.61	12.99	10.06	32.67	23.05	56.00	46.00	23.33	22.95	L
38	1.34522	20.07	10.93	10.07	30.14	21.00	56.00	46.00	25.86	25.00	L
39	1.65135	25.14	12.59	10.10	35.24	22.69	56.00	46.00	20.76	23.31	L
40	1.64591	23.68	11.23	10.10	33.78	21.33	56.00	46.00	22.22	24.67	L
41	2.11932	24.99	12.46	10.12	35.11	22.58	56.00	46.00	20.89	23.42	L
42	2.20924	25.07	14.02	10.12	35.19	24.14	56.00	46.00	20.81	21.86	L
43	3.33481	22.32	11.22	10.16	32.48	21.38	56.00	46.00	23.52	24.62	L
44	4.08267	20.83	10.32	10.18	31.01	20.50	56.00	46.00	24.99	25.50	L
45	4.60676	21.69	10.59	10.20	31.89	20.79	56.00	46.00	24.11	25.21	L
46	4.84247	21.99	10.78	10.22	32.21	21.00	56.00	46.00	23.79	25.00	L
47	5.32896	21.01	9.72	10.22	31.23	19.94	60.00	50.00	28.77	30.06	L
48	12.02147	14.76	4.52	10.38	25.14	14.90	60.00	50.00	34.86	35.10	L

AC Line Conducted Emissions (Graph)

Test Mode: U-NII 2C & TM 1 & MIMO(CDD) & 5500 MHz



Results of Conducted Emission

DTNC Date 2020-05-08

Order No.	DTNC2004-03119	Reference No.	
Model No.	LM-G910HMW	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 °C / 42 %
Test Condition	5.5GHz	Operator	InHee Bae

Memo

LIMIT : FCC P15.207 QP  
FCC P15.207 AV





### AC Line Conducted Emissions (Data List)

Test Mode: U-NII 2C & TM 1 & MIMO(CDD) & 5500 MHz

## Results of Conducted Emission

DTNC

Date 2020-05-08

Order No.	DTNC2004-03119	Reference No.	
Model No.	LM-G910HMW	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 'C / 42 %
Test Condition	5.5GHz	Operator	InHee Bae

Memo

LIMIT : FCC P15.207 QP  
FCC P15.207 AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]			
1	0.16658	15.14	5.60	10.02	25.16	15.62	65.13	55.13	39.97	39.51	N
2	0.31021	13.58	4.28	10.03	23.61	14.31	59.96	49.96	36.35	35.65	N
3	0.34856	11.74	2.99	10.04	21.78	13.03	59.00	49.00	37.22	35.97	N
4	0.39721	19.63	11.61	10.06	29.69	21.67	57.91	47.91	28.22	26.24	N
5	0.96029	17.61	6.74	10.06	27.67	16.80	56.00	46.00	28.33	29.20	N
6	1.05276	19.97	10.33	10.06	30.03	20.39	56.00	46.00	25.97	25.61	N
7	1.31128	19.62	9.46	10.07	29.69	19.53	56.00	46.00	26.31	26.47	N
8	1.74792	19.72	8.25	10.09	29.81	18.34	56.00	46.00	26.19	27.66	N
9	2.51732	17.77	8.74	10.14	27.91	18.88	56.00	46.00	28.09	27.12	N
10	5.55564	14.48	7.22	10.24	24.72	17.46	60.00	50.00	35.28	32.54	N
11	7.26521	12.62	4.36	10.27	22.89	14.63	60.00	50.00	37.11	35.37	N
12	19.24699	11.45	2.99	10.52	21.97	13.51	60.00	50.00	38.03	36.49	N
13	0.15582	14.88	6.81	10.01	24.89	16.82	65.68	55.68	40.79	38.86	L
14	0.18085	16.54	5.97	10.01	26.55	15.98	64.45	54.45	37.90	38.47	L
15	0.34733	12.30	3.59	10.04	22.34	13.63	59.03	49.03	36.69	35.40	L
16	0.46952	20.46	10.04	10.06	30.52	20.10	56.52	46.52	26.00	26.42	L
17	0.86478	24.37	11.71	10.05	34.42	21.76	56.00	46.00	21.58	24.24	L
18	1.33323	25.29	13.62	10.07	35.36	23.89	56.00	46.00	20.64	22.11	L
19	2.08097	24.98	13.74	10.12	35.10	23.86	56.00	46.00	20.90	22.14	L
20	4.13203	21.77	11.47	10.18	31.95	21.65	56.00	46.00	24.05	24.35	L
21	4.62953	21.71	10.65	10.20	31.91	20.85	56.00	46.00	24.09	25.15	L
22	11.63774	15.60	4.97	10.37	25.97	15.34	60.00	50.00	34.03	34.66	L
23	12.25263	15.32	4.48	10.38	25.70	14.86	60.00	50.00	34.30	35.14	L
24	20.38872	15.10	3.22	10.50	25.60	13.72	60.00	50.00	34.40	36.28	L

**AC Line Conducted Emissions (Graph)**

Test Mode: U-NII 2C & TM 1 & MIMO(CDD) & 5785 MHz

**Results of Conducted Emission**

DTNC



Date 2020-05-08

Order No. DTNC2004-03119  
 Model No. LM-G910HMW  
 Serial No.  
 Test Condition 5.7GHz

Reference No.  
 Power Supply 120 V, 60 Hz  
 Temp/Humi. 23 °C / 42 %  
 Operator InHee Bae

Memo

LIMIT : FCC P15.207 QP  
 FCC P15.207 AV



**AC Line Conducted Emissions (Data List)**

Test Mode: U-NII 2C &amp; TM 1 &amp; MIMO(CDD) &amp; 5785 MHz

## Results of Conducted Emission

DTNC

Date 2020-05-08

Order No.	DTNC2004-03119	Reference No.	
Model No.	LM-G910HMW	Power Supply	120 V, 60 Hz
Serial No.		Temp/Humi.	23 'C / 42 %
Test Condition	5.7GHz	Operator	InHee Bae

Memo

 LIMIT : FCC P15.207 QP  
 FCC P15.207 AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.16531	16.38	5.73	10.02	26.40	15.75	65.19	55.19	38.79	39.44	N
2	0.29442	15.29	5.49	10.03	25.32	15.52	60.40	50.40	35.08	34.88	N
3	0.35600	14.86	5.06	10.04	24.90	15.10	58.82	48.82	33.92	33.72	N
4	0.39737	19.47	11.66	10.06	29.53	21.72	57.91	47.91	28.38	26.19	N
5	0.43538	17.04	6.89	10.06	27.10	16.95	57.15	47.15	30.05	30.20	N
6	0.86046	17.36	7.74	10.05	27.41	17.79	56.00	46.00	28.59	28.21	N
7	1.71947	21.74	11.13	10.09	31.83	21.22	56.00	46.00	24.17	24.78	N
8	2.36774	17.57	9.00	10.13	27.70	19.13	56.00	46.00	28.30	26.87	N
9	3.21782	18.40	9.60	10.15	28.55	19.75	56.00	46.00	27.45	26.25	N
10	5.88067	13.89	6.64	10.24	24.13	16.88	60.00	50.00	35.87	33.12	N
11	11.14633	11.34	2.65	10.37	21.71	13.02	60.00	50.00	38.29	36.98	N
12	18.70833	11.30	2.20	10.50	21.80	12.70	60.00	50.00	38.20	37.30	N
13	0.15786	14.64	6.58	10.01	24.65	16.59	65.58	55.58	40.93	38.99	L
14	0.16278	17.42	5.99	10.01	27.43	16.00	65.32	55.32	37.89	39.32	L
15	0.39901	22.44	13.03	10.04	32.48	23.07	57.87	47.87	25.39	24.80	L
16	0.71644	23.26	12.67	10.04	33.30	22.71	56.00	46.00	22.70	23.29	L
17	0.94229	25.28	13.68	10.05	35.33	23.73	56.00	46.00	20.67	22.27	L
18	1.17128	25.05	13.30	10.07	35.12	23.37	56.00	46.00	20.88	22.63	L
19	1.78495	24.92	13.35	10.11	35.03	23.46	56.00	46.00	20.97	22.54	L
20	1.92859	22.24	12.49	10.12	32.36	22.61	56.00	46.00	23.64	23.39	L
21	2.40467	24.60	13.27	10.13	34.73	23.40	56.00	46.00	21.27	22.60	L
22	4.12571	23.02	11.99	10.18	33.20	22.17	56.00	46.00	22.80	23.83	L
23	4.49667	20.75	10.48	10.20	30.95	20.68	56.00	46.00	25.05	25.32	L
24	5.97853	20.23	9.36	10.24	30.47	19.60	60.00	50.00	29.53	30.40	L
25	10.33338	15.15	4.94	10.34	25.49	15.28	60.00	50.00	34.51	34.72	L
26	20.49664	14.66	3.00	10.50	25.16	13.50	60.00	50.00	34.84	36.50	L

## 9. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY50410357
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY48011700
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY48010133
Spectrum Analyzer	Agilent Technologies	N9030A	19/12/16	20/12/16	MY53310140
DC Power Supply	Agilent Technologies	66332A	19/06/25	20/06/25	MY43000211
Multimeter	FLUKE	17B	19/12/16	20/12/16	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	19/12/16	20/12/16	255571
Signal Generator	ANRITSU	MG3695C	19/12/16	20/12/16	173501
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-1
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-2
Thermohygrometer	BODYCOM	BJ5478	19/09/18	20/09/18	N/A
HYGROMETER	TESTO	608-H1	20/01/21	21/01/21	34862883
Loop Antenna	Schwarzbeck	FMZB1513	20/02/19	22/02/19	1513-128
BILOG ANTENNA	Schwarzbeck	VULB 9160	19/04/23	21/04/23	9160-3362
Horn Antenna	ETS-Lindgren	3115	20/01/30	22/01/30	6419
Horn Antenna	A.H.Systems Inc.	SAS-574	19/07/03	21/07/03	155
PreAmplifier	tsj	MLA-0118-B01-40	19/12/16	20/12/16	1852267
PreAmplifier	tsj	MLA-1840-J02-45	19/06/27	20/06/27	16966-10728
PreAmplifier	H.P	8447D	19/12/16	20/12/16	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	19/06/26	20/06/26	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	19/06/26	20/06/26	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	19/06/27	20/06/27	3
Attenuator	Hefei Shunze	SS5T2.92-10-40	19/06/27	20/06/27	16012202
Attenuator	SRTechnology	F01-B0606-01	19/06/27	20/06/27	13092403
Attenuator	Aeroflex/Weinschel	20515	19/06/27	20/06/27	Y2370
Attenuator	SMAJK	SMAJK-2-3	19/06/27	20/06/27	2
Attenuator	SMAJK	SMAJK-50-10	19/08/07	20/08/07	15081901
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2488B MA2491A	20/01/02	21/01/02	0846002
			20/01/02	21/01/02	0845295
EMI Receiver	ROHDE&SCHWARZ	ESW44	19/07/30	20/07/30	101645
HYGROMETER	TESTO	608-H1	20/01/21	21/01/21	34862883
EMI Test Receiver	Rohde Schwarz	ESCI7	20/01/20	21/01/20	100910
PULSE LIMITER	Rohde Schwarz	ESH3-Z2	19/09/17	20/09/17	101333
LISN	SCHWARZBECK	NNLK 8121	19/05/23	20/05/23	6183
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-04
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-07
Cable	DT&C	Cable	20/01/13	21/01/13	G-13
Cable	DT&C	Cable	20/01/13	21/01/13	G-14
Cable	HUBER+SUHNER	SUCOFLEX 104	20/01/13	21/01/13	G-15
Cable	Radiall	TESTPRO3	20/01/16	21/01/16	M-01
Cable	Junkosha	MWX315	20/01/16	21/01/16	M-05
Cable	Junkosha	MWX221	20/01/16	21/01/16	M-06
Cable	DT&C	Cable	20/01/16	21/01/16	RF-82


Note 1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017

Note 2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself

## APPENDIX I

### Conducted Test set up Diagram

- Conducted Measurement



## APPENDIX II

### Duty Cycle Information

#### ■ Test Procedure

**Duty Cycle [X = On Time / ( On + Off time )]** is measured using Measurement Procedure of **KDB789033 D02v02r01**

1. Set the center frequency of the spectrum analyzer to the center frequency of the transmission.
2. Set RBW  $\geq$  EBW if possible; otherwise, set RBW to the largest available value.
3. Set VBW  $\geq$  RBW. Set detector = peak.
4. Note : The zero-span measurement method shall not be used unless both **RBW and VBW are  $> 50/T$** , where  $T$  is defined in section II.B.1.a), and **the number of sweep points across duration  $T$  exceeds 100**. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

$T$ : The minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

( $T$  = On time of the above table since the EUT operates with above fixed Duty Cycle and it is the minimum On time)

#### ■ Test Results:

##### Duty cycle: CDD


Mode	Data Rate	Tested Frequency [MHz]	Maximum Achievable Duty Cycle (x) = On / (On+Off)			Duty Cycle Correction Factor [dB]	50/T [kHz]
			On Time [ms]	(On+Off) Time [ms]	x		
TM 1	6Mbps	5180	2.023	2.073	0.9759	0.11	24.72
TM 2	MCS 0	5180	0.973	1.017	0.9570	0.19	51.37
TM 3	MCS 0	5190	0.661	0.703	0.9411	0.26	75.61
TM 4	MCS 0	5210	1.168	1.213	0.9629	0.16	42.81

Test Plot:

Multiple Transmit


Duty Cycle

Test Mode: TM 1 & Ch.36




Duty Cycle

Test Mode: TM 2 & Ch.36




Duty Cycle

Test Mode: TM 3 & Ch.38



Duty Cycle

Test Mode: TM 4 & Ch.42






APPENDIX III

Unwanted Emissions (Radiated) Test Plot: MIMO(CDD)


TM 1 & U-NII 1 & Ch.36 & Z axis & Hor

Detector Mode : PK



TM 1 & U-NII 1 & Ch.36 & Z axis & Hor

Detector Mode : AV



TM 1 & U-NII 1 & Ch.40 & X axis & Ver

Detector Mode : PK

