

# EMI CERTIFICATION REPORT

**Applicant:**

**LG Electronics MobileComm U.S.A., Inc.**  
**1000 Sylvan Avenue, Englewood Cliffs NJ 07632**

**Date of Receipt: March 17, 2015****Date of Issue: April 01, 2015****Test Report No. HCT-E-1504-F005****HCT FRN: 0005866421****FCC ID:****ZNFH220****Rule Part(s) / Standard(s):**

FCC CFR 47 PART 15 Subpart B Class B

**FCC Classification:**

JBP (Part 15 B – Class B Computing Device Peripheral)

**EUT Type:**

Cellular/PCS GSM Phone with WLAN and Bluetooth

**Model Name:**

LG-H220

**Additional Model Name:**

LGH220, H220

**Test Port:**

USB / Earphone Port

**Date of Test:**

March 19, 2015 - March 20, 2015

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

**Tested By**

**Kyoung-Hee Yoon**  
Test Engineer  
EMC Team  
Certification Division

**Reviewed By**

**Jin-Pyo Hong**  
Technical Manager  
EMC Team  
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



## DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1504-F005	April 01, 2015	Initial Release



## TABLE OF CONTENTS

	<b>PAGE</b>
1. GENERAL INFORMATION .....	4
1.1 Description of EUT .....	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Test Facility .....	5
1.4 Tested System Details.....	6
1.5 Cable Description .....	7
1.6 Noise Suppression Parts on Cable. (I/O Cable) .....	7
2. DESCRIPTION OF TEST.....	8
3. PRELIMINARY TEST .....	11
3.1 Conducted Emission Test .....	11
3. 2 Radiated Emission Test .....	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY .....	12
4.1 Conducted Emission Test .....	12
4.2 Radiated Emission Test .....	19
5. LIST OF TEST EQUIPMENT .....	21
6. CONCLUSION .....	22

**ATTACHMENT:     TEST SETUP PHOTOGRAPHS**



## 1. GENERAL INFORMATION

### 1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**  
Its basic purpose is used for communications.

<b>Model</b>	LG-H220
<b>FCC ID</b>	ZNFH220
<b>Additional Model</b>	LGH220, H220
<b>EUT Type</b>	Cellular/PCS GSM Phone with WLAN and Bluetooth
<b>TX Frequency</b>	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900)
<b>RX Frequency</b>	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900)

### 1.2 Related Submittal(s) / Grant(s)

Original submittal only.



### 1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



## 1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-H220	LG	ZNFH220	Notebook PC, Earphone
USB cable	EAD62377902	Ningbo Broad	-	EUT, Notebook PC
Earphone	EAB62808211	I-SOUND	-	EUT
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	16 GB	Samsung	-	EUT



## 1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

\* The marked "(D)" means the data cable and "(P)" means the power cable.

## 1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



## 2. DESCRIPTION OF TEST

### 2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 7

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).  
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).  
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

#### [ Conducted Emission Limits ]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

\*Decreases with the logarithm of the frequency.



## 2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a 3 m shield room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

### [ Radiated Emission Limits ]

Frequency (MHz)	Antenna Distance (m)	Field Strength ( $\mu\text{V}/\text{m}$ )	Quasi-Peak (dB( $\mu\text{V}$ ))/m)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak (dB( $\mu\text{V}$ ))/m)	Average (dB( $\mu\text{V}$ ))/m)
Above 1 000	3	74	54




## 2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

## 2.3 Configuration of Tested System





### 3. PRELIMINARY TEST

#### 3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

**Operation Mode:**       Data Communication mode

#### 3.2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

**Operation Mode:**       Data Communication mode



## 4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY


### 4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Quasi-Peak, CISPR-Average
<b>Bandwidth</b>	9 kHz (6 dB)
<b>Operation Mode</b>	Data Communication mode
<b>Kind of Test Site</b>	Shielded Room
<b>Temperature</b>	22.5 °C
<b>Relative Humidity</b>	33.7 %
<b>Test Date</b>	March 20, 2015

#### - Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage = Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

**Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)**




## QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	44.6	9.000	L1	9.6	21.4	66.0
0.160000	40.7	9.000	L1	9.6	24.8	65.5
0.196000	54.6	9.000	L1	9.6	9.2	63.8
0.200000	54.2	9.000	L1	9.7	9.4	63.6
0.208000	53.3	9.000	L1	9.7	10.0	63.3
0.214000	50.7	9.000	L1	9.7	12.3	63.0
4.462000	41.5	9.000	L1	9.9	14.5	56.0
4.466000	40.5	9.000	L1	9.9	15.5	56.0
4.532000	41.6	9.000	L1	9.9	14.4	56.0
4.602000	41.6	9.000	L1	9.9	14.4	56.0
4.606000	40.3	9.000	L1	9.9	15.7	56.0
4.674000	40.5	9.000	L1	9.9	15.5	56.0
17.844000	34.7	9.000	L1	10.3	25.3	60.0
17.902000	35.1	9.000	L1	10.3	24.9	60.0
18.094000	34.1	9.000	L1	10.3	25.9	60.0
18.482000	32.5	9.000	L1	10.3	27.5	60.0
20.318000	34.4	9.000	L1	10.3	25.6	60.0
20.392000	34.0	9.000	L1	10.3	26.0	60.0



## CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.3	9.000	L1	9.6	27.7	56.0
0.192000	36.7	9.000	L1	9.6	17.2	53.9
0.198000	40.4	9.000	L1	9.6	13.3	53.7
0.202000	40.3	9.000	L1	9.7	13.2	53.5
0.210000	37.9	9.000	L1	9.7	15.3	53.2
0.216000	31.3	9.000	L1	9.7	21.7	53.0
4.464000	33.8	9.000	L1	9.9	12.2	46.0
4.534000	34.0	9.000	L1	9.9	12.0	46.0
4.602000	34.2	9.000	L1	9.9	11.8	46.0
4.606000	33.7	9.000	L1	9.9	12.3	46.0
4.622000	33.9	9.000	L1	9.9	12.1	46.0
4.684000	33.7	9.000	L1	9.9	12.3	46.0
17.844000	27.8	9.000	L1	10.3	22.2	50.0
17.902000	27.6	9.000	L1	10.3	22.4	50.0
17.966000	27.0	9.000	L1	10.3	23.0	50.0
18.054000	27.3	9.000	L1	10.3	22.7	50.0
18.482000	24.5	9.000	L1	10.3	25.5	50.0
20.392000	25.9	9.000	L1	10.3	24.1	50.0

**Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)**



## QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.196000	52.7	9.000	N	9.6	11.1	63.8
0.202000	51.9	9.000	N	9.6	11.6	63.5
0.206000	51.6	9.000	N	9.6	11.8	63.4
0.212000	50.5	9.000	N	9.6	12.6	63.1
0.244000	47.3	9.000	N	9.6	14.7	62.0
0.260000	45.7	9.000	N	9.7	15.7	61.4
4.314000	41.4	9.000	N	9.8	14.6	56.0
4.384000	41.8	9.000	N	9.9	14.2	56.0
4.454000	42.0	9.000	N	9.9	14.0	56.0
4.524000	42.1	9.000	N	9.9	13.9	56.0
4.596000	41.1	9.000	N	9.9	14.9	56.0
4.666000	40.8	9.000	N	9.9	15.2	56.0
17.958000	32.5	9.000	N	10.3	27.5	60.0
19.796000	34.3	9.000	N	10.3	25.7	60.0
19.866000	34.1	9.000	N	10.3	25.9	60.0
19.882000	34.3	9.000	N	10.3	25.7	60.0
19.938000	34.1	9.000	N	10.3	25.9	60.0
20.008000	33.6	9.000	N	10.3	26.4	60.0



## CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.0	9.000	N	9.6	28.0	56.0
0.160000	27.5	9.000	N	9.6	28.0	55.5
0.194000	37.6	9.000	N	9.6	16.3	53.9
0.198000	38.9	9.000	N	9.6	14.8	53.7
0.206000	38.1	9.000	N	9.6	15.3	53.4
0.212000	35.5	9.000	N	9.6	17.6	53.1
3.750000	31.8	9.000	N	9.8	14.2	46.0
3.888000	32.3	9.000	N	9.8	13.7	46.0
4.104000	33.6	9.000	N	9.8	12.4	46.0
4.170000	34.1	9.000	N	9.8	11.9	46.0
4.384000	34.1	9.000	N	9.9	11.9	46.0
4.600000	33.3	9.000	N	9.9	12.7	46.0
16.724000	27.3	9.000	N	10.2	22.7	50.0
17.394000	27.6	9.000	N	10.2	22.4	50.0
17.958000	24.9	9.000	N	10.3	25.1	50.0
19.306000	27.7	9.000	N	10.3	22.3	50.0
19.866000	25.0	9.000	N	10.3	25.0	50.0
20.008000	24.4	9.000	N	10.3	25.6	50.0



## 4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

### -For Measurement Below 1 GHz

<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Quasi-Peak
<b>Bandwidth</b>	120 kHz (6 dB)
<b>Operation Mode</b>	Data Communication mode
<b>Kind of Test Site</b>	3 m semi anechoic chamber
<b>Temperature</b>	21.8 °C
<b>Relative Humidity</b>	26.9 %
<b>Test Date</b>	March 19, 2015

Frequency (MHz)	Quasi Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
30.080000	26.0	100.0	V	73.0	14.8	14.0	40.0
59.518317	32.0	100.0	V	358.0	15.5	8.0	40.0
85.228858	33.0	250.0	H	281.0	11.6	7.0	40.0
86.732745	33.6	330.0	H	257.0	11.5	6.4	40.0
625.029659	37.1	100.0	V	6.0	25.8	8.9	46.0

### *- Calculation Formula:*

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



## -For Measurement Above 1 GHz

<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
<b>Highest Operating Frequency</b>	1.2 GHz
<b>Testing Frequency Range</b>	1 GHz to 6 GHz
<b>Operation Mode</b>	Data Communication mode
<b>Kind of Test Site</b>	3 m semi anechoic chamber
<b>Temperature</b>	21.8 °C
<b>Relative Humidity</b>	26.9 %
<b>Test Date</b>	March 19, 2015

Frequency (MHz)	Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1998.046092	53.3	100.0	V	42.0	-7.8	20.7	74.0
2037.124248	52.8	100.0	V	22.0	-7.6	21.2	74.0
2664.178356	49.8	100.0	V	28.0	-4.8	24.2	74.0

Frequency (MHz)	CAverage (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1998.046092	35.9	100.0	V	42.0	-7.8	18.1	54.0
2037.124248	36.4	100.0	V	22.0	-7.6	17.6	54.0
2664.178356	33.5	100.0	V	28.0	-4.8	20.5	54.0

### *- Calculation Formula:*

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



## 5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
-------------	---------------------	-------------------	----------------------	--------------------------	-----------------

### Conducted Emission

<input checked="" type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	01.13.2015
<input checked="" type="checkbox"/>	LISN	EMCO	3816/2SH	9706-1070	1 year	04.07.2014
<input checked="" type="checkbox"/>	LISN	Rohde & Schwarz	ENV216	100073	1 year	01.13.2015
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-

### Radiated Emission

#### -For measurement below 1 GHz

<input checked="" type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07.2014
<input checked="" type="checkbox"/>	Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17.2014
<input checked="" type="checkbox"/>	Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/>	Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/>	Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/>	Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18.2014
<input type="checkbox"/>	Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/>	Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-

#### -For measurement above 1 GHz

<input checked="" type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07.2014
<input checked="" type="checkbox"/>	Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/>	Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/>	Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/>	Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/>	Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.11.2014
<input checked="" type="checkbox"/>	Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.11.2014
<input checked="" type="checkbox"/>	Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.07.2013
<input type="checkbox"/>	Horn Antenna	Schwarzbeck	BBHA 9120D	1151	2 year	07.05.2013
<input type="checkbox"/>	EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18.2014
<input type="checkbox"/>	Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input type="checkbox"/>	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170124	2 year	10.30.2013
<input type="checkbox"/>	Power Amplifier	CERNEX	CBL18265035	22966	1 year	07.23.2014
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32	-	-	-



## 6. CONCLUSION

The data collected shows that the **EUT Type: Cellular/PCS GSM Phone with WLAN and Bluetooth, FCC ID: ZNFH220, Model: LG-H220** complies with §15.107 and §15.109 of the FCC rules.