

FCC REPORT

Certification

Applicant Name:
LG Electronics MobileComm U.S.A., Inc.**Address:**
1000 Sylvan Avenue, Englewood Cliffs NJ 07632**Date of Issue:**

January 29, 2015

Test Site/Location:HCT CO., LTD., 74, Seoicheon-ro 578beon-gil,
Majang-myeon, Icheon-si, Gyeonggi-do, Korea**Report No.:** HCT-R-1501-F021-1**HCT FRN:** 0005866421**FCC ID:** ZNFH340N**APPLICANT:** LG Electronics MobileComm U.S.A., Inc.**FCC Model(s):** LG-H340n
Additional Model(s): LG-H340n, LGH340n, H340n, LG-H340N, LGH340N, H340N
EUT Type: Cellular/PCS GSM/WCDMA Phone with WLAN and Bluetooth, NFC**RF Output Field Strength:** 17.09 dBuV/m @30 m**Frequency of Operation:** 13.5594 MHz**Modulation type:** ASK**FCC Classification:** Low Power Communication Device – Transmitter**FCC Rule Part(s):** FCC Part 15.225 Subpart C

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)



Report prepared by
: Jong Seok Lee
Test Engineer of RF Team



Approved by
: Sang Jun Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1501-F021	January 16, 2015	- First Approval Report
HCT-R-1501-F021-1	January 29, 2015	-Revised the 20dB bandwidth plot on page 14 -Revised the miss typo section 11

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
3.5 STANDARDS	6
4. INSTRUMENT CALIBRATION.....	7
5. FACILITIES AND ACCREDITATIONS	7
5.1 FACILITIES	7
5.2 EQUIPMENT	7
6. ANTENNA REQUIREMENTS	7
7. TEST SUMMARY	8
8. RADIATED EMISSION MEASUREMENT	9
8.1. RADIATED EMISSION 9 kHz – 30 MHz.....	10
8.2. RADIATED EMISSION 30 MHz – 1000 MHz	13
9. EMISSION BANDWIDTH PLOT.....	14
10. FREQUENCY TOLERANCE.....	15
11. POWERLINE CONDUCTED EMISSIONS	16
12. LIST OF TEST EQUIPMENT	25
12.1 LIST OF TEST EQUIPMENT(Conducted Test)	25
12.2 LIST OF TEST EQUIPMENT(Radiated Test)	26

1. GENERAL INFORMATION

Applicant: LG Electronics MobileComm U.S.A., Inc.
Address: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
FCC ID: ZNFH340N
EUT Type: Cellular/PCS GSM/WCDMA Phone with WLAN and Bluetooth, NFC
Model name(s): LG-H340n
Additional Model(s): LG-H340n, LGH340n, H340n, LG-H340N, LGH340N, H340N
Date(s) of Tests: January 06, 2015 ~ January 29, 2015
Place of Tests: HCT Co., Ltd.
 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea
 (IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

FCC Model Name	LG-H340n
Additional Model	LG-H340n, LGH340n, H340n, LG-H340N, LGH340N, H340N
EUT Type	Cellular/PCS GSM/WCDMA Phone with WLAN and Bluetooth, NFC
Power Supply	DC 3.8 V
Battery Type	Li-ion Battery(Standard)
Frequency of Operation	13.5594 MHz
Transmit Power	17.09 dBuV/m @30 m
Modulation Type	ASK
Antenna Specification	Manufacturer: IMTECH Antenna type: FPCB Antenna

3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.10-2009).

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.225 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2009) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.3 of ANSI C63.10. (Version: 2009).

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3.5 STANDARDS

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance With

FCC Part 15.Subpart C

Regulation	Measurement standard	Range
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(a)	ANSI C63.10:2009	13.553MHz to 13.567MHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(d)	ANSI C63.10:2009	outside of the 13.110-14.010 MHz band
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209	ANSI C63.10:2009	9kHz to 30MHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209	ANSI C63.10:2009	30MHz to 1GHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.207	ANSI C63.10:2009	150kHz to 30MHz
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(e)	ANSI C63.10:2009	0.01% of nominal
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.215(c)	ANSI C63.10:2009	-

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The 10 m semi anechoic chamber used to collect the Conducted and Radiated data is located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4. Detailed description of test facilities was submitted to the Commission and accepted dated February 28, 2014 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned loop, dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

7. TEST SUMMARY

The results in this report apply only to sample tested

Regulation	Test Type	Range	Result
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(a)	Radiated Electric Field Emissions	13.553MHz to 13.567MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(b)	Radiated Electric Field Emissions	13.410MHz to 13.553MHz and 13.567MHz to 13.710MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(c)	Radiated Electric Field Emissions	13.110 MHz to 13.410 MHz and 13.710 MHz to 14.010 MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209 (d)	Radiated Electric Field Emissions	9kHz to 30MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.209	Radiated Electric Field Emissions	30MHz to 1GHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.207	AC power conducted emissions	150kHz to 30MHz	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.225(e)	Frequency Stability	0.01% of nominal	Pass
Title 47 of the CFR: Part 15 Subpart (c), Clause 15.215(c)	20 dB Bandwidth	-	Pass

8. RADIATED EMISSION MEASUREMENT

Requirement(s): 15.209, 15.225

Except as provided elsewhere in this paragraph the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Minimum Standard: FCC Part 15.225 / 15.209

Rule Part	Frequency (MHz)	Limit
Part 15.209	0.009 ~ 0.490	2400/F(kHz) uV/m@300 m
	0.490 ~1.705	24000/F(kHz) uV/m@30 m
	1.705 ~ 30	30 uV/m@30 m
	30 ~ 88	100 ** uV/m@3 m
	88 ~ 216	150 ** uV/m@3 m
	216 ~ 960	200 ** uV/m@3 m
	Above 960	500 uV/m@3 m

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

15.225 Operation within the band 13.110 – 14.010 MHz.

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter (= 84 dBuV/m) at 30 meters.

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter (=50.5dBuV/m) at 30 meters.

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter (=40.5 dBuV/m) at 30 meters.


(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

(e) The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

(f) In the case of radio frequency powered tags designed to operate with a device authorized under this section, the tag may be approved with the device or be considered as a separate device subject to its own authorization. Powered tags approved with a device under a single application shall be labeled with the same identification number as the device.

8.1. RADIATED EMISSION 9 kHz – 30 MHz

Test Set-up



Test Procedure

The EUT was placed on a non-conductive table located on a large open test site. The loop antenna was placed at a location 3m from the EUT. Radiated emissions were measured with the loop antenna both parallel and perpendicular to the plane of the EUT loop antenna and with x, y, z planes in EUT.

The limit is converted from microvolts/meter to decibel microvolts/meter. Sample Calculation:

Corrected Amplitude = Raw Amplitude(dB μ V/m) + ACF(dB) + Cable Loss(dB) – Distance Correction Factor

The spectrum analyzer is set to:

Frequency Range = 9 kHz ~ 1 GHz

RBW = 9 kHz (9 kHz ~ 30 MHz)
= 120 kHz (30 MHz ~ 1 GHz)

Trace Mode = max hold

Detector Mode = peak / Quasi-peak

Sweep time = auto

Test Results

13.553 MHz-13.567 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.5594(H)*	36.72	20.37	-40	17.09	84	66.91
13.5600(V)*	31.98	20.37	-40	12.35	84	71.65

13.410 MHz-13.553 MHz and 13.567 MHz-13.710 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.5530	23.82	20.37	-40	4.19	50.47	46.28
13.5670	23.57	20.37	-40	3.94	50.47	46.53

13.110 MHz – 13.410 MHz and 13.710 MHz-14.010 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
13.2756	9.52	20.37	-40	-10.11	40.51	50.62
13.8546	10.35	20.37	-40	-9.28	40.51	49.79


9 kHz -30 MHz						
Frequency (MHz)	Read Level (dBuV)@3m	Ant.Factor+Cable Loss (dB/m)	Distance Correction (dB)	Result Level (dBuV/m)@30m	Limit (dBuV/m)@30m	Margin (dB)
*12.2915	10.14	20.62	-40	-9.24	29.54	38.78
14.1060	8.85	20.34	-40	-10.81	29.54	40.35
27.2920	8.16	20.65	-40	-11.19	29.54	40.73
27.1740	8.10	20.65	-40	-11.25	29.54	40.79
*25.6125	8.03	20.61	-40	-11.36	29.54	40.90
*16.6950	8.15	20.34	-40	-11.51	29.54	41.05

Note :

1. Distance Correction Below 30MHz = $40\log(3m/30m) = -40$ dB
Measurement Distance : 3 m (Below 30 MHz)
2. Factor = Antenna Factor + Cable Loss
3. Result Level = Read Level + Factor + Distance Correction
4. Margin = Limit – Result Level
5. We have done x, y, z planes in EUT
6. Antenna rotated about its vertical/horizontal axis for maximum response at each azimuth position around the EUT.
7. Worst case of operating mode is type A, analog mode and 106 kbps.
8. '*' is the result for restricted band.

8.2. RADIATED EMISSION 30 MHz – 1000 MHz

Test Set-up



Test Procedures: Radiated emissions were measured according to ANSI C63.10.

The EUT was set to transmit at the highest output power.

The EUT was set 3 meter away from the measuring antenna.

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
*37.66	19.13	11.24	0.58	H	30.95	40.00	9.05
43.76	18.88	11.95	0.66	H	31.49	40.00	8.51
*75.15	18.83	8.19	0.78	V	27.80	40.00	12.20
98.88	17.86	9.27	0.88	H	28.01	43.50	15.49
*129.11	18.3	12.24	1.00	H	31.54	43.50	11.96
196.84	20.85	9.64	1.22	V	31.71	43.50	11.79

Remark


1. Result Level = Read Level + (Antenna Factor+ Cable Loss)
2. Margin = Limit – Result Level
3. '*' is the result for restricted band.

9. EMISSION BANDWIDTH PLOT.

Requirement(s):

Test Set-up: The EUT was connected to a spectrum analyzer.

Test Procedure: The 20 dB bandwidth was measured by using a spectrum analyzer.



10. FREQUENCY TOLERANCE

Procedure: Part 15.225, ANSI 63.10

If required, the operating or transmitting frequency of an intentional radiator should be measured in accordance with the following procedure to ensure that the device operates outside certain precluded frequency bands and within the frequency range. No modulation needs to be supplied to the intentional radiator during these tests, unless modulation is required to produce an output, e.g., single-sideband suppressed carrier transmitters.

The frequency stability of the transmitter is measured by:

- a) Temperature: The temperature is varied from -20°C to + 50°C using an environmental chamber.
- b) For battery operated equipment, the equipment tests shall be performed using a new battery.

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency.

Measurement Result:

VOLTAGE	POWER	Temperature	Frequency	Frequency Error	
(%)		(°C)	(MHz)	(Hz)	
100%	3.8 V	-20	13.559880	-120.00	
100%		-10	13.559892	-108.00	
100%		0	13.559903	-97.00	
100%		10	13.559915	-85.00	
100%		20	13.559925	-75.00	
100%		30	13.559938	-62.00	
100%		40	13.559951	-49.00	
100%		50	13.559966	-34.00	
115%		4.37	20	13.559936	-64.00
85%		3.23	20	13.559912	-88.00

11. POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. The EUT is the device with a detachable antenna operating below 30 MHz.
 - For unterminated the Antenna, the AC line conducted tests are performed with the antenna connected
 - For terminated the Antenna, the AC line conducted tests are performed with a dummy load connected to the EUT antenna output terminal.

Test Plots

Untermine the Antenna

Conducted Emissions (Line 1)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H340n
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: NFC MODE(UNTERMINATION)
 Operator Name: JS LEE

FCC CLASS B



— FCCCLASS B_QP — FCCCLASS B_AV — Preview Result 1-PK+
— Preview Result 2-AVG x Final Result 1-QPK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	38.2	9.000	Off	N	9.6	27.8	66.0
0.156000	34.5	9.000	Off	N	9.6	31.2	65.7
0.342000	34.2	9.000	Off	N	9.7	25.0	59.2
0.370000	35.5	9.000	Off	N	9.7	23.0	58.5
0.374000	34.8	9.000	Off	N	9.7	23.6	58.4
0.380000	35.2	9.000	Off	N	9.7	23.1	58.3
0.914000	28.1	9.000	Off	N	9.7	27.9	56.0
1.294000	27.6	9.000	Off	N	9.8	28.4	56.0
1.298000	27.0	9.000	Off	N	9.8	29.0	56.0
1.318000	26.1	9.000	Off	N	9.8	29.9	56.0
1.502000	25.9	9.000	Off	N	9.8	30.1	56.0
1.542000	25.1	9.000	Off	N	9.8	30.9	56.0
6.840000	24.2	9.000	Off	N	10.0	35.8	60.0
7.510000	24.3	9.000	Off	N	10.0	35.7	60.0
13.560000	42.8	9.000	Off	N	10.1	17.2	60.0
13.656000	21.6	9.000	Off	N	10.1	38.4	60.0

1/13/2015

10:54:33

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
14.804000	21.6	9.000	Off	N	10.2	38.4	60.0
15.018000	21.8	9.000	Off	N	10.2	38.2	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.152000	27.9	9.000	Off	N	9.6	28.0	55.9
0.188000	22.9	9.000	Off	N	9.7	31.2	54.1
0.226000	21.4	9.000	Off	N	9.7	31.2	52.6
0.338000	26.1	9.000	Off	N	9.7	23.2	49.3
0.346000	25.9	9.000	Off	N	9.7	23.2	49.1
0.374000	30.5	9.000	Off	N	9.7	17.9	48.4
0.914000	18.6	9.000	Off	N	9.7	27.4	46.0
1.294000	18.1	9.000	Off	N	9.8	27.9	46.0
1.334000	18.3	9.000	Off	N	9.8	27.7	46.0
1.372000	18.8	9.000	Off	N	9.8	27.2	46.0
1.480000	18.1	9.000	Off	N	9.8	27.9	46.0
1.488000	18.5	9.000	Off	N	9.8	27.5	46.0
5.490000	17.4	9.000	Off	N	9.9	32.6	50.0
13.560000	41.1	9.000	Off	N	10.1	8.9	50.0
13.656000	15.0	9.000	Off	N	10.1	35.0	50.0
14.028000	15.0	9.000	Off	N	10.2	35.0	50.0
14.418000	14.9	9.000	Off	N	10.2	35.1	50.0
14.804000	14.7	9.000	Off	N	10.2	35.3	50.0

1/13/2015

10:54:33

Conducted Emissions (Line 2)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H340n
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: NFC MODE(UNTERMINATION)
 Operator Name: JS LEE

FCC CLASS B



— FCC CLASS B_OP — FCC CLASS B_AV — Preview Result 1-PK+
— Preview Result 2-AVG x Final Result 1-CFK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154000	36.8	9.000	Off	L1	9.6	29.0	65.8
0.372000	34.8	9.000	Off	L1	9.7	23.7	58.5
0.688000	35.2	9.000	Off	L1	9.7	20.8	56.0
0.692000	32.7	9.000	Off	L1	9.7	23.3	56.0
0.722000	35.6	9.000	Off	L1	9.7	20.4	56.0
0.726000	34.9	9.000	Off	L1	9.7	21.1	56.0
1.450000	32.3	9.000	Off	L1	9.7	23.7	56.0
1.480000	32.6	9.000	Off	L1	9.7	23.4	56.0
1.520000	33.0	9.000	Off	L1	9.8	23.0	56.0
1.524000	33.1	9.000	Off	L1	9.8	22.9	56.0
1.530000	31.7	9.000	Off	L1	9.8	24.3	56.0
1.558000	32.2	9.000	Off	L1	9.8	23.8	56.0
13.560000	49.0	9.000	Off	L1	10.2	11.0	60.0
14.268000	27.7	9.000	Off	L1	10.2	32.3	60.0
14.690000	27.9	9.000	Off	L1	10.2	32.1	60.0
14.788000	27.6	9.000	Off	L1	10.2	32.4	60.0

1/13/2015

10:45:29

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
15.212000	27.0	9.000	Off	L1	10.3	33.0	60.0
16.056000	27.5	9.000	Off	L1	10.3	32.5	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	26.7	9.000	Off	L1	9.6	29.3	56.0
0.572000	24.4	9.000	Off	L1	9.6	21.6	46.0
0.650000	23.6	9.000	Off	L1	9.7	22.4	46.0
0.690000	24.6	9.000	Off	L1	9.7	21.4	46.0
0.726000	24.4	9.000	Off	L1	9.7	21.6	46.0
0.750000	20.4	9.000	Off	L1	9.7	25.6	46.0
1.410000	22.4	9.000	Off	L1	9.7	23.6	46.0
1.450000	22.4	9.000	Off	L1	9.7	23.6	46.0
1.484000	22.6	9.000	Off	L1	9.7	23.4	46.0
1.522000	22.3	9.000	Off	L1	9.8	23.7	46.0
1.528000	21.7	9.000	Off	L1	9.8	24.3	46.0
1.558000	21.4	9.000	Off	L1	9.8	24.6	46.0
13.542000	19.9	9.000	Off	L1	10.2	30.1	50.0
13.560000	44.7	9.000	Off	L1	10.2	5.3	50.0
14.268000	18.9	9.000	Off	L1	10.2	31.1	50.0
14.690000	18.8	9.000	Off	L1	10.2	31.2	50.0
14.826000	18.6	9.000	Off	L1	10.2	31.4	50.0
15.128000	18.3	9.000	Off	L1	10.3	31.7	50.0

1/13/2015

10:45:29

**Terminate the Antenna
Conducted Emissions (Line 1)**

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H340n
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: NFC MODE(TERMINATION)
 Operator Name: JS LEE

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG × Final Result 1-QPK × Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.152000	37.6	9.000	Off	N	9.6	28.3	65.9
0.156000	34.6	9.000	Off	N	9.6	31.1	65.7
0.346000	34.2	9.000	Off	N	9.7	24.9	59.1
0.366000	33.0	9.000	Off	N	9.7	25.6	58.6
0.370000	35.4	9.000	Off	N	9.7	23.1	58.5
0.374000	35.0	9.000	Off	N	9.7	23.4	58.4
0.920000	26.0	9.000	Off	N	9.7	30.0	56.0
1.292000	27.1	9.000	Off	N	9.8	28.9	56.0
1.488000	27.1	9.000	Off	N	9.8	28.9	56.0
1.504000	25.5	9.000	Off	N	9.8	30.5	56.0
1.530000	26.3	9.000	Off	N	9.8	29.7	56.0
1.538000	25.8	9.000	Off	N	9.8	30.2	56.0
5.688000	23.5	9.000	Off	N	9.9	36.5	60.0
5.786000	23.6	9.000	Off	N	9.9	36.4	60.0
13.900000	22.1	9.000	Off	N	10.2	37.9	60.0
14.494000	22.2	9.000	Off	N	10.2	37.8	60.0

1/13/2015

11:07:09

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
15.216000	21.8	9.000	Off	N	10.2	38.2	60.0
15.386000	21.2	9.000	Off	N	10.2	38.8	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.152000	28.0	9.000	Off	N	9.6	27.9	55.9
0.188000	23.2	9.000	Off	N	9.7	30.9	54.1
0.226000	21.6	9.000	Off	N	9.7	31.0	52.6
0.340000	26.4	9.000	Off	N	9.7	22.8	49.2
0.344000	26.1	9.000	Off	N	9.7	23.0	49.1
0.372000	29.7	9.000	Off	N	9.7	18.8	48.5
0.916000	18.7	9.000	Off	N	9.7	27.3	46.0
1.356000	16.8	9.000	Off	N	9.8	29.2	46.0
1.482000	18.3	9.000	Off	N	9.8	27.7	46.0
1.488000	18.5	9.000	Off	N	9.8	27.5	46.0
1.506000	16.2	9.000	Off	N	9.8	29.8	46.0
1.558000	17.7	9.000	Off	N	9.8	28.3	46.0
5.688000	17.7	9.000	Off	N	9.9	32.3	50.0
5.786000	17.8	9.000	Off	N	9.9	32.2	50.0
13.900000	15.4	9.000	Off	N	10.2	34.6	50.0
14.494000	15.4	9.000	Off	N	10.2	34.6	50.0
15.216000	14.5	9.000	Off	N	10.2	35.5	50.0
15.386000	14.3	9.000	Off	N	10.2	35.7	50.0

1/13/2015

11:07:09

Conducted Emissions (Line 2)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H340n
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: NFC MODE(TERMINATION)
 Operator Name: JS LEE

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG × Final Result 1-QPK × Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.152000	37.7	9.000	Off	L1	9.6	28.2	65.9
0.366000	32.8	9.000	Off	L1	9.7	25.8	58.6
0.372000	34.8	9.000	Off	L1	9.7	23.7	58.5
0.684000	35.1	9.000	Off	L1	9.7	20.9	56.0
0.688000	34.7	9.000	Off	L1	9.7	21.3	56.0
0.726000	34.5	9.000	Off	L1	9.7	21.5	56.0
1.392000	29.8	9.000	Off	L1	9.7	26.2	56.0
1.482000	33.1	9.000	Off	L1	9.7	22.9	56.0
1.486000	32.9	9.000	Off	L1	9.7	23.2	56.0
1.490000	31.8	9.000	Off	L1	9.7	24.2	56.0
1.520000	32.8	9.000	Off	L1	9.8	23.2	56.0
1.528000	31.7	9.000	Off	L1	9.8	24.3	56.0
13.654000	28.4	9.000	Off	L1	10.2	31.6	60.0
14.102000	28.6	9.000	Off	L1	10.2	31.4	60.0
14.324000	29.1	9.000	Off	L1	10.2	30.9	60.0
14.658000	29.1	9.000	Off	L1	10.2	30.9	60.0

1/13/2015

11:14:36

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
14.852000	28.9	9.000	Off	L1	10.2	31.1	60.0
15.000000	28.6	9.000	Off	L1	10.3	31.4	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	26.9	9.000	Off	L1	9.6	29.1	56.0
0.376000	27.3	9.000	Off	L1	9.7	21.1	48.4
0.570000	24.1	9.000	Off	L1	9.6	21.9	46.0
0.686000	24.3	9.000	Off	L1	9.7	21.7	46.0
0.722000	23.8	9.000	Off	L1	9.7	22.2	46.0
0.726000	24.2	9.000	Off	L1	9.7	21.8	46.0
0.880000	21.5	9.000	Off	L1	9.7	24.5	46.0
1.354000	19.3	9.000	Off	L1	9.7	26.7	46.0
1.486000	22.5	9.000	Off	L1	9.7	23.5	46.0
1.520000	22.1	9.000	Off	L1	9.8	23.9	46.0
1.524000	22.1	9.000	Off	L1	9.8	23.9	46.0
1.536000	20.5	9.000	Off	L1	9.8	25.5	46.0
13.654000	19.5	9.000	Off	L1	10.2	30.5	50.0
14.102000	19.7	9.000	Off	L1	10.2	30.3	50.0
14.490000	19.6	9.000	Off	L1	10.2	30.4	50.0
14.526000	19.5	9.000	Off	L1	10.2	30.5	50.0
14.852000	19.3	9.000	Off	L1	10.2	30.7	50.0
15.520000	18.4	9.000	Off	L1	10.3	31.6	50.0

1/13/2015

11:14:36

12. LIST OF TEST EQUIPMENT

12.1 LIST OF TEST EQUIPMENT(Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216/ LISN	01/29/2014	Annual	100073
Agilent	E4440A/ Spectrum Analyzer	04/09/2014	Annual	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	05/23/2014	Annual	MY51110063
Agilent	87300B/Directional Coupler	12/08/2014	Annual	3116A03621
ITECH	IT6720 / DC POWER SUPPLY	11/04/2014	Annual	0100021562870011 99
TESCOM	TC-3000C / BLUETOOTH TESTER	04/11/2014	Annual	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/07/2014	Annual	100422
Agilent	8493C / Attenuator(10 dB)	07/21/2014	Annual	76649

12.2 LIST OF TEST EQUIPMENT(Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Schwarzbeck	VULB 9160/ TRILOG Antenna	10/10/2014	Biennial	3368
Rohde & Schwarz	FSV40 / SPECTRUM ANALYZER	06/09/2014	Annual	1307.9002K40- 100931-NK
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	09/04/2014	Annual	10094
CERNEX	CBL18265035 / POWER AMP	07/23/2014	Annual	22966
CERNEX	CBL26405040 / POWER AMP	04/04/2014	Annual	19660
Wainwright Instrument	WHF3.0/18G-10EF / High Pass Filter	02/03/2014	Annual	F6
Wainwright Instrument	WHNX6.0/26.5G-6SS / High Pass Filter	04/09/2014	Annual	1
Wainwright Instrument	WHNX7.0/18G-8SS / High Pass Filter	04/04/2014	Annual	29
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	06/17/2014	Annual	1
TESCOM	TC-3000C / BLUETOOTH TESTER	04/11/2014	Annual	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/07/2014	Annual	100422
Rohde & Schwarz	LOOP ANTENNA	09/03/2014	Biennial	1513-175
CERNEX	CBL06185030 / POWER AMP	07/21/2014	Annual	22965
CERNEX	CBLU1183540 / POWER AMP	07/21/2014	Annual	22964