



**FCC CFR47 PART 15 SUBPART C  
INDUSTRY CANADA RSS-247 ISSUE 1**

**BLUETOOTH LOW ENERGY  
C2PC CERTIFICATION TEST REPORT**

**FOR**

**CDMA/GSM/WCDMA/LTE PHONE + BLUETOOTH, DTS/UNII a/b/g/n/ac & NFC  
MODEL NUMBER: LG-H790, LGH790, H790**

**FCC ID: ZNFH790  
IC: 2703C-H790**

**REPORT NUMBER: 15I21523-E3V1**

**ISSUE DATE: SEPTEMBER 15, 2015**

*Prepared for*  
**LG ELECTRONICS MOBILECOMM U.S.A., INC  
1000 SYLVAN AVENUE  
ENGLEWOOD CLIFFS,  
NEW JERSEY, 07632, U.S.A**

*Prepared by*  
**UL VERIFICATION SERVICES INC.  
47173 BENICIA STREET  
FREMONT, CA 94538, U.S.A.  
TEL: (510) 771-1000  
FAX: (510) 661-0888**



**NVLAP LAB CODE 200065-0**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	9/15/15	Initial Issue	H. Mustapha

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>6</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>6</i>
4.2. <i>SAMPLE CALCULATION .....</i>	<i>6</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>8</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>8</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>8</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>8</i>
5.4. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>8</i>
5.5. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>9</i>
<b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>	<b>11</b>
<b>7. SUMMARY TABLE .....</b>	<b>12</b>
<b>8. ANTENNA PORT TEST RESULTS .....</b>	<b>13</b>
8.1. <i>6 dB BANDWIDTH.....</i>	<i>13</i>
8.2. <i>99% BANDWIDTH.....</i>	<i>17</i>
8.3. <i>OUTPUT POWER.....</i>	<i>21</i>
8.4. <i>AVERAGE POWER.....</i>	<i>25</i>
8.5. <i>POWER SPECTRAL DENSITY .....</i>	<i>26</i>
8.6. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	<i>30</i>
<b>9. RADIATED TEST RESULTS.....</b>	<b>37</b>
9.1. <i>LIMITS AND PROCEDURE .....</i>	<i>37</i>
9.2. <i>TRANSMITTER ABOVE 1 GHz.....</i>	<i>38</i>
9.3. <i>WORST-CASE BELOW 1 GHz.....</i>	<i>51</i>
<b>10. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>53</b>
<b>11. SETUP PHOTOS .....</b>	<b>54</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** LG ELECTRONICS MOBILECOMM U.S.A., INC.  
**EUT DESCRIPTION:** CDMA/GSM/WCDMA/LTE PHONE + BLUETOOTH, DTS/UNII a/b/g/n/ac & NFC  
**MODEL:** LG-H790, LGH790, H790  
**SERIAL NUMBER:** Conducted (21SE0), Radiated (21SDP)  
**DATE TESTED:** AUGUST 17 – 31, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass
INDUSTRY CANADA RSS-247 Issue 1	Pass
INDUSTRY CANADA RSS-GEN Issue 4	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Verification Services Inc. By:

Tested By:

*Huda Mustapha*

*Steven Tran*

---

HUDA MUSTAPHA  
CONSUMER TECHNOLOGY DIVISION  
WiSE PROJECT LEAD  
UL VERIFICATION SERVICES INC

---

STEVEN TRAN  
CONSUMER TECHNOLOGY DIVISION  
WiSE LAB ENGINEER  
UL VERIFICATION SERVICES INC

*Dan Coronia*

---

DAN CORONIA  
CONSUMER TECHNOLOGY DIVISION  
WiSE PROJECT LEAD  
UL VERIFICATION SERVICES INC

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, and KDB 558074 D01 v03r03, ANSI C63.10-2009 for FCC and ANSI C63.10-2013 for IC, RSS-GEN Issue 4, and RSS-247 Issue 1.

### ANSI C63.10-2009 Deviation

Radiated spurious emission above 1GHz was performed with the EUT elevated at 1.5m instead of 0.8m. 1.5m is the required height in ANSI C63.10:2013 as referenced by RSS GEN issue 4.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
<input type="checkbox"/> Chamber A(IC: 2324B-1)	<input type="checkbox"/> Chamber D(IC: 2324B-4)
<input checked="" type="checkbox"/> Chamber B(IC: 2324B-2)	<input type="checkbox"/> Chamber E(IC: 2324B-5)
<input checked="" type="checkbox"/> Chamber C(IC: 2324B-3)	<input type="checkbox"/> Chamber F(IC: 2324B-6)
	<input checked="" type="checkbox"/> Chamber G(IC: 2324B-7)
	<input type="checkbox"/> Chamber H(IC: 2324B-8)

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable} \\ &\text{Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a CDMA/GSM/WCDMA/LTE PHONE + BLUETOOTH, DTS/UNII a/b/g/n/ac & NFC.

### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402-2480	BLE	1.90	1.55

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PIF (Planar Inverted F) antenna, with a maximum gain of -0.05 dBi.

### 5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1 GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.



## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	LG	MCS-N04WS	SA560000030	N/A
Earphone	LG	N/A	N/A	N/A


### I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

### TEST SETUP

EUT was set in the BLE mode to enable BLE communications.

**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/15
Spectrum Analyzer,9KHz-40GHz	HP	8564E	C00986	04/01/16
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15
Antenna, Horn, 1-18 GHz	ETS	3117	C01022	02/21/16
Antenna, Horn,18- 26 GHz	ARA	MWH-1826/B	C00946	11/12/15
Antenna, Horn, 26-40 GHz	ARA	MWH-2640	C00891	06/28/16
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	T243	03/06/16
RF Preamplifier, 1GHz - 18GHz	Miteq	NSP4000-SP2	924343	03/23/16
RF Preamplifier, 1GHz - 26.5GHz	HP	8449B	T404	06/29/16
AC Power Supply, 2,500VA 45-500Hz	Elgar-Ametek	CW2501M	F00013	CNR
RF Preamplifier, 1GHz - 40GHz	Miteq	NSP4000-SP2	C00990	08/20/15
Attenuator / Switch driver	HP	11713A	F00204	CNR
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	F00219	05/23/16
High Pass Filter 6GHz	Micro-Tronics	HPS17542	F00222	05/22/16
High Pass Filter 3GHz	Micro-Tronics	HPM17543	F00224	05/22/16

Test Software List			
Description	Manufacturer	Model	Version
Radiated Software	UL	UL EMC	Version 9.5, 07/22/14
Conducted Software	UL	UL EMC	Version 9.5, 05/17/14
CLT Software	UL	UL RF	Version 1.0, 02/02/15
Antenna Port Software	UL	UL RF	Version 2.1.1.1, 1/20/15

## 7. SUMMARY TABLE

C2PC reason: **Please see LG-H790 change note for details.**

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	RSS-247 5.2.1	Occupied Band width (6dB)	>500KHz	Conducted	Pass	0.64 MHz
2.1051, 15.247 (d)	RSS-247 5.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-49.36 dBm
15.247	RSS-247 5.4.4	TX conducted output power	<30dBm		Pass	1.9 dBm
15.247	RSS-247 5.2.2	PSD	<8dBm		Pass	-0.99 dBm
15.207 (a)	RSS-GEN 8.8	AC Power Line conducted emissions	Section 10	Radiated	Pass	See Original
15.205, 15.209	RSS-GEN 8.9/7	Radiated Spurious Emission	< 54dBuV/m		Pass	39.47 dBuV/m

## 8. ANTENNA PORT TEST RESULTS

### 8.1. 6 dB BANDWIDTH

#### LIMITS

FCC §15.247 (a) (2)

IC RSS-247 5.2.1

The minimum 6 dB bandwidth shall be at least 500 kHz.

#### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

#### RESULTS


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.640	0.5
Middle	2440	0.642	0.5
High	2480	0.647	0.5

**6 dB BANDWIDTH PLOTS**


**LOW CHANNEL**



**MID CHANNEL**



**HIGH CHANNEL**





## 8.2. 99% BANDWIDTH

### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Reference to KDB558074 D01 DTS Meas Guidance v03r03: The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

### RESULTS


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0531
Middle	2440	1.0557
High	2480	1.0546

**99% BANDWIDTH PLOTS**

**LOW CHANNEL**

Agilent 14:59:13 Aug 22, 2015 <span style="float: right;">L</span>		<b>Measure</b>				
Ch Freq 2.402 GHz <span style="float: right;">Trig Free</span>		<b>Meas Off</b>				
Occupied Bandwidth <span style="float: right;">Averages: 20</span>		<b>Channel Power</b>				
APv3.3(080515),TC, Conducted B Ref 20 dBm <span style="float: right;">Atten 20 dB</span>		<b>Occupied BW</b>				
#Samp Log 10 dB/ Offst 10.9 dB		<b>ACP</b>				
		<b>Multi Carrier Power</b>				
Center 2.402 000 GHz <span style="float: right;">Span 2 MHz</span> #Res BW 18 kHz <span style="float: right;">#VBW 56 kHz</span> <span style="float: right;">#Sweep 100 ms (1001 pts)</span>		<b>Power Stat CCDF</b>				
<table border="1" style="width: 100%;"> <tr> <td style="text-align: left;"> <b>Occupied Bandwidth</b>                              1.0531 MHz                         </td> <td style="text-align: right;"> <b>Occ BW % Pwr</b> 99.00 %  <b>x dB</b> -26.00 dB                         </td> </tr> <tr> <td> <b>Transmit Freq Error</b> 12.337 kHz  <b>x dB Bandwidth</b> 1.241 MHz*                         </td> <td></td> </tr> </table>		<b>Occupied Bandwidth</b> 1.0531 MHz	<b>Occ BW % Pwr</b> 99.00 % <b>x dB</b> -26.00 dB	<b>Transmit Freq Error</b> 12.337 kHz <b>x dB Bandwidth</b> 1.241 MHz*		<b>More</b> 1 of 2
<b>Occupied Bandwidth</b> 1.0531 MHz	<b>Occ BW % Pwr</b> 99.00 % <b>x dB</b> -26.00 dB					
<b>Transmit Freq Error</b> 12.337 kHz <b>x dB Bandwidth</b> 1.241 MHz*						
Copyright 2000-2011 Agilent Technologies						

**MID CHANNEL**

* Agilent 14:53:19 Aug 22, 2015		L	Measure
Ch Freq 2.44 GHz		Trig Free	Meas Off
Occupied Bandwidth		Averages: 20	Channel Power
APv3.3(080515),TC, Conducted B			Occupied BW
Ref 20 dBm Atten 20 dB			ACP
#Samp			Multi Carrier Power
Log	Center 2.440 000 GHz		Power Stat
10	#Res BW 18 kHz #VBW 56 kHz #Sweep 100 ms (1001 pts)		CCDF
dB/	Occupied Bandwidth		More
Offst	1.0557 MHz		
10.9	Occ BW % Pwr 99.00 %		1 of 2
dB	x dB -26.00 dB		
	Transmit Freq Error 13.913 kHz		
	x dB Bandwidth 1.222 MHz*		
Copyright 2000-2011 Agilent Technologies			

**HIGH CHANNEL**

Agilent 15:07:23 Aug 22, 2015 <span style="float: right;">L</span>		<b>Measure</b>
<b>Ch Freq</b> 2.48 GHz <span style="float: right;"><b>Trig</b> Free</span>		<b>Meas Off</b>
Occupied Bandwidth <span style="float: right;">Averages: 20</span>		<b>Channel Power</b>
APv3.3(080515),TC, Conducted B Ref 20 dBm Atten 20 dB		<b>Occupied BW</b>
#Samp Log 10 dB/ Offst 10.9 dB		<b>ACP</b>
		<b>Multi Carrier Power</b>
Center 2.480 000 GHz <span style="float: right;">Span 2 MHz</span> #Res BW 13 kHz <span style="margin-left: 100px;">#VBW 39 kHz</span> <span style="margin-left: 100px;">#Sweep 100 ms (1001 pts)</span>		<b>Power Stat CCDF</b>
<b>Occupied Bandwidth</b> <span style="float: right;"><b>Occ BW % Pwr</b> 99.00 %</span> <span style="margin-left: 100px;">1.0546 MHz</span> <span style="margin-left: 100px;"><b>x dB</b> -26.00 dB</span>		<b>More</b>
<b>Transmit Freq Error</b> 14.354 kHz <b>x dB Bandwidth</b> 1.244 MHz*		1 of 2
Copyright 2000-2011 Agilent Technologies		

### 8.3. OUTPUT POWER

#### LIMITS

FCC §15.247 (b)

IC RSS-247 5.4.4

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

#### TEST PROCEDURE


Peak power is measured using KDB558074 D01 DTS Meas Guidance v03r03 utilizing spectrum analyzer.

#### RESULTS


Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-0.56	30	-30.560
Middle	2440	1.90	30	-28.100
High	2480	0.52	30	-29.480

**OUTPUT POWER PLOTS**


**LOW CHANNEL**



**MID CHANNEL**



### HIGH CHANNEL





## 8.4. AVERAGE POWER

### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to a power meter.

### RESULTS

The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	-1.38
Middle	2440	1.12
High	2480	-0.21

## 8.5. POWER SPECTRAL DENSITY

### LIMITS

FCC §15.247 (e)

IC RSS-247 5.2.2

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST PROCEDURE


Power Spectral Density was performed utilizing the “Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v03r03.

### RESULTS


Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-1.04	8	-9.04
Middle	2440	-0.99	8	-8.99
High	2480	-3.24	8	-11.24

**POWER SPECTRAL DENSITY PLOTS**


**LOW CHANNEL**



**MID CHANNEL**



### HIGH CHANNEL



## **8.6. CONDUCTED SPURIOUS EMISSIONS**

### **LIMITS**

FCC §15.247 (d)

IC RSS-247 5.5

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.

### **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


### **RESULTS**

**SPURIOUS EMISSIONS, LOW CHANNEL**

**LOW CHANNEL BANDEDGE**




**LOW CHANNEL SPURIOUS**






**SPURIOUS EMISSIONS, MID CHANNEL**

**MID CHANNEL REFERENCE**




**MID CHANNEL SPURIOUS**




**SPURIOUS EMISSIONS, HIGH CHANNEL**

**HIGH CHANNEL BANDEDGE**



### HIGH CHANNEL SPURIOUS



## 9. RADIATED TEST RESULTS

### 9.1. LIMITS AND PROCEDURE LIMITS

FCC §15.205 and §15.209

IC RSS-GEN Clause 8.9 (Transmitter)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

### TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor =  $10 \log (1/x)$ . For this sample:  $DCF = 10 \log (1/0.647) = 1.89 \text{ dB}$


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

## 9.2. TRANSMITTER ABOVE 1 GHz RESTRICTED BANDEGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



### HORIZONTAL DATA

#### Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.382	42.08	PK	32	-22.4	0	51.68	-	-	74	-22.32	306	301	H
4	* 2.386	30.75	RMS	32	-22.4	1.89	42.24	54	-11.76	-	-	306	301	H
1	* 2.39	40.04	PK	32	-22.4	0	49.64	-	-	74	-24.36	306	301	H
3	* 2.39	30.57	RMS	32	-22.4	1.89	42.06	54	-11.94	-	-	306	301	H

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK - Peak detector

RMS - RMS detection

**VERTICAL PEAK AND AVERAGE PLOT**



**VERTICAL DATA**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fitter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.356	42.5	PK	31.8	-22.4	0	51.9	-	-	74	-22.1	270	374	V
4	* 2.386	30.65	RMS	32	-22.4	1.89	42.14	54	-11.86	-	-	270	374	V
1	* 2.39	39.3	PK	32	-22.4	0	48.9	-	-	74	-25.1	270	374	V
3	* 2.39	30.37	RMS	32	-22.4	1.89	41.86	54	-12.14	-	-	270	374	V


\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK - Peak detector

RMS - RMS detection

**AUTHORIZED BANDEDGE (HIGH CHANNEL)**

**HORIZONTAL PEAK AND AVERAGE PLOT**



**HORIZONTAL DATA**

**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fitter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.26	PK	32.3	-22.1	0	50.46	-	-	74	-23.54	302	380	H
2	* 2.484	42.84	PK	32.3	-22.1	0	53.04	-	-	74	-20.96	302	380	H
3	* 2.484	30.48	RMS	32.3	-22.1	1.89	42.57	54	-11.43	-	-	302	380	H
4	2.556	30.81	RMS	32.4	-22	1.89	43.1	54	-10.9	-	-	302	380	H


\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK - Peak detector

RMS - RMS detection



**VERTICAL PEAK AND AVERAGE PLOT**



**VERTICAL DATA**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	39.62	PK	32.3	-22.1	0	49.82	-	-	74	-24.18	268	383	V
3	* 2.484	30.33	RMS	32.3	-22.1	1.89	42.42	54	-11.58	-	-	268	383	V
4	2.53	30.74	RMS	32.4	-22	1.89	43.03	54	-10.97	-	-	268	383	V
2	2.543	42.5	PK	32.4	-21.9	0	53	-	-	74	-21	268	383	V


\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK - Peak detector

RMS - RMS detection


**HARMONICS AND SPURIOUS EMISSIONS**

**LOW CHANNEL HORIZONTAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### LOW CHANNEL DATA

#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.297	33.96	PK	29.9	-23.2	0	40.66	-	-	74	-33.34	0-360	200	H
2	* 4.211	31.21	PK	33.3	-29.9	0	34.61	-	-	74	-39.39	0-360	100	H
5	* 4.776	31.53	PK	34	-29.9	0	35.63	-	-	74	-38.37	0-360	200	V
6	7.892	28.98	PK	35.8	-26	0	38.78	-	-	-	-	0-360	200	V
3	14.851	30.1	PK	39.8	-25.7	0	44.2	-	-	-	-	0-360	200	H
4	17.66	26.44	PK	41.4	-20.7	0	47.14	-	-	-	-	0-360	200	H

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK - Peak detector

#### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/ Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 1.296	42.55	PK1	29.9	-23.2	0	49.25	-	-	74	-24.75	11	150	H
* 1.297	30.88	AD1	29.9	-23.2	1.89	39.47	54	-14.53	-	-	11	150	H
* 4.211	40.44	PK1	33.3	-29.9	0	43.84	-	-	74	-30.16	54	118	H
* 4.212	28.48	AD1	33.3	-29.9	1.89	33.77	54	-20.23	-	-	54	118	H
* 4.775	40.84	PK1	34	-29.9	0	44.94	-	-	74	-29.06	320	200	V
* 4.776	29.01	AD1	34	-29.9	1.89	35	54	-19	-	-	320	200	V
7.89	37.84	PK1	35.8	-26	0	47.64	-	-	-	-	197	241	V
14.85	39.15	PK1	39.8	-25.7	0	53.25	-	-	-	-	136	200	H
17.66	35.33	PK1	41.4	-20.7	0	56.03	-	-	-	-	104	174	H

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK1 - KDB789033 Method: Peak


AD1 - KDB789033 Method: AD Primary Power Average

### MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### MID CHANNEL DATA

#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 9.395	28.39	PK	36.4	-24.1	0	40.69	-	-	74	-33.31	0-360	200	H
1	6.186	31.41	PK	35.3	-29.3	0	37.41	-	-	-	-	0-360	100	H
5	6.619	30.06	PK	35.6	-27.8	0	37.86	-	-	-	-	0-360	200	V
3	12.793	29.67	PK	39.1	-25.7	0	43.07	-	-	-	-	0-360	100	H
6	17.217	27.71	PK	41.3	-22.4	0	46.61	-	-	-	-	0-360	100	V
4	17.661	25.95	PK	41.4	-20.7	0	46.65	-	-	-	-	0-360	100	H

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK - Peak detector

#### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/ Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 9.396	37.27	PK1	36.4	-24.1	0	49.57	-	-	74	-24.43	285	240	H
* 9.396	25.09	AD1	36.4	-24.1	1.89	39.28	54	-14.72	-	-	285	240	H
6.187	40.34	PK1	35.3	-29.3	0	46.34	-	-	-	-	344	109	H
6.62	39.4	PK1	35.6	-27.9	0	47.1	-	-	-	-	175	200	V
12.794	37.58	PK1	39.1	-25.7	0	50.98	-	-	-	-	222	130	H
17.217	36.03	PK1	41.3	-22.4	0	54.93	-	-	-	-	175	100	V
17.659	35.92	PK1	41.4	-20.7	0	56.62	-	-	-	-	235	100	H

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average


### HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



### HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### HIGH CHANNEL DATA

#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	* 4.946	31.7	PK	34	-30	0	35.7	-	-	74	-38.3	0-360	100	V
1	2	33.62	PK	31.5	-22.5	0	42.62	-	-	-	-	0-360	100	H
2	7.878	29.43	PK	35.8	-26.2	0	39.03	-	-	-	-	0-360	100	H
3	10.424	27.81	PK	37.3	-23.4	0	41.71	-	-	-	-	0-360	100	H
4	16.374	28.52	PK	40.7	-23.9	0	45.32	-	-	-	-	0-360	100	H
6	17.646	26.49	PK	41.4	-21.1	0	46.79	-	-	-	-	0-360	100	V

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

PK - Peak detector

#### Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/ Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.945	40.27	PK1	34	-29.9	0	44.37	-	-	74	-29.63	56	110	V
* 4.946	29.2	AD1	34	-30	1.89	35.09	54	-18.91	-	-	56	110	V
1.999	42.6	PK1	31.5	-22.5	0	51.6	-	-	-	-	340	107	H
7.879	37.61	PK1	35.8	-26.2	0	47.21	-	-	-	-	287	127	H
10.425	36.12	PK1	37.3	-23.4	0	50.02	-	-	-	-	220	148	H
16.374	37.44	PK1	40.7	-23.9	0	54.24	-	-	-	-	98	100	H
17.647	36.02	PK1	41.4	-21	0	56.42	-	-	-	-	131	100	V

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band


PK1 - KDB789033 Method: Peak

AD1 - KDB789033 Method: AD Primary Power Average


### 9.3. WORST-CASE BELOW 1 GHz

#### SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

#### HORIZONTAL PLOT



### VERTICAL PLOT



### BELOW 1 GHz TABLE

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPK Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 73.945	42.98	Pk	8	-28.4	22.58	40	-17.42	0-360	101	V
1	54.1825	52.13	Pk	7.4	-28.5	31.03	40	-8.97	0-360	101	V
6	92.5175	37.05	Pk	8.3	-28.2	17.15	43.52	-26.37	0-360	101	V
3	196.515	46.8	Pk	12.3	-27.1	32	43.52	-11.52	0-360	101	H
4	213.7	50.84	Pk	10.5	-26.9	34.44	43.52	-9.08	0-360	101	H
5	296.2	40.8	Pk	13.3	-26.2	27.9	46.02	-18.12	0-360	101	H

\* - indicates frequency in CFR15.205/IC8.10 Restricted Band

Pk - Peak detector

## 10. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

RSS-Gen 8.8

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### TEST PROCEDURE

ANSI C63.10

### RESULTS

See original report