



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
http://www.pctestlab.com



## MEASUREMENT REPORT FCC Part 22, 24, & 27

**Applicant Name:**  
LG Electronics MobileComm U.S.A  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States

**Date of Testing:**  
12/27/2016 - 2/15/2017  
**Test Site/Location:**  
PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
1M1701180032-02-R2.ZNF


<b>FCC ID:</b>	<b>ZNFH871</b>
<b>APPLICANT:</b>	<b>LG ELECTRONICS MOBILECOMM U.S.A</b>

**Application Type:** Certification  
**Model:** LG-H871  
**Additional Model(s):** LGH871, H871, LG-H872, LGH872, H872, LG-H873, LGH873, H873, LG-H872PR, LGH872PR, H872PR  
**EUT Type:** Portable Handset  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part(s):** §2 §22(H) §24(E) §27(L)  
**Test Procedure(s):** ANSI/TIA-603-D-2010, KDB 971168 D01 v02r02, KDB 648474 D03 v01r04  
**Test Device Serial No.:** [S/N: 06634, 06519, 06527, 06535, 08416]



This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1701180032-02-R2.ZNF) supersedes and replaces the previously issued test report (S/N: 1M1701180032-02-R1.ZNF) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



  
 Randy Ortanez  
 President




<b>FCC ID:</b> ZNFH871		<b>FCC Pt. 22, 24, &amp; 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1701180032-02-R2.ZNF	<b>Test Dates:</b> 12/27/2016 - 2/15/2017	<b>EUT Type:</b> Portable Handset	Page 1 of 83	

# T A B L E O F C O N T E N T S


FCC PART 22, 24, & 27 MEASUREMENT REPORT .....		3
1.0 INTRODUCTION .....		5
1.1 Scope.....		5
1.2 Testing Facility.....		5
2.0 PRODUCT INFORMATION.....		6
2.1 Equipment Description .....		6
2.2 Device Capabilities .....		6
2.3 Test Configuration.....		6
2.4 EMI Suppression Device(s)/Modifications.....		6
3.0 DESCRIPTION OF TESTS .....		7
3.1 Evaluation Procedure.....		7
3.2 Cellular - Base Frequency Blocks .....		7
3.3 Cellular - Mobile Frequency Blocks.....		7
3.4 PCS - Base Frequency Blocks.....		7
3.5 PCS - Mobile Frequency Blocks .....		8
3.6 AWS - Base Frequency Blocks .....		8
3.7 AWS - Mobile Frequency Blocks.....		8
3.8 Radiated Measurements .....		9
4.0 MEASUREMENT UNCERTAINTY .....		10
5.0 TEST EQUIPMENT CALIBRATION DATA .....		11
6.0 SAMPLE CALCULATIONS .....		12
7.0 TEST RESULTS .....		13
7.1 Summary.....		13
7.2 Occupied Bandwidth .....		14
7.3 Spurious and Harmonic Emissions at Antenna Terminal.....		19
7.4 Band Edge Emissions at Antenna Terminal.....		43
7.5 Peak-Average Ratio.....		52
7.6 Radiated Power (ERP/EIRP) .....		55
7.7 Radiated Spurious Emissions Measurements.....		60
7.8 Frequency Stability / Temperature Variation.....		72
8.0 CONCLUSION.....		83

<b>FCC ID:</b> ZNFH871		<b>FCC Pt. 22, 24, &amp; 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1701180032-02-R2.ZNF	<b>Test Dates:</b> 12/27/2016 - 2/15/2017	<b>EUT Type:</b> Portable Handset	Page 2 of 83	



# MEASUREMENT REPORT

## FCC Part 22, 24, & 27





### §2.1033 General Information



**APPLICANT:** LG Electronics MobileComm U.S.A  
**APPLICANT ADDRESS:** 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA  
**FCC RULE PART(S):** §2 §22(H) §24(E) §27(L)  
**BASE MODEL:** LG-H871  
**FCC ID:** ZNFH871  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**MODE:** GSM / GPRS / EDGE / WCDMA  
**FREQUENCY TOLERANCE:** ±0.00025 % (2.5 ppm)  
**Test Device Serial No.:** 06634, 06519, 06527,  Production  Pre-Production  Engineering  
 06535, 08416  
**DATE(S) OF TEST:** 12/27/2016 - 2/15/2017  
**TEST REPORT S/N:** 1M1701180032-02-R2.ZNF


### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 3 of 83	





## MEASUREMENT REPORT

### FCC Part 22, 24, & 27



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP/EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	
GPRS850	22H	824.2 - 848.8	0.659	28.19	246KGXW
EDGE850	22H	824.2 - 848.8	0.274	24.38	243KG7W
WCDMA850	22H	826.4 - 846.6	0.062	17.93	4M14F9W
WCDMA1700	27	1712.4 - 1752.6	0.114	20.58	4M14F9W
GPRS1900	24E	1850.2 - 1909.8	0.881	29.45	243KGXW
EDGE1900	24E	1850.2 - 1909.8	0.424	26.27	242KG7W
WCDMA1900	24E	1852.4 - 1907.6	0.203	23.07	4M15F9W

#### EUT Overview

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 4 of 83	

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.






Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 5 of 83	

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFH871**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC



### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v02r02. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on a certified wireless charging pad (WCP) while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 6 of 83

### 3.0 DESCRIPTION OF TESTS


#### 3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-D-2010) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v02r02) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

#### 3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A\* Low + A)


BLOCK 3: 890 – 891.5 MHz (A\* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B\*)

#### 3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A\* Low + A)


BLOCK 3: 845 – 846.5 MHz (A\* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B\*)

#### 3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)



BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 7 of 83	

### 3.5 PCS - Mobile Frequency Blocks


§24.229



- BLOCK 1: 1850 – 1865 MHz (A)
- BLOCK 2: 1865 – 1870 MHz (D)
- BLOCK 3: 1870 – 1885 MHz (B)
- BLOCK 4: 1885 – 1890 MHz (E)
- BLOCK 5: 1890 – 1895 MHz (F)
- BLOCK 6: 1895 – 1910 MHz (C)

### 3.6 AWS - Base Frequency Blocks


§27.5(h)





- BLOCK 1: 2110 – 2120 MHz (A)
- BLOCK 2: 2120 – 2130 MHz (B)
- BLOCK 3: 2130 – 2135 MHz (C)
- BLOCK 4: 2135 – 2140 MHz (D)
- BLOCK 5: 2140 – 2145 MHz (E)
- BLOCK 6: 2145 – 2155 MHz (F)

### 3.7 AWS - Mobile Frequency Blocks

§27.5(h)



- BLOCK 1: 1710 – 1720 MHz (A)
- BLOCK 2: 1720 – 1730 MHz (B)
- BLOCK 3: 1730 – 1735 MHz (C)
- BLOCK 4: 1735 – 1740 MHz (D)
- BLOCK 5: 1740 – 1745 MHz (E)
- BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 8 of 83	



### 3.8 Radiated Measurements

**§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(d)(10) §27.53(h)**

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.



The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .



Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/ITA-603-D-2010.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 9 of 83	

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 10 of 83	

## 5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX3	Licensed Transmitter Cable Set	7/12/2016	Annual	7/12/2017	N/A
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/1/2016	Annual	3/1/2017	MY52350166
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	2/26/2016	Biennial	2/26/2018	441128
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
Espec	ESX-2CA	Environmental Chamber	3/4/2016	Annual	3/4/2017	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/26/2016	Biennial	4/26/2018	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	8/28/2016	Biennial	8/28/2018	135427
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128338
K & L	11SH10-3075/U18000	High Pass Filter	7/11/2016	Annual	7/11/2017	11SH10-3075/U18000-2
K & L	13SH10-1000/U1000	N Type High Pass Filter	7/6/2016	Annual	7/6/2017	13SH10-1000/U1000-1
Mini-Circuits	PWR-SENS-4RMS	USB Power Sensor	3/4/2016	Annual	3/7/2017	11210140001
Mini-Circuits	SSG-4000HP	USB Synthesized Signal Generator	N/A			11208010032
Mini-Circuits	TVA-11-422	RF Power Amp	N/A			QA1303002
PCTEST	-	EMC Switch System	7/11/2016	Annual	7/11/2017	NM1
PCTEST	-	EMC Switch System	7/6/2016	Annual	7/6/2017	NM2
Rohde & Schwarz	CMU200	Base Station Simulator	6/2/2016	Annual	6/2/2017	109892
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/15/2016	Annual	7/15/2017	100348
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/7/2016	Annual	3/7/2017	100040
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Schwarzbeck	VULB-9161SE	Trilog Super Broadband Test Antenna	11/13/2015	Biennial	11/13/2017	9161-4075
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

**Table 5-1. Test Equipment**

**Notes:**

1. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 11 of 83	

## 6.0 SAMPLE CALCULATIONS

### GPRS Emission Designator

**Emission Designator = 250KGXW**

GPRS BW = 250 kHz  
 G = Phase Modulation  
 X = Cases not otherwise covered  
 W = Combination (Audio/Data)

### EDGE Emission Designator

**Emission Designator = 250KG7W**

EDGE BW = 250 kHz  
 G = Phase Modulation  
 7 = Quantized/Digital Info  
 W = Combination (Audio/Data)

### WCDMA Emission Designator



**Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz  
 F = Frequency Modulation  
 9 = Composite Digital Info  
 W = Combination (Audio/Data)

### Spurious Radiated Emission

**Example: Spurious emission at 3700.40 MHz**

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was 25.50 dBm so this harmonic was  $25.50$  dBm  $- (-24.80) = 50.3$  dBc.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 12 of 83	

## 7.0 TEST RESULTS

### 7.1 Summary



Company Name: LG Electronics MobileComm U.S.A  
 FCC ID: ZNFH871  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): GSM / GPRS / EDGE / WCDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	Conducted Band Edge / Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a.2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d.4)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	Radiated Spurious Emissions	> 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions		PASS	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.7.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 13 of 83	

## 7.2 Occupied Bandwidth

### §2.1049

#### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Procedure Used


KDB 971168 D01 v02r02 – Section 4.2

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

#### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-1. Test Instrument & Measurement Setup**

#### Test Notes

None.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 14 of 83	




Plot 7-1. Occupied Bandwidth Plot (Cellular GPRS Mode – Ch. 190)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 15 of 83




Plot 7-3. Occupied Bandwidth Plot (PCS GPRS Mode – Ch. 661)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 16 of 83






Plot 7-5. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4183)



Plot 7-6. Occupied Bandwidth Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 17 of 83



Plot 7-7. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 18 of 83

### 7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h)

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

#### Test Procedure Used


KDB 971168 D01 v02r02 – Section 6.0

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

#### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**


#### Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24, Part 27. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 19 of 83	




Plot 7-8. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)




Plot 7-9. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 20 of 83




**Plot 7-10. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 128)**




**Plot 7-11. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 21 of 83




Plot 7-12. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)




Plot 7-13. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 190)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 22 of 83	




**Plot 7-14. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)**




**Plot 7-15. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 23 of 83	




Plot 7-16. Conducted Spurious Plot (Cellular GPRS Mode – Ch. 251)




Plot 7-17. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 24 of 83








**Plot 7-18. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)**




**Plot 7-19. Conducted Spurious Plot (PCS GPRS Mode – Ch. 512)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 25 of 83




Plot 7-20. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)




Plot 7-21. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 26 of 83




Plot 7-22. Conducted Spurious Plot (PCS GPRS Mode – Ch. 661)




Plot 7-23. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 27 of 83




**Plot 7-24. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)**




**Plot 7-25. Conducted Spurious Plot (PCS GPRS Mode – Ch. 810)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 28 of 83




Plot 7-26. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-27. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)



FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 29 of 83	




**Plot 7-28. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)**




**Plot 7-29. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)**



FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 30 of 83




**Plot 7-30. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)**




**Plot 7-31. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 31 of 83




Plot 7-32. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-33. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 32 of 83








**Plot 7-34. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)**




**Plot 7-35. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)**



FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 33 of 83




**Plot 7-36. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)**




**Plot 7-37. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 34 of 83	




Plot 7-38. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-39. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 35 of 83	




**Plot 7-40. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)**




**Plot 7-41. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 36 of 83




Plot 7-42. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)




Plot 7-43. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1513)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 37 of 83




Plot 7-44. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-45. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)



FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 38 of 83




**Plot 7-46. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)**




**Plot 7-47. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 39 of 83




**Plot 7-48. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)**




**Plot 7-49. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 40 of 83	






Plot 7-50. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)





Plot 7-51. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 41 of 83	



**Plot 7-52. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 42 of 83	

## 7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h)

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

*The minimum permissible attenuation level of any spurious emission is  $43 + \log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.*

### Test Procedure Used


KDB 971168 D01 v02r02 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq$  1% of the emission bandwidth
4. VBW  $\geq$  3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq$  2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**


### Test Notes

Per 22.917(b), 24.238(b), 27.53(h)(3), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 43 of 83	




Plot 7-53. Band Edge Plot (Cellular GPRS Mode – Ch. 128)




Plot 7-54. Band Edge Plot (Cellular GPRS Mode – Ch. 251)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 44 of 83




Plot 7-55. Band Edge Plot (PCS GPRS Mode – Ch. 512)




Plot 7-56. 4MHz Span Plot (PCS GPRS Mode – Ch. 512)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 45 of 83



Plot 7-57. Band Edge Plot (PCS GPRS Mode – Ch. 810)



Plot 7-58. 4MHz Span Plot (PCS GPRS Mode – Ch. 810)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 46 of 83	




Plot 7-59. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-60. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)



FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 47 of 83	




Plot 7-61. Band Edge Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-62. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 48 of 83






Plot 7-63. Band Edge Plot (AWS WCDMA Mode – Ch. 1513)




Plot 7-64. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1513)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 49 of 83	



Plot 7-65. Band Edge Plot (PCS WCDMA Mode – Ch. 9262)



Plot 7-66. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 50 of 83



Plot 7-67. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)



Plot 7-68. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 51 of 83

## 7.5 Peak-Average Ratio

### §24.232(d)

#### Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

#### Test Procedure Used

KDB 971168 D01 v02r02 – Section 5.7.1

#### Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.







Figure 7-4. Test Instrument & Measurement Setup


#### Test Notes

None

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 52 of 83	




Plot 7-69. Peak-Average Ratio Plot (PCS GPRS Mode – Ch. 661)



Plot 7-70. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 53 of 83	



**Plot 7-71. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 54 of 83

## 7.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c) 27.50(d.4)

### Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.



### Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".  
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize


FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 55 of 83	

### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Radiated Test Setup <1GHz**





**Figure 7-6. Radiated Test Setup >1GHz**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 56 of 83	



**Test Notes**

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 57 of 83

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.20	GPRS850	H	203	85	22.70	5.49	28.19	0.659	38.45	-10.26
836.60	GPRS850	H	100	94	22.52	5.13	27.65	0.583	38.45	-10.80
848.80	GPRS850	H	100	86	22.60	4.68	27.28	0.535	38.45	-11.17
824.20	GPRS850	V	100	171	21.60	5.36	26.96	0.496	38.45	-11.49
824.20	EDGE850	H	203	85	18.89	5.49	24.38	0.274	38.45	-14.07
824.20	GPRS850 (WCP)	H	113	51	21.08	5.49	26.57	0.454	38.45	-11.88



**Table 7-2. ERP (Cellular GPRS/EDGE)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Positioner Azimuth [degree]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBd]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	7	81	18.58	-0.65	17.93	0.062	38.45	-20.52
836.60	WCDMA850	H	5	70	17.78	-0.65	17.13	0.052	38.45	-21.32
846.60	WCDMA850	H	11	76	17.53	-0.65	16.88	0.049	38.45	-21.57
826.40	WCDMA850	V	39	121	16.16	-0.65	15.51	0.036	38.45	-22.94
826.40	WCDMA850 (WCP)	H	15	67	17.52	-0.65	16.87	0.049	38.45	-21.58

**Table 7-3. ERP (Cellular WCDMA)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Positioner Azimuth [degree]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	H	0	60	14.84	5.55	20.39	0.109	30.00	-9.61
1732.60	WCDMA1700	H	0	53	15.05	5.41	20.46	0.111	30.00	-9.54
1752.60	WCDMA1700	H	0	55	15.31	5.27	20.58	0.114	30.00	-9.42
1752.60	WCDMA1700	V	0	167	14.04	5.19	19.23	0.084	30.00	-10.77
1752.60	WCDMA1700 (WCP)	H	0	67	14.71	5.27	19.98	0.100	30.00	-10.02

**Table 7-4. EIRP (AWS WCDMA)**



FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 58 of 83	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Positioner Azimuth [degree]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	H	343	209	24.63	4.82	29.45	0.881	33.01	-3.56
1880.00	GPRS1900	H	340	205	24.02	4.74	28.76	0.752	33.01	-4.25
1909.80	GPRS1900	H	340	205	23.39	4.68	28.07	0.641	33.01	-4.94
1850.20	GPRS1900	V	51	161	22.66	4.79	27.45	0.556	33.01	-5.56
1850.20	EDGE1900	H	343	209	21.45	4.82	26.27	0.424	33.01	-6.74
1850.20	GPRS1900 (WCP)	H	337	196	23.37	4.82	28.19	0.659	33.01	-4.82

**Table 7-5. EIRP (PCS GPRS/EDGE)**

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Positioner Azimuth [degree]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	0	229	18.05	4.81	22.86	0.193	33.01	-10.15
1880.00	WCDMA1900	H	0	220	18.33	4.74	23.07	0.203	33.01	-9.94
1907.60	WCDMA1900	H	0	231	18.09	4.68	22.78	0.189	33.01	-10.23
1880.00	WCDMA1900	V	133	184	16.97	4.84	21.81	0.152	33.01	-11.20
1880.00	WCDMA1900 (WCP)	H	0	225	18.00	4.74	22.74	0.188	33.01	-10.27

**Table 7-6. EIRP (PCS WCDMA)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 59 of 83	

## 7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) 24.238(a) 27.53(h)

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.



### Test Procedures Used

KDB 971168 D01 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 60 of 83	

## Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-7. Test Instrument & Measurement Setup**

## Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 5) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 6) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 7) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 61 of 83	

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MEASURED OUTPUT POWER: 28.19 dBm = 0.659 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  41.19 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1648.40	H	105	202	-46.32	6.30	-40.02	68.2
2472.60	H	204	88	-33.17	6.85	-26.32	54.5
3296.80	H	100	250	-60.31	7.12	-53.19	81.4
4121.00	H	143	288	-54.38	7.67	-46.71	74.9
4945.20	H	-	-	-65.11	9.13	-55.98	84.2
5769.40	H	100	352	-54.34	9.29	-45.05	73.2
6593.60	H	100	111	-56.07	9.17	-46.90	75.1
7417.80	H	100	127	-47.71	8.76	-38.96	67.1
8242.00	H	100	309	-55.15	9.54	-45.61	73.8

**Table 7-7. Radiated Spurious Data (Cellular GPRS Mode – Ch. 128)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MEASURED OUTPUT POWER: 27.65 dBm = 0.583 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  40.65 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	111	125	-47.31	6.21	-41.10	68.8
2509.80	H	100	261	-30.06	6.86	-23.20	50.9
3346.40	H	100	110	-59.69	7.26	-52.43	80.1
4183.00	H	105	162	-63.50	8.07	-55.43	83.1
5019.60	H	-	-	-64.50	9.00	-55.50	83.2
5856.20	H	-	-	-63.50	9.31	-54.20	81.8
6692.80	H	100	159	-52.26	8.77	-43.49	71.1
7529.40	H	100	26	-56.35	9.10	-47.25	74.9
8366.00	H	100	102	-55.59	9.54	-46.04	73.7

**Table 7-8. Radiated Spurious Data (Cellular GPRS Mode – Ch. 190)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 62 of 83	

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MEASURED OUTPUT POWER: 27.28 dBm = 0.535 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  40.28 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1697.60	H	121	356	-47.23	6.12	-41.12	68.4
2546.40	H	100	121	-44.60	6.97	-37.63	64.9
3395.20	H	100	245	-59.05	7.41	-51.64	78.9
4244.00	H	134	44	-62.53	8.39	-54.13	81.4
5092.80	H	-	-	-64.22	8.84	-55.38	82.7
5941.60	H	-	-	-63.31	9.23	-54.08	81.4
6790.40	H	100	102	-54.54	8.61	-45.93	73.2
7639.20	H	100	68	-55.40	9.35	-46.05	73.3
8488.00	H	100	226	-53.51	9.46	-44.04	71.3

**Table 7-9. Radiated Spurious Data (Cellular GPRS Mode – Ch. 251)**

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MEASURED OUTPUT POWER: 26.57 dBm = 0.454 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  39.57 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1648.40	H	167	274	-43.90	6.30	-37.60	64.2
2472.60	H	202	80	-44.99	6.85	-38.14	64.7
3296.80	H	100	178	-61.35	7.12	-54.23	80.8
4121.00	H	197	293	-64.48	7.67	-56.81	83.4
4945.20	H	-	-	-65.11	9.13	-55.98	82.5
5769.40	H	-	-	-62.31	9.29	-53.02	79.6
6593.60	H	103	358	-57.18	9.17	-48.01	74.6
7417.80	H	132	334	-53.53	8.76	-44.78	71.3
8242.00	H	162	62	-55.95	9.54	-46.41	73.0

**Table 7-10. Radiated Spurious Data with WCP (Cellular GPRS Mode – Ch. 128)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 63 of 83	

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MEASURED OUTPUT POWER: 17.93 dBm = 0.062 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  30.93 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1652.80	H	121	87	-71.85	6.28	-65.56	83.5
2479.20	H	-	-	-71.21	6.84	-64.37	82.3
3305.60	H	-	-	-67.81	7.14	-60.67	78.6

**Table 7-11. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)**

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 4183  
 MEASURED OUTPUT POWER: 17.13 dBm = 0.052 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  30.13 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1673.20	H	208	80	-74.02	6.21	-67.81	84.9
2509.80	H	116	264	-67.88	6.86	-61.02	78.2
3346.40	H	-	-	-68.07	7.26	-60.81	77.9

**Table 7-12. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 64 of 83	



OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MEASURED OUTPUT POWER: 16.88 dBm = 0.049 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  29.88 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1693.20	H	-	-	-73.02	6.13	-66.88	83.8
2539.80	H	165	106	-68.56	6.95	-61.62	78.5
3386.40	H	-	-	-67.63	7.38	-60.25	77.1

**Table 7-13. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)**

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MEASURED OUTPUT POWER: 16.87 dBm = 0.049 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  29.87 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	[dBc]
1652.80	H	114	110	-72.90	6.28	-66.61	83.5
2479.20	H	-	-	-70.91	6.84	-64.07	80.9
3305.60	H	-	-	-67.81	7.14	-60.67	77.5

**Table 7-14. Radiated Spurious Data with WCP (Cellular WCDMA Mode – Ch. 4132)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 65 of 83	

OPERATING FREQUENCY: 1712.40 MHz  
 CHANNEL: 1312  
 MEASURED OUTPUT POWER: 20.39 dBm = 0.109 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  33.39 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3424.80	H	175	314	-67.38	9.65	-57.73	78.1
5137.20	H	176	7	-65.81	10.91	-54.90	75.3
6849.60	H	-	-	-59.19	10.78	-48.40	68.8

**Table 7-15. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)**

OPERATING FREQUENCY: 1732.60 MHz  
 CHANNEL: 1413  
 MEASURED OUTPUT POWER: 20.46 dBm = 0.111 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  33.46 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3465.20	H	116	46	-69.20	9.77	-59.43	79.9
5197.80	H	121	11	-65.71	10.81	-54.90	75.4
6930.40	H	-	-	-58.69	10.89	-47.81	68.3

**Table 7-16. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1413)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 66 of 83	

OPERATING FREQUENCY: 1752.60 MHz  
 CHANNEL: 1513  
 MEASURED OUTPUT POWER: 20.58 dBm = 0.114 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  33.58 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.20	H	241	58	-69.00	9.89	-59.12	79.7
5257.80	H	178	91	-66.64	10.92	-55.72	76.3
7010.40	H	-	-	-59.68	11.06	-48.62	69.2

Table 7-17. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)

OPERATING FREQUENCY: 1752.60 MHz  
 CHANNEL: 1513  
 MEASURED OUTPUT POWER: 19.98 dBm = 0.100 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  32.98 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3505.20	H	141	308	-68.47	9.89	-58.59	78.6
5257.80	H	200	52	-67.39	10.92	-56.47	76.4
7010.40	H	-	-	-59.65	11.06	-48.59	68.6

Table 7-18. Radiated Spurious Data with WCP (AWS WCDMA Mode – Ch. 1513)

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 67 of 83	

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 29.45 dBm = 0.881 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  42.45 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3700.40	H	200	43	-58.13	10.03	-48.10	77.5
5550.60	H	199	208	-57.64	11.18	-46.46	75.9
7400.80	H	-	-	-57.29	10.85	-46.44	75.9

**Table 7-19. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MEASURED OUTPUT POWER: 28.76 dBm = 0.752 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  41.76 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	149	327	-57.81	9.79	-48.03	76.8
5640.00	H	189	0	-59.20	11.35	-47.85	76.6
7520.00	H	-	-	-58.20	11.22	-46.98	75.7

**Table 7-20. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 68 of 83	

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MEASURED OUTPUT POWER: 28.07 dBm = 0.641 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  41.07 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3819.60	H	176	86	-59.66	9.56	-50.10	78.2
5729.40	H	178	311	-61.89	11.43	-50.46	78.5
7639.20	H	-	-	-57.96	11.50	-46.46	74.5

**Table 7-21. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)**

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 28.19 dBm = 0.659 W  
 MODULATION SIGNAL: GPRS (GMSK)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  41.19 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3700.40	H	149	327	-57.25	10.03	-47.22	75.4
5550.60	H	100	81	-60.74	11.18	-49.56	77.8
7400.80	H	-	-	-57.25	10.85	-46.40	74.6

**Table 7-22. Radiated Spurious Data with WCP (PCS GPRS Mode – Ch. 512)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 69 of 83	

OPERATING FREQUENCY: 1852.40 MHz  
 CHANNEL: 9262  
 MEASURED OUTPUT POWER: 22.86 dBm = 0.193 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.86 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3704.80	H	193	103	-68.50	10.01	-58.48	81.3
5557.20	H	-	-	-67.32	11.20	-56.12	79.0
7409.60	H	-	-	-58.85	10.88	-47.97	70.8

**Table 7-23. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 9400  
 MEASURED OUTPUT POWER: 23.07 dBm = 0.203 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.07 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	156	307	-68.71	9.79	-58.93	82.0
5640.00	H	197	25	-67.31	11.35	-55.97	79.0
7520.00	H	-	-	-57.66	11.22	-46.45	69.5

**Table 7-24. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 70 of 83	

OPERATING FREQUENCY: 1907.60 MHz  
 CHANNEL: 9538  
 MEASURED OUTPUT POWER: 22.78 dBm = 0.189 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.78 dBc



Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3815.20	H	104	314	-67.78	9.57	-58.21	81.0
5722.80	H	164	30	-66.64	11.43	-55.21	78.0
7630.40	H	-	-	-59.06	11.49	-47.57	70.3

**Table 7-25. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)**

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 9400  
 MEASURED OUTPUT POWER: 22.74 dBm = 0.188 W  
 MODULATION SIGNAL: WCDMA  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  35.74 dBc

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	[dBc]
3760.00	H	211	109	-68.30	9.79	-58.52	81.3
5640.00	H	-	-	-67.55	11.35	-56.21	78.9
7520.00	H	-	-	-59.25	11.22	-48.04	70.8

**Table 7-26. Radiated Spurious Data with WCP (PCS WCDMA Mode – Ch. 9400)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 71 of 83	

## 7.8 Frequency Stability / Temperature Variation

**\$2.1055 \$22.355 \$24.235 \$27.54**

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 22, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.***

### Test Procedure Used

ANSI/TIA-603-D-2010

### Test Settings



1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes

None

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 72 of 83	





## Frequency Stability / Temperature Variation

§2.1055 §22.355

OPERATING FREQUENCY: 836,600,000 Hz  
 CHANNEL: 190  
 REFERENCE VOLTAGE: 3.80 VDC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,599,808	-192	-0.0000230
100 %		- 30	836,599,921	-79	-0.0000094
100 %		- 20	836,599,926	-74	-0.0000088
100 %		- 10	836,600,016	16	0.0000019
100 %		0	836,600,115	115	0.0000137
100 %		+ 10	836,600,360	360	0.0000430
100 %		+ 20	836,600,258	258	0.0000308
100 %		+ 30	836,599,699	-301	-0.0000360
100 %		+ 40	836,599,834	-166	-0.0000198
100 %		+ 50	836,600,163	163	0.0000195
BATT. ENDPOINT	3.40	+ 20	836,599,716	-284	-0.0000339

Table 7-27. Frequency Stability Data (Cellular GPRS Mode – Ch. 190)



FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 73 of 83	

**Frequency Stability / Temperature Variation**

**§2.1055 §22.355**



**Figure 7-8. Frequency Stability Graph (Cellular GPRS Mode – Ch. 190)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 74 of 83	



## Frequency Stability / Temperature Variation

§2.1055 §22.355

OPERATING FREQUENCY: 836,600,000 Hz  
 CHANNEL: 4183  
 REFERENCE VOLTAGE: 3.80 VDC  
 DEVIATION LIMIT:  $\pm 0.00025$  % or 2.5 ppm


VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,599,973	-27	-0.0000032
100 %		- 30	836,599,625	-375	-0.0000448
100 %		- 20	836,600,085	85	0.0000102
100 %		- 10	836,600,108	108	0.0000129
100 %		0	836,599,809	-191	-0.0000228
100 %		+ 10	836,600,235	235	0.0000281
100 %		+ 20	836,599,858	-142	-0.0000170
100 %		+ 30	836,599,571	-429	-0.0000513
100 %		+ 40	836,599,989	-11	-0.0000013
100 %		+ 50	836,600,006	6	0.0000007
BATT. ENDPOINT	3.40	+ 20	836,599,836	-164	-0.0000196

**Table 7-28. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)**



FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 75 of 83	

**Frequency Stability / Temperature Variation**

**§2.1055 §22.355**



**Figure 7-9. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 76 of 83	

## Frequency Stability / Temperature Variation

**§2.1055 §27.54**



OPERATING FREQUENCY: 1,732,600,000 Hz  
 CHANNEL: 1413  
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,732,599,933	-67	-0.0000039
100 %		- 30	1,732,599,962	-38	-0.0000022
100 %		- 20	1,732,599,817	-183	-0.0000106
100 %		- 10	1,732,599,574	-426	-0.0000246
100 %		0	1,732,600,078	78	0.0000045
100 %		+ 10	1,732,599,798	-202	-0.0000117
100 %		+ 20	1,732,599,775	-225	-0.0000130
100 %		+ 30	1,732,599,984	-16	-0.0000009
100 %		+ 40	1,732,599,962	-38	-0.0000022
100 %		+ 50	1,732,599,954	-46	-0.0000027
BATT. ENDPOINT	3.40	+ 20	1,732,600,152	152	0.0000088


**Table 7-29. Frequency Stability Data (AWS WCDMA Mode – Ch. 1412)**

**Note:**



Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 77 of 83	

**Frequency Stability / Temperature Variation**  
**§2.1055 §27.54**



**Figure 7-10. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1412)**

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 78 of 83	

## Frequency Stability / Temperature Variation

**§2.1055 §24.235**



OPERATING FREQUENCY: 1,880,000,000 Hz  
 CHANNEL: 661  
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,879,999,887	-113	-0.0000060
100 %		- 30	1,880,000,470	470	0.0000250
100 %		- 20	1,879,999,854	-146	-0.0000078
100 %		- 10	1,880,000,089	89	0.0000047
100 %		0	1,880,000,081	81	0.0000043
100 %		+ 10	1,879,999,883	-117	-0.0000062
100 %		+ 20	1,879,999,959	-41	-0.0000022
100 %		+ 30	1,879,999,903	-97	-0.0000052
100 %		+ 40	1,880,000,234	234	0.0000124
100 %		+ 50	1,879,999,916	-84	-0.0000045
BATT. ENDPOINT	3.40	+ 20	1,879,999,889	-111	-0.0000059


**Table 7-30. Frequency Stability Data (PCS GPRS Mode – Ch. 661)**

**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 79 of 83	

**Frequency Stability / Temperature Variation**  
**§2.1055 §24.235**



**Figure 7-11. Frequency Stability Graph (PCS GPRS Mode – Ch. 661)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 80 of 83	



## Frequency Stability / Temperature Variation

§2.1055 §24.235



OPERATING FREQUENCY:	1,880,000,000	Hz
CHANNEL:	9400	
REFERENCE VOLTAGE:	3.80	VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,879,999,842	-158	-0.0000084
100 %		- 30	1,879,999,915	-85	-0.0000045
100 %		- 20	1,880,000,193	193	0.0000103
100 %		- 10	1,879,999,990	-10	-0.0000005
100 %		0	1,880,000,063	63	0.0000034
100 %		+ 10	1,879,999,902	-98	-0.0000052
100 %		+ 20	1,880,000,254	254	0.0000135
100 %		+ 30	1,879,999,776	-224	-0.0000119
100 %		+ 40	1,879,999,896	-104	-0.0000055
100 %		+ 50	1,879,999,806	-194	-0.0000103
BATT. ENDPOINT	3.40	+ 20	1,879,999,587	-413	-0.0000220

**Table 7-31. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)**


**Note:**

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 81 of 83	

**Frequency Stability / Temperature Variation**

**§2.1055 §24.235**





**Figure 7-12. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)**

FCC ID: ZNFH871	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)	LG	Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset	Page 82 of 83	

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFH871** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules.

FCC ID: ZNFH871		FCC Pt. 22, 24, & 27 GSM / GPRS / EDGE / WCDMA MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1701180032-02-R2.ZNF	Test Dates: 12/27/2016 - 2/15/2017	EUT Type: Portable Handset		Page 83 of 83