



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. +1.410.290.6652 / Fax +1.410.290.6654
<http://www.pctestlab.com>



SAR EVALUATION REPORT

Applicant Name:
LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:
01/15/2017
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Document Serial No.:
1M1701030009-01-R1.ZNF

FCC ID: ZNFH910

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A., INC.


DUT Type: Portable Handset
Application Type: Class II Permissive Change
FCC Rule Part(s): CFR §2.1093
Model(s): LG-H910
Additional Model(s): LGH910, H910, LG-H915, LGH915, H915
Test Device Serial No.: [S/N: 05710]
Permissive Change(s): Adding additional DL carrier aggregation combinations

Note: This revised Test Report (S/N: 1M1701030009-01-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

Note: The following test data was evaluated for the current test report. Please refer to RF Exposure Technical Report S/N 0Y1607051171-R4.ZNF and RF Exposure Technical Report S/N 0Y1608121352-R1.ZNF for original compliance evaluation.



This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.4 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President





The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | | Page 1 of 11 |

T A B L E O F C O N T E N T S



| | | |
|---|----------------------------------|----|
| 1 | DEVICE UNDER TEST | 3 |
| 2 | LTE INFORMATION | 5 |
| 3 | FCC MEASUREMENT PROCEDURES | 6 |
| 4 | RF CONDUCTED POWERS | 7 |
| 5 | EQUIPMENT LIST | 8 |
| 6 | CONCLUSION | 9 |
| 7 | REFERENCES | 10 |

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | Page 2 of 11 | |

1 DEVICE UNDER TEST

1.1 Device Overview

| Band & Mode | Operating Modes | Tx Frequency |
|--------------------|-----------------|-----------------------|
| GSM/GPRS/EDGE 850 | Voice/Data | 824.20 - 848.80 MHz |
| UMTS 850 | Voice/Data | 826.40 - 846.60 MHz |
| UMTS 1750 | Voice/Data | 1712.4 - 1752.6 MHz |
| GSM/GPRS/EDGE 1900 | Voice/Data | 1850.20 - 1909.80 MHz |
| UMTS 1900 | Voice/Data | 1852.4 - 1907.6 MHz |
| LTE Band 12 | Voice/Data | 699.7 - 715.3 MHz |
| LTE Band 17 | Voice/Data | 706.5 - 713.5 MHz |
| LTE Band 5 (Cell) | Voice/Data | 824.7 - 848.3 MHz |
| LTE Band 66 (AWS) | Voice/Data | 1712.5 - 1777.5 MHz |
| LTE Band 4 (AWS) | Voice/Data | 1710.7 - 1754.3 MHz |
| LTE Band 2 (PCS) | Voice/Data | 1850.7 - 1909.3 MHz |
| LTE Band 30 | Voice/Data | 2307.5 - 2312.5 MHz |
| LTE Band 7 | Voice/Data | 2502.5 - 2567.5 MHz |
| 2.4 GHz WLAN | Voice/Data | 2412 - 2462 MHz |
| U-NII-1 | Voice/Data | 5180 - 5240 MHz |
| U-NII-2A | Voice/Data | 5260 - 5320 MHz |
| U-NII-2C | Voice/Data | 5500 - 5720 MHz |
| U-NII-3 | Voice/Data | 5745 - 5825 MHz |
| Bluetooth | Data | 2402 - 2480 MHz |
| NFC | Data | 13.56 MHz |

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | | Page 3 of 11 |

1.2 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications for LTE B2/4/7/66. See RF Exposure Technical Report S/N 0Y1607051171-R4.ZNF and RF Exposure Technical Report S/N 0Y1608121352-R1.ZNF for complete maximum and nominal output power specifications.



| Mode / Band | | Modulated Average (dBm) |
|-------------------|---------|-------------------------|
| LTE Band 66 (AWS) | Maximum | 25.0 |
| | Nominal | 24.5 |
| LTE Band 4 (AWS) | Maximum | 25.0 |
| | Nominal | 24.5 |
| LTE Band 2 (PCS) | Maximum | 25.2 |
| | Nominal | 24.7 |
| LTE Band 7 | Maximum | 23.7 |
| | Nominal | 23.2 |

1.3 SAR Test Exclusion



Additional SAR measurements are not required per FCC KDB Publication 941225 D05Av01r02. See RF Exposure Technical Report S/N 0Y1607051171-R4.ZNF and RF Exposure Technical Report S/N 0Y1608121352-R1.ZNF for SAR compliance evaluation and complete RF conducted output power measurements.

1.4 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D05v02r04, D05Av01r02 (4G)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | Page 4 of 11 | |

| LTE Information | | | |
|---|---|----------------|-----------------|
| FCC ID | ZNFH910 | | |
| Form Factor | Portable Handset | | |
| Frequency Range of each LTE transmission band | LTE Band 12 (699.7 - 715.3 MHz) | | |
| | LTE Band 17 (706.5 - 713.5 MHz) | | |
| | LTE Band 5 (Cell) (824.7 - 848.3 MHz) | | |
| | LTE Band 66 (AWS) (1712.5 - 1777.5 MHz) | | |
| | LTE Band 4 (AWS) (1710.7 - 1754.3 MHz) | | |
| | LTE Band 2 (PCS) (1850.7 - 1909.3 MHz) | | |
| | LTE Band 30 (2307.5 - 2312.5 MHz) | | |
| | LTE Band 7 (2502.5 - 2567.5 MHz) | | |
| Channel Bandwidths | LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz | | |
| | LTE Band 17: 5 MHz, 10 MHz | | |
| | LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz | | |
| | LTE Band 66 (AWS): 5 MHz, 10 MHz, 15 MHz, 20 MHz | | |
| | LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz | | |
| | LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz | | |
| | LTE Band 30: 5 MHz, 10 MHz | | |
| Channel Numbers and Frequencies (MHz) | Low | Mid | High |
| | LTE Band 12: 1.4 MHz | 699.7 (23017) | 707.5 (23095) |
| LTE Band 12: 3 MHz | 700.5 (23025) | 707.5 (23095) | 714.5 (23165) |
| LTE Band 12: 5 MHz | 701.5 (23035) | 707.5 (23095) | 713.5 (23155) |
| LTE Band 12: 10 MHz | 704 (23060) | 707.5 (23095) | 711 (23130) |
| LTE Band 17: 5 MHz | 706.5 (23755) | 710 (23790) | 713.5 (23825) |
| LTE Band 17: 10 MHz | 709 (23780) | 710 (23790) | 711 (23800) |
| LTE Band 5 (Cell): 1.4 MHz | 824.7 (20407) | 836.5 (20525) | 848.3 (20643) |
| LTE Band 5 (Cell): 3 MHz | 825.5 (20415) | 836.5 (20525) | 847.5 (20635) |
| LTE Band 5 (Cell): 5 MHz | 826.5 (20425) | 836.5 (20525) | 846.5 (20625) |
| LTE Band 5 (Cell): 10 MHz | 829 (20450) | 836.5 (20525) | 844 (20600) |
| LTE Band 66 (AWS): 5 MHz | 1712.5 (131997) | 1745 (132322) | 1777.5 (132647) |
| LTE Band 66 (AWS): 10 MHz | 1715 (132022) | 1745 (132322) | 1775 (132622) |
| LTE Band 66 (AWS): 15 MHz | 1717.5 (132047) | 1745 (132322) | 1772.5 (132597) |
| LTE Band 66 (AWS): 20 MHz | 1720 (132072) | 1745 (132322) | 1770 (132572) |
| LTE Band 4 (AWS): 1.4 MHz | 1710.7 (19957) | 1732.5 (20175) | 1754.3 (20393) |
| LTE Band 4 (AWS): 3 MHz | 1711.5 (19965) | 1732.5 (20175) | 1753.5 (20385) |
| LTE Band 4 (AWS): 5 MHz | 1712.5 (19975) | 1732.5 (20175) | 1752.5 (20375) |
| LTE Band 4 (AWS): 10 MHz | 1715 (20000) | 1732.5 (20175) | 1750 (20350) |
| LTE Band 4 (AWS): 15 MHz | 1717.5 (20025) | 1732.5 (20175) | 1747.5 (20325) |
| LTE Band 4 (AWS): 20 MHz | 1720 (20050) | 1732.5 (20175) | 1745 (20300) |
| LTE Band 2 (PCS): 1.4 MHz | 1850.7 (18607) | 1880 (18900) | 1909.3 (19193) |
| LTE Band 2 (PCS): 3 MHz | 1851.5 (18615) | 1880 (18900) | 1908.5 (19185) |
| LTE Band 2 (PCS): 5 MHz | 1852.5 (18625) | 1880 (18900) | 1907.5 (19175) |
| LTE Band 2 (PCS): 10 MHz | 1855 (18650) | 1880 (18900) | 1905 (19150) |
| LTE Band 2 (PCS): 15 MHz | 1857.5 (18675) | 1880 (18900) | 1902.5 (19125) |
| LTE Band 2 (PCS): 20 MHz | 1860 (18700) | 1880 (18900) | 1900 (19100) |
| LTE Band 30: 5 MHz | 2307.5 (27685) | 2310 (27710) | 2312.5 (27735) |
| LTE Band 30: 10 MHz | N/A | 2310 (27710) | N/A |
| LTE Band 7: 5 MHz | 2502.5 (20775) | 2535 (21100) | 2567.5 (21425) |
| LTE Band 7: 10 MHz | 2505 (20800) | 2535 (21100) | 2565 (21400) |
| LTE Band 7: 15 MHz | 2507.5 (20825) | 2535 (21100) | 2562.5 (21375) |
| LTE Band 7: 20 MHz | 2510 (20850) | 2535 (21100) | 2560 (21350) |
| UE Category | 11 | | |
| Modulations Supported in UL | QPSK, 16QAM | | |
| LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided) | YES | | |
| A-MPR (Additional MPR) disabled for SAR Testing? | YES | | |
| LTE Carrier Aggregation Possible Combinations | The technical description includes all the possible carrier aggregation combinations | | |
| LTE Release 10 Additional Information | This device does not support full CA features on 3GPP Release 10. It supports a maximum of 3 carriers in the downlink. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 10 Features are not supported: Relay, HetNet, Enhanced MIMO, eICIC, WiFi Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA. | | |



| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | | Page 5 of 11 |

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

3.1.1 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

For 3CC downlink carrier aggregation combinations, PCC uplink channel was selected based on section C)3)b)ii) of KDB 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers. All selected downlink channels remained fully within the downlink transmission band of the respective component carrier.

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | Page 6 of 11 | |

4 RF CONDUCTED POWERS

4.1 LTE Conducted Powers

4.1.1 LTE Carrier Aggregation Conducted Powers

Table 4-1
LTE Carrier Aggregation Conducted Powers 2CC Powers

| PCC | | | | | | | | | SCC | | | | Power | |
|----------|---------------------|------------------|--------------------------|------------|------------|------------------|------------------|--------------------------|----------|---------------------|------------------|--------------------------|---------------------------|---------------------------|
| PCC Band | PCC Bandwidth [MHz] | PCC (UL) Channel | PCC (UL) Frequency [MHz] | Modulation | PCC UL# RB | PCC UL RB Offset | PCC (DL) Channel | PCC (DL) Frequency [MHz] | SCC Band | SCC Bandwidth [MHz] | SCC (DL) Channel | SCC (DL) Frequency [MHz] | LTE Rel 10 Tx.Power (dBm) | LTE Rel. 8 Tx.Power (dBm) |
| LTE B7 | 15 | 21100 | 2535 | QPSK | 1 | 36 | 3100 | 2655 | LTE B7 | 5 | 2775 | 2622.5 | 23.50 | 23.70 |

Table 4-2
LTE Carrier Aggregation Conducted Powers 3CC Powers

| PCC | | | | | | | | | SCC 1 | | | SCC 2 | | | | Power | | |
|----------|---------------------|------------------|--------------------------|------------|------------|------------------|------------------|--------------------------|----------|---------------------|------------------|--------------------------|----------|---------------------|------------------|--------------------------|---------------------------|---------------------------|
| PCC Band | PCC Bandwidth [MHz] | PCC (UL) Channel | PCC (UL) Frequency [MHz] | Modulation | PCC UL# RB | PCC UL RB Offset | PCC (DL) Channel | PCC (DL) Frequency [MHz] | SCC Band | SCC Bandwidth [MHz] | SCC (DL) Channel | SCC (DL) Frequency [MHz] | SCC Band | SCC Bandwidth [MHz] | SCC (DL) Channel | SCC (DL) Frequency [MHz] | LTE Rel 10 Tx.Power (dBm) | LTE Rel. 8 Tx.Power (dBm) |
| LTE B2 | 15 | 18900 | 1880 | QPSK | 1 | 0 | 900 | 1960 | LTE B4 | 20 | 2175 | 2132.5 | LTE B29 | 10 | 9715 | 722.5 | 25.11 | 25.20 |
| LTE B4 | 20 | 20300 | 1745 | QPSK | 1 | 0 | 2300 | 2145 | LTE B2 | 20 | 900 | 1960 | LTE B29 | 10 | 9715 | 722.5 | 24.95 | 25.00 |

Notes:

1. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. For 3CC downlink carrier aggregation combinations, PCC uplink channel was selected based on section C)3)b)ii) of KBD 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers. All selected downlink channels remained fully within the downlink transmission band of the respective component carrier.
2. All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
3. Since the supported frequency span for LTE B4 falls completely within the supported frequency span for LTE B66, both LTE bands have the same target power, and both LTE bands share the same transmission path, the configuration with the highest conducted power from LTE B66 was used to assess LTE CA combinations with LTE B4.
4. See RF Exposure Technical Report S/N 0Y1607051171-R4.ZNF and RF Exposure Technical Report S/N 0Y1608121352-R1.ZNF for complete RF conducted output power measurements.






Figure 4-1
Power Measurement Setup

| | | | | |
|---|---------------------------|-------------------------------|--------------|---------------------------------|
| FCC ID: ZNFH910 | | SAR EVALUATION REPORT | | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | Page 7 of 11 | |

5

EQUIPMENT LIST



| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|-----------------|----------|-------------------------------------|-----------|--------------|-----------|---------------|
| MCL | BW-N6W5+ | 6dB Attenuator | CBT | N/A | CBT | 1139 |
| Seekonk | NC-100 | Torque Wrench (8" lb) | 8/30/2016 | Biennial | 8/30/2018 | N/A |
| Rohde & Schwarz | CMW500 | Wideband Radio Communication Tester | 7/20/2016 | Annual | 7/20/2017 | 132885 |

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | | Page 8 of 11 |

6.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.



Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | Page 9 of 11 | |



7

REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

| | | | | |
|---|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFH910 |  | SAR EVALUATION REPORT |  | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | | Page 10 of 11 |

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

| | | | |
|--|--|--------------------------------------|--|
| FCC ID: ZNFH910 |  SAR EVALUATION REPORT  | | Reviewed by: Quality Manager |
| Document S/N: 1M1701030009-01-R1.ZNF | Test Dates: 01/15/2017 | DUT Type: Portable Handset | Page 11 of 11 |