

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC1708-0139(1)
2. Customer
 - Name : LG Electronics MobileComm USA, Inc.
 - Address : 1000 Sylvan Ave., Englewood Cliffs, New Jersey, United States, 07632
3. Use of Report : FCC Original Grant
4. Product Name / Model Name : Mobile Phone / LG-H930
FCC ID : ZNFH930
5. Test Method Used : KDB789033 D02v01r04
Test Specification : FCC Part 15.407 Subpart E
6. Date of Test : 2017.06.21 ~ 2017.07.25
7. Testing Environment : Refer to appended test report.
8. Test Result : Refer to the attached test result.

Affirmation	Tested by	Technical Manager
	Name : SunGeun Lee (Signature)	Name : Geunki Son (Signature)

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2017 . 08 . 09 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description
DRTFCC1708-0139	Aug. 03, 2017	Initial issue
DRTFCC1708-0139(1)	Aug. 09, 2017	Revised the typo error in section 2.1 Added the note in section 9

CONTENTS

1. EUT DESCRIPTION.....	4
2. Information about test items	5
2.1 Transmitting configuration of EUT	5
2.2 Tested Channel Information.....	5
2.3 Testing Environment.....	6
2.4 EMI Suppression Device(s)/Modifications	6
2.5 Measurement Uncertainty	6
3. SUMMARY OF TESTS.....	7
4. TEST METHODOLOGY.....	8
4.1 EUT configuration.....	8
4.2 EUT exercise	8
4.3 General test procedures	8
4.4 Description of test modes	8
5. INSTRUMENT CALIBRATION.....	9
6. FACILITIES AND ACCREDITATIONS	9
6.1 Facilities	9
6.2 Equipment	9
7. ANTENNA REQUIREMENTS	9
8. TEST RESULT	10
8.1 Emission Bandwidth (26 dB Bandwidth).....	10
8.2 Minimum Emission Bandwidth (6 dB Bandwidth)	44
8.3 Maximum Conducted Output Power.....	57
8.4 Maximum Power Spectral Density.....	66
8.5 Frequency Stability.....	151
8.6 Radiated Spurious Emission Measurements.....	153
8.7 AC Conducted Emissions.....	168
9. LIST OF TEST EQUIPMENT	177
APPENDIX I	178
APPENDIX II.....	179
APPENDIX III	184

1. EUT DESCRIPTION

FCC Equipment Class	Unlicensed National Information Infrastructure (UNII)
Product	Mobile Phone
Model Name	LG-H930
Add Model Name	LG-H930DS, LG-H930K, LG-H930G
Power Supply	DC 3.85 V
Modulation type	OFDM
Antenna Specification	Antenna type: Internal Antenna Antenna gain: Refer to the clause 7 in test report.

5GHz Band	Mode	Tx frequency (MHz)	Max power(dBm)
U-NII 1	802.11a	5180 ~ 5240	18.26
	802.11n(HT20)	5180 ~ 5240	17.21
	802.11ac(VHT20)	5180 ~ 5240	17.02
	802.11n(HT40)	5190 ~ 5230	17.83
	802.11ac(VHT40)	5190 ~ 5230	17.89
	802.11ac(VHT80)	5210	16.01
U-NII 2A	802.11a	5260 ~ 5320	18.13
	802.11n(HT20)	5260 ~ 5320	16.99
	802.11ac(VHT20)	5260 ~ 5320	17.15
	802.11n(HT40)	5270 ~ 5310	17.87
	802.11ac(VHT40)	5270 ~ 5310	17.90
	802.11ac(VHT80)	5290	14.52
U-NII 2C	802.11a	5500 ~ 5580	17.80
	802.11n(HT20)	5500 ~ 5580	16.94
	802.11ac(VHT20)	5500 ~ 5580	17.03
	802.11n(HT40)	5510 ~ 5550	17.93
	802.11ac(VHT40)	5510 ~ 5550	17.90
	802.11ac(VHT80)	5530	14.67
	802.11a	5660 ~ 5720	17.66
	802.11n(HT20)	5660 ~ 5720	16.86
	802.11ac(VHT20)	5660 ~ 5720	16.95
	802.11n(HT40)	5670 ~ 5710	17.57
	802.11ac(VHT40)	5670 ~ 5710	17.59
	802.11ac(VHT80)	5690	16.44
U-NII 3	802.11a	5745 ~ 5825	17.84
	802.11n(HT20)	5745 ~ 5825	17.28
	802.11ac(VHT20)	5745 ~ 5825	17.31
	802.11n(HT40)	5755 ~ 5795	17.94
	802.11ac(VHT40)	5755 ~ 5795	17.93
	802.11ac(VHT80)	5775	16.78

2. Information about test items

2.1 Transmitting configuration of EUT

Mode	SISO		MIMO (CDD)	MIMO (SDM)
	Ant 1	Ant 2	Ant 1 & 2	Ant 1 & 2
	Data rate			
802.11a	6~54Mbps	6~54Mbps	6~54Mbps	-
802.11n(HT20)	MCS 0 ~ 7	MCS 0 ~ 7	MCS 0 ~ 7	MCS 8 ~ 15
802.11ac(VHT20)	MCS 0 ~ 8	MCS 0 ~ 8	MCS 0 ~ 8	MCS 0 ~ 8
802.11n(HT40)	MCS 0 ~ 7	MCS 0 ~ 7	-	MCS 8 ~ 15
802.11ac(VHT40)	MCS 0 ~ 9	MCS 0 ~ 9	-	MCS 0 ~ 9
802.11ac(VHT80)	MCS 0 ~ 9	MCS 0 ~ 9	-	MCS 0 ~ 9

Note1: SDM = Spatial Diversity Multiplexing, CDD = Cycle Delay Diversity

Note2: This device supports WiFi DBS(dual-band simultaneous) transmission operation, which allows for two SISO channels to operate independent of one another in the 2.4GHz and 5GHz bands simultaneously on each antenna. (Ant 1: 2.4GHz band transmitting & ANT 2: 5GHz band transmitting)

And the test results for WiFi DBS were included in this test report.

2.2 Tested Channel Information

5GHz Band	802.11a/n(HT20)		802.11n/ac(VHT40)		802.11n/ac(VHT80)	
	Channel	Frequency [MHz]	Channel	Frequency [MHz]	Channel	Frequency [MHz]
U-NII 1	36	5180	38	5190	42	5210
	40	5200	-	-	-	-
	48	5240	46	5230	-	-
U-NII 2A	52	5260	54	5270	58	5290
	60	5300	-	-	-	-
	64	5320	62	5310	-	-
U-NII 2C	100	5500	102	5510	106	5530
	116	5580	110	5550	-	-
	144	5720	142	5710	138	5690
U-NII 3	149	5745	151	5755	155	5775
	157	5785	-	-	-	-
	165	5825	159	5795	-	-

2.3 Testing Environment

Temperature	: 22 °C ~ 26 °C
Relative humidity content	: 40 % ~ 45 % R.H.
Details of power supply	: DC 3.85 V

2.4 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing
 → None

2.5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014 and ANSI C 63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Test items	Measurement uncertainty
Transmitter Output Power	± 0.7 dB (The confidence level is about 95 %, $k = 2$)
Conducted spurious emission	± 1.0 dB (The confidence level is about 95 %, $k = 2$)
AC conducted emission	± 2.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (1 GHz Below)	± 5.1 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (1 GHz ~ 18 GHz)	± 5.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated spurious emission (18 GHz Above)	± 5.3 dB (The confidence level is about 95 %, $k = 2$)

3. SUMMARY OF TESTS

FCC Part Section(s)	Parameter	Limit	Test Condition	Status Note 1
I. Transmitter Mode (TX)				
15.407(a)	Emission Bandwidth (26 dB Bandwidth)	N/A	Conducted	C
15.407(e)	Minimum Emission Bandwidth (6 dB Bandwidth)	> 500 kHz in 5725 ~ 5850 MHz		C
15.407(a)	Maximum Conducted Output Power	5150 ~ 5250 MHz : < 23.97 dBm 5250 ~ 5350 & 5470 ~ 5725 MHz : < 250 mW or < 11 + 10 log ₁₀ (B) dBm, whichever power is less. (B is the 26dB BW.) 5725 ~ 5850 MHz : < 30 dBm		C
15.407(a)	Peak Power Spectral Density	5150 ~ 5250 MHz : 11 dBm/MHz 5250 ~ 5350 MHz : 11 dBm/MHz 5470 ~ 5725 MHz : 11 dBm/MHz 5725 ~ 5850 MHz : 30 dBm/500kHz		C
15.407(g)	Frequency Stability	N/A		C
15.407(h)	Dynamic Frequency Selection	FCC 15.407(h)		C Note 2
15.407(b)	Undesirable Emissions	5150 ~ 5725 MHz: < -27 dBm/MHz EIRP 5725 ~ 5850 MHz: < -27 dBm/MHz or < 10 dBm/MHz or 15.6 dBm/MHz < 27dBm/MHz EIRP	Radiated	C Note 3, 4
15.205 15.209 15.407(b)	General Field Strength Limits(Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		C Note 3, 4
15.207	AC Conducted Emissions	FCC 15.207	AC Line Conducted	C
15.203	Antenna Requirements	FCC 15.203	-	C

Note 1: **C** = Comply **NC** = Not Comply **NT** = Not Tested **NA** = Not Applicable

Note 2: Refer to the DFS test report.

Note 3: This device supports wireless charging capability.

So per KDB648474 D03 v01r04, the radiated test items were performed both normal and charging conditions. For wireless charging condition, the handset is placed on the representative charging pad under normal conditions and in a simulated call configuration. And the worst case data was reported.

Note 4: In case of this test item, we have done all TX test cases. And we attached the result of MIMO mode since MIMO is the worst case.

Note 5: The sample was tested according to the following specification:

KDB789033 D02v01r04, KDB662911 D01v02r01, KDB648474 D03v01r04

4. TEST METHODOLOGY

Generally the tests were performed according to the **KDB789033 D02v01r04**. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing

4.1 EUT configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT exercise

The EUT was operated in the test mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E.

4.3 General test procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB789033 D02v01r04. So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB789033 D02v01r04. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on KDB789033 D02v01r04.

The EUT is placed on a non-conductive table, which is 0.8 m above ground plane. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 1 or 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axis.

4.4 Description of test modes

The EUT has been tested with all modes of operating conditions to determine the worst case emission characteristics. A test program is used to control the EUT for staying in continuous transmitting mode with maximum fixed duty cycle.

5. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

6. FACILITIES AND ACCREDITATIONS

6.1 Facilities

DT&C Co., Ltd.	
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The site is constructed in conformance with the requirements. - FCC MRA Accredited Test Firm No. : KR0034	
www.dtnet.net	
Telephone	: + 82-31-321-2664
FAX	: + 82-31-321-1664

6.2 Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, loop, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

7. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The antenna is attached on the device by means of unique coupling method (Spring Tension).

Therefore this E.U.T Complies with the requirement of §15.203

Directional antenna gain:

Bands	SISO		MIMO (CDD) ^{Note 1.}	MIMO (SDM) ^{Note 2}
	ANT 1 [dBi]	ANT 2 [dBi]	Directional Gain[dBi]	Directional Gain[dBi]
U-NII 1	-1.63	-0.32	+2.06	-0.93
U-NII 2A	-1.63	-0.32	+2.06	-0.93
U-NII 2C	-1.61	-0.50	+1.97	-1.02
U-NII 3	-1.55	-1.59	+1.44	-1.57

Note 1. Directional gain(correlated signal with unequal antenna gain and equal transmit power)

$$10 \log \left[\left(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20} \right)^2 / N^{ANT} \right] \text{ dBi}$$

Note 2. Directional gain(completely uncorrelated signal with unequal antenna gain and equal transmit power)

$$10 \log \left[\left(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10} \right) / N^{ANT} \right] \text{ dBi}$$

8. TEST RESULT

8.1 Emission Bandwidth (26 dB Bandwidth)

■ Test Requirements

The bandwidth at 26 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The 26 dB bandwidth is used to determine the conducted output power limit.

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v01r04**.

1. Set resolution bandwidth (RBW) = approximately **1 %** of the EBW.
2. Set the video bandwidth (**VBW**) > **RBW**.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.


TEST RESULTS: Comply

Mode	Band	Channel	Frequency [MHz]	Test Result [MHz]	
				ANT 1	ANT 2
802.11a	U-NII 1	36	5180	22.68	21.65
		40	5200	21.95	22.14
		48	5240	21.47	21.92
	U-NII 2A	52	5260	22.37	21.57
		60	5300	21.88	21.99
		64	5320	22.63	21.42
	U-NII 2C	100	5500	21.87	21.45
		116	5580	22.18	21.70
		144	5720	21.89	22.16
802.11n (HT20)	U-NII 1	36	5180	21.28	22.63
		40	5200	22.55	22.71
		48	5240	22.34	22.33
	U-NII 2A	52	5260	22.27	22.02
		60	5300	22.37	21.88
		64	5320	21.58	21.98
	U-NII 2C	100	5500	22.14	22.01
		116	5580	21.14	22.84
		144	5720	24.11	23.57
802.11n (HT40)	U-NII 1	38	5190	41.08	40.70
		46	5230	40.34	40.48
	U-NII 2A	54	5270	40.53	40.37
		62	5310	40.24	40.58
	U-NII 2C	102	5510	40.85	40.10
		110	5550	41.18	41.00
802.11ac (VHT80)	U-NII 1	42	5210	82.01	81.78
		-	-	-	-
	U-NII 2A	58	5290	82.42	82.27
		-	-	-	-
	U-NII 2C	106	5530	82.82	82.25
		138	5690	82.44	83.11

Result Plots


26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.36




26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.40



26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.48




26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.52




26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.60




26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.64




26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.100




26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.116




26 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.144



26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.36




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.40




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.48




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.52




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.60




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.64




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.100




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.116




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.144




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.38




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.46




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.54




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.62




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.102




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.110




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.142




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 1 & Ch.42




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 1 & Ch.58




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 1 & Ch.106




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 1 & Ch.138




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.36




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.40




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.48




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.52




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.60




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.64




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.100




26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.116



26 dB Bandwidth

Test Mode: 802.11a & ANT 2 & Ch.144




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.36




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.40




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.48




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.52




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.60




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.64




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.100




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.116




26 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 2 & Ch.144




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 2 & Ch.38




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 2 & Ch.46




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 2 & Ch.54




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 2 & Ch.62




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 2 & Ch.102




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 2 & Ch.110




26 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 2 & Ch.142




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 2 & Ch.42




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 2 & Ch.58




26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 1 & Ch.106



26 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 1 & Ch.138



8.2 Minimum Emission Bandwidth (6 dB Bandwidth)

■ Test Requirements

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

■ Test Configuration

Refer to the APPENDIX I.

■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v01r04**.

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth $\geq 3 \times \text{RBW}$.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


■ TEST RESULTS: **Comply**

Mode	Band	Channel	Frequency [MHz]	Test Result [MHz]	
				ANT 1	ANT 2
802.11a	U-NII 3	149	5745	15.12	15.16
		157	5785	15.13	15.11
		165	5825	15.10	15.06
802.11n (HT20)	U-NII 3	149	5745	15.06	15.14
		157	5785	15.05	15.16
		165	5825	15.11	15.14
802.11n (HT40)	U-NII 3	151	5755	35.06	35.07
		159	5795	33.79	33.84
802.11ac (VHT80)	U-NII 3	155	5775	73.86	73.82

RESULT PLOTS


6 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.149




6 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.157




6 dB Bandwidth

Test Mode: 802.11a & ANT 1 & Ch.165




6 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.149




6 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.157




6 dB Bandwidth

Test Mode: 802.11n HT20 & ANT 1 & Ch.165




6 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.151



6 dB Bandwidth

Test Mode: 802.11n HT40 & ANT 1 & Ch.159



6 dB Bandwidth

Test Mode: 802.11ac VHT80 & ANT 1 & Ch.155

