

## FCC ID : ZNFHBS510

According to KDB 447498 D01 General RF Exposure Guidance

At 100 MHz to 6 GHz and for test separation distances  $\leq 50$  mm, the SAR test exclusion threshold is determined according to the following

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \times \sqrt{f(\text{GHz})} \right] \leq 3.0$$

### 1. SAR test exclusion threshold

**Frequency : 2 480 MHz (min. separation distances = 0 mm)**

SAR test exclusion thresholds(5 mm) =  $3 \times 5 / (\sqrt{2.480}) = 9.525$  mW

Max. tune-up tolerance(mW)	SAR Test Exclusion Thresholds(5 mm) (mW)
2	9.525

Calculation value :  $2 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 0.63$

So, Calculation value  $\leq 3.0$

Remark:

-Max. conducted power (mW) : maximum tolerance power of EUT (3 dBm)

-Max. conducted power 1.995 (mW) is closet 2 (mW), so 2 (mW) was calculated.

-When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

### 2. Conclusion : No SAR is required.