

# EMI CERTIFICATION REPORT

**Applicant:**

LG Electronics MobileComm U.S.A., Inc.  
1000 Sylvan Avenue, Englewood Cliffs NJ 07632

**Date of Receipt: November 20, 2015****Date of Issue: December 09, 2015****Test Report No. HCT-E-1512-F016****HCT FRN: 0005866421****FCC ID :****ZNFK120H**

**Rule Part(s) / Standard(s):** FCC CFR 47 PART 15 Subpart B Class B  
**FCC Classification:** JBP (Part 15 B – Class B Computing Device Peripheral)  
**EUT Type:** GSM WCDMA and LTE Phone with BT & WLAN  
**Model Name:** LG-K120H  
**Additional Model Name:** LGK120H, K120H  
**Test Port:** USB / Earphone Port  
**Date of Test:** December 07, 2015 – December 08, 2015

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

**Tested By**

**Gu-Cheol Yoon**  
Test Engineer  
EMC Team  
Certification Division

**Reviewed By**

**Jin-Pyo Hong**  
Technical Manager  
EMC Team  
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



## DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1512-F016	December 09, 2015	Initial Release



## TABLE OF CONTENTS

	<b>PAGE</b>
1. GENERAL INFORMATION .....	4
1.1 Description of EUT .....	4
1.2 Related Submittal(s) / Grant(s).....	5
1.3 Test Facility .....	5
1.4 Tested System Details.....	6
1.5 Cable Description .....	7
1.6 Noise Suppression Parts on Cable. (I/O Cable) .....	7
2. DESCRIPTION OF TEST .....	8
3. PRELIMINARY TEST .....	11
3.1 Conducted Emission Test .....	11
3. 2 Radiated Emission Test .....	11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY .....	12
4.1 Conducted Emission Test .....	12
4.2 Radiated Emission Test .....	19
5. LIST OF TEST EQUIPMENT .....	21
6. CONCLUSION .....	22

**ATTACHMENT:     TEST SETUP PHOTOGRAPHS**



## 1. GENERAL INFORMATION

### 1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**  
Its basic purpose is used for communications.

<b>Model</b>	LG-K120H
<b>Additional Model</b>	LGK120H, K120H
<b>FCC ID</b>	ZNFK120H
<b>EUT Type</b>	GSM WCDMA and LTE Phone with BT & WLAN
<b>TX Frequency</b>	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 826.40 MHz to 846.60 MHz (WCDMA 850) 1 852.4 MHz to 1 907.6 MHz (WCDMA 1 900) 1712.4 MHz to 1752.6 MHz (WCDMA 1 700) 1 850.7 MHz to 1 909.3 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 2 496 MHz to 2570 MHz (LTE B7) 704 MHz to 716 MHz (LTE B17)
<b>RX Frequency</b>	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 871.40 MHz to 891.60 MHz (WCDMA 850) 1 932.4 MHz to 1 987.6 MHz (WCDMA 1 900) 2 112.4 MHz to 2 152.6 MHz (WCDMA 1 700) 1 930.00 MHz to 1 990.00 MHz (LTE B2) 2 110 MHz to 2 155 MHz (LTE B4) 2 516 MHz to 2690 MHz (LTE B7) 734 MHz to 746 MHz (LTE B17)



## 1.2 Related Submittal(s) / Grant(s)

Original submittal only.

## 1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
HCT FRN: 0005866421 Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
HCT FRN: 0005866421 Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)



## 1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-K120H	LG	ZNFK120H	USB cable, Earphone
USB cable	EAD62377902	Ningbo Broad	-	EUT, Notebook PC
Earphone	EAB62808211	I-SOUND	-	EUT
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	PPP009D	DELTA Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	TL-WR747N	TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	-	Gateway
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	16 GB	Samsung	-	EUT



## 1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.0
Notebook PC	RJ 45	N/A	N	(D)2.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

\* The marked “(D)” means the data cable and “(P)” means the power cable.

## 1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	EUT End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



## 2. DESCRIPTION OF TEST

### 2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).  
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).  
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

#### [ Conducted Emission Limits ]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

*\*Decreases with the logarithm of the frequency.*





## 2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

### [ Radiated Emission Limits ]

Frequency (MHz)	Antenna Distance (m)	Field Strength ( $\mu\text{V}/\text{m}$ )	Quasi-Peak ( $\text{dB}(\mu\text{V})/\text{m}$ )
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak ( $\text{dB}(\mu\text{V})/\text{m}$ )	Average ( $\text{dB}(\mu\text{V})/\text{m}$ )
Above 1 000	3	74	54




### 2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

### 2.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



### 3. PRELIMINARY TEST

#### 3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

**Operation Mode:**       Data Communication mode

#### 3.2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

**Operation Mode:**       Data Communication mode



## 4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

### 4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:


<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Quasi-Peak, CISPR-Average
<b>Bandwidth</b>	9 kHz (6 dB)
<b>Operation Mode</b>	Data Communication mode
<b>Kind of Test Site</b>	Shielded Room
<b>Temperature</b>	23.7 °C
<b>Relative Humidity</b>	35.1 %
<b>Test Date</b>	December 08, 2015

#### *- Calculation Formula:*

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage



Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)





## QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	51.2	9.000	L1	9.6	14.6	65.8
0.158000	50.6	9.000	L1	9.6	15.0	65.6
0.162000	49.8	9.000	L1	9.6	15.6	65.4
0.166000	49.2	9.000	L1	9.6	16.0	65.2
0.174000	48.0	9.000	L1	9.6	16.8	64.8
0.196000	52.1	9.000	L1	9.6	11.7	63.8
3.766000	38.5	9.000	L1	9.8	17.5	56.0
3.800000	38.0	9.000	L1	9.8	18.0	56.0
3.832000	38.5	9.000	L1	9.8	17.5	56.0
3.846000	39.2	9.000	L1	9.8	16.8	56.0
3.886000	38.8	9.000	L1	9.8	17.2	56.0
3.960000	38.2	9.000	L1	9.8	17.8	56.0
18.818000	35.3	9.000	L1	10.3	24.7	60.0
19.010000	36.0	9.000	L1	10.3	24.0	60.0
19.126000	35.5	9.000	L1	10.3	24.5	60.0
19.212000	36.0	9.000	L1	10.3	24.0	60.0
19.238000	36.0	9.000	L1	10.3	24.0	60.0
19.280000	35.9	9.000	L1	10.3	24.1	60.0




## CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	27.4	9.000	L1	9.6	28.6	56.0
0.154000	21.6	9.000	L1	9.6	34.2	55.8
0.158000	21.2	9.000	L1	9.6	34.4	55.6
0.162000	20.5	9.000	L1	9.6	34.9	55.4
0.166000	20.2	9.000	L1	9.6	35.0	55.2
0.196000	36.3	9.000	L1	9.6	17.5	53.8
3.832000	29.7	9.000	L1	9.8	16.3	46.0
3.836000	29.7	9.000	L1	9.8	16.3	46.0
3.848000	30.3	9.000	L1	9.8	15.7	46.0
3.926000	30.1	9.000	L1	9.8	15.9	46.0
3.938000	29.8	9.000	L1	9.8	16.2	46.0
4.100000	29.8	9.000	L1	9.8	16.2	46.0
18.822000	28.1	9.000	L1	10.3	21.9	50.0
18.986000	27.6	9.000	L1	10.3	22.4	50.0
19.024000	28.6	9.000	L1	10.3	21.4	50.0
19.100000	28.1	9.000	L1	10.3	21.9	50.0
19.324000	27.7	9.000	L1	10.3	22.3	50.0
19.422000	27.6	9.000	L1	10.3	22.4	50.0



Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)







## QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	51.7	9.000	N	9.6	14.3	66.0
0.158000	50.4	9.000	N	9.6	15.2	65.6
0.166000	49.4	9.000	N	9.6	15.8	65.2
0.190000	52.8	9.000	N	9.6	11.2	64.0
0.194000	54.0	9.000	N	9.6	9.9	63.9
0.200000	53.5	9.000	N	9.6	10.1	63.6
3.788000	37.4	9.000	N	9.8	18.6	56.0
3.880000	37.7	9.000	N	9.8	18.3	56.0
3.886000	38.1	9.000	N	9.8	17.9	56.0
3.926000	37.6	9.000	N	9.8	18.4	56.0
3.954000	37.8	9.000	N	9.8	18.2	56.0
3.974000	38.0	9.000	N	9.8	18.0	56.0
16.924000	32.7	9.000	N	10.2	27.3	60.0
19.224000	35.6	9.000	N	10.3	24.4	60.0
19.482000	35.4	9.000	N	10.3	24.6	60.0
20.762000	35.3	9.000	N	10.3	24.7	60.0
21.020000	35.7	9.000	N	10.3	24.3	60.0
21.212000	35.4	9.000	N	10.3	24.6	60.0



## CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	27.1	9.000	N	9.6	28.9	56.0
0.158000	20.9	9.000	N	9.6	34.7	55.6
0.162000	20.3	9.000	N	9.6	35.1	55.4
0.166000	20.2	9.000	N	9.6	35.0	55.2
0.190000	31.6	9.000	N	9.6	22.4	54.0
0.200000	36.2	9.000	N	9.6	17.4	53.6
3.788000	29.6	9.000	N	9.8	16.4	46.0
3.880000	29.4	9.000	N	9.8	16.6	46.0
3.888000	29.3	9.000	N	9.8	16.7	46.0
3.944000	29.0	9.000	N	9.8	17.0	46.0
3.954000	28.9	9.000	N	9.8	17.1	46.0
4.098000	28.7	9.000	N	9.8	17.3	46.0
16.924000	25.5	9.000	N	10.2	24.5	50.0
19.286000	28.0	9.000	N	10.3	22.0	50.0
19.364000	27.5	9.000	N	10.3	22.5	50.0
19.482000	27.1	9.000	N	10.3	22.9	50.0
21.212000	27.7	9.000	N	10.3	22.3	50.0
21.280000	26.9	9.000	N	10.3	23.1	50.0



## 4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

### -For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.1 °C
Relative Humidity	37.0 %
Test Date	December 07, 2015

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
32.103888	23.7	100.0	V	6.0	14.9	16.3	40.0
56.254429	29.6	100.0	V	137.0	15.6	10.4	40.0
66.413868	30.4	400.0	H	4.0	14.6	9.6	40.0
86.572745	31.4	275.0	H	97.0	11.5	8.6	40.0
266.554309	34.5	115.0	H	137.0	16.9	11.5	46.0
800.000000	37.0	100.0	H	240.0	28.4	9.0	46.0

### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



## -For Measurement Above 1 GHz

<b>Rule Part / Standard</b>	FCC PART 15 Subpart B Class B
<b>Detector</b>	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
<b>Highest Operating Frequency</b>	1.0 GHz
<b>Testing Frequency Range</b>	1 GHz to 6 GHz
<b>Operation Mode</b>	Data Communication mode
<b>Kind of Test Site</b>	3 m semi anechoic chamber
<b>Temperature</b>	23.1 °C
<b>Relative Humidity</b>	37.0 %
<b>Test Date</b>	December 07, 2015

Frequency (MHz)	Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1329.308618	50.7	100.0	V	231.0	-9.7	23.3	74.0
1400.050100	49.7	194.0	V	27.0	-9.6	24.3	74.0
1991.633267	54.7	100.0	V	228.0	-7.9	19.3	74.0

Frequency (MHz)	CAverage (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1329.308618	27.6	100.0	V	231.0	-9.7	26.4	54.0
1400.050100	47.2	194.0	V	27.0	-9.6	6.8	54.0
1991.633267	30.0	100.0	V	228.0	-7.9	24.0	54.0

### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



## 5. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<b><u>Conducted Emission</u></b>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	01.13.2015
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	06.11.2015
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	100073	1 year	01.13.2015
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
<b><u>Radiated Emission</u></b>					
<b>-For measurement below 1 GHz</b>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.01.2015
<input checked="" type="checkbox"/> Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17.2014
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.05.2015
<input type="checkbox"/> Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-
<b>-For measurement above 1 GHz</b>					
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.01.2015
<input checked="" type="checkbox"/> Antenna master	HD GmbH	MA240	240/520	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
<input checked="" type="checkbox"/> Turn Table	EMCO	1060-2M	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	EMCO	2090	9702-1224	N/A	-
<input type="checkbox"/> Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.06.2015
<input checked="" type="checkbox"/> Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.15.2015
<input checked="" type="checkbox"/> Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.07.2014
<input type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.05.2015
<input type="checkbox"/> Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32	-	-	-



## 6. CONCLUSION

The data collected shows that the **EUT Type: GSM WCDMA and LTE Phone with BT & WLAN, Model: LG-K120H, FCC ID: ZNFK120H** complies with §15.107 and §15.109 of the FCC rules.