



SAR EVALUATION REPORT

Applicant Name:
 LG Electronics U.S.A., Inc.
 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
 United States

Date of Testing:
 02/20/20 - 03/09/20
Test Site/Location:
 PCTEST Lab, Columbia, MD, USA
Document Serial No.:
 1M2002170021-01-R1.ZNF

FCC ID: ZNFK300UM
APPLICANT: LG ELECTRONICS U.S.A., INC.

DUT Type: Portable Handset
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: LM-K300UM
Additional Model(s): LMK300UM, K300UM, LM-K300WM, LMK300WM, K300WM, LM-K300QM6, LMK300QM6, K300QM6

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1g Head (W/kg)	1g Body-Worn (W/kg)	1g Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.52	0.66	0.66
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.22	0.32	0.54
PCE	UMTS 850	826.40 - 846.60 MHz	0.39	0.51	0.51
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.28	0.86	0.86
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.48	0.87	0.86
PCE	Cell CDMA/EVDO	824.70 - 848.31 MHz	0.38	0.50	0.46
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.45	0.74	0.65
PCE	LTE Band 12	699.7 - 715.3 MHz	0.36	0.43	0.55
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A	N/A	N/A
PCE	LTE Band 13	779.5 - 784.5 MHz	0.40	0.51	0.51
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.36	0.46	0.46
PCE	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	0.28	0.91	0.91
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.45	0.88	0.93
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A
PCE	LTE Band 7	2502.5 - 2567.5 MHz	0.18	0.81	0.81
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.35	0.30	0.30
DSS/DTS	Bluetooth	2402 - 2480 MHz	< 0.1	N/A	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			0.87	1.21	1.24

Note: This revised Test Report (S/N:1M2002170021-01-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
 President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: ZNFK300UM	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 1 of 73

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	9
3	INTRODUCTION	10
4	DOSIMETRIC ASSESSMENT	11
5	DEFINITION OF REFERENCE POINTS.....	12
6	TEST CONFIGURATION POSITIONS.....	13
7	RF EXPOSURE LIMITS	16
8	FCC MEASUREMENT PROCEDURES.....	17
9	RF CONDUCTED POWERS	23
10	SYSTEM VERIFICATION.....	46
11	SAR DATA SUMMARY	49
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	63
13	SAR MEASUREMENT VARIABILITY	68
14	EQUIPMENT LIST.....	69
15	MEASUREMENT UNCERTAINTIES.....	70
16	CONCLUSION.....	71
17	REFERENCES	72
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: SAR TISSUE SPECIFICATIONS		
APPENDIX D: SAR SYSTEM VALIDATION		
APPENDIX E: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX F: PROBE AND DIPOLE CALIBRAITON CERTIFICATIONS		

FCC ID: ZNFK300UM	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 2 of 73

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
Cell. CDMA/EVDO	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 7	Voice/Data	2502.5 - 2567.5 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Output Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
			1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots
GSM/GPRS/EDGE 850	Maximum	32.7	32.7	31.7	29.7	28.7	27.7	25.7	24.7	23.7
	Nominal	32.2	32.2	31.2	29.2	28.2	27.2	25.2	24.2	23.2
GSM/GPRS/EDGE 1900	Maximum	30.7	30.7	28.7	26.7	25.7	26.7	24.7	23.7	22.7
	Nominal	30.2	30.2	28.2	26.2	25.2	26.2	24.2	23.2	22.2

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 3 of 73

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	25.2	25.2	25.2	25.2
	Nominal	24.7	24.7	24.7	24.7
UMTS Band 4 (1750 MHz)	Maximum	24.7	24.7	24.7	24.7
	Nominal	24.2	24.2	24.2	24.2
UMTS Band 2 (1900 MHz)	Maximum	24.7	24.7	24.7	24.7
	Nominal	24.2	24.2	24.2	24.2

Mode / Band		Modulated Average (dBm)
Cell. CDMA/EVDO	Maximum	25.2
	Nominal	24.7
PCS CDMA/EVDO	Maximum	24.7
	Nominal	24.2

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 4 of 73	

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	25.2
	Nominal	24.7
LTE Band 17	Maximum	25.2
	Nominal	24.7
LTE Band 13	Maximum	25.2
	Nominal	24.7
LTE Band 5 (Cell)	Maximum	25.2
	Nominal	24.7
LTE Band 66 (AWS)	Maximum	24.7
	Nominal	24.2
LTE Band 4 (AWS)	Maximum	24.7
	Nominal	24.2
LTE Band 25 (PCS)	Maximum	24.7
	Nominal	24.2
LTE Band 2 (PCS)	Maximum	24.7
	Nominal	24.2
LTE Band 7	Maximum	22.7
	Nominal	22.2

1.3.2 Maximum Bluetooth and WLAN Output

Mode / Band		Modulated Average (dBm)		
Channel		1	2-10	11
IEEE 802.11b (2.4 GHz)	Maximum	19.0		
	Nominal	18.0		
IEEE 802.11g (2.4 GHz)	Maximum	15.0	17.5	15.0
	Nominal	14.0	16.5	14.0
IEEE 802.11n (2.4 GHz)	Maximum	14.0	17.0	14.0
	Nominal	13.0	16.0	13.0

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 5 of 73

Mode / Band		Modulated Average (dBm)
Bluetooth 1 Mbps (GFSK)	Maximum	10.0
	Nominal	9.0
Bluetooth 2 Mbps (DPSK)	Maximum	9.5
	Nominal	8.5
Bluetooth 3 Mbps (8DPSK)	Maximum	9.5
	Nominal	8.5
Bluetooth LE	Maximum	6.5
	Nominal	5.5

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. The overall diagonal dimension of the device is ≤160 mm and the diagonal display is ≤150 mm. A diagram showing the location of the device antennas can be found in Appendix E.

**Table 1-1
Device Edges/Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	No	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	No
UMTS 850	Yes	Yes	No	Yes	No	Yes
UMTS 1750	Yes	Yes	No	Yes	Yes	No
UMTS 1900	Yes	Yes	No	Yes	Yes	No
Cell. EVDO	Yes	Yes	No	Yes	No	Yes
PCS EVDO	Yes	Yes	No	Yes	Yes	No
LTE Band 12	Yes	Yes	No	Yes	No	Yes
LTE Band 13	Yes	Yes	No	Yes	No	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	No	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	Yes	No
LTE Band 25 (PCS)	Yes	Yes	No	Yes	Yes	No
LTE Band 7	Yes	Yes	No	Yes	Yes	No
2.4 GHz WLAN	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III. The distances between the transmit antennas and the edges of the device are included in the filing.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 6 of 73

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

**Table 1-2
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	1x CDMA voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
2	1x CDMA voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	^Bluetooth Tethering is considered
3	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	
4	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	^Bluetooth Tethering is considered
5	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	
6	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	^Bluetooth Tethering is considered
7	LTE + 2.4 GHz WI-FI	Yes	Yes	Yes	
8	LTE + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	^Bluetooth Tethering is considered
9	CDMA/EVDO data + 2.4 GHz WI-FI	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
10	CDMA/EVDO data + 2.4 GHz Bluetooth	Yes^*	Yes*	Yes^	* Pre-installed VOIP applications are considered ^Bluetooth Tethering is considered
11	GPRS/EDGE + 2.4 GHz WI-FI	Yes*	Yes*	Yes	* Pre-installed VOIP applications are considered
12	GPRS/EDGE + 2.4 GHz Bluetooth	Yes^*	Yes*	Yes^	* Pre-installed VOIP applications are considered ^Bluetooth Tethering is considered

- 2.4 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
- Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
- This device supports VOLTE.
- This device supports Bluetooth Tethering.

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn and hotspot Bluetooth SAR was not required; $[(10/10) * \sqrt{2.480}] = 1.6 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 7 of 73	

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

This device supports 64QAM on the uplink for LTE Operations. Conducted powers for 64QAM uplink configurations were measured per Section 5.1 of FCC KDB Publication 941225D05v02r05. SAR was not required for 64QAM since the highest maximum output power for 64QAM is $\leq \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg, per Section 5.2.4 of FCC KDB Publication 941225 D05v02r05.

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 8 of 73

2

LTE INFORMATION

LTE Information					
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 7 (2502.5 - 2567.5 MHz)				
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 17: 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)		715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)		714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)		713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)		711 (23130)
LTE Band 17: 5 MHz	706.5 (23755)		710 (23790)		713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)		710 (23790)		711 (23800)
LTE Band 13: 5 MHz	779.5 (23205)		782 (23230)		784.5 (23255)
LTE Band 13: 10 MHz	N/A		782 (23230)		N/A
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)		848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)		847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)		846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)		844 (20600)
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)		1745 (132322)		1779.3 (132665)
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)		1745 (132322)		1778.5 (132657)
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)		1745 (132322)		1777.5 (132647)
LTE Band 66 (AWS): 10 MHz	1715 (132022)		1745 (132322)		1775 (132622)
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)		1745 (132322)		1772.5 (132597)
LTE Band 66 (AWS): 20 MHz	1720 (132072)		1745 (132322)		1770 (132572)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)		1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)		1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)		1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)		1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)		1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)		1745 (20300)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)		1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)		1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)		1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)		1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)		1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)		1905 (26590)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)		1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)		1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)		1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)		1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)		1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)		1900 (19100)
LTE Band 7: 5 MHz	2502.5 (20775)		2535 (21100)		2567.5 (21425)
LTE Band 7: 10 MHz	2505 (20800)		2535 (21100)		2565 (21400)
LTE Band 7: 15 MHz	2507.5 (20825)		2535 (21100)		2562.5 (21375)
LTE Band 7: 20 MHz	2510 (20850)		2535 (21100)		2560 (21350)
UE Category	DL UE Cat 4, UL UE Cat 5				
Modulations Supported in UL	QPSK, 16QAM, 64QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	Not Supported				
LTE Additional Information	This device does not support full CA features on 3GPP Release 11. All uplink communications are identical to the Release 8 Specifications. The following LTE Release 11 Features are not supported: LTE CA, Relay, HetNet, Enhanced MIMO, eICIC, WIF Offloading, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 9 of 73	

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 10 of 73	

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n-1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 11 of 73

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 12 of 73

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 13 of 73




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 14 of 73

contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1g body and 10g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 15 of 73

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 16 of 73

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 17 of 73

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
$\frac{I_{or}}{I_{or}}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
$\frac{I_{or}}{I_{or}}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with EVDO capabilities, the 3G SAR test reduction procedure is applied to EVDO Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 18 of 73	

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For EVDO data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with EVDO Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCH_n and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1s". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 19 of 73	

12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5.6 SAR Measurements Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 20 of 73	

- i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
 - c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
 - d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.7.2 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 21 of 73	

8.7.3 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.7.4 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.7.5 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6).

8.7.6 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 22 of 73	

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

Table 9-1
Maximum Conducted Power

Band	Channel	Frequency	SO55 [dBm]	SO55 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	RC1	RC3	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	1013	824.7	25.08	25.14	24.13	25.13	24.57	24.46
	384	836.52	25.12	25.17	24.12	25.18	24.66	24.66
	777	848.31	25.11	25.16	24.16	25.16	24.54	24.55
PCS	25	1851.25	24.48	24.56	23.56	24.56	24.68	24.69
	600	1880	24.34	24.41	23.43	24.44	24.50	24.51
	1175	1908.75	24.25	24.33	23.34	24.37	24.52	24.54

Note: RC1 is only applicable for IS-95 compatibility.




Figure 9-1
Power Measurement Setup

FCC ID: ZNFK300UM	PCTEST	SAR EVALUATION REPORT	LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 23 of 73

9.2 GSM Conducted Powers

Table 9-2
Maximum Conducted Power

Maximum Burst-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.61	32.59	31.42	29.39	28.40	27.57	25.33	24.24	23.16
	190	32.69	32.56	31.40	29.38	28.37	27.62	25.41	24.33	23.19
	251	32.66	32.57	31.41	29.42	28.42	27.62	25.46	24.26	23.25
GSM 1900	512	30.40	30.40	28.45	26.49	25.70	26.44	24.50	23.30	22.09
	661	30.27	30.28	28.22	26.21	25.40	26.45	24.49	23.31	22.12
	810	30.44	30.45	28.27	26.20	25.42	26.53	24.58	23.39	22.25

Calculated Maximum Frame-Averaged Output Power										
Band	Channel	Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
		GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.41	23.39	25.23	24.96	25.22	18.37	19.14	19.81	19.98
	190	23.49	23.36	25.21	24.95	25.19	18.42	19.22	19.90	20.01
	251	23.46	23.37	25.22	24.99	25.24	18.42	19.27	19.83	20.07
GSM 1900	512	21.20	21.20	22.26	22.06	22.52	17.24	18.31	18.87	18.91
	661	21.07	21.08	22.03	21.78	22.22	17.25	18.30	18.88	18.94
	810	21.24	21.25	22.08	21.77	22.24	17.33	18.39	18.96	19.07

GSM 850	Frame Avg.Targets:	23.00	23.00	25.01	24.77	25.02	18.00	19.01	19.77	20.02
GSM 1900		21.00	21.00	22.01	21.77	22.02	17.00	18.01	18.77	19.02

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 24 of 73	

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8-PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 12 (Max 4 Tx uplink slots)
EDGE Multislot class: 12 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A




Figure 9-2
Power Measurement Setup

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT		 Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 25 of 73

9.3 UMTS Conducted Powers

**Table 9-3
Maximum Conducted Power**

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	25.05	25.06	25.07	24.57	24.45	24.44	24.60	24.55	24.35	-
99		12.2 kbps AMR	25.06	25.05	25.08	24.58	24.42	24.44	24.59	24.52	24.33	-
6	HSDPA	Subtest 1	24.12	24.07	24.03	23.56	23.44	23.50	23.62	23.49	23.50	1
6		Subtest 2	24.00	24.03	23.99	23.51	23.41	23.46	23.57	23.64	23.43	1
6		Subtest 3	23.43	23.56	23.50	23.10	22.92	22.93	23.05	22.95	23.02	1.5
6		Subtest 4	23.55	23.50	23.44	23.09	22.96	22.90	23.03	22.86	22.96	1.5
6	HSUPA	Subtest 1	22.15	22.11	22.07	21.57	21.45	21.45	21.55	21.42	21.43	3
6		Subtest 2	22.14	22.09	22.06	21.56	21.35	21.39	21.52	21.38	21.69	3
6		Subtest 3	23.10	23.05	23.01	22.54	22.41	22.39	22.56	22.41	22.46	2
6		Subtest 4	21.66	21.65	21.58	21.08	20.95	20.93	21.12	20.98	21.00	3.5
6		Subtest 5	23.04	23.05	23.08	22.51	22.37	22.38	22.64	22.65	22.67	2
8	DC-HSDPA	Subtest 1	24.10	24.15	24.14	23.67	23.56	23.60	23.69	23.64	23.47	1
8		Subtest 2	24.11	24.12	24.13	23.70	23.61	23.61	23.70	23.63	23.46	1
8		Subtest 3	23.57	23.59	23.56	23.20	23.08	23.09	23.20	23.09	23.00	1.5
8		Subtest 4	23.55	23.50	23.62	23.19	23.10	23.07	23.19	23.10	22.99	1.5

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA



**Figure 9-3
Power Measurement Setup**

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 26 of 73	

9.4 LTE Conducted Powers

9.4.1

LTE Band 12

Table 9-4
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.82	0	0
	1	25	24.99		0
	1	49	24.84		0
	25	0	23.88	0-1	1
	25	12	23.90		1
	25	25	23.85		1
	50	0	23.88		1
16QAM	1	0	23.78	0-1	1
	1	25	23.96		1
	1	49	23.72		1
	25	0	22.97	0-2	2
	25	12	23.00		2
	25	25	22.94		2
	50	0	22.93		2
64QAM	1	0	22.98	0-2	2
	1	25	23.10		2
	1	49	23.00		2
	25	0	22.00	0-3	3
	25	12	21.99		3
	25	25	21.93		3
	50	0	22.01		3

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 27 of 73

**Table 9-5
LTE Band 12 Conducted Powers - 5 MHz Bandwidth**

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.93	24.96	24.85	0	0
	1	12	25.12	25.02	25.06		0
	1	24	24.98	24.97	24.82		0
	12	0	23.92	24.03	24.02	0-1	1
	12	6	24.05	24.06	24.01		1
	12	13	23.99	24.04	23.94		1
16QAM	25	0	23.93	23.99	24.00	0-1	1
	1	0	23.87	23.80	23.89		1
	1	12	24.08	24.11	24.16		1
	1	24	23.86	23.96	23.90	0-2	1
	12	0	23.02	23.08	23.00		2
	12	6	23.10	23.15	23.00		2
64QAM	12	13	22.99	23.08	22.91	0-2	2
	25	0	22.95	23.09	22.95		2
	1	0	23.02	22.91	22.85		0-3
	1	12	23.16	22.84	23.10	2	
	1	24	22.86	22.84	22.86	2	
	12	0	21.96	22.00	21.95	0-3	3
12	6	22.02	22.01	22.03	3		
12	13	21.99	21.99	21.89	3		
	25	0	21.95	21.92	22.08		3

**Table 9-6
LTE Band 12 Conducted Powers - 3 MHz Bandwidth**

LTE Band 12 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.97	25.00	24.99	0	0	
	1	7	25.04	25.12	25.08		0	
	1	14	24.91	24.96	24.94		0	
	8	0	23.95	23.98	24.05	0-1	1	
	8	4	24.04	24.07	24.09		1	
	8	7	24.00	24.01	24.01		1	
16QAM	15	0	23.98	23.99	23.98	0-1	1	
	1	0	23.85	24.01	23.81		0-1	1
	1	7	23.83	23.99	23.92			1
	1	14	23.72	23.92	23.77	0-2		1
	8	0	22.97	23.06	23.02		2	
	8	4	23.02	23.14	23.04		2	
64QAM	8	7	22.92	23.09	22.95	0-2	2	
	15	0	22.93	23.00	22.98		2	
	1	0	23.11	23.01	22.93		0-2	2
	1	7	23.19	23.03	22.93	2		
	1	14	23.17	23.14	22.90	0-3		2
	8	0	22.02	22.06	21.96		3	
8	4	22.03	22.10	21.98	3			
	8	7	22.01	21.97	21.97		3	
	15	0	21.98	21.89	21.94		3	

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 28 of 73	

Table 9-7
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.90	24.95	25.09	0	0
	1	2	24.98	25.07	25.18		0
	1	5	24.86	25.00	25.06		0
	3	0	25.06	25.04	25.07		0
	3	2	25.12	25.08	25.08		0
	3	3	25.07	25.13	25.02		0
	6	0	24.00	24.07	24.08	0-1	1
16QAM	1	0	23.72	23.98	23.72	0-1	1
	1	2	23.75	24.05	23.78		1
	1	5	23.71	24.05	23.75		1
	3	0	24.11	24.11	24.03		1
	3	2	23.96	24.00	24.08		1
	3	3	23.94	24.08	24.04		1
	6	0	23.11	22.95	23.19	0-2	2
64QAM	1	0	23.08	23.04	23.14	0-2	2
	1	2	23.12	23.00	23.10		2
	1	5	23.07	23.02	23.15		2
	3	0	22.96	22.93	22.98		2
	3	2	23.12	23.00	23.04		2
	3	3	22.94	22.98	23.01		2
	6	0	21.88	21.90	21.96	0-3	3

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 29 of 73	

9.4.2

LTE Band 13

Table 9-8
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.00	0	0
	1	25	25.08		0
	1	49	24.95		0
	25	0	23.87	0-1	1
	25	12	24.00		1
	25	25	23.96		1
	50	0	23.92		1
16QAM	1	0	24.12	0-1	1
	1	25	24.20		1
	1	49	24.18		1
	25	0	22.93	0-2	2
	25	12	23.00		2
	25	25	22.98		2
	50	0	22.94		2
64QAM	1	0	22.96	0-2	2
	1	25	23.10		2
	1	49	23.09		2
	25	0	21.98	0-3	3
	25	12	21.99		3
	25	25	21.92		3
	50	0	21.94		3

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 30 of 73

**Table 9-9
LTE Band 13 Conducted Powers - 5 MHz Bandwidth**

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.80	0	0
	1	12	24.93		0
	1	24	24.73		0
	12	0	23.85	0-1	1
	12	6	23.93		1
	12	13	23.90		1
	25	0	23.84		1
16QAM	1	0	23.78	0-1	1
	1	12	24.04		1
	1	24	23.75		1
	12	0	22.87	0-2	2
	12	6	22.95		2
	12	13	22.86		2
	25	0	23.00		2
64QAM	1	0	22.96	0-2	2
	1	12	23.07		2
	1	24	23.09		2
	12	0	21.97	0-3	3
	12	6	21.91		3
	12	13	21.99		3
	25	0	21.96		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 31 of 73

9.4.3

LTE Band 5 (Cell)

Table 9-10
 LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.86	0	0
	1	25	25.04		0
	1	49	24.92		0
	25	0	23.95	0-1	1
	25	12	24.00		1
	25	25	23.94		1
	50	0	23.97		1
16QAM	1	0	23.84	0-1	1
	1	25	23.97		1
	1	49	23.81		1
	25	0	23.00	0-2	2
	25	12	23.02		2
	25	25	22.98		2
	50	0	22.96		2
64QAM	1	0	23.10	0-2	2
	1	25	23.19		2
	1	49	23.09		2
	25	0	22.00	0-3	3
	25	12	21.98		3
	25	25	21.96		3
	50	0	21.93		3

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 32 of 73

**Table 9-11
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth**

LTE Band 5 (Cell) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.70	24.81	24.62	0	0	
	1	12	24.98	25.09	24.91		0	
	1	24	24.76	24.80	24.62		0	
	16QAM	12	0	23.88	23.90	23.87	0-1	1
		12	6	23.91	23.98	23.94		1
		12	13	23.89	23.89	23.78		1
		25	0	23.82	23.90	23.89		1
1		0	23.74	24.04	23.76	1		
64QAM	1	12	24.02	24.06	24.08	0-1	1	
	1	24	23.80	24.12	23.78		1	
	12	0	22.91	22.97	22.88		0-2	2
	12	6	22.97	23.08	22.97	2		
	12	13	22.96	22.97	22.87	2		
	25	0	22.89	23.05	22.89	2		
	64QAM	1	0	23.05	23.04	22.93	0-2	2
1		12	23.14	23.00	23.06	2		
1		24	22.99	23.12	23.04	2		
64QAM		12	0	21.94	21.96	21.99	0-3	3
		12	6	21.97	22.02	21.97		3
		12	13	22.02	21.93	22.01		3
		25	0	21.90	21.96	21.94		3

**Table 9-12
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth**

LTE Band 5 (Cell) 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.72	24.80	24.79	0	0	
	1	7	24.90	24.96	24.90		0	
	1	14	24.77	24.84	24.74		0	
	16QAM	8	0	23.86	23.82	23.85	0-1	1
		8	4	23.83	23.90	23.91		1
		8	7	23.77	23.84	23.84		1
		15	0	23.81	23.88	23.84		1
1		0	23.76	23.98	23.75	0-1		1
1	7	23.73	23.90	23.85	1			
1	14	23.76	23.99	23.76	1			
64QAM	8	0	22.80	22.99	22.92		0-2	2
	8	4	22.85	23.03	22.93			2
	8	7	22.78	22.95	22.85	2		
	15	0	22.77	22.88	22.91	2		
	1	0	23.15	23.08	23.09	0-2		2
1	7	23.05	23.20	23.14	2			
1	14	23.06	23.14	23.05	2			
64QAM	8	0	21.99	21.98	21.86	0-3	3	
	8	4	22.01	22.01	21.87		3	
	8	7	21.80	22.00	21.92		3	
	64QAM	15	0	21.92	21.95		21.95	3

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 33 of 73	

Table 9-13
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.65	24.86	24.65	0	0
	1	2	24.73	24.95	24.72		0
	1	5	24.66	24.87	24.63		0
	3	0	24.83	24.89	24.80		0
	3	2	24.87	24.89	24.88		0
	3	3	24.83	24.87	24.83		0
	6	0	23.87	23.85	23.83		0-1
16QAM	1	0	23.78	23.64	23.69	0-1	1
	1	2	23.85	23.70	23.73		1
	1	5	23.77	23.67	23.69		1
	3	0	23.90	24.03	23.89		1
	3	2	23.95	24.03	23.93		1
	3	3	23.92	24.03	23.92		1
	6	0	23.01	23.06	22.98		0-2
64QAM	1	0	23.12	23.10	23.07	0-2	2
	1	2	23.20	23.17	23.20		2
	1	5	23.08	23.02	23.06		2
	3	0	23.18	23.08	23.09		2
	3	2	23.09	23.18	23.00		2
	3	3	23.08	23.03	23.07		2
	6	0	21.96	21.92	22.02		0-3

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 34 of 73	

9.4.4

LTE Band 66 (AWS)

Table 9-14
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.17	24.15	24.00	0	0	
	1	50	24.40	24.48	24.26		0	
	1	99	24.14	24.20	23.97		0	
	50	0	23.27	23.27	23.32	0-1	1	
	50	25	23.30	23.36	23.31		1	
	50	50	23.24	23.21	23.27		1	
16QAM	100	0	23.29	23.21	23.28	0-1	1	
	1	0	23.45	23.63	23.56		0-1	1
	1	50	23.70	23.70	23.66			1
	1	99	23.49	23.62	23.53	0-2		1
	50	0	22.32	22.37	22.44		2	
	50	25	22.36	22.36	22.43		2	
64QAM	50	50	22.41	22.27	22.36	0-2	2	
	100	0	22.39	22.30	22.34		2	
	1	0	22.39	22.32	22.38		0-2	2
	1	50	22.56	22.55	22.58	0-3		2
	1	99	22.53	22.53	22.41			2
	50	0	21.40	21.36	21.44		0-3	3
50	25	21.44	21.37	21.40	3			
50	50	21.44	21.32	21.33	3			
100	0	21.45	21.30	21.35		3		

Table 9-15
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.33	24.39	24.41	0	0	
	1	36	24.35	24.60	24.55		0	
	1	74	24.29	24.42	24.42		0	
	36	0	23.52	23.37	23.40	0-1	1	
	36	18	23.37	23.39	23.30		1	
	36	37	23.35	23.27	23.29		1	
16QAM	75	0	23.24	23.40	23.50	0-1	1	
	1	0	23.39	23.50	23.36		0-1	1
	1	36	23.61	23.55	23.48			1
	1	74	23.43	23.54	23.36	0-2		1
	36	0	22.67	22.28	22.28		2	
	36	18	22.70	22.50	22.34		2	
64QAM	36	37	22.66	22.40	22.66	0-2	2	
	75	0	22.68	22.50	22.67		2	
	1	0	22.41	22.44	22.69		0-2	2
	1	36	22.46	22.48	22.43	0-3		2
	1	74	22.49	22.45	22.47			2
	36	0	21.44	21.36	21.36		0-3	3
36	18	21.44	21.39	21.44	3			
36	37	21.45	21.37	21.49	3			
75	0	21.41	21.31	21.49		3		

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 35 of 73	

Table 9-16
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.47	24.53	24.53	0	0
	1	25	24.69	24.48	24.69		0
	1	49	24.43	24.54	24.48		0
	25	0	23.56	23.56	23.65	0-1	1
	25	12	23.59	23.59	23.63		1
	25	25	23.58	23.55	23.55		1
16QAM	50	0	23.59	23.56	23.60	0-1	1
	1	0	23.26	23.56	23.47		1
	1	25	23.35	23.61	23.52		1
	1	49	23.27	23.62	23.43	0-2	1
	25	0	22.60	22.64	22.67		2
	25	12	22.49	22.66	22.54		2
64QAM	25	25	22.52	22.60	22.48	0-2	2
	50	0	22.69	22.63	22.64		2
	1	0	22.49	22.42	22.47		0-3
	1	25	22.59	22.39	22.65	2	
	1	49	22.65	22.62	22.56	2	
	25	0	21.44	21.39	21.48	0-3	3
25	12	21.41	21.31	21.46	3		
25	25	21.42	21.27	21.41	3		
50	0	21.55	21.40	21.48		3	

Table 9-17
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.46	24.52	24.34	0	0	
	1	12	24.44	24.57	24.61		0	
	1	24	24.43	24.54	24.36		0	
	12	0	23.54	23.53	23.53	0-1	1	
	12	6	23.62	23.59	23.57		1	
	12	13	23.61	23.52	23.53		1	
16QAM	25	0	23.51	23.51	23.52	0-1	1	
	1	0	23.39	23.58	23.43		0-1	1
	1	12	23.62	23.37	23.45			1
	1	24	23.40	23.63	23.47	0-2		1
	12	0	22.63	22.62	22.62		2	
	12	6	22.68	22.68	22.63		2	
64QAM	12	13	22.62	22.61	22.62	0-2	2	
	25	0	22.57	22.64	22.59		2	
	1	0	22.34	22.36	22.44		0-2	2
	1	12	22.63	22.63	22.66	2		
	1	24	22.28	22.37	22.41	0-3		2
	12	0	21.40	21.32	21.38		3	
12	6	21.45	21.52	21.42	3			
12	13	21.46	21.38	21.45	0-3	3		
25	0	21.34	21.41	21.37		3		

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 36 of 73

Table 9-18
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.46	24.53	24.49	0	0
	1	7	24.57	24.66	24.64		0
	1	14	24.43	24.53	24.48		0
	8	0	23.54	23.54	23.55	0-1	1
	8	4	23.60	23.57	23.62		1
	8	7	23.53	23.53	23.56		1
16QAM	15	0	23.51	23.52	23.52	0-1	1
	1	0	23.28	23.56	23.41		1
	1	7	23.37	23.66	23.55		1
	1	14	23.19	23.57	23.42	0-2	1
	8	0	22.49	22.66	22.63		2
	8	4	22.55	22.70	22.68		2
64QAM	8	7	22.48	22.62	22.59	0-2	2
	15	0	22.53	22.58	22.59		2
	1	0	22.49	22.44	22.48		0-2
	1	7	22.30	22.64	22.42	2	
	1	14	22.43	22.53	22.52	0-3	
	8	0	21.55	21.35	21.46		3
8	4	21.30	21.37	21.41	3		
64QAM	8	7	21.50	21.41	21.45	0-3	3
	15	0	21.54	21.36	21.36		3

Table 9-19
LTE Band 66 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.47	24.61	24.44	0	0
	1	2	24.58	24.37	24.54		0
	1	5	24.48	24.59	24.46		0
	3	0	24.60	24.63	24.63	0	0
	3	2	24.62	24.63	24.45		0
	3	3	24.59	24.62	24.65		0
16QAM	6	0	23.58	23.61	23.64	0-1	1
	1	0	23.56	23.30	23.27	0-1	1
	1	2	23.69	23.37	23.31		1
	1	5	23.57	23.31	23.32		1
	3	0	23.58	23.63	23.39	0-1	1
	3	2	23.55	23.69	23.44		1
3	3	23.49	23.47	23.59	1		
64QAM	6	0	22.47	22.38	22.35	0-2	2
	1	0	22.41	22.45	22.47	0-2	2
	1	2	22.51	22.50	22.45		2
	1	5	22.32	22.34	22.46		2
	3	0	22.40	22.39	22.43	0-2	2
	3	2	22.33	22.43	22.56		2
3	3	22.44	22.54	22.44	2		
6	0	21.33	21.37	21.32	0-3	3	

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 37 of 73

9.4.5

LTE Band 25 (PCS)

Table 9-20
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.25	24.33	24.04	0	0
	1	50	24.51	24.52	24.27		0
	1	99	24.34	24.29	24.02		0
	50	0	23.34	23.38	23.37	0-1	1
	50	25	23.44	23.46	23.35		1
	50	50	23.39	23.43	23.20		1
16QAM	100	0	23.32	23.40	23.24	0-1	1
	1	0	23.69	23.67	23.60		1
	1	50	23.61	23.70	23.65		1
	1	99	23.68	23.68	23.60	0-2	1
	50	0	22.41	22.47	22.50		2
	50	25	22.54	22.51	22.46		2
64QAM	50	50	22.47	22.53	22.34	0-2	2
	100	0	22.43	22.50	22.33		2
	1	0	22.32	22.41	22.30		0-2
	1	50	22.58	22.53	22.64	2	
	1	99	22.32	22.35	22.57	2	
	64QAM	50	0	21.30	21.35	21.40	0-3
50		25	21.39	21.30	21.44	3	
50		50	21.32	21.37	21.23	3	
100		0	21.29	21.43	21.29	3	

Table 9-21
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.36	24.18	24.15	0	0
	1	36	24.50	24.28	24.31		0
	1	74	24.33	24.14	24.17		0
	36	0	23.41	23.34	23.45	0-1	1
	36	18	23.47	23.38	23.45		1
	36	37	23.45	23.36	23.41		1
16QAM	75	0	23.45	23.40	23.40	0-1	1
	1	0	23.40	23.55	23.39		1
	1	36	23.39	23.47	23.30		1
	1	74	23.40	23.57	23.43	0-2	1
	36	0	22.39	22.34	22.45		2
	36	18	22.43	22.43	22.48		2
64QAM	36	37	22.40	22.39	22.40	0-2	2
	75	0	22.39	22.37	22.38		2
	1	0	22.43	22.41	22.40		0-2
	1	36	22.59	22.47	22.49	2	
	1	74	22.34	22.53	22.21	2	
	64QAM	36	0	21.35	21.39	21.40	0-3
36		18	21.34	21.41	21.37	3	
36		37	21.39	21.39	21.28	3	
75		0	21.39	21.35	21.31	3	

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 38 of 73	

**Table 9-22
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth**

LTE Band 25 (PCS) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.29	24.23	24.19	0	0	
	1	25	24.47	24.40	24.44		0	
	1	49	24.28	24.25	24.26		0	
	25	0	23.42	23.34	23.41	0-1	1	
	25	12	23.46	23.39	23.42		1	
	25	25	23.49	23.40	23.28		1	
16QAM	50	0	23.56	23.35	23.36	0-1	1	
	1	0	23.34	23.55	23.40		0-1	1
	1	25	23.30	23.50	23.36			1
	1	49	23.35	23.52	23.34	0-2		1
	25	0	22.56	22.47	22.53		2	
	25	12	22.60	22.45	22.47		2	
64QAM	25	25	22.61	22.49	22.41	0-2	2	
	50	0	22.55	22.43	22.38		2	
	1	0	22.46	22.50	22.48		0-2	2
	1	25	22.55	22.56	22.40	2		
	1	49	22.23	22.49	22.58	0-3		2
	25	0	21.36	21.43	21.41		3	
25	12	21.38	21.39	21.39	3			
64QAM	25	25	21.34	21.46	21.30	0-3	3	
	50	0	21.39	21.45	21.36		3	

**Table 9-23
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth**

LTE Band 25 (PCS) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.31	24.26	24.13	0	0	
	1	12	24.49	24.52	24.38		0	
	1	24	24.27	24.24	24.15		0	
	12	0	23.45	23.30	23.41	0-1	1	
	12	6	23.44	23.31	23.41		1	
	12	13	23.43	23.34	23.28		1	
16QAM	25	0	23.40	23.30	23.34	0-1	1	
	1	0	23.30	23.38	23.26		0-1	1
	1	12	23.50	23.44	23.51			1
	1	24	23.30	23.29	23.26	0-2		1
	12	0	22.50	22.37	22.43		2	
	12	6	22.53	22.48	22.49		2	
64QAM	12	13	22.53	22.45	22.32	0-2	2	
	25	0	22.48	22.44	22.40		2	
	1	0	22.36	22.33	22.39		0-2	2
	1	12	22.60	22.68	22.63	2		
	1	24	22.58	22.38	22.35	0-3		2
	12	0	21.16	21.32	21.44		3	
12	6	21.47	21.52	21.39	3			
64QAM	12	13	21.47	21.43	21.25	0-3	3	
	25	0	21.34	21.31	21.31		3	

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 39 of 73

Table 9-24
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.34	24.22	24.27	0	0
	1	7	24.41	24.39	24.41		0
	1	14	24.26	24.23	24.23		0
	8	0	23.42	23.28	23.39	0-1	1
	8	4	23.43	23.31	23.40		1
	8	7	23.39	23.27	23.33		1
16QAM	15	0	23.39	23.32	23.36	0-1	1
	1	0	23.35	23.50	23.40		1
	1	7	23.32	23.61	23.34		1
	1	14	23.32	23.50	23.33	0-2	1
	8	0	22.40	22.44	22.43		2
	8	4	22.44	22.46	22.45		2
64QAM	8	7	22.37	22.38	22.33	0-2	2
	15	0	22.44	22.34	22.45		2
	1	0	22.39	22.44	22.50		0-2
	1	7	22.59	22.55	22.56	2	
	1	14	22.45	22.52	22.42	0-3	
	8	0	21.36	21.39	21.33		3
8	4	21.41	21.39	21.39	3		
64QAM	8	7	21.51	21.35	21.34	0-3	3
	15	0	21.35	21.32	21.29		3

Table 9-25
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.29	24.25	24.40	0	0
	1	2	24.38	24.33	24.51		0
	1	5	24.28	24.24	24.45		0
	3	0	24.48	24.41	24.45	0	0
	3	2	24.55	24.42	24.47		0
	3	3	24.52	24.44	24.51		0
16QAM	6	0	23.48	23.33	23.40	0-1	1
	1	0	23.15	23.66	23.12	0-1	1
	1	2	23.22	23.59	23.21		1
	1	5	23.20	23.69	23.12		1
	3	0	23.58	23.57	23.53	0-1	1
	3	2	23.62	23.48	23.57		1
3	3	23.61	23.44	23.55	1		
64QAM	6	0	22.67	22.27	22.60	0-2	2
	1	0	22.42	22.40	22.35	0-2	2
	1	2	22.56	22.50	22.52		2
	1	5	22.41	22.56	22.55		2
	3	0	22.39	22.40	22.41	0-2	2
	3	2	22.49	22.55	22.39		2
3	3	22.45	22.44	22.38	2		
64QAM	6	0	21.32	21.23	21.31	0-3	3

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 40 of 73

9.4.6

LTE Band 7

Table 9-26
LTE Band 7 Conducted Powers - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	22.50	22.35	22.45	0	0	
	1	50	22.70	22.59	22.65		0	
	1	99	22.43	22.39	22.50		0	
	50	0	21.40	21.37	21.41	0-1	1	
	50	25	21.42	21.39	21.37		1	
	50	50	21.38	21.35	21.32		1	
16QAM	100	0	21.40	21.35	21.36	0-1	1	
	1	0	21.32	21.15	21.29		0-1	1
	1	50	21.49	21.33	21.21			1
	1	99	21.15	21.34	21.23	0-2		1
	50	0	20.45	20.45	20.45		2	
	50	25	20.47	20.48	20.41		2	
64QAM	50	50	20.49	20.44	20.33	0-2	2	
	100	0	20.44	20.38	20.35		2	
	1	0	20.59	20.37	20.40		0-2	2
	1	50	20.66	20.61	20.52	2		
	1	99	20.43	20.30	20.45	0-3		2
	50	0	19.44	19.34	19.32		3	
50	25	19.54	19.32	19.29	3			
64QAM	50	50	19.44	19.30	19.12	0-3	3	
	100	0	19.46	19.29	19.27		3	

Table 9-27
LTE Band 7 Conducted Powers - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	22.38	22.19	22.15	0	0	
	1	36	22.46	22.18	22.13		0	
	1	74	22.28	22.11	22.14		0	
	36	0	21.46	21.31	21.29	0-1	1	
	36	18	21.46	21.35	21.22		1	
	36	37	21.44	21.24	21.23		1	
16QAM	75	0	21.45	21.25	21.25	0-1	1	
	1	0	21.62	21.42	21.42		0-1	1
	1	36	21.56	21.54	21.48			1
	1	74	21.35	21.41	21.53	0-2		1
	36	0	20.53	20.31	20.29		2	
	36	18	20.46	20.35	20.18		2	
64QAM	36	37	20.49	20.26	20.17	0-2	2	
	75	0	20.48	20.29	20.29		2	
	1	0	20.56	20.34	20.40		0-2	2
	1	36	20.37	20.41	20.50	2		
	1	74	20.64	20.36	20.45	0-3		2
	36	0	19.51	19.25	19.33		3	
36	18	19.50	19.31	19.30	3			
64QAM	36	37	19.40	19.25	19.24	0-3	3	
	75	0	19.46	19.24	19.25		3	

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 41 of 73	

**Table 9-28
LTE Band 7 Conducted Powers - 10 MHz Bandwidth**

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.41	22.27	22.21	0	0
	1	25	22.40	22.39	22.39		0
	1	49	22.39	22.19	22.37		0
	25	0	21.48	21.36	21.37	0-1	1
	25	12	21.58	21.30	21.32		1
	25	25	21.57	21.29	21.24		1
16QAM	50	0	21.52	21.39	21.25	0-1	1
	1	0	21.64	21.51	21.56		1
	1	25	21.62	21.48	21.66		1
	1	49	21.58	21.68	21.67	0-2	1
	25	0	20.51	20.42	20.41		2
	25	12	20.56	20.34	20.38		2
64QAM	25	25	20.56	20.32	20.31	0-2	2
	50	0	20.51	20.37	20.23		2
	1	0	20.65	20.50	20.42		0-2
	1	25	20.63	20.47	20.55	2	
	1	49	20.60	20.41	20.53	0-3	
	25	0	19.52	19.34	19.27		3
25	12	19.55	19.32	19.30	3		
64QAM	25	25	19.54	19.28	19.31	0-3	3
	50	0	19.48	19.29	19.35		3

**Table 9-29
LTE Band 7 Conducted Powers - 5 MHz Bandwidth**

LTE Band 7 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	22.28	22.10	22.15	0	0	
	1	12	22.56	22.46	22.47		0	
	1	24	22.31	22.30	22.16		0	
	12	0	21.45	21.23	21.28	0-1	1	
	12	6	21.47	21.37	21.38		1	
	12	13	21.46	21.31	21.24		1	
16QAM	25	0	21.47	21.20	21.28	0-1	1	
	1	0	21.63	21.31	21.45		0-1	1
	1	12	21.32	21.57	21.69			1
	1	24	21.70	21.45	21.53	0-2		1
	12	0	20.42	20.22	20.31		2	
	12	6	20.44	20.45	20.42		2	
64QAM	12	13	20.49	20.26	20.36	0-2	2	
	25	0	20.54	20.28	20.33		2	
	1	0	20.46	20.24	20.36		0-2	2
	1	12	20.68	20.62	20.65	2		
	1	24	20.58	20.35	20.33	0-3		2
	12	0	19.47	19.30	19.44		3	
12	6	19.45	19.34	19.41	0-3		3	
12	13	19.50	19.24	19.34		3		
25	0	19.47	19.25	19.33		3		

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 42 of 73	

9.5 WLAN Conducted Powers

Table 9-30
2.4 GHz WLAN Maximum Average RF Power

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	18.06	14.19	13.19
2417	2	N/A	16.89	16.31
2437	6	18.53	16.87	16.28
2457	10	N/A	16.92	16.32
2462	11	18.50	14.53	13.38

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.




Figure 9-4
Power Measurement Setup

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 43 of 73	

Equation 9-1
Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{2.888ms}{3.748ms} * 100\% = 77.1\%$$




Figure 9-6
Power Measurement Setup

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 45 of 73	

10 SYSTEM VERIFICATION

10.1 Tissue Verification

**Table 10-1
Head Measured Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
02/24/2020	750 Head	20.5	700	0.879	40.803	0.889	42.201	-1.12%	-3.31%
			710	0.883	40.781	0.890	42.149	-0.79%	-3.25%
			750	0.898	40.659	0.894	41.942	0.45%	-3.06%
			770	0.905	40.599	0.895	41.838	1.12%	-2.96%
			785	0.910	40.566	0.896	41.760	1.56%	-2.86%
02/20/2020	835 Head	20.7	820	0.923	43.320	0.899	41.578	2.67%	4.19%
			835	0.929	43.271	0.900	41.500	3.22%	4.27%
			850	0.936	43.224	0.916	41.500	2.18%	4.15%
03/02/2020	835 Head	21.3	820	0.863	39.963	0.899	41.578	-4.00%	-3.88%
			835	0.878	39.760	0.900	41.500	-2.44%	-4.19%
			850	0.891	39.570	0.916	41.500	-2.73%	-4.65%
02/24/2020	1750 Head	20.5	1710	1.340	38.700	1.348	40.142	-0.59%	-3.59%
			1720	1.346	38.687	1.354	40.126	-0.59%	-3.59%
			1745	1.361	38.646	1.368	40.087	-0.51%	-3.59%
			1750	1.364	38.637	1.371	40.079	-0.51%	-3.60%
			1770	1.375	38.593	1.383	40.047	-0.58%	-3.63%
02/28/2020	1900 Head	22.5	1790	1.387	38.548	1.394	40.016	-0.50%	-3.67%
			1850	1.393	38.591	1.400	40.000	-0.50%	-3.52%
			1860	1.404	38.547	1.400	40.000	0.29%	-3.63%
			1880	1.425	38.463	1.400	40.000	1.79%	-3.84%
			1900	1.447	38.379	1.400	40.000	3.36%	-4.05%
03/02/2020	1900 Head	22.1	1905	1.452	38.356	1.400	40.000	3.71%	-4.11%
			1910	1.458	38.335	1.400	40.000	4.14%	-4.16%
			1850	1.386	39.375	1.400	40.000	-1.00%	-1.56%
			1860	1.397	39.332	1.400	40.000	-0.21%	-1.67%
			1880	1.418	39.244	1.400	40.000	1.29%	-1.89%
02/24/2020	2450 Head	20.0	1900	1.439	39.154	1.400	40.000	2.79%	-2.11%
			1905	1.444	39.132	1.400	40.000	3.14%	-2.17%
			1910	1.449	39.109	1.400	40.000	3.50%	-2.23%
			2400	1.817	38.826	1.756	39.289	3.47%	-1.18%
			2450	1.857	38.723	1.800	39.200	3.17%	-1.22%
02/27/2020	2450 Head	21.2	2500	1.900	38.618	1.855	39.136	2.43%	-1.32%
			2400	1.820	38.548	1.756	39.289	3.64%	-1.89%
			2450	1.858	38.473	1.800	39.200	3.22%	-1.85%
			2500	1.897	38.384	1.855	39.136	2.26%	-1.92%
			2510	1.905	38.370	1.866	39.123	2.09%	-1.92%
			2535	1.925	38.336	1.893	39.092	1.69%	-1.93%
			2550	1.937	38.308	1.909	39.073	1.47%	-1.96%
			2560	1.945	38.289	1.920	39.060	1.30%	-1.97%
			2600	1.978	38.224	1.964	39.009	0.71%	-2.01%
			2650	2.019	38.141	2.018	38.945	0.05%	-2.06%
			2680	2.044	38.086	2.051	38.907	-0.34%	-2.11%
			2700	2.061	38.053	2.073	38.882	-0.58%	-2.13%
03/02/2020	2450 Head	22.5	2400	1.790	38.507	1.756	39.289	1.94%	-1.99%
			2450	1.829	38.432	1.800	39.200	1.61%	-1.96%
			2500	1.865	38.343	1.855	39.136	0.54%	-2.03%

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 46 of 73

**Table 10-2
Body Measured Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
02/24/2020	750 Body	19.7	700	0.940	53.588	0.959	55.726	-1.98%	-3.84%
			710	0.944	53.566	0.960	55.687	-1.67%	-3.81%
			750	0.959	53.459	0.964	55.531	-0.52%	-3.73%
02/26/2020	750 Body	21.4	750	0.977	53.132	0.964	55.531	1.35%	-4.32%
			770	0.984	53.077	0.965	55.453	1.97%	-4.28%
			785	0.989	53.030	0.966	55.395	2.38%	-4.27%
02/27/2020	835 Body	21.1	820	0.943	53.581	0.969	55.258	-2.68%	-3.03%
			835	0.959	53.418	0.970	55.200	-1.13%	-3.23%
			890	0.975	53.251	0.988	55.154	-1.32%	-3.45%
03/04/2020	835 Body	21.3	820	0.946	54.343	0.969	55.258	-2.37%	-1.66%
			835	0.961	54.192	0.970	55.200	-0.93%	-1.83%
			850	0.976	54.041	0.988	55.154	-1.21%	-2.02%
02/20/2020	1750 Body	21.0	1710	1.473	55.286	1.463	53.537	0.68%	3.27%
			1720	1.485	55.245	1.469	53.511	1.09%	3.24%
			1745	1.514	55.148	1.485	53.445	1.95%	3.19%
			1750	1.519	55.129	1.488	53.432	2.08%	3.18%
			1770	1.540	55.051	1.501	53.379	2.60%	3.13%
			1790	1.562	54.977	1.514	53.326	3.17%	3.10%
02/24/2020	1750 Body	21.0	1710	1.442	55.974	1.463	53.537	-1.44%	4.55%
			1720	1.455	55.940	1.469	53.511	-0.95%	4.54%
			1745	1.485	55.855	1.485	53.445	0.00%	4.51%
			1750	1.491	55.836	1.488	53.432	0.20%	4.50%
			1770	1.512	55.758	1.501	53.379	0.73%	4.46%
			1790	1.533	55.670	1.514	53.326	1.25%	4.40%
02/25/2020	1900 Body	23.4	1850	1.515	51.928	1.520	53.300	-0.33%	-2.57%
			1860	1.526	51.898	1.520	53.300	0.39%	-2.63%
			1880	1.548	51.830	1.520	53.300	1.84%	-2.76%
			1900	1.570	51.753	1.520	53.300	3.29%	-2.90%
			1905	1.575	51.735	1.520	53.300	3.62%	-2.94%
			1910	1.581	51.716	1.520	53.300	4.01%	-2.97%
02/27/2020	1900 Body	23.0	1850	1.525	53.261	1.520	53.300	0.33%	-0.07%
			1860	1.537	53.233	1.520	53.300	1.12%	-0.13%
			1880	1.561	53.174	1.520	53.300	2.70%	-0.24%
			1900	1.583	53.107	1.520	53.300	4.14%	-0.36%
			1905	1.589	53.091	1.520	53.300	4.54%	-0.39%
			1910	1.595	53.075	1.520	53.300	4.93%	-0.42%
03/09/2020	1900 Body	24.0	1850	1.503	53.234	1.520	53.300	-1.12%	-0.12%
			1860	1.515	53.205	1.520	53.300	-0.33%	-0.18%
			1880	1.538	53.140	1.520	53.300	1.18%	-0.30%
			1900	1.560	53.061	1.520	53.300	2.63%	-0.45%
			1905	1.566	53.041	1.520	53.300	3.03%	-0.49%
			1910	1.571	53.019	1.520	53.300	3.36%	-0.53%
02/24/2020	2450 Body	24.0	2400	1.921	53.203	1.902	52.767	1.00%	0.83%
			2450	1.988	53.017	1.950	52.700	1.95%	0.60%
			2500	2.058	52.838	2.021	52.636	1.83%	0.38%
03/02/2020	2450 Body	22.5	2400	1.979	52.157	1.902	52.767	4.05%	-1.16%
			2450	2.039	51.998	1.950	52.700	4.56%	-1.33%
			2500	2.098	51.848	2.021	52.636	3.81%	-1.50%
			2510	2.111	51.818	2.035	52.623	3.73%	-1.53%
			2535	2.142	51.741	2.071	52.592	3.43%	-1.62%
			2550	2.160	51.697	2.092	52.573	3.25%	-1.67%
			2560	2.172	51.670	2.106	52.560	3.13%	-1.69%
			2600	2.217	51.546	2.163	52.509	2.50%	-1.83%
			2650	2.281	51.379	2.234	52.445	2.10%	-2.03%
			2680	2.317	51.300	2.277	52.407	1.76%	-2.11%
			2700	2.341	51.243	2.305	52.382	1.56%	-2.17%

The above measured tissue parameters were used in the DASy software. The DASy software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.


FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 47 of 73

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix D.

**Table 10-3
System Verification Results**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
L	750	HEAD	02/24/2020	21.6	20.0	0.200	1054	7410	1.720	8.290	8.600	3.74%
L	835	HEAD	02/20/2020	23.7	20.2	0.200	4d132	7410	2.010	9.650	10.050	4.15%
H	835	HEAD	03/02/2020	22.7	21.3	0.200	4d133	7406	1.890	9.430	9.450	0.21%
L	1750	HEAD	02/24/2020	22.3	20.0	0.100	1148	7410	3.730	37.000	37.300	0.81%
G	1900	HEAD	02/28/2020	22.7	22.5	0.100	5d149	7409	4.000	39.300	40.000	1.78%
G	1900	HEAD	03/02/2020	22.3	22.1	0.100	5d149	7409	4.050	39.300	40.500	3.05%
M	2450	HEAD	02/24/2020	21.0	20.0	0.100	797	7570	5.310	52.700	53.100	0.76%
M	2450	HEAD	02/27/2020	20.8	22.2	0.100	719	7570	5.380	53.100	53.800	1.32%
E	2450	HEAD	03/02/2020	22.5	23.5	0.100	719	3589	5.190	53.100	51.900	-2.26%
M	2600	HEAD	02/27/2020	20.8	22.2	0.100	1064	7570	5.720	58.100	57.200	-1.55%
E	750	BODY	02/24/2020	22.7	19.7	0.200	1003	3589	1.810	8.580	9.050	5.48%
E	750	BODY	02/26/2020	22.7	21.4	0.200	1054	3589	1.810	8.550	9.050	5.85%
P	835	BODY	02/27/2020	23.1	21.1	0.200	4d133	7551	2.030	9.750	10.150	4.10%
D	835	BODY	03/04/2020	21.9	21.3	0.200	4d047	7488	1.790	9.470	8.950	-5.49%
I	1750	BODY	02/20/2020	22.3	21.0	0.100	1148	7357	4.010	37.700	40.100	6.37%
I	1750	BODY	02/24/2020	21.4	21.0	0.100	1148	7357	3.950	37.700	39.500	4.77%
J	1900	BODY	02/25/2020	21.9	21.9	0.100	5d080	7571	3.960	39.200	39.600	1.02%
J	1900	BODY	02/27/2020	21.9	21.2	0.100	5d080	7571	4.230	39.200	42.300	7.91%
J	1900	BODY	03/09/2020	22.7	23.4	0.100	5d080	7571	4.140	39.200	41.400	5.61%
P	2450	BODY	02/24/2020	21.9	22.3	0.100	719	7551	5.130	50.800	51.300	0.98%
K	2450	BODY	03/02/2020	23.0	22.5	0.100	797	7547	5.070	51.100	50.700	-0.78%
K	2600	BODY	03/02/2020	23.0	22.5	0.100	1004	7547	5.610	54.800	56.100	2.37%



**Figure 10-1
System Verification Setup Diagram**



**Figure 10-2
System Verification Setup Photo**

FCC ID: ZNFK300UM	PCTEST	SAR EVALUATION REPORT	LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 48 of 73

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

**Table 11-1
GSM 850 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.7	32.69	-0.06	Right	Cheek	01624	1	1:8.3	0.334	1.002	0.335	
836.60	190	GSM 850	GSM	32.7	32.69	0.01	Right	Tilt	01624	1	1:8.3	0.191	1.002	0.191	
836.60	190	GSM 850	GSM	32.7	32.69	-0.01	Left	Cheek	01624	1	1:8.3	0.330	1.002	0.331	
836.60	190	GSM 850	GSM	32.7	32.69	-0.20	Left	Tilt	01624	1	1:8.3	0.173	1.002	0.173	
836.60	190	GSM 850	GPRS	28.7	28.37	0.07	Right	Cheek	01624	4	1:2.076	0.482	1.079	0.520	A1
836.60	190	GSM 850	GPRS	28.7	28.37	0.05	Right	Tilt	01624	4	1:2.076	0.250	1.079	0.270	
836.60	190	GSM 850	GPRS	28.7	28.37	-0.14	Left	Cheek	01624	4	1:2.076	0.446	1.079	0.481	
836.60	190	GSM 850	GPRS	28.7	28.37	0.01	Left	Tilt	01624	4	1:2.076	0.262	1.079	0.283	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

**Table 11-2
GSM 1900 Head SAR**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.7	30.27	0.14	Right	Cheek	01624	1	1:8.3	0.177	1.104	0.195	
1880.00	661	GSM 1900	GSM	30.7	30.27	0.03	Right	Tilt	01624	1	1:8.3	0.115	1.104	0.127	
1880.00	661	GSM 1900	GSM	30.7	30.27	0.15	Left	Cheek	01624	1	1:8.3	0.157	1.104	0.173	
1880.00	661	GSM 1900	GSM	30.7	30.27	0.14	Left	Tilt	01624	1	1:8.3	0.071	1.104	0.078	
1880.00	661	GSM 1900	GPRS	25.7	25.40	0.15	Right	Cheek	01624	4	1:2.076	0.202	1.072	0.217	A2
1880.00	661	GSM 1900	GPRS	25.7	25.40	0.05	Right	Tilt	01624	4	1:2.076	0.141	1.072	0.151	
1880.00	661	GSM 1900	GPRS	25.7	25.40	0.03	Left	Cheek	01624	4	1:2.076	0.187	1.072	0.200	
1880.00	661	GSM 1900	GPRS	25.7	25.40	-0.14	Left	Tilt	01624	4	1:2.076	0.086	1.072	0.092	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 49 of 73

**Table 11-3
UMTS 850 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.2	25.06	0.11	Right	Cheek	01632	1:1	0.351	1.033	0.363	
836.60	4183	UMTS 850	RMC	25.2	25.06	0.02	Right	Tilt	01632	1:1	0.183	1.033	0.189	
836.60	4183	UMTS 850	RMC	25.2	25.06	-0.06	Left	Cheek	01632	1:1	0.377	1.033	0.389	A3
836.60	4183	UMTS 850	RMC	25.2	25.06	0.02	Left	Tilt	01632	1:1	0.206	1.033	0.213	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-4
UMTS 1750 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	0.03	Right	Cheek	01640	1:1	0.261	1.059	0.276	A4
1732.40	1412	UMTS 1750	RMC	24.7	24.45	0.17	Right	Tilt	01640	1:1	0.200	1.059	0.212	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	0.09	Left	Cheek	01640	1:1	0.202	1.059	0.214	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	0.05	Left	Tilt	01640	1:1	0.143	1.059	0.151	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-5
UMTS 1900 Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.7	24.55	0.09	Right	Cheek	01640	1:1	0.460	1.035	0.476	A5
1880.00	9400	UMTS 1900	RMC	24.7	24.55	0.04	Right	Tilt	01640	1:1	0.357	1.035	0.369	
1880.00	9400	UMTS 1900	RMC	24.7	24.55	0.08	Left	Cheek	01640	1:1	0.392	1.035	0.406	
1880.00	9400	UMTS 1900	RMC	24.7	24.55	0.12	Left	Tilt	01640	1:1	0.213	1.035	0.220	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 50 of 73

**Table 11-6
Cell. CDMA Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	Cell. CDMA	RC3 / SO55	25.2	25.17	0.05	Right	Cheek	01624	1:1	0.355	1.007	0.357	A6
836.52	384	Cell. CDMA	RC3 / SO55	25.2	25.17	0.05	Right	Tilt	01624	1:1	0.200	1.007	0.201	
836.52	384	Cell. CDMA	RC3 / SO55	25.2	25.17	0.02	Left	Cheek	01624	1:1	0.328	1.007	0.330	
836.52	384	Cell. CDMA	RC3 / SO55	25.2	25.17	0.06	Left	Tilt	01624	1:1	0.173	1.007	0.174	
836.52	384	Cell. CDMA	EVDO Rev. A	25.2	24.66	0.00	Right	Cheek	01624	1:1	0.289	1.132	0.327	
836.52	384	Cell. CDMA	EVDO Rev. A	25.2	24.66	-0.14	Right	Tilt	01624	1:1	0.158	1.132	0.179	
836.52	384	Cell. CDMA	EVDO Rev. A	25.2	24.66	0.03	Left	Cheek	01624	1:1	0.290	1.132	0.328	
836.52	384	Cell. CDMA	EVDO Rev. A	25.2	24.66	-0.06	Left	Tilt	01624	1:1	0.164	1.132	0.186	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

**Table 11-7
PCS CDMA Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	0.04	Right	Cheek	01640	1:1	0.422	1.069	0.451	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	0.06	Right	Tilt	01640	1:1	0.301	1.069	0.322	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	0.05	Left	Cheek	01640	1:1	0.424	1.069	0.453	A7
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.41	0.09	Left	Tilt	01640	1:1	0.196	1.069	0.210	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	0.19	Right	Cheek	01640	1:1	0.357	1.045	0.373	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	0.09	Right	Tilt	01640	1:1	0.272	1.045	0.284	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	0.05	Left	Cheek	01640	1:1	0.358	1.045	0.374	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.51	-0.05	Left	Tilt	01640	1:1	0.190	1.045	0.199	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 51 of 73

**Table 11-8
LTE Band 12 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	-0.07	0	Right	Cheek	QPSK	1	25	01640	1:1	0.286	1.050	0.300	
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.14	1	Right	Cheek	QPSK	25	12	01640	1:1	0.224	1.072	0.240	
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	-0.10	0	Right	Tilt	QPSK	1	25	01640	1:1	0.153	1.050	0.161	
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.02	1	Right	Tilt	QPSK	25	12	01640	1:1	0.117	1.072	0.125	
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	-0.05	0	Left	Cheek	QPSK	1	25	01640	1:1	0.339	1.050	0.356	A8
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	-0.01	1	Left	Cheek	QPSK	25	12	01640	1:1	0.256	1.072	0.274	
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	0.00	0	Left	Tilt	QPSK	1	25	01640	1:1	0.195	1.050	0.205	
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.09	1	Left	Tilt	QPSK	25	12	01640	1:1	0.144	1.072	0.154	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-9
LTE Band 13 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	0.08	0	Right	Cheek	QPSK	1	25	01640	1:1	0.345	1.028	0.355	
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	0.16	1	Right	Cheek	QPSK	25	12	01640	1:1	0.261	1.047	0.273	
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	0.09	0	Right	Tilt	QPSK	1	25	01640	1:1	0.169	1.028	0.174	
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	0.10	1	Right	Tilt	QPSK	25	12	01640	1:1	0.132	1.047	0.138	
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	-0.01	0	Left	Cheek	QPSK	1	25	01640	1:1	0.386	1.028	0.397	A9
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	0.01	1	Left	Cheek	QPSK	25	12	01640	1:1	0.291	1.047	0.305	
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	-0.09	0	Left	Tilt	QPSK	1	25	01640	1:1	0.186	1.028	0.191	
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	0.02	1	Left	Tilt	QPSK	25	12	01640	1:1	0.146	1.047	0.153	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-10
LTE Band 5 (Cell) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.10	0	Right	Cheek	QPSK	1	25	01632	1:1	0.338	1.038	0.351	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.11	1	Right	Cheek	QPSK	25	12	01632	1:1	0.263	1.047	0.275	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.04	0	Right	Tilt	QPSK	1	25	01632	1:1	0.183	1.038	0.190	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.04	1	Right	Tilt	QPSK	25	12	01632	1:1	0.135	1.047	0.141	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.05	0	Left	Cheek	QPSK	1	25	01632	1:1	0.347	1.038	0.360	A10
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.09	1	Left	Cheek	QPSK	25	12	01632	1:1	0.270	1.047	0.283	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.02	0	Left	Tilt	QPSK	1	25	01632	1:1	0.191	1.038	0.198	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.10	1	Left	Tilt	QPSK	25	12	01632	1:1	0.156	1.047	0.163	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1-ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 52 of 73	

**Table 11-11
LTE Band 66 (AWS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	-0.05	0	Right	Cheek	QPSK	1	50	01640	1:1	0.266	1.052	0.280	A11
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.01	1	Right	Cheek	QPSK	50	25	01640	1:1	0.210	1.081	0.227	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	0.21	0	Right	Tilt	QPSK	1	50	01640	1:1	0.238	1.052	0.250	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.17	1	Right	Tilt	QPSK	50	25	01640	1:1	0.182	1.081	0.197	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	0.10	0	Left	Cheek	QPSK	1	50	01640	1:1	0.241	1.052	0.254	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.14	1	Left	Cheek	QPSK	50	25	01640	1:1	0.191	1.081	0.206	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	0.14	0	Left	Tilt	QPSK	1	50	01640	1:1	0.162	1.052	0.170	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.06	1	Left	Tilt	QPSK	50	25	01640	1:1	0.128	1.081	0.138	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-12
LTE Band 25 (PCS) Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	-0.11	0	Right	Cheek	QPSK	1	50	01640	1:1	0.429	1.042	0.447	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	0.02	1	Right	Cheek	QPSK	50	25	01640	1:1	0.348	1.057	0.368	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	0.16	0	Right	Tilt	QPSK	1	50	01640	1:1	0.318	1.042	0.331	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	0.02	1	Right	Tilt	QPSK	50	25	01640	1:1	0.257	1.057	0.272	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	-0.03	0	Left	Cheek	QPSK	1	50	01640	1:1	0.431	1.042	0.449	A12
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	-0.05	1	Left	Cheek	QPSK	50	25	01640	1:1	0.331	1.057	0.350	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	0.01	0	Left	Tilt	QPSK	1	50	01640	1:1	0.230	1.042	0.240	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	-0.10	1	Left	Tilt	QPSK	50	25	01640	1:1	0.182	1.057	0.192	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 11-13
LTE Band 7 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	-0.02	0	Right	Cheek	QPSK	1	50	01624	1:1	0.126	1.000	0.126	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.14	1	Right	Cheek	QPSK	50	25	01624	1:1	0.106	1.067	0.113	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	0.13	0	Right	Tilt	QPSK	1	50	01624	1:1	0.109	1.000	0.109	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.19	1	Right	Tilt	QPSK	50	25	01624	1:1	0.086	1.067	0.092	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	0.13	0	Left	Cheek	QPSK	1	50	01624	1:1	0.125	1.000	0.125	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.17	1	Left	Cheek	QPSK	50	25	01624	1:1	0.099	1.067	0.106	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	0.02	0	Left	Tilt	QPSK	1	50	01624	1:1	0.176	1.000	0.176	A13
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.09	1	Left	Tilt	QPSK	50	25	01624	1:1	0.137	1.067	0.146	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 53 of 73	

**Table 11-14
DTS Head SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	19.0	18.53	0.12	Right	Cheek	01764	1	99.2	0.417	0.311	1.114	1.008	0.349	A14
2437	6	802.11b	DSSS	22	19.0	18.53	-0.14	Right	Tilt	01764	1	99.2	0.364	-	1.114	1.008	-	
2437	6	802.11b	DSSS	22	19.0	18.53	0.14	Left	Cheek	01764	1	99.2	0.178	-	1.114	1.008	-	
2437	6	802.11b	DSSS	22	19.0	18.53	-0.12	Left	Tilt	01764	1	99.2	0.136	-	1.114	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-15
DSS Head SAR**

MEASUREMENT RESULTS																	
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #	
MHz	Ch.											(W/kg)			(W/kg)		
2441.00	39	Bluetooth	FHSS	10.0	9.08	0.08	Right	Cheek	01764	1	77.1	0.044	1.236	1.297	0.071	A15	
2441.00	39	Bluetooth	FHSS	10.0	9.08	0.15	Right	Tilt	01764	1	77.1	0.032	1.236	1.297	0.051		
2441.00	39	Bluetooth	FHSS	10.0	9.08	0.14	Left	Cheek	01764	1	77.1	0.015	1.236	1.297	0.024		
2441.00	39	Bluetooth	FHSS	10.0	9.08	0.15	Left	Tilt	01764	1	77.1	0.013	1.236	1.297	0.021		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 54 of 73

11.2 Standalone Body-Worn SAR Data

**Table 11-16
GSM/UMTS/CDMA Body-Worn SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.7	32.69	0.06	10 mm	01624	1	1:8.3	back	0.442	1.002	0.443	
824.20	128	GSM 850	GPRS	28.7	28.40	0.00	10 mm	01624	4	1:2.076	back	0.590	1.072	0.632	
836.60	190	GSM 850	GPRS	28.7	28.37	-0.03	10 mm	01624	4	1:2.076	back	0.607	1.079	0.655	A16
848.80	251	GSM 850	GPRS	28.7	28.42	0.00	10 mm	01624	4	1:2.076	back	0.472	1.067	0.504	
1880.00	661	GSM 1900	GSM	30.7	30.27	-0.05	10 mm	01657	1	1:8.3	back	0.253	1.104	0.279	
1880.00	661	GSM 1900	GPRS	25.7	25.40	-0.15	10 mm	01657	4	1:2.076	back	0.301	1.072	0.323	A17
836.60	4183	UMTS 850	RMC	25.2	25.06	0.02	10 mm	01657	N/A	1:1	back	0.489	1.033	0.505	A19
1712.40	1312	UMTS 1750	RMC	24.7	24.57	0.05	10 mm	01624	N/A	1:1	back	0.792	1.030	0.816	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	-0.02	10 mm	01624	N/A	1:1	back	0.813	1.059	0.861	A20
1752.60	1513	UMTS 1750	RMC	24.7	24.44	0.01	10 mm	01624	N/A	1:1	back	0.731	1.062	0.776	
1852.40	9262	UMTS 1900	RMC	24.7	24.60	-0.08	10 mm	01640	N/A	1:1	back	0.749	1.023	0.766	
1880.00	9400	UMTS 1900	RMC	24.7	24.55	-0.08	10 mm	01640	N/A	1:1	back	0.725	1.035	0.750	
1907.60	9538	UMTS 1900	RMC	24.7	24.35	0.00	10 mm	01640	N/A	1:1	back	0.803	1.084	0.870	A21
836.52	384	Cell. CDMA	TDSO / SO32	25.2	25.18	0.02	10 mm	01624	N/A	1:1	back	0.499	1.005	0.501	A23
1851.25	25	PCS CDMA	TDSO / SO32	24.7	24.56	-0.06	10 mm	01640	N/A	1:1	back	0.683	1.033	0.706	A25
1880.00	600	PCS CDMA	TDSO / SO32	24.7	24.44	-0.14	10 mm	01640	N/A	1:1	back	0.663	1.062	0.704	
1908.75	1175	PCS CDMA	TDSO / SO32	24.7	24.37	-0.06	10 mm	01640	N/A	1:1	back	0.683	1.079	0.737	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 55 of 73	

**Table 11-17
LTE Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	0.02	0	01624	QPSK	1	25	10 mm	back	1:1	0.411	1.050	0.432	A27
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.02	1	01624	QPSK	25	12	10 mm	back	1:1	0.314	1.072	0.337	
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	0.03	0	01624	QPSK	1	25	10 mm	back	1:1	0.500	1.028	0.514	A29
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	-0.05	1	01624	QPSK	25	12	10 mm	back	1:1	0.384	1.047	0.402	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.01	0	01657	QPSK	1	25	10 mm	back	1:1	0.442	1.038	0.459	A30
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.03	1	01657	QPSK	25	12	10 mm	back	1:1	0.351	1.047	0.367	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.7	24.40	-0.01	0	01624	QPSK	1	50	10 mm	back	1:1	0.850	1.072	0.911	A31
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	0.03	0	01624	QPSK	1	50	10 mm	back	1:1	0.797	1.052	0.838	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.26	-0.02	0	01624	QPSK	1	50	10 mm	back	1:1	0.754	1.107	0.835	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.01	1	01624	QPSK	50	25	10 mm	back	1:1	0.614	1.081	0.664	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.7	23.29	0.03	1	01624	QPSK	100	0	10 mm	back	1:1	0.621	1.099	0.682	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.7	24.40	-0.01	0	01624	QPSK	1	50	10 mm	back	1:1	0.846	1.072	0.907	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.7	24.51	-0.06	0	01640	QPSK	1	50	10 mm	back	1:1	0.784	1.045	0.819	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	-0.05	0	01640	QPSK	1	50	10 mm	back	1:1	0.731	1.042	0.762	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.27	-0.14	0	01640	QPSK	1	50	10 mm	back	1:1	0.793	1.104	0.875	A32
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	-0.06	1	01640	QPSK	50	25	10 mm	back	1:1	0.575	1.057	0.608	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.40	-0.05	1	01640	QPSK	100	0	10 mm	back	1:1	0.575	1.072	0.616	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	-0.15	0	01657	QPSK	1	50	10 mm	back	1:1	0.813	1.000	0.813	A34
2535.00	21100	Mid	LTE Band 7	20	22.7	22.59	0.03	0	01657	QPSK	1	50	10 mm	back	1:1	0.746	1.026	0.765	
2560.00	21350	High	LTE Band 7	20	22.7	22.65	0.10	0	01657	QPSK	1	50	10 mm	back	1:1	0.722	1.012	0.731	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.05	1	01657	QPSK	50	25	10 mm	back	1:1	0.625	1.067	0.667	
2510.00	20850	Low	LTE Band 7	20	21.7	21.40	0.07	1	01657	QPSK	100	0	10 mm	back	1:1	0.611	1.072	0.655	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	0.05	0	01657	QPSK	1	50	10 mm	back	1:1	0.811	1.000	0.811	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

Note: Blue entry represents variability measurement

**Table 11-18
DTS Body-Worn SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR	Plot #
MHz	Ch.												(W/kg)	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	19.0	18.53	-0.05	10 mm	01772	1	back	99.2	0.476	0.269	1.114	1.008	0.302	A35
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 56 of 73

11.3 Standalone Hotspot SAR Data

**Table 11-19
GPRS/UMTS/CDMA Hotspot SAR Data**

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
824.20	128	GSM 850	GPRS	28.7	28.40	0.00	10 mm	01624	4	1:2.076	back	0.590	1.072	0.632	
836.60	190	GSM 850	GPRS	28.7	28.37	-0.03	10 mm	01624	4	1:2.076	back	0.607	1.079	0.655	A16
848.80	251	GSM 850	GPRS	28.7	28.42	0.00	10 mm	01624	4	1:2.076	back	0.472	1.067	0.504	
836.60	190	GSM 850	GPRS	28.7	28.37	0.06	10 mm	01624	4	1:2.076	front	0.535	1.079	0.577	
836.60	190	GSM 850	GPRS	28.7	28.37	0.04	10 mm	01624	4	1:2.076	bottom	0.245	1.079	0.264	
836.60	190	GSM 850	GPRS	28.7	28.37	0.01	10 mm	01624	4	1:2.076	left	0.490	1.079	0.529	
1880.00	661	GSM 1900	GPRS	25.7	25.40	-0.15	10 mm	01657	4	1:2.076	back	0.301	1.072	0.323	
1880.00	661	GSM 1900	GPRS	25.7	25.40	0.04	10 mm	01657	4	1:2.076	front	0.499	1.072	0.535	A18
1880.00	661	GSM 1900	GPRS	25.7	25.40	0.03	10 mm	01657	4	1:2.076	bottom	0.353	1.072	0.378	
1880.00	661	GSM 1900	GPRS	25.7	25.40	0.08	10 mm	01657	4	1:2.076	right	0.157	1.072	0.168	
836.60	4183	UMTS 850	RMC	25.2	25.06	0.02	10 mm	01657	N/A	1:1	back	0.489	1.033	0.505	A19
836.60	4183	UMTS 850	RMC	25.2	25.06	0.07	10 mm	01657	N/A	1:1	front	0.412	1.033	0.426	
836.60	4183	UMTS 850	RMC	25.2	25.06	0.13	10 mm	01657	N/A	1:1	bottom	0.216	1.033	0.223	
836.60	4183	UMTS 850	RMC	25.2	25.06	-0.05	10 mm	01657	N/A	1:1	left	0.413	1.033	0.427	
1712.40	1312	UMTS 1750	RMC	24.7	24.57	0.05	10 mm	01624	N/A	1:1	back	0.792	1.030	0.816	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	-0.02	10 mm	01624	N/A	1:1	back	0.813	1.059	0.861	A20
1752.60	1513	UMTS 1750	RMC	24.7	24.44	0.01	10 mm	01624	N/A	1:1	back	0.731	1.062	0.776	
1712.40	1312	UMTS 1750	RMC	24.7	24.57	0.06	10 mm	01624	N/A	1:1	front	0.681	1.030	0.701	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	0.11	10 mm	01624	N/A	1:1	front	0.768	1.059	0.813	
1752.60	1513	UMTS 1750	RMC	24.7	24.44	0.08	10 mm	01624	N/A	1:1	front	0.742	1.062	0.788	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	0.01	10 mm	01624	N/A	1:1	bottom	0.567	1.059	0.600	
1732.40	1412	UMTS 1750	RMC	24.7	24.45	-0.16	10 mm	01624	N/A	1:1	right	0.204	1.059	0.216	
1852.40	9262	UMTS 1900	RMC	24.7	24.60	-0.08	10 mm	01640	N/A	1:1	back	0.749	1.023	0.766	
1880.00	9400	UMTS 1900	RMC	24.7	24.55	-0.08	10 mm	01640	N/A	1:1	back	0.725	1.035	0.750	
1907.60	9538	UMTS 1900	RMC	24.7	24.35	0.00	10 mm	01640	N/A	1:1	back	0.803	1.084	0.870	
1852.40	9262	UMTS 1900	RMC	24.7	24.60	-0.08	10 mm	01640	N/A	1:1	front	0.875	1.023	0.895	A22
1880.00	9400	UMTS 1900	RMC	24.7	24.55	0.01	10 mm	01640	N/A	1:1	front	0.847	1.035	0.877	
1907.60	9538	UMTS 1900	RMC	24.7	24.35	0.12	10 mm	01640	N/A	1:1	front	0.867	1.084	0.940	
1880.00	9400	UMTS 1900	RMC	24.7	24.55	-0.02	10 mm	01640	N/A	1:1	bottom	0.759	1.035	0.786	
1880.00	9400	UMTS 1900	RMC	24.7	24.55	-0.04	10 mm	01640	N/A	1:1	right	0.318	1.035	0.329	
1852.40	9262	UMTS 1900	RMC	24.7	24.60	-0.08	10 mm	01640	N/A	1:1	front	0.873	1.023	0.893	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.2	24.66	-0.13	10 mm	01624	N/A	1:1	back	0.408	1.132	0.462	A24
836.52	384	Cell. CDMA	EVDO Rev. 0	25.2	24.66	0.00	10 mm	01624	N/A	1:1	front	0.384	1.132	0.435	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.2	24.66	0.05	10 mm	01624	N/A	1:1	bottom	0.164	1.132	0.186	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.2	24.66	0.10	10 mm	01624	N/A	1:1	left	0.356	1.132	0.403	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.50	-0.14	10 mm	01640	N/A	1:1	back	0.618	1.047	0.647	
1851.25	25	PCS CDMA	EVDO Rev. 0	24.7	24.68	0.11	10 mm	01640	N/A	1:1	front	0.640	1.005	0.643	A26
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.50	-0.03	10 mm	01640	N/A	1:1	front	0.621	1.047	0.650	
1908.75	1175	PCS CDMA	EVDO Rev. 0	24.7	24.52	0.09	10 mm	01640	N/A	1:1	front	0.622	1.042	0.648	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.50	-0.01	10 mm	01640	N/A	1:1	bottom	0.589	1.047	0.617	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.50	0.00	10 mm	01640	N/A	1:1	right	0.332	1.047	0.348	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Note: Blue entry represents variability measurement

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 57 of 73	

**Table 11-20
LTE Band 12 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	0.02	0	01624	QPSK	1	25	10 mm	back	1:1	0.411	1.050	0.432	
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.02	1	01624	QPSK	25	12	10 mm	back	1:1	0.314	1.072	0.337	
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	0.00	0	01624	QPSK	1	25	10 mm	front	1:1	0.419	1.050	0.440	
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.02	1	01624	QPSK	25	12	10 mm	front	1:1	0.324	1.072	0.347	
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	0.07	0	01624	QPSK	1	25	10 mm	bottom	1:1	0.130	1.050	0.137	
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.09	1	01624	QPSK	25	12	10 mm	bottom	1:1	0.100	1.072	0.107	
707.50	23095	Mid	LTE Band 12	10	25.2	24.99	0.00	0	01624	QPSK	1	25	10 mm	left	1:1	0.527	1.050	0.553	A28
707.50	23095	Mid	LTE Band 12	10	24.2	23.90	0.01	1	01624	QPSK	25	12	10 mm	left	1:1	0.406	1.072	0.435	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-21
LTE Band 13 Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	0.03	0	01624	QPSK	1	25	10 mm	back	1:1	0.500	1.028	0.514	A29
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	-0.05	1	01624	QPSK	25	12	10 mm	back	1:1	0.384	1.047	0.402	
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	0.00	0	01624	QPSK	1	25	10 mm	front	1:1	0.409	1.028	0.420	
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	0.01	1	01624	QPSK	25	12	10 mm	front	1:1	0.320	1.047	0.335	
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	0.08	0	01624	QPSK	1	25	10 mm	bottom	1:1	0.204	1.028	0.210	
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	0.04	1	01624	QPSK	25	12	10 mm	bottom	1:1	0.156	1.047	0.163	
782.00	23230	Mid	LTE Band 13	10	25.2	25.08	-0.18	0	01624	QPSK	1	25	10 mm	left	1:1	0.321	1.028	0.330	
782.00	23230	Mid	LTE Band 13	10	24.2	24.00	0.00	1	01624	QPSK	25	12	10 mm	left	1:1	0.252	1.047	0.264	
									Body 1.6 W/kg (mW/g) averaged over 1 gram										

**Table 11-22
LTE Band 5 (Cell) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.01	0	01657	QPSK	1	25	10 mm	back	1:1	0.442	1.038	0.459	A30
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.03	1	01657	QPSK	25	12	10 mm	back	1:1	0.351	1.047	0.367	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.03	0	01657	QPSK	1	25	10 mm	front	1:1	0.391	1.038	0.406	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.01	1	01657	QPSK	25	12	10 mm	front	1:1	0.313	1.047	0.328	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.01	0	01657	QPSK	1	25	10 mm	bottom	1:1	0.212	1.038	0.220	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	-0.02	1	01657	QPSK	25	12	10 mm	bottom	1:1	0.167	1.047	0.175	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.2	25.04	0.01	0	01657	QPSK	1	25	10 mm	left	1:1	0.351	1.038	0.364	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.2	24.00	0.04	1	01657	QPSK	25	12	10 mm	left	1:1	0.293	1.047	0.307	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 58 of 73	

**Table 11-23
LTE Band 66 (AWS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.7	24.40	-0.01	0	01624	QPSK	1	50	10 mm	back	1:1	0.850	1.072	0.911	A31
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	0.03	0	01624	QPSK	1	50	10 mm	back	1:1	0.797	1.052	0.838	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.26	-0.02	0	01624	QPSK	1	50	10 mm	back	1:1	0.754	1.107	0.835	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.01	1	01624	QPSK	50	25	10 mm	back	1:1	0.614	1.081	0.664	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.7	23.29	0.03	1	01624	QPSK	100	0	10 mm	back	1:1	0.621	1.099	0.682	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.7	24.40	0.06	0	01624	QPSK	1	50	10 mm	front	1:1	0.771	1.072	0.827	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	0.08	0	01624	QPSK	1	50	10 mm	front	1:1	0.779	1.052	0.820	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.26	-0.12	0	01624	QPSK	1	50	10 mm	front	1:1	0.686	1.107	0.759	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	-0.12	1	01624	QPSK	50	25	10 mm	front	1:1	0.614	1.081	0.664	
1720.00	132072	Low	LTE Band 66 (AWS)	20	23.7	23.29	0.04	1	01624	QPSK	100	0	10 mm	front	1:1	0.550	1.099	0.604	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	-0.05	0	01624	QPSK	1	50	10 mm	bottom	1:1	0.586	1.052	0.616	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.01	1	01624	QPSK	50	25	10 mm	bottom	1:1	0.445	1.081	0.481	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	24.7	24.48	0.11	0	01624	QPSK	1	50	10 mm	right	1:1	0.210	1.052	0.221	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	23.7	23.36	0.02	1	01624	QPSK	50	25	10 mm	right	1:1	0.163	1.081	0.176	
1720.00	132072	Low	LTE Band 66 (AWS)	20	24.7	24.40	-0.01	0	01624	QPSK	1	50	10 mm	back	1:1	0.846	1.072	0.907	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement

**Table 11-24
LTE Band 25 (PCS) Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.7	24.51	-0.06	0	01640	QPSK	1	50	10 mm	back	1:1	0.784	1.045	0.819	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	-0.05	0	01640	QPSK	1	50	10 mm	back	1:1	0.731	1.042	0.762	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.27	-0.14	0	01640	QPSK	1	50	10 mm	back	1:1	0.793	1.104	0.875	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	-0.06	1	01640	QPSK	50	25	10 mm	back	1:1	0.575	1.057	0.608	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.40	-0.05	1	01640	QPSK	100	0	10 mm	back	1:1	0.575	1.072	0.616	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.7	24.51	-0.03	0	01640	QPSK	1	50	10 mm	front	1:1	0.867	1.045	0.906	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	0.05	0	01640	QPSK	1	50	10 mm	front	1:1	0.868	1.042	0.904	A33
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.27	0.09	0	01640	QPSK	1	50	10 mm	front	1:1	0.844	1.104	0.932	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	-0.05	1	01640	QPSK	50	25	10 mm	front	1:1	0.677	1.057	0.716	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.40	0.12	1	01640	QPSK	100	0	10 mm	front	1:1	0.667	1.072	0.715	
1860.00	26140	Low	LTE Band 25 (PCS)	20	24.7	24.51	-0.11	0	01624	QPSK	1	50	10 mm	bottom	1:1	0.750	1.045	0.784	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	-0.01	0	01624	QPSK	1	50	10 mm	bottom	1:1	0.770	1.042	0.802	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.27	0.05	0	01624	QPSK	1	50	10 mm	bottom	1:1	0.804	1.104	0.888	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	-0.09	1	01624	QPSK	50	25	10 mm	bottom	1:1	0.605	1.057	0.639	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.40	0.02	1	01624	QPSK	100	0	10 mm	bottom	1:1	0.586	1.072	0.628	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	24.7	24.52	0.06	0	01624	QPSK	1	50	10 mm	right	1:1	0.346	1.042	0.361	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	23.7	23.46	0.02	1	01624	QPSK	50	25	10 mm	right	1:1	0.267	1.057	0.282	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFK300UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 59 of 73	

**Table 11-25
LTE Band 7 Hotspot SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.														(W/kg)		(W/kg)	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	-0.15	0	01657	QPSK	1	50	10 mm	back	1:1	1.000	0.813	A34
2535.00	21100	Mid	LTE Band 7	20	22.7	22.59	0.03	0	01657	QPSK	1	50	10 mm	back	1:1	1.026	0.765	
2560.00	21350	High	LTE Band 7	20	22.7	22.65	0.10	0	01657	QPSK	1	50	10 mm	back	1:1	1.012	0.731	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.05	1	01657	QPSK	50	25	10 mm	back	1:1	1.067	0.667	
2510.00	20850	Low	LTE Band 7	20	21.7	21.40	0.07	1	01657	QPSK	100	0	10 mm	back	1:1	1.072	0.655	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	0.08	0	01657	QPSK	1	50	10 mm	front	1:1	1.000	0.154	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.07	1	01657	QPSK	50	25	10 mm	front	1:1	1.067	0.130	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	0.01	0	01657	QPSK	1	50	10 mm	bottom	1:1	1.000	0.758	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.03	1	01657	QPSK	50	25	10 mm	bottom	1:1	1.067	0.623	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	-0.04	0	01657	QPSK	1	50	10 mm	right	1:1	1.000	0.210	
2510.00	20850	Low	LTE Band 7	20	21.7	21.42	0.04	1	01657	QPSK	50	25	10 mm	right	1:1	1.067	0.175	
2510.00	20850	Low	LTE Band 7	20	22.7	22.70	0.05	0	01657	QPSK	1	50	10 mm	back	1:1	1.000	0.811	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

Note: Blue entry represents variability measurement

**Table 11-26
WLAN Hotspot SAR**

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	19.0	18.53	-0.05	10 mm	01772	1	back	99.2	0.476	0.269	1.114	1.008	0.302	A35
2437	6	802.11b	DSSS	22	19.0	18.53	0.09	10 mm	01772	1	front	99.2	0.106	-	1.114	1.008	-	
2437	6	802.11b	DSSS	22	19.0	18.53	0.08	10 mm	01772	1	top	99.2	0.136	-	1.114	1.008	-	
2437	6	802.11b	DSSS	22	19.0	18.53	-0.02	10 mm	01772	1	left	99.2	0.151	-	1.114	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram										

11.4 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 60 of 73

8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address possible VoIP scenarios.

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT		 Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 61 of 73

LTE Notes:

1. LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g evaluations, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
3. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 9.6 for the time domain plot and calculation for the duty factor of the device.
2. Head Bluetooth SAR were evaluated for BT BR tethering applications.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 62 of 73

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1
Estimated SAR**

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	10.00	10	0.210

Note: Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 63 of 73

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.520	0.349	0.869
	GSM/GPRS 1900	0.217	0.349	0.566
	UMTS 850	0.389	0.349	0.738
	UMTS 1750	0.276	0.349	0.625
	UMTS 1900	0.476	0.349	0.825
	Cell. CDMA/EVDO	0.357	0.349	0.706
	PCS CDMA/EVDO	0.453	0.349	0.802
	LTE Band 12	0.356	0.349	0.705
	LTE Band 13	0.397	0.349	0.746
	LTE Band 5 (Cell)	0.360	0.349	0.709
	LTE Band 66 (AWS)	0.280	0.349	0.629
	LTE Band 25 (PCS)	0.449	0.349	0.798
	LTE Band 7	0.176	0.349	0.525

Table 12-3
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.520	0.071	0.591
	GSM/GPRS 1900	0.217	0.071	0.288
	UMTS 850	0.389	0.071	0.460
	UMTS 1750	0.276	0.071	0.347
	UMTS 1900	0.476	0.071	0.547
	Cell. CDMA/EVDO	0.357	0.071	0.428
	PCS CDMA/EVDO	0.453	0.071	0.524
	LTE Band 12	0.356	0.071	0.427
	LTE Band 13	0.397	0.071	0.468
	LTE Band 5 (Cell)	0.360	0.071	0.431
	LTE Band 66 (AWS)	0.280	0.071	0.351
	LTE Band 25 (PCS)	0.449	0.071	0.520
	LTE Band 7	0.176	0.071	0.247

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 64 of 73	

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM/GPRS 850	0.655	0.302	0.957
	GSM/GPRS 1900	0.323	0.302	0.625
	UMTS 850	0.505	0.302	0.807
	UMTS 1750	0.861	0.302	1.163
	UMTS 1900	0.870	0.302	1.172
	Cell. CDMA	0.501	0.302	0.803
	PCS CDMA	0.737	0.302	1.039
	LTE Band 12	0.432	0.302	0.734
	LTE Band 13	0.514	0.302	0.816
	LTE Band 5 (Cell)	0.459	0.302	0.761
	LTE Band 66 (AWS)	0.911	0.302	1.213
	LTE Band 25 (PCS)	0.875	0.302	1.177
	LTE Band 7	0.813	0.302	1.115

Table 12-5
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM/GPRS 850	0.655	0.210	0.865
	GSM/GPRS 1900	0.323	0.210	0.533
	UMTS 850	0.505	0.210	0.715
	UMTS 1750	0.861	0.210	1.071
	UMTS 1900	0.870	0.210	1.080
	Cell. CDMA	0.501	0.210	0.711
	PCS CDMA	0.737	0.210	0.947
	LTE Band 12	0.432	0.210	0.642
	LTE Band 13	0.514	0.210	0.724
	LTE Band 5 (Cell)	0.459	0.210	0.669
	LTE Band 66 (AWS)	0.911	0.210	1.121
	LTE Band 25 (PCS)	0.875	0.210	1.085
	LTE Band 7	0.813	0.210	1.023

Note: Bluetooth SAR was not required to be measured per FCC KDB Publication 447498 D01v06. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 65 of 73	

12.5 Hotspot SAR Simultaneous Transmission Analysis.

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.655	0.302	0.957
	GPRS 1900	0.535	0.302	0.837
	UMTS 850	0.505	0.302	0.807
	UMTS 1750	0.861	0.302	1.163
	UMTS 1900	0.940	0.302	1.242
	Cell. EVDO	0.462	0.302	0.764
	PCS EVDO	0.650	0.302	0.952
	LTE Band 12	0.553	0.302	0.855
	LTE Band 13	0.514	0.302	0.816
	LTE Band 5 (Cell)	0.459	0.302	0.761
	LTE Band 66 (AWS)	0.911	0.302	1.213
	LTE Band 25 (PCS)	0.932	0.302	1.234
	LTE Band 7	0.813	0.302	1.115

Table 12-7
Simultaneous Transmission Scenario with Bluetooth (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.655	0.210	0.865
	GPRS 1900	0.535	0.210	0.745
	UMTS 850	0.505	0.210	0.715
	UMTS 1750	0.861	0.210	1.071
	UMTS 1900	0.940	0.210	1.150
	Cell. EVDO	0.462	0.210	0.672
	PCS EVDO	0.650	0.210	0.860
	LTE Band 12	0.553	0.210	0.763
	LTE Band 13	0.514	0.210	0.724
	LTE Band 5 (Cell)	0.459	0.210	0.669
	LTE Band 66 (AWS)	0.911	0.210	1.121
	LTE Band 25 (PCS)	0.932	0.210	1.142
	LTE Band 7	0.813	0.210	1.023

Note: Bluetooth SAR was not required to be measured per FCC KDB Publication 447498 D01v06. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 66 of 73	

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 67 of 73

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

**Table 13-1
Body SAR Measurement Variability Results**

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1852.40	9262	UMTS 1900	RMC	front	10 mm	0.875	0.873	1.00	N/A	N/A	N/A	N/A
1750	1720.00	132072	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	back	10 mm	0.850	0.846	1.00	N/A	N/A	N/A	N/A
2450	2510.00	20850	LTE Band 7, 20 MHz Bandwidth	QPSK, 1 RB, 50 RB Offset	back	10 mm	0.813	0.811	1.00	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 68 of 73	

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	E4432B	ESG-D Series Signal Generator	7/14/2019	Annual	7/14/2020	US40053896
Agilent	E5515C	Wireless Communications Test Set	9/25/2019	Annual	9/25/2020	GB43304278
Agilent	N9020A	MXA Signal Analyzer	4/20/2019	Annual	4/20/2020	US46470561
Agilent	8753ES	S-Parameter Network Analyzer	12/31/2019	Annual	12/31/2020	US39170122
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	6/3/2019	Annual	6/3/2020	109892
Agilent	E5515C	Wireless Communications Test Set	6/26/2019	Annual	6/26/2020	MYS0267125
Agilent	N5182A	MXG Vector Signal Generator	6/27/2019	Annual	6/27/2020	US46240505
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	120
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
MCL	BW-NGW5+	6dB Attenuator	CBT	N/A	CBT	1139
Anritsu	MA24106A	USB Power Sensor	5/22/2019	Annual	5/22/2020	1231535
Anritsu	MA24106A	USB Power Sensor	5/6/2019	Annual	5/6/2020	1231538
Anritsu	MT8820C	Radio Communication Analyzer	7/25/2019	Annual	7/25/2020	6201240328
Anritsu	MT8820C	Radio Communication Analyzer	3/29/2019	Annual	3/29/2020	6201300731
Anritsu	MT8821C	Radio Communication Analyzer	8/16/2019	Annual	8/16/2020	6201144418
Anritsu	MT8821C	Radio Communication Analyzer	3/18/2019	Annual	3/18/2020	6201144419
Anritsu	ML2495A	Power Meter	12/17/2019	Annual	12/17/2020	941001
Anritsu	MA2411B	Pulse Power Sensor	8/8/2019	Annual	8/8/2020	1339008
Anritsu	MA2411B	Pulse Power Sensor	6/11/2019	Annual	6/11/2020	1207364
Anritsu	MT8821C	Radio Communication Analyzer	10/2/2019	Annual	10/2/2020	6201664756
Anritsu	MT8862A	Wireless Connectivity Test Set	8/8/2019	Annual	8/8/2020	6261782395
Anritsu	MT8821C	Radio Communication Analyzer	5/13/2019	Annual	5/13/2020	6201524637
Control Company	4352	Ultra Long Stem Thermometer	11/29/2018	Biennial	11/29/2020	181766816
Control Company	4352	Ultra Long Stem Thermometer	11/29/2018	Biennial	11/29/2020	181766817
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433974
Control Company	4040	Therm./ Clock/ Humidity Monitor	10/9/2018	Biennial	10/9/2020	181647802
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MYS2180215
Mitutoyo	CD-6°CSX	Digital Caliper	4/18/2018	Biennial	4/18/2020	13264165
Rohde & Schwarz	CMW500	Radio Communication Tester	8/26/2019	Annual	8/26/2020	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	6/26/2019	Annual	6/26/2020	112347
Rohde & Schwarz	CMW500	Radio Communication Tester	6/24/2019	Annual	6/24/2020	101699
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	11/14/2019	Annual	11/14/2020	164948
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	6/6/2019	Annual	6/6/2020	161662
Rohde & Schwarz	ZNL6	Vector Network Analyzer	10/11/2019	Annual	10/11/2020	101307
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	21053
Seekonk	NC-100	Torque Wrench (8" lb)	5/23/2018	Biennial	5/23/2020	N/A
SPEAG	EX3DV4	SAR Probe	7/16/2019	Annual	7/16/2020	7410
SPEAG	EX3DV4	SAR Probe	12/11/2019	Annual	12/11/2020	7570
SPEAG	EX3DV4	SAR Probe	9/19/2019	Annual	9/19/2020	7551
SPEAG	EX3DV4	SAR Probe	5/16/2019	Annual	5/16/2020	7406
SPEAG	EX3DV4	SAR Probe	1/21/2020	Annual	1/21/2021	3589
SPEAG	EX3DV4	SAR Probe	4/24/2019	Annual	4/24/2020	7357
SPEAG	EX3DV4	SAR Probe	1/21/2020	Annual	1/21/2021	7488
SPEAG	EX3DV4	SAR Probe	12/11/2019	Annual	12/11/2020	7571
SPEAG	EX3DV4	SAR Probe	7/15/2019	Annual	7/15/2020	7547
SPEAG	EX3DV4	SAR Probe	6/19/2019	Annual	6/19/2020	7409
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/11/2019	Annual	7/11/2020	1322
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/13/2020	Annual	1/13/2021	1558
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/17/2019	Annual	9/17/2020	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/8/2019	Annual	5/8/2020	728
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/18/2019	Annual	4/18/2020	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/13/2020	Annual	1/13/2021	1530
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/5/2019	Annual	12/5/2020	1533
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/11/2019	Annual	7/11/2020	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/18/2019	Annual	12/18/2020	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/20/2019	Annual	6/20/2020	1334
SPEAG	D750V3	750 MHz SAR Dipole	1/15/2018	Triennial	1/15/2021	1003
SPEAG	D835V2	835 MHz SAR Dipole	3/13/2019	Annual	3/13/2020	4d047
SPEAG	D835V2	835 MHz SAR Dipole	1/13/2020	Annual	1/13/2021	4d132
SPEAG	D835V2	835 MHz SAR Dipole	10/19/2018	Biennial	10/19/2020	4d133
SPEAG	D1750V2	1750 MHz SAR Dipole	5/15/2019	Annual	5/15/2020	1148
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Biennial	10/23/2020	5d080
SPEAG	D2450V2	2450 MHz SAR Dipole	8/14/2019	Annual	8/14/2020	719
SPEAG	D2600V2	2600 MHz SAR Dipole	6/14/2019	Annual	6/14/2020	1064
SPEAG	D2450V2	2450 MHz SAR Dipole	9/11/2017	Triennial	9/11/2020	797
SPEAG	D1900V2	1900 MHz SAR Dipole	10/23/2018	Biennial	10/23/2020	5d149
SPEAG	D750V3	750 MHz Dipole	3/18/2019	Annual	3/18/2020	1054
SPEAG	D2600V2	2600 MHz SAR Dipole	4/11/2018	Biennial	4/11/2020	1004
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/7/2019	Annual	5/7/2020	1070

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 69 of 73

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 70 of 73

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: ZNFK300UM	 PCTEST	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset		Page 71 of 73

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT		 Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 72 of 73

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFK300UM	 SAR EVALUATION REPORT		 Approved by: Quality Manager
Document S/N: 1M2002170021-01-R1.ZNF	Test Dates: 02/20/20 - 03/09/20	DUT Type: Portable Handset	Page 73 of 73